

## Microwave Specifications

- Product Shipping Weight (approx.) 59 Lbs.
- Voltage Rating 120V/60 Hz/15 Amps
   Connected Load (kW Rating) @ 120 Volts = 1.6kW (For use on adequately wired 120V, dedicated circuit having 2-wire service with a separate ground wire. Appliance must be grounded for safe operation.)
- Amps @ 120 Volts = 13 Amps
- Always consult local and national electric codes.
- · Grounded outlet should be located in cabinet above, with hole in base to route power cord. Carefully follow top template instructions for power cord clearance when installing beneath smooth, flat cabinets.
- Microwave's exhaust ventilation system is preset to recirculate air inside with no ducting system required. Exhausting air outside is optional, using either vertical or horizontal ducting system. (Refer to Ducted Option Specifications for outside ventilation.)
  For safe and proper installation, microwave MUST be mounted to BOTH a top cabinet AND a wall, and connected to at least one wall stud. Can NOT be installed in island or peninsula cabinet arrangements.
- Cabinet bottom MUST be level to insure proper installation.
- Cabinet MUST be capable of supporting a total load of 135 lbs.
- When installing beneath smooth, flat cabinets, refer to cabinet template for detailed power cord clearance instructions.
- If cabinet depth (including doors) is deeper than 13", unit MUST be spaced out from rear wall using adequate materials (supporting 150 lbs.) to allow proper top vent air exhaust/intake.
- Filler blocks recommended for installation when cabinet front hangs below recessed bottom shelf.
- Minimum distance of 30" required from cooking surface to bottom edge of top cabinet.
- Minimum distance of 66" required from floor to top of microwave.

- Opening between cabinets MUST be 30" wide and free of obstructions.
   For openings up to 36" wide, order optional 36" Filler Panel Kit to fill in gap between unit and cabinets.
- · Allow 26" minimum clearance for 90° door swing.

## **Ducted Option Specifications**

- · For outside ventilation.
- Exhaust duct adapter will be needed for outside ventilation, to mate with standard 3-1/4"×10" rectangular duct. If round duct required, rectangular-to-round transition adapter will be needed with no less than 6" diameter.
- For most efficient airflow exhaust, use a straight run or as few elbows as possible with a maximum duct length of 3-1/4" x 10" rectangular or 6" diameter round duct, not to exceed 120 equivalent feet.

  For horizontal installation, be sure to allow enough space between
- wall studs to accommodate exhaust.
- · Refer to installation instructions on web for detailed duct preparation and converting exhaust vent blower system for exterior exhaust ventilation.

Note: For planning purposes only, Refer to Product Installation Guide on the web at frigidaire.com for detailed instructions.

## Optional Accessories

- · 36" Stainless Steel Filler Panel Kit (PN# MWFILKTSS).
- 36" White Filler Panel Kit (PN# MWFILKTWH).
  36" Black Filler Panel Kit (PN# MWFILKTBK).
- 15" Bump-Out Kit (PN# 5304508807). · Charcoal Filter - (PN# 5304464577).

cessories information available on the web at frigidaire.com



## FRIGIDAIRE

USA - 10200 David Taylor Drive - Charlotte, NC 28262 - 1-800-FRIGIDAIRE - frigidaire.com CANADA - 5855 Terry Fox Way - Mississauga, ON L5V 3E4 - 1-800-265-8352 - frigidaire.ca

9 2017 Electrolux Home Products, Inc.

The Ross

