
COUNTERTOP MICROWAVE OVEN SPECIFICATIONS SIGNATURE





Shown with Trim Kit (MK2030F)

Signature Kitchen Suite

Model	UPRM3010ST
FEATURE	
Capacity	2.0 cu. ft.
Power Output	1200 W
Sensor Cook	Yes
Easy Clean Cavity	Yes
COOKING MENU	
Humidity Sensor	Yes
Turntable Diameter	406 mm
Push out type	Yes
Display Type	White, Red VFD
Sensor Touch	Reheat , Potato, Rice, Popcorn
Cooking Options	Hot Dog, Baby Food, Oat Meal, Soup
Auto Defrost	Meat, Poultry, Fish
Quick Defrost	Yes .
Melt	Butter / Margarine, Chocolate, Cheese, Marshmallows
Soften	Butter, Ice Cream, Cream Cheese, Frozen Juice
Multi-Stage Cooking	3 Stages including Defrost Cycle
Power Level	10 Power levels
Stop/Clear, Start/enter	Yes
Time of Day	12 hours set
Kitchen Timer	Yes
Child Saftey Lock	Yes
Ez-On	Yes
DIMENSIONS & WE	GHT
Width	23 7/8"
Depth	19 13/16"
Height	13 9/16"
Net Weight	37.5 lbs
Shipping Weight	48.8 lbs
WARRANTY	
Limited Warranty	3 Year


AUG 2 4 2022 Cedar Ridge Lot SD (

COUNTERTOP MICROWAVE OVEN SPECIFICATIONS SIGNATURE



DIMENSIONS AND CLEARANCES

- The following opening dimensions in feet must be available in the installation cabinet: $25\,1/2\times16\,3/4\times19\,1/2$ or 22. (W x H x D)
- Warning: This trim kit uses air flow from the top, bottom and sides of the trim frame. Blocking the air flow can cause the microwave to function improperly and may cause damage to the microwave.
- Allow a 1" clearance beyond the edge of the trim frame to provide proper air flow. On 27" models, allow 1 1/8" at the top, 11/16" on the sides and 11/4" at the bottom for overlap of the Trim Frame over the edges of the cutout. On 30" models, allow 1 1/8" at the top, 2 1/16" on the sides and 11/4" at the bottom for overlap of the Trim Frame over the edges of the cutout.
- For installation above a built-in oven Microwave oven should be installed on a 3/8" plywood base and supported by 2x4 or 1x2 equivalent runners on all sides. Base must support a minimum of 100 lbs.



AUG 2 4 2022

Cedar Ridge Lot SD (V)