CONSTRUCTION SUMMARY inview Heights (G) - Russell Gardens Build

PURCHAS	ERS: JONATHA		and PENA LUGO KRISNEYRIS MILA	; Ltd. TEL: RES.: 647-	923-6100
	Γ/PHASE 165/2	REG. PLAN # 62M-1238	HOUSE TYPE Rosewood 3 Elev 1		
CABINET	RY				
1 - KITCHE SPECIFICA VENT - PU	N - DELETE CA TIONS AND VE		VENDOR WILL SUPPLY 6 INCH VENT AS PE APPROPRIATE LOCATION FOR INSTALLATI LOSING (TEMP. FAN MA)
	TRY - KITCHEN Note:	N - LIGHT VALENCE			
CABINETI	RY ACCESSO	RIES			
		BASE - SLIDE IN RANGE F	PROVISION		
23Jul18	Note: Specs	s. Attached			
	N CABINETRY Note:	UPPER - MICROWAVE SH	ELF STANDARD - 700MM WIDE - STANDAR	D	
	N CABINETRY Note:	UPPER - ANGLED CORNE	R CABINET - FITS TALL UPPER CABINETS -	PER UNIT - STANDARD	
	N CABINETRY Note:	BASE - PULLOUT WIRE SE	PICE RACK - PRICE IS EACH		
	UNIT UPGRAD Note:	DE - TO GO FROM 300MM	TO 600MM DEEP - PRICE IS PER FOOT - STA	NDARD	
Per sur Per derector	N CABINETRY Note:	UPPER - FULL DEPTH ABO	OVE FRIDGE - WITH GABLES - 600MM - PRIC	CE IS EACH - STANDARD	
CERAMIC	TILE	-			
	PGRADE 2 WAL Note:	L TILE BATHROOM 4 -	- TUB AREA	E .	
1 - TILE - U 23Jul18		OR TILE BATHROOM 4	- FLOOR		
	PGRADE 2 WAI Note:	LL TILE BATHROOM 2/.	3 - SHOWER		
	PGRADE 2 FLOO Note:	OR TILE BATHROOM 2	2/3 - FLOOR		
	PGRADE 2 WAL Note:	LL TILE ENSUITE WALI	L TILE - SHOWER		
1 - TILE - U 23Jul18		OR TILE ENSUITE BAT	THROOM - FLOOR		
CONSTRU	CTION				
		FIRST FLOOR ONLY			
23Jul18	Note:				a .
COUNTER	TOP				
	URFACE COUN' Note:	TERTOP - ENSUITE 4			
	URFACE COUN Note:	TERTOP - ENSUITE 2/3			

23Jul18 Note:

1 - HARD SURFACE COUNTERTOP - ENSUITE

CONSTRUCTION SUMMARY Mountainview Heights (G) - Russell Gardens Building Ltd. PURCHASERS: JONATHAN A DOS SANTOS BOZA and PENA LUGO KRISNEYRIS MILA **TEL:** RES.: 647-923-6100 LOT / PHASE REG. PLAN# HOUSE TYPE 165 / 2 62M-1238 Rosewood 3 Elev 1 1 - HARD SURFACE COUNTERTOP - POWDER ROOM 23Jul18 Note: 1 - HARD SURFACE COUNTERTOP - KITCHEN 23Jul18 Note: ELECTRICAL 1 - PLUG - ELECTRICAL PLUG - FOR MICROWAVE SHELF 23Jul18 Note: 1 - KITCHEN - VALANCE LIGHTING - FLORESCENT LIGHTING 23Jul18 Note: 1 - RELOCATE STANDARD KITCHEN LIGHT TO BE CENTERED OVER ISLAND 24Apr18 Note: 30 - POT LIGHT - LOW VOLTAGE LED - FIRST FLOOR INSTALLATION 24Apr18 Note: 1 - PLUG - ELECTRICAL PLUG - TO BE INSTALLED OVER FIREPLACE 24Apr18 Note: 1 - 200 AMP ELECTRICAL SERVICE 24Apr18 Note: FIREPLACE AND ACCESSORIES 1 - GAS LINE ROUGH-IN FOR STOVE (INCLUDES ELECTRICAL OUTLET) - FIRST FLOOR 23Jul18 Note: HARDWOOD FLOORING 1 - LAMINATE -UPGRADE TO LEXINGTON SERIES IN LIEU OF STANDARD LAMINATE 23Jul18 1 - KITCHEN HARDWOOD IN LIEU OF TILES - GROUP B 5" ENGINEERED 23Jul18 Note: 1 - FIRST FLOOR UPGRADE HARDWOOD TO GROUP B 5INCH IN LIEU OF STANDARD 23Jul18 Note: MIRRORS AND GLASS 1 - FRAMELESS GLASS SHOWER ENCLOSURE 24Apr18 Note: IN MASTER ENSUITE SHOWER **PLUMBING** 5 - SINK - UNDERMOUNT SINK - CONTRAC COLLETTE #4220CIY- ALL BATHROOMS 23Jul18 Note: 1 - SINK - UNDERMOUNT SINK - BLANCO QUATRUS R15 U2 #401519 KITCHEN 23.Jul18 Note: 1 - WATER LINE FOR FRIDGE - ROUGH-IN ONLY 23Jul18 Note: PROMOTIONAL 1 - FURTHER VENDOR DISCOUNT 23Jul18 Note:

CONSTRUCTION SUMMARY

Mountainview Heights (G) - Russell Gardens Building Ltd.

PURCHASERS: JONATHAN A DOS SANTOS BOZA and PENA LUGO KRISNEYRIS MILA

TEL: RES.: 647-923-6100

LOT / PHASE	REG. PLAN #	HOUSE TYPE	
165 / 2	62M-1238	Rosewood 3 Elev 1	
			1

1 - PARTIAL REDEMTION OF PROMOTIONAL PACKAGE \$\$\$\$\$\$\$ BALANCE FORWARD TO BE USED AT A LATER DATE. ORIGINAL PROMOTIONAL PACKAGE OF \$\$\$\$ AS PER SCHEDULE PE DATED MMMDDYYYY. 24Apr18 Note:

STAIRS AND RAILINGS

1 - EUROLINE 1 BLACK IRON PICKETS	
23Jul18 Note:	
1 - STAINED HANDRAIL, TREADS, RISERS AND STRINGER EXCLUDING PICKETS (FOR IRON PICKETS) - STANDARD STAIRCASE	
- PRICE IS PER SET	
23Jul18 Note:	

EXTRAS AS PER OFFER

The Vendor agrees that notwithstanding any other term or provision in this Agreement included in the Purchase Price and in addition to those items detailed in Schedule GP to the Agreement of Purchase and Sale, the Purchaser is entitled to a credit of Ten <i>Worksheet</i> Note:	
The Purchaser acknowledges that the Purchase Price is inclusive of all credits and promotional packages available at the time of purchase. Worksheet Note:	

This Document is Extremely Time Sensitive - Printed 23 Jul 18 at 14:55

INTERIOR COLOUR SCHEME

Purchasers:

JONATHAN A DOS SANTOS BOZA & PENA LU(Property: 165

Telephone Res. / Bus: (647) 923-6100 /

Project: Russell Gardens Building Ltd.

Decor Advisor:

Natalie Mancuso

Model and Elevation: Rosewood 3 Elev 1

Lock Date:

23-Jul-18

23-Jul-18

Plan #:

62M-1238

Layout Changes: Yes	No Sketch Attached: Yes No Exterior Colour Scheme:	
1. Cabinetry	Chula and Calaur	Hardware
Kitchen / Breakfast	Style and Colour EVEREST WHITE	1001
Laundry Room	ELISSE	Standard
Powder Room	MONACO W350XZ4	1001
Master Ensuite Bathroom	MONACO W350XZ4	1001
Ensuite Bath - Bedroom 2/3		1001
Ensuite Bath - Bedroom 4	MONACO W350XZ4	1001
Appliances:	Built In Appliances Yes No Slide In Store	ve • Yes O No
Appliances: Dishwasher Cabinet Stove Opening Fridge Opening		E: Standard Cabinet Height is
Dishwasher Cabinet Stove Opening	Closed Open 41" Upper Cabinets Yes No Please NOTE NOTE: If not specified, opening will be set to builder's standard opening of appro	E: Standard Cabinet Height is
Dishwasher Cabinet Stove Opening Fridge Opening	Closed Open 41" Upper Cabinets Yes No Please NOTE NOTE: If not specified, opening will be set to builder's standard opening of appro	E: Standard Cabinet Height is
Dishwasher Cabinet Stove Opening Fridge Opening	Closed Open 41" Upper Cabinets Yes No Please NOTE NOTE: If not specified, opening will be set to builder's standard opening of appro	E: Standard Cabinet Height is
Dishwasher Cabinet Stove Opening Fridge Opening	Closed Open 41" Upper Cabinets Yes No Please NOTE NOTE: If not specified, opening will be set to builder's standard opening of appro	E: Standard Cabinet Height is
Dishwasher Cabinet Stove Opening Fridge Opening	Closed Open 41" Upper Cabinets Yes No Please NOTE NOTE: If not specified, opening will be set to builder's standard opening of appro	E: Standard Cabinet Height is

	Counter	Edge
chen / Breakfast	QUARTZITE- SUPERWHITE	#320 PENCIL
aundry Room	N/A	
Powder Room	MARBLE- BIANCO CARRARA BRUSHED	#320 PENCIL
Master Ensuite Bathroom	MARBLE- BIANCO CARRARA BRUSHED	#320 PENCIL
Ensuite Bath - Bedroom 2/3	MARBLE- BIANCO CARRARA BRUSHED	#320 PENCIL
Ensuite Bath - Bedroom 4	MARBLE- BIANCO CARRARA BRUSHED	#320 PENCIL
** Refer to Construction S	Summary	

Greenpark. INTERIOR COLOUR SCHEME JONATHAN A DOS SANTOS BOZA & PENA LU(Property: 165 Purchasers: Project: Russell Gardens Building Ltd. Telephone Res. / Bus: (647) 923-6100 / Model and Elevation: Rosewood 3 Elev 1 **Decor Advisor:** Natalie Mancuso 62M-1238 23-Jul-18 Plan #: Lock Date: 23-Jul-18 3. Ceramic Flooring At a 45 Threshold-If App. METAL STRIP THROUGHOUT **Entrance Vestibule** TILE- BEACHES LIGHT GREY 13X13 Main Hall HARDWOOD Kitchen / Breakfast HARDWOOD Laundry Room TILE- BEACHES LIGHT GREY 13X13 **Powder Room** TILE- BEACHES LIGHT GREY 13X13 Master Ensuite Bathroom TILE- VERSAILLES CHATEAUX IVORIE 12X24 Ensuite Bath - Bedroom 2/3 TILE- VERSAILLES CHATEAUX IVORIE 12X24 Ensuite Bath - Bedroom 4 TILE- VERSAILLES CHATEAUX IVORIE 12X24 ** Refer to Construction Summary 4. Ceramic Wall Tile Describe Selection Master Ensuite Bathroom **Tub Deck Wall Tub Deck Tub Deck Skirt** Shower Stall TILE- IND OXIDIZED METAL 12X24 **Bathtub Enclosure Walls** TILE- IND OXIDIZED METAL 12X24 Ensuite Bath - Bedroom 2/3 TILE- IND OXIDIZED METAL 12X24 Ensuite Bath - Bedroom 4 Kitchen Backsplash ** Refer to Construction Summary - STANDARD GROUT THROUGHOUT UNLESS SPECIFIED 5. Plumbing Fixtures Whirlpool White All Bathrooms Yes No Dishwasher Rough-In Yes No Waterline for Fridge Yes No

Interior Doors Interior Trim 3" BB CASING WITH 5 1/4" BASEBOARD - COLONIAL As Per Construction Specifications	
As Par Construction Specifications	
Door Handles As Per Construction Specifications	
Exterior Front Door Handle As Per Construction Specifications	

Initials:

** Refer to Construction Summary

Greenpa	rk,	INTERIOR CO	DLOUR SCHEME	
urchasers:	JONATHAN A DOS SA	ANTOS BOZA & PENA LUC	Property: 165	
elephone Res. / Bus	s: (647) 923-6100 /		Project: Russell Gardens Building Ltd	
ecor Advisor:	Natalie Mancuso	Model and E	Elevation: Rosewood 3 Elev 1	
ock Date:	23-Jul-18	23-Jul-18	Plan #: 62M-1238	
. Onler Flooring				
lain Hall	HARDWOOD- MIRAG	GE 5" ENGINEERED MAPLE CHA	RACTER- DRIFTWOOD- DURAMATT	
iving Room			RACTER- DRIFTWOOD- DURAMATT	
ining Room	HARDWOOD- MIRAG	SE 5" ENGINEERED MAPLE CHA	RACTER- DRIFTWOOD- DURAMATT	
amily Room	HARDWOOD- MIRAG	SE 5" ENGINEERED MAPLE CHA	RACTER- DRIFTWOOD- DURAMATT	
en / Library / Study				
asement Landing(If App				
ower Landing (If Applies	HARDWOOD- MIRAG	SE 5" ENGINEERED MAPLE CHA	RACTER- DRIFTWOOD- DURAMATT	
per Landing	HARDWOOD- MIRAG	SE 5" ENGINEERED MAPLE CHA	RACTER- DRIFTWOOD- DURAMATT	
per Hall	LAMINATE-LEXINGTO	ON - HAZELWOOD OAK TL-2101	6-M	
aster Bedroom		ON - HAZELWOOD OAK TL-2101		
edroom #2	LAMINATE-LEXINGTO	ON - HAZELWOOD OAK TL-2101	6-M	
edroom #3				
edroom #4	LAMINATE-LEXINGTO	ON - HAZELWOOD OAK TL-2101	6-M	
edroom #5				
ITCHEN/BREAKFAST	HARDWOOD- MIRAG	GE 5" ENGINEERED MAPLE CHA	ARACTER- DRIFTWOOD- DURAMATT	
Inderpad	Туре	Area	a	
Refer to Construct	ion Summary			
Dellings and D); alvata			
8. Railings and P		DECISIONED CALANIA	MIDACE DRIETWOOD	
Railing Type A	Pickets S PER CONSTRUCTION SF UROLINE 1	PECIFICATIONS Colour	MIRAGE- DRIFTWOOD BLACK	

Railing Type	AS PER CONSTRUCTION SPECIFICATIONS	Coloui	WIIITAGE BITTI TWOOD
Picket Type	EUROLINE 1	Colour	BLACK
Stringer / Riser	AS PER CONSTRUCTION SPECIFICATIO	Colour	MIRAGE- DRIFTWOOD
Treads	AS PER CONSTRUCTION SPECIFICATIO	Colour	MIRAGE- DRIFTWOOD
	Red Oak Stairs with Semi Gloss Finish		● Yes ○ No
** Refer to Cons	struction Summary		

Main & Upper Hall	22 WARM GREY	Master Bedroom	22 WARM GREY
Living Room	22 WARM GREY	Bedroom #2	22 WARM GREY
Dining Room	22 WARM GREY	Bedroom #3	22 WARM GREY
Kitchen / Breakfast	22 WARM GREY	Bedroom #4	22 WARM GREY
Family Room	22 WARM GREY	Bedroom #5	
Powder Room	22 WARM GREY	Master Ensuite	22 WARM GREY
Laundry Room	22 WARM GREY	Ensuite Bath - Bedroom 2/3	22 WARM GREY
Den/Library		Ensuite Bath - Bedroom 4	22 WARM GREY
Trim Paint-Semi Gloss	BIRCH WHITE		
Smooth Ceilings First I	Floor Yes	○ No	

Decor Advisor: Natalie	3-6100 / Mancuso 8 23-J Medallions mary Family	Model and Elevation: u -18 Kitchen/Breakfast Den/Library Lower Landing	Russell Gardens Build	ling Ltd.
Decor Advisor: Natalie	3-6100 / Mancuso 8 23-J Medallions mary Family	Project: Model and Elevation: u -18 Kitchen/Breakfast Den/Library Lower Landing	Russell Gardens Build Rosewood 3 Elev 1	ling Ltd.
Decor Advisor: Lock Date: 23-Jul-1 10. Plaster Mouldings and Entrance Vestibule Main Hall Living Room Dining Room Family Room ** Refer to Construction Sumr 11. Fireplace Living Room Purchased As Per Plan Fireplace Type Mantle Type Colour / Stain	Mancuso 8 23-J Medallions mary Family	Model and Elevation: u -18 Kitchen/Breakfast Den/Library Lower Landing	Rosewood 3 Elev 1	ling Ltd.
Lock Date: 23-Jul-18 10. Plaster Mouldings and Entrance Vestibule Main Hall Living Room Dining Room Family Room ** Refer to Construction Sumr 11. Fireplace Living Room Purchased As Per Plan Fireplace Type Mantle Type Colour / Stain	Medallions mary Family	Kitchen/Breakfast Den/Library Lower Landing		
10. Plaster Mouldings and Entrance Vestibule Main Hall Living Room Dining Room Family Room ** Refer to Construction Sumr 11. Fireplace Living Room Purchased As Per Plan O Fireplace Type Mantle Type Colour / Stain	Medallions mary Family	Kitchen/Breakfast Den/Library Lower Landing	Plan #: 62M-1238	
Entrance Vestibule Main Hall Living Room Dining Room Family Room ** Refer to Construction Sumr 11. Fireplace Living Room Purchased As Per Plan Pireplace Type Mantle Type Colour / Stain	mary	Den/Library Lower Landing		
Living Room Dining Room Family Room ** Refer to Construction Sumr 11. Fireplace Living Room Purchased As Per Plan Fireplace Type Mantle Type Colour / Stain	Family	Den/Library Lower Landing		
Dining Room Family Room ** Refer to Construction Sumr 11. Fireplace Living Room Purchased As Per Plan Fireplace Type Mantle Type Colour / Stain	Family	Lower Landing		
Family Room ** Refer to Construction Sumr 11. Fireplace Living Room Purchased As Per Plan Fireplace Type Mantle Type Colour / Stain	Family			
** Refer to Construction Sumr 11. Fireplace Living Room Purchased As Per Plan Fireplace Type Mantle Type Colour / Stain	Family	Deam		
T1. Fireplace Living Room Purchased As Per Plan Fireplace Type Mantle Type Colour / Stain	Family	Desir		
Fireplace Type Mantle Type Colour / Stain		Desir		
Fireplace Type Mantle Type Colour / Stain		Desir		
Fireplace Type Mantle Type Colour / Stain		Danie		
Purchased As Per Plan Fireplace Type Mantle Type Colour / Stain		Deam		
Fireplace Type Mantle Type Colour / Stain	N/A Purc		Other Room - Specify	
Mantle Type Colour / Stain		hased As Per Plan N/A	Purchased As Per Pla	n N/A
Mantle Type Colour / Stain	FLAT	ON WALL	0 0	•
		E M2-STANDARD		
O		R CONSTRUCTION SPECIFICATION	ONS	
Surround	BIANCO			
Hearth ** Refer to Construction Summar	NO			
12. Heating and Air Condition Air Conditioning No Gas Provisions Dryer No Comment * Refer to Construction Summar	0	Gas Provisio	ons Stove YES ons Barbecue NO	
13. Electrical				
Plugs and Switches White	DECOR	Abovo K	itahan Cahinat Linkt	() V - • N
	RD WHITE		itchen Cabinet Light	
			itchen Cabinet Light Stove N	licrowave
○ Yes	No Yes	_	<u> </u>	res No
Dishwasher Rough-in Yes				
* Refer to Construction Summary				
14. General Comments * Refer to Construction Summary				

Location Requirements

IMPORTANT: Observe all governing codes and ordinances. Do not obstruct flow of combustion and ventilation air

- It is the installer's responsibility to comply with installation clearances specified on the model/serial/rating plate. The model/serial/rating plate is located on the right vertical surface of the oven doorframe.
- It is recommended that a 600 CFM or larger range hood be installed above the range.
- It is not recommended that a microwave hood combination be mounted above the range.
- Recessed installations must provide complete enclosure of the sides and rear of the range.
- To eliminate the risk of burns or fire by reaching over the heated surface units, cabinet storage space located above the surface units should be avoided. If cabinet storage is to be provided, the risk can be reduced by installing a range hood that projects horizontally a minimum of 5" (12.7 cm) beyond the bottom of the cabinets.
- All openings in the wall or floor where range is to be installed must be sealed.
- Do not seal the range to the side cabinets.
- Cabinet opening dimensions that are shown must be used. Given dimensions are minimum clearances.
- The anti-tip bracket must be installed. To install the anti-tip bracket shipped with the range, see the "Install Anti-Tip Bracket" section.
- Grounded electrical supply is required. See the "Electrical Requirements" section.
- Proper gas supply connection must be available. See the "Gas Supply Requirements" section.
- Contact a qualified floor covering installer to check that the floor covering can withstand at least 200°F (93°C). Use an insulated pad or 1/4" (0.64 cm) plywood over carpet and under range if installing range over carpeting.

IMPORTANT: To avoid damage to your cabinets, check with your builder or cabinet supplier to make sure that the materials used will not discolor, delaminate, or sustain other damage. This oven has been designed in accordance with the requirements of UL and CSA International and complies with the maximum allowable wood cabinet temperatures of 194°F (90°C).

Mobile Home - Additional Installation Requirements

The installation of this range must conform to the Manufactured Home Construction and Safety Standard, Title 24 CFR, Part 3280 (formerly the Federal Standard for Mobile Home Construction and Safety, Title 24, HUD Part 280). When such standard is not applicable, use the Standard for Manufactured Home Installations, ANSI A225.1/NFPA 501A, or local codes.


In Canada, the installation of this range must conform with the current standards CAN/CSA-A240 latest edition or with

Mobile Home Installations Require:

When this range is installed in a mobile home, it must be secured to the floor during transit. Any method of securing the range is adequate as long as it conforms to the standards listed above.


Product Dimensions

30" (76.2 cm) models




- A. Optional backguard may be installed.
- 273/4" (70.5 cm) depth with control panel (See NOTE)
- 35³/>" (90.8 cm) cooktop height when sitting on the wheels
- D. 30" (76.2 cm) width E. Model/serial/rating plate location

36" (91.4 cm) models




- A. Optional backguard may be installed.
- B. 273/4" (70.5 cm) depth with control panel (See NOTE)
- 353/4" (90.8 cm) cooktop height when sitting on the wheels
- D. 36" (91.4 cm) width
- E. Model/serial/rating plate location



48" (121.9 cm) models

NOTE: The following illustration is for dimension planning purposes only, and the locations and appearances of the features shown may not match those of your model.




- A. Optional backguard may be installed.
- B. 27³/₄" (70.5 cm) depth with control panel (See NOTE) C. 35³/₄" (90.8 cm) cooktop height when sitting on the wheels
- D. 48" (121.9 cm) width
- E. Model/serial/rating plate location

NOTE: When installed in a 24" (61.0 cm) base cabinet with 25" (63.5 cm) countertop, front of oven door protrudes $1^7/8$ " (4.8 cm) beyond 24" (61.0 cm) base cabinet.

Cabinet Dimensions

Cabinet opening dimensions shown are for 25" (64.0 cm) countertop depth, 24" (61.0 cm) base cabinet depth, and 36" (91.4 cm) countertop height. Dimensions must be met in order to ensure a flush fit to back wall.

IMPORTANT: If installing a range hood or hood liner above the range, follow the range hood or hood liner installation instructions for dimensional clearances above the cooktop surface.



- A. 18" (45.7 cm) upper cabinet to countertop
 B. 30" (76.2 cm) model: 30" (76.2 cm) min. upper cabinet width
 36" (91.4 cm) model: 36" (91.4 cm) min. upper cabinet width
 48" (121.9 cm) model: 48" (121.9 cm) min. upper cabinet width
- C. 13" (33 cm) max. upper cabinet depth
- D. For minimum clearance to top of range**
- E. 30¹/₄" (76.8 cm) on 30" (76.2 cm) models 36¹/₄" (92.1 cm) on 36" (91.4 cm) models 48¹/₄" (122.6 cm) on 48" (121.9 cm) models
- F. 6" (15.2 cm) min. clearance from both sides of range to side wall or other combustible material
- G. 15" (38.1 cm)
- H. 22" (55.9 cm) on 30" (76.2 cm) models 28" (71.1 cm) on 36" (91.4 cm) models 40" (101.6 cm) on 48" (121.9 cm) models
- 11/2" (3.8 cm)
- J. 3" (7.6 cm)
- K. 5" (12.7 cm)
- L. 6" (15.2 cm) on 30" (76.2 cm) models 14" (35.5 cm) on 36" (91.4 cm) models 24" (61.0 cm) on 48" (121.9 cm) models
- M. 101/2" (26.7 cm)
- N. 6" (15.2 cm)
- O. 6" (15.2 cm)***

*Receptacle must be rotated 90° for Canadian installation.

**Minimum Clearances

30" (76.2 cm) models: 30" (76.2 cm) minimum clearance between the top of the cooking platform and the bottom of an uncovered wood or metal cabinet

36" (91.4 cm) models: 42" (106.7 cm) minimum clearance between the top of the cooking platform and the bottom of an uncovered wood or metal cabinet

48" (121.9 cm) models: 42" (106.7 cm) minimum clearance between the top of the cooking platform and the bottom of an uncovered wood or metal cabinet

***If the surface of the back wall is constructed of a combustible material and a backguard is not installed, a 6" (15.2 cm) minimum clearance is required for all models.

INSTALLATION REQUIREMENTS

Tools and Parts

Gather the required tools and parts before starting installation. Read and follow the instructions provided with any tools listed here.

Tools needed:

- Level
- Drill
- Drill 11/4" (3 cm) drill bit
- 3/32" (2.4 mm) drill bit if installing into wood
- Pencil
- Wire stripper or utility knife
- Tape measure or ruler
- Pliers
- Caulking gun and weatherproof caulking compound
- Vent clamps
- Jigsaw or keyhole saw
- Flat-blade screwdriver
- Metal snips
- Phillips screwdriver
- Scissors

Parts needed:

- Home power supply cable
- 1 1/2" (12.7 mm) UL listed or CSA approved strain relief
- 3 UL listed wire connectors
- 1 wall or roof cap
- Metal vent system
- 2 175-watt max heat lamp bulbs
- Blower motor system internal or external (see "Blower Motor System" in the "Accessories" section).

Parts supplied:

Remove parts from packages. Check that all parts are included.

- 2 metal grease filters for 36" (91.4 cm) models
 3 metal grease filters for 48" (121.9 cm) models
- Damper
- 2 Vent cover support brackets
- 2 10 x 50 mm wall anchor
- 2 8 x 40 mm wall anchor
- 2 D5.3 x 20 mm washers
- 4 5 x 45 mm screws
- 9 4.2 x 8 mm screws
- T20® TORX®† adapter

Location Requirements

IMPORTANT: Observe all governing codes and ordinances.

Have a qualified technician install the range hood. It is the installer's responsibility to comply with installation clearances specified on the model/serial/rating plate. The model/serial/rating plate is located inside the range hood on the rear wall of the range hood.

This range hood is recommended for use with cooktops with a maximum total rating of 105,000 BTUs or less.

Canopy range hood location should be away from strong draft areas, such as windows, doors and strong heating vents.

Cabinet opening dimensions that are shown must be used. Given dimensions provide minimum clearance.

The canopy range hood is factory set for venting through the roof or through the wall.


All openings in ceiling and wall where canopy range hood will be installed must be sealed.

For Mobile Home Installations:


The installation of this range hood must conform to the Manufactured Home Construction Safety Standards, Title 24 CFR, Part 328 (formerly the Federal Standard for Mobile Home Construction and Safety, Title 24, HUD, Part 280) or when such standard is not applicable, the standard for Manufactured Home Installation 1982 (Manufactured Home Sites, Communities and Setups) ANSI A225.1/NFPA 501A, or latest edition, or with local codes.

Product Dimensions

Vented Installations:



Installation Dimensions



IMPORTANT:

Minimum distance "X": 24" (61 cm) from electric cooking surfaces

Minimum distance "X": 30" (76.2 cm) from gas cooking surfaces

The chimneys can be adjusted for different ceiling heights. See the following chart.

Vented Installations		
	Min. ceiling height	Max. ceiling height
Electric cooking surface	7' 9" (2.36 m)	10' 2" (3.1 m)
Gas cooking surface	8' 3" (2.51 m)	10' 2" (3.1 m)

*NOTE: The range hood chimneys are adjustable and designed to meet varying ceiling or soffit heights depending on the distance "X" between the bottom of the range hood and the cooking surface. For higher ceilings, an Extension Kit Part Number W10352733 is available from your dealer or an authorized parts distributor. The chimney extension replaces the chimney shipped with the range hood.

Venting Requirements

- Vent system must terminate to the outdoors.
- Do not terminate the vent system in an attic or other enclosed area.
- Do not use 4" (10.2 cm) laundry-type wall caps.
- Use metal vent only. Rigid metal vent is recommended.
 Plastic or metal foil vent is not recommended.
- The length of vent system and number of elbows should be kept to a minimum to provide efficient performance.

For the Most Efficient and Quiet Operation:

- Use no more than three 90° elbows.
- Make sure there is a minimum of 24" (61.0 cm) of straight vent between the elbows if more than 1 elbow is used.
- Do not install 2 elbows together.
- Use clamps to seal all joints in the vent system.
- The vent system must have a damper. If the roof or wall cap has a damper, do not use the damper supplied with the range hood.
- Use caulking to seal exterior wall or roof opening around the cap.
- The size of the vent should be uniform.

Cold Weather Installations:

An additional back draft damper should be installed to minimize backward cold air flow and a thermal break should be installed to minimize conduction of outside temperatures as part of the vent system. The damper should be on the cold air side of the thermal break.

The break should be as close as possible to where the vent system enters the heated portion of the house.

Makeup Air:

Local building codes may require the use of makeup air systems when using ventilation systems greater than specified CFM of air movement. The specified CFM varies from locale to locale. Consult your HVAC professional for specific requirements in your area.

Venting Methods

Typical Internal Blower Motor System Venting Installations:

A 10" (25.4 cm) round vent system is needed for installation (not included). The range hood exhaust opening is 10" (25.4 cm) round.

NOTE: Flexible vent is not recommended. Flexible vent creates back pressure and air turbulence that greatly reduce performance.

Vent system can terminate either through the roof or wall. To vent through the wall, a 90° elbow is needed.

