

ROOM USE		FAM		L/D		K/B		L/H		LND		W/R		FOY		MUD				WOD		BAS		
EXP. WALL		36		30		37		19		12		18		18		30				46		182		
CLG. HT.		11		11		11		11		9		11		12		12				8		8		
FACTORS																								
GRS.WALL AREA		396		330		487		209		108		198		216		360				368		1116		
LOSS GAIN		LOSS GAIN		LOSS GAIN		LOSS GAIN		LOSS GAIN		LOSS GAIN		LOSS GAIN		LOSS GAIN		LOSS GAIN				LOSS GAIN		LOSS GAIN		
GLAZING																								
NORTH		19.8	16.1	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
EAST		19.8	39.0	0	0	0	0	0	0	0	0	0	22	435	858	6	119	234	0	0	0	0		
SOUTH		19.8	23.5	0	0	0	0	40	791	939	0	0	0	0	0	0	0	0	0	0	0	0		
WEST		19.8	39.0	40	791	1561	0	0	0	0	23	455	397	0	0	0	0	0	0	0	0	0		
SKYLT.		34.6	101.5	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
DOORS		23.5	4.3	0	0	0	0	0	0	0	0	0	0	0	0	40	938	179	0	0	0	0		
NET EXPOSED WALL		4.1	0.8	356	1476	268	290	1202	216	344	1426	259	196	813	147	101	419	76	176	730	132	170	765	128
NET EXPOSED BSMT WALL ABOVE GR		3.3	0.6	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
EXPOSED CLG		1.2	0.6	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
NO ATTIC EXPOSED CLG		2.6	1.3	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
EXPOSED FLOOR		2.4	0.4	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
BASEMENT/CRAWL HEAT LOSS		0		0		0		0		0		0		0		0		0		0		5736		
SLAB ON GRADE HEAT LOSS		0		0		0		0		0		0		0		0		0		0		0		
SUBTOTAL HT LOSS		2267		1993		2671		1070		772		1165		1762		1602		0		1120		7540		
SUB TOTAL HT GAIN				1828		1157		1762		453		346		991		532		371		626		526		
LEVEL FACTOR / MULTIPLIER		0.30	0.46	0.30		0.46	0.30	0.46	0.30	0.46	0.20	0.28	0.30	0.46	0.30	0.46	0.30	0.46	0.50		1.12			
AIR CHANGE HEAT LOSS		1049		922		1236		495		213		539		815		741				9664				
AIR CHANGE HEAT GAIN				157		99		151		39		30		85		46				98				
DUCT LOSS		0		0		0		0		0		0		0		0				0				
DUCT GAIN		0		0		0		0		0		0		0		0				0				
HEAT GAIN PEOPLE		240	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0		
HEAT GAIN APPLIANCES/LIGHTS		547		547		547		547		547		547		547		547		547		547		547		
TOTAL HT LOSS BTU/H		3316		2515		3908		1565		985		1703		2577		2343				1120		17203		
TOTAL HT GAIN x 1.3 BTU/H		3292		2345		3199		1350		1200		1399		751		524				817		1524		

TOTAL HEAT GAIN BTU/H: 35778	TONS: 3.06	LOSS DUE TO VENTILATION LOAD BTU/H: 1819	STRUCTURAL HEAT LOSS: 55131	TOTAL COMBINED HEAT LOSS BTU/H: 56949
------------------------------	------------	--	-----------------------------	---------------------------------------

SITE NAME: RUSSEL GARDENS PHASE 3
BUILDER: GREENPARK HOMES

LOT 258
TYPE: MOUNTAINASH 5

DATE: Oct-20

GFA: 3288

LO# 87759

HEATING CFM 1131 COOLING CFM 1131
TOTAL HEAT LOSS 55,131 TOTAL HEAT GAIN 36,449
AIR FLOW RATE CFM 20.51 AIR FLOW RATE CFM 31.03

furnace pressure 0.6
furnace filter 0.05
a/c coil pressure 0.2
available pressure for s/a & r/a 0.35

#GOODMAN
GMEC960803BNA 60
FAN SPEED LOW

AFUE = 96 %
INPUT (BTU/H) = 60,000
OUTPUT (BTU/H) = 57,600

RUN COUNT	4th	3rd	2nd	1st	Bas
S/A	0	0	14	8	4
R/A	0	0	6	2	1

plenum pressure s/a 0.18 r/a pressure 0.17
max s/a dif press. loss 0.02 r/a grille press. Loss 0.02
min adjusted pressure s/a 0.16 adjusted pressure r/a 0.15

MEDLOW
MEDIUM 928
MEDIUM HIGH 1017
HIGH 1131

DESIGN CFM = 1131
CFM @ .5" E.S.P.

TEMPERATURE RISE 47 °F

All S/A diffusers 4"x10" unless noted otherwise on layout.
All S/A runs 5"Ø unless noted otherwise on layout.

RUN #	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24
ROOM NAME	MBR	ENS	WIC	BED-3	BED-4	BED-5	ENS-3	BED-2	WIC-4	MBR	ENS-2	FAM	L/D	K/B	K/B	L/H	LND	W/R	FOY	MUD	BAS	BAS	BAS	BAS
RM LOSS MBH	1.32	2.18	0.55	2.00	1.71	1.16	0.80	1.53	0.66	1.32	0.53	3.32	2.92	1.95	1.95	1.56	0.99	1.70	2.58	2.34	4.58	4.58	4.58	4.58
CFM PER RUN HEAT	27	45	11	41	35	24	17	31	14	27	11	68	60	40	40	32	20	35	53	48	94	94	94	94
RM GAIN MBH	1.81	1.37	0.18	2.48	2.48	1.80	0.33	1.85	0.65	1.81	0.34	3.29	2.34	1.60	1.60	1.35	1.20	1.40	0.75	0.52	0.59	0.59	0.59	0.59
CFM PER RUN COOLING	56	42	6	77	77	56	10	57	20	56	11	102	73	50	50	42	37	43	23	16	18	18	18	18
ADJUSTED PRESSURE	0.17	0.17	0.17	0.17	0.17	0.17	0.17	0.17	0.17	0.17	0.17	0.16	0.17	0.17	0.17	0.17	0.17	0.17	0.17	0.17	0.16	0.16	0.16	0.16
ACTUAL DUCT LGH.	37	54	39	59	56	34	34	51	45	39	39	22	10	40	31	27	20	33	41	44	38	19	5	31
EQUIVALENT LENGTH	190	130	150	130	170	200	220	160	110	130	150	140	130	150	160	140	180	110	90	140	140	120	140	130
TOTAL EFFECTIVE LENGTH	227	184	189	189	226	234	254	211	155	169	189	162	140	190	191	167	200	143	131	184	178	139	145	161
ADJUSTED PRESSURE	0.08	0.09	0.09	0.09	0.08	0.07	0.07	0.08	0.11	0.1	0.09	0.1	0.12	0.09	0.09	0.1	0.09	0.12	0.13	0.09	0.09	0.12	0.11	0.1
ROUND DUCT SIZE	5	5	4	6	6	5	4	5	4	5	4	6	5	5	5	4	4	4	5	5	6	6	6	6
HEATING VELOCITY (ft/min)	198	330	126	209	178	176	195	228	161	198	126	347	441	294	294	367	229	402	389	352	479	479	479	479
COOLING VELOCITY (ft/min)	411	308	69	393	393	411	115	419	229	411	126	520	536	367	367	482	424	493	169	117	92	92	92	92
OUTLET GRILL SIZE	3X10	3X10	3X10	4X10	4X10	3X10	3X10	3X10	3X10	3X10	3X10	4X10	3X10	3X10	3X10	3X10	3X10	3X10	3X10	3X10	4X10	4X10	4X10	4X10
TRUNK	B	A	B	D	C	C	C	A	D	B	D	B	D	A	A	C	B	C	C	A	A	B	D	C

RUN #	25	26
ROOM NAME	BED-3	BED-4
RM LOSS MBH	2.00	1.71
CFM PER RUN HEAT	41	35
RM GAIN MBH	2.48	2.48
CFM PER RUN COOLING	77	77
ADJUSTED PRESSURE	0.17	0.17
ACTUAL DUCT LGH.	52	48
EQUIVALENT LENGTH	120	170
TOTAL EFFECTIVE LENGTH	172	218
ADJUSTED PRESSURE	0.1	0.08
ROUND DUCT SIZE	6	6
HEATING VELOCITY (ft/min)	209	178
COOLING VELOCITY (ft/min)	393	393
OUTLET GRILL SIZE	4X10	4X10
TRUNK	D	C

SUPPLY AIR TRUNK SIZE												RETURN AIR TRUNK SIZE														
	TRUNK CFM	STATIC PRESS.	ROUND DUCT	RECT DUCT	VELOCITY (ft/min)					TRUNK CFM	STATIC PRESS.	ROUND DUCT	RECT DUCT	VELOCITY (ft/min)					TRUNK CFM	STATIC PRESS.	ROUND DUCT	RECT DUCT	VELOCITY (ft/min)			
TRUNK A	298	0.08	8.9	10	x	8	536		TRUNK G	0	0.00	0	0	x	8	0		TRUNK O	0	0.05	0	0	x	8	0	
TRUNK B	545	0.08	11.2	14	x	8	701		TRUNK H	0	0.00	0	0	x	8	0		TRUNK P	0	0.05	0	0	x	8	0	
TRUNK C	325	0.07	9.5	12	x	8	488		TRUNK I	0	0.00	0	0	x	8	0		TRUNK Q	0	0.05	0	0	x	8	0	
TRUNK D	586	0.07	11.9	18	x	8	586		TRUNK J	0	0.00	0	0	x	8	0		TRUNK R	0	0.05	0	0	x	8	0	
TRUNK E	0	0.00	0	0	x	8	0		TRUNK K	0	0.00	0	0	x	8	0		TRUNK S	0	0.05	0	0	x	8	0	
TRUNK F	0	0.00	0	0	x	8	0		TRUNK L	0	0.00	0	0	x	8	0		TRUNK T	0	0.05	0	0	x	8	0	
																		TRUNK U	0	0.05	0	0	x	8	0	
																		TRUNK V	0	0.05	0	0	x	8	0	
																		TRUNK W	0	0.05	0	0	x	8	0	
RETURN AIR #	1	2	3	4	5	6	7	8								BR		TRUNK X	1041	0.05	16	30	x	8	625	
AIR VOLUME	90	85	90	90	85	75	360	85	0	0	0	0	0	0	0	171		TRUNK Y	695	0.05	13.8	22	x	8	569	
PLENUM PRESSURE	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15		TRUNK Z	445	0.05	11.6	16	x	8	501	
ACTUAL DUCT LGH.	41	52	53	58	53	59	45	41	1	1	1	1	1	1	1	15		DROP	1131	0.05	16.5	24	x	10	679	
EQUIVALENT LENGTH	185	195	165	165	215	265	165	190	0	0	0	0	0	0	0	150										
TOTAL EFFECTIVE LH	226	247	218	223	268	324	210	231	1	1	1	1	1	1	1	165										
ADJUSTED PRESSURE	0.07	0.06	0.07	0.07	0.06	0.05	0.07	0.06	14.80	14.80	14.80	14.80	14.80	14.80	14.80	0.09										
ROUND DUCT SIZE	5.9	6	5.9	5.9	6	6	9.9	6	0	0	0	0	0	0	0	7										
INLET GRILL SIZE	8	8	8	8	8	8	8	8	0	0	0	0	0	0	0	8										
	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X										
INLET GRILL SIZE	14	14	14	14	14	14	30	14	0	0	0	0	0	0	0	14										

TYPE: MOUNTAINASH 5
SITE NAME: RUSSEL GARDENS PHASE 3

LO # 87759
LOT 258

RESIDENTIAL MECHANICAL VENTILATION DESIGN SUMMARY

COMBUSTION APPLIANCES		9.32.3.1(1)
a) ☒	Direct vent (sealed combustion) only	
b) ☐	Positive venting induced draft (except fireplaces)	
c) ☐	Natural draft, B-vent or induced draft gas fireplace	
d) ☐	Solid Fuel (including fireplaces)	
e) ☐	No Combustion Appliances	

HEATING SYSTEM	
☒	Forced Air
☐	Non Forced Air
☐	Electric Space Heat

HOUSE TYPE		9.32.1(2)
☒	I Type a) or b) appliance only, no solid fuel	
☐	II Type I except with solid fuel (including fireplaces)	
☐	III Any Type c) appliance	
☐	IV Type I, or II with electric space heat	
☐	Other: Type I, II or IV no forced air	

SYSTEM DESIGN OPTIONS		O.N.H.W.P.
☐	1 Exhaust only/Forced Air System	
☐	2 HRV with Ducting/Forced Air System	
☒	3 HRV Simplified/connected to forced air system	
☐	4 HRV with Ducting/non forced air system	
☐	Part 6 Design	

TOTAL VENTILATION CAPACITY		9.32.3.3(1)
Basement + Master Bedroom	2 @ 21.2 cfm	42.4 cfm
Other Bedrooms	4 @ 10.6 cfm	42.4 cfm
Kitchen & Bathrooms	5 @ 10.6 cfm	53 cfm
Other Rooms	7 @ 10.6 cfm	74.2 cfm
Table 9.32.3.A.	TOTAL	212.0 cfm

PRINCIPAL VENTILATION CAPACITY REQUIRED		9.32.3.4.(1)
1 Bedroom	31.8	cfm
2 Bedroom	47.7	cfm
3 Bedroom	63.6	cfm
4 Bedroom	79.5	cfm
5 Bedroom	95.4	cfm
TOTAL	95.4	cfm

SUPPLEMENTAL VENTILATION CAPACITY		9.32.3.5.
Total Ventilation Capacity	212	cfm
Less Principal Ventil. Capacity	95.4	cfm
Required Supplemental Capacity	116.6	cfm

PRINCIPAL EXHAUST FAN CAPACITY	
Model: VANEE 65H	Location: BSMT
95.4 cfm	3.0 sones
☒ HVI Approved	

PRINCIPAL EXHAUST HEAT LOSS CALCULATION				
CFM	ΔT °F	FACTOR	% LOSS	
95.4 CFM	X 71 F	X 1.08	X	0.25

SUPPLEMENTAL FANS		PANASONIC		
Location	Model	cfm	HVI	Sones
ENS	FV-05-11VK1	50	☒	0.3
ENS-3	FV-05-11VK1	50	☒	0.3
ENS-2	FV-05-11VK1	50	☒	0.3
WR	FV-05-11VK1	50	☒	0.3

HEAT RECOVERY VENTILATOR		9.32.3.11.
Model: VANEE 65H		
155 cfm high	64 cfm low	
75 % Sensible Efficiency	☒ HVI Approved	
@ 32 deg F (0 deg C)		

LOCATION OF INSTALLATION	
Lot:	Concession
Township	Plan:
Address	
Roll #	Building Permit #

BUILDER: GREENPARK HOMES	
Name:	
Address:	
City:	
Telephone #:	Fax #:

INSTALLING CONTRACTOR	
Name:	
Address:	
City:	
Telephone #:	Fax #:

DESIGNER CERTIFICATION	
I hereby certify that this ventilation system has been designed in accordance with the Ontario Building Code.	
Name:	HVAC Designs Ltd.
Signature:	<i>Michael O'Rourke</i>
HRAI #	001820
Date:	October-20

I REVIEW AND TAKE RESPONSIBILITY FOR THE DESIGN WORK AND AM QUALIFIED IN THE APPROPRIATE CATEGORY AS AN "OTHER DESIGNER" UNDER DIVISION C, 3.2.5 OF THE BUILDING CODE.
INDIVIDUAL BCIN: 19889 *Michael O'Rourke* MICHAEL O'ROURKE

CSA F280-12 Residential Heat Loss and Heat Gain Calculations
Formula Sheet (For Air Leakage / Ventilation Calculation)

LO#: 87759

Model: MOUNTAINASH 5

Builder: GREENPARK HOMES

Date: 05/10/2020

Volume Calculation

House Volume			
Level	Floor Area (ft²)	Floor Height (ft)	Volume (ft³)
Bsmt	1451	8	11608
First	1451	11	15961
Second	1837	9	16533
Third	0	9	0
Fourth	0	9	0
Total:			44,102.0 ft³
Total:			1248.8 m³

Air Change & Delta T Data

WINTER NATURAL AIR CHANGE RATE	0.347
SUMMER NATURAL AIR CHANGE RATE	0.124

Design Temperature Difference				
	T _{in} °C	T _{out} °C	ΔT °C	ΔT °F
Winter DTD _h	22	-17	39	71
Summer DTD _c	24	31	7	13

5.2.3.1 Heat Loss due to Air Leakage

$$HL_{airb} = LR_{airh} \times \frac{V_b}{3.6} \times DTD_h \times 1.2$$

0.347 x 346.90 x 39 °C x 1.2 = 5665 W

= 19327 Btu/h

6.2.6 Sensible Gain due to Air Leakage

$$HG_{salb} = LR_{airc} \times \frac{V_b}{3.6} \times DTD_c \times 1.2$$

= 0.124 x 346.90 x 7 °C x 1.2 = 368 W

= 1255 Btu/h

5.2.3.2 Heat Loss due to Mechanical Ventilation

$$HL_{vaib} = PVC \times DTD_h \times 1.08 \times (1 - E)$$

95 CFM x 71 °F x 1.08 x 0.25 = 1819 Btu/h

6.2.7 Sensible heat Gain due to Ventilation

$$HL_{vaib} = PVC \times DTD_h \times 1.08 \times (1 - E)$$

95 CFM x 13 °F x 1.08 x 0.25 = 330 Btu/h

5.2.3.3 Calculation of Air Change Heat Loss for Each Room (Floor Multiplier Section)

$$HL_{airr} = Level\ Factor \times HL_{airbv} \times \{(HL_{agcr} + HL_{bgcr}) \div (HL_{agclevel} + HL_{bgclevel})\}$$

Level	Level Factor (LF)	HL _{airbv} Air Leakage + Ventilation Heat Loss (Btu/h)	Level Conductive Heat Loss: (HL _{devel})	Air Leakage Heat Loss Multiplier (LF x HL _{airbv} / HL _{level})
1	0.5	19,327	8,659	1.116
2	0.3		12,528	0.463
3	0.2		13,980	0.277
4	0		0	0.000
5	0		0	0.000

*HL_{airbv} = Air leakage heat loss + ventilation heat loss

*For a balanced or supply only ventilation system HL_{airv} = 0

HEAT LOSS AND GAIN SUMMARY SHEET

MODEL: MOUNTAINASH 5	LOT 258	BUILDER: GREENPARK HOMES
SFQT: 3288	LO# 87759	SITE: RUSSEL GARDENS PHASE 3

DESIGN ASSUMPTIONS

HEATING	°F	COOLING	°F
OUTDOOR DESIGN TEMP.	1	OUTDOOR DESIGN TEMP.	88
INDOOR DESIGN TEMP.	72	INDOOR DESIGN TEMP. (MAX 75°F)	75

BUILDING DATA

ATTACHMENT:	DETACHED	# OF STORIES (+BASEMENT):	3
FRONT FACES:	EAST	ASSUMED (Y/N):	Y
AIR CHANGES PER HOUR:	3.57	ASSUMED (Y/N):	Y
AIR TIGHTNESS CATEGORY:	AVERAGE	ASSUMED (Y/N):	Y
WIND EXPOSURE:	SHELTERED	ASSUMED (Y/N):	Y
HOUSE VOLUME (ft³):	44102.0	ASSUMED (Y/N):	Y
INTERNAL SHADING:	BLINDS/CURTAINS	ASSUMED OCCUPANTS:	6
INTERIOR LIGHTING LOAD (Btu/h/ft²):	1.27	DC BRUSHLESS MOTOR (Y/N):	Y
FOUNDATION CONFIGURATION	BCIN_1	DEPTH BELOW GRADE:	5.5 ft
LENGTH: 54.0 ft	WIDTH: 37.0 ft	EXPOSED PERIMETER:	182.0 ft

2012 OBC - COMPLIANCE PACKAGE		
Component	Compliance Package A1	
	Nominal	Min. Eff.
Ceiling with Attic Space Minimum RSI (R)-Value	60	59.22
Ceiling Without Attic Space Minimum RSI (R)-Value	31	27.65
Exposed Floor Minimum RSI (R)-Value	31	29.80
Walls Above Grade Minimum RSI (R)-Value	22	17.03
Basement Walls Minimum RSI (R)-Value	20 ci	21.12
Below Grade Slab Entire surface > 600 mm below grade Minimum RSI (R)-Value	-	-
Edge of Below Grade Slab ≤ 600 mm Below Grade Minimum RSI (R)-Value	10	10
Heated Slab or Slab ≤ 600 mm below grade Minimum RSI (R)-Value	10	11.13
Windows and Sliding Glass Doors Maximum U-Value	0.28	-
Skylights Maximum U-Value	0.49	-
Space Heating Equipment Minimum AFUE	0.96	-
HRV Minimum Efficiency	75%	-
Domestic Hot Water Heater Minimum EF	0.8	-


INDIVIDUAL BCIN: 19669

MICHAEL O'ROURKE



Residential Foundation Thermal Load Calculator

Supplemental tool for CAN/CSA-F280

Weather Station Description		
Province:	Ontario	
Region:	Hamilton	
Site Description		
Soil Conductivity:	Normal conductivity: dry sand, loam, clay	
Water Table:	Normal (7-10 m, 23-33 ft)	
Foundation Dimensions		
Floor Length (m):	16.5	 Insulation Configuration
Floor Width (m):	11.3	
Exposed Perimeter (m):	0.0	
Wall Height (m):	2.4	
Depth Below Grade (m):	1.68	
Window Area (m ²):	2.0	
Door Area (m ²):	1.9	
Radiant Slab		
Heated Fraction of the Slab:	0	
Fluid Temperature (°C):	33	
Design Months		
Heating Month	1	
Foundation Loads		
Heating Load (Watts):		1681

TYPE: MOUNTAINASH 5
LO# 87759

LOT 258


Air Infiltration Residential Load Calculator

Supplemental tool for CAN/CSA-F280

Weather Station Description				
Province:	Ontario			
Region:	Hamilton			
Weather Station Location:	Open flat terrain, grass			
Anemometer height (m):	10			
Local Shielding				
Building Site:	Suburban, forest			
Walls:	Heavy			
Flue:	Heavy			
Highest Ceiling Height (m):	7.92			
Building Configuration				
Type:	Detached			
Number of Stories:	Two			
Foundation:	Full			
House Volume (m ³):	1248.8			
Air Leakage/Ventilation				
Air Tightness Type:	Present (1961-) (3.57 ACH)			
Custom BDT Data:	ELA @ 10 Pa.	1664.7 cm ²		
	3.57	ACH @ 50 Pa		
Mechanical Ventilation (L/s):	Total Supply	Total Exhaust		
	45.0	45.0		
Flue Size				
Flue #:	#1	#2	#3	#4
Diameter (mm):	0	0	0	0
Natural Infiltration Rates				
Heating Air Leakage Rate (ACH/H):	0.347			
Cooling Air Leakage Rate (ACH/H):	0.124			

TYPE: MOUNTAINASH 5
LO# 87759

LOT 258



BASEMENT FLOOR PLAN '1'


LOT 258
CSA-F280-12
PACKAGE A1

I MICHAEL O'Rourke HAS REVIEWED AND TAKEN RESPONSIBILITY FOR THE DESIGN WORK AND AM QUALIFIED UNDER DIVISION C, 3.2.5 OF THE BUILDING CODE.
Michael O'Rourke
Michael O'Rourke, BCIN# 19669
HVAC DESIGNS LTD.

HVAC LEGEND						3.		
SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION	2.
	SUPPLY AIR GRILLE		6" SUPPLY AIR BOOT ABOVE		14"x8" RETURN AIR GRILLE		RETURN AIR STACK ABOVE	1.
	SUPPLY AIR GRILLE 6" BOOT		SUPPLY AIR STACK FROM 2nd FLOOR		30"x8" RETURN AIR GRILLE		RETURN AIR STACK 2nd FLOOR	No. Description Date
	SUPPLY AIR BOOT ABOVE		6" SUPPLY AIR STACK 2nd FLOOR		FRA- FLOOR RETURN AIR GRILLE		REDUCER	REVISIONS

ALL DRAWINGS, CALCULATIONS AND SPECIFICATIONS ARE THE PROPERTY OF HVAC DESIGNS LTD.© AND MAY NOT BE REPRODUCED, MODIFIED OR ALTERED WITHOUT EXPRESSED WRITTEN CONSENT. THE DRAWINGS ARE DATED AND USE OF THESE DRAWINGS AFTER ONE YEAR FROM THE DATED NOTED IS NOT AUTHORIZED. CONTRACTOR SHALL CHECK ALL CONDITIONS BEFORE PROCEEDING WITH WORK. LATEST MUNICIPAL APPROVED DRAWINGS ONLY TO BE USED DURING INSTALLATION OF HEATING SYSTEM. HVAC DESIGNS LTD. IS NOT LIABLE FOR ANY CLAIMS ARISING FROM UNAUTHORIZED USE OF THE DRAWINGS OR FROM ANY CHANGES TO ACCEPTED STANDARDS AND/OR THE ONTARIO BUILDING CODE.

Client GREENPARK HOMES		 375 Finley Ave. Suite 202 - Ajax, Ontario L1S 2E2 Tel. 905.619.2300 - 905.420.5300 Fax 905.619.2375 Email: info@hvacdesigns.ca Web: www.hvacdesigns.ca Specializing in Residential Mechanical Design Services Installation to comply with the latest Ontario Building Code. All supply branch outlets shall be equipped with a manual balancing damper. Ductwork which passes through the garage or unheated spaces shall be adequately insulated and be gas-proofed.	HEAT LOSS 56949 BTU/H UNIT DATA		# OF RUNS S/A R/A FANS			Sheet Title BASEMENT HEATING LAYOUT	
Project Name RUSSEL GARDENS PHASE 3 HAMILTON, ONTARIO			MAKE GOODMAN	3RD FLOOR					Date OCT/2020
			MODEL GMEC960603BNA	2ND FLOOR		14	6	3	
			INPUT 60 MBTU/H	1ST FLOOR		8	2	2	
			OUTPUT 57.6 MBTU/H	BASEMENT		4	1	0	
LOT 258 MOUNTAINASH 5 3288 sqft		COOLING 3.0 TONS	ALL S/A DIFFUSERS 4 "x10" UNLESS NOTED OTHERWISE ON LAYOUT. ALL S/A RUNS 5"Ø UNLESS NOTED OTHERWISE ON LAYOUT. UNDERCUT DOORS 1" min. FOR R/A						Scale 3/16" = 1'-0"
		FAN SPEED 1131 cfm @ 0.6" w.c.							BCIN# 19669
								LO# 87759	




I MICHAEL O'Rourke HAVE REVIEWED AND TAKE RESPONSIBILITY FOR THE DESIGN WORK AND AM QUALIFIED UNDER DIVISION C.23.5 OF THE BUILDING CODE.
Michael O'Rourke
Michael O'Rourke, BCIN# 19669
HVAC DESIGNS LTD.

LOT 258
CSA-F280-12
PACKAGE A1

HVAC LEGEND						3.		
SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION	
	SUPPLY AIR GRILLE		6" SUPPLY AIR BOOT ABOVE		14"x8" RETURN AIR GRILLE		RETURN AIR STACK ABOVE	2.
	SUPPLY AIR GRILLE 6" BOOT		SUPPLY AIR STACK FROM 2nd FLOOR		30"x8" RETURN AIR GRILLE		RETURN AIR STACK 2nd FLOOR	1.
	SUPPLY AIR BOOT ABOVE		6" SUPPLY AIR STACK 2nd FLOOR		FRA- FLOOR RETURN AIR GRILLE		REDUCER	No. Description Date
REVISIONS								

ALL DRAWINGS, CALCULATIONS AND SPECIFICATIONS ARE THE PROPERTY OF HVAC DESIGNS LTD.© AND MAY NOT BE REPRODUCED, MODIFIED OR ALTERED WITHOUT EXPRESSED WRITTEN CONSENT. THE DRAWINGS ARE DATED AND USE OF THESE DRAWINGS AFTER ONE YEAR FROM THE DATED NOTED IS NOT AUTHORIZED. CONTRACTOR SHALL CHECK ALL CONDITIONS BEFORE PROCEEDING WITH WORK. LATEST MUNICIPAL APPROVED DRAWINGS ONLY TO BE USED DURING INSTALLATION OF HEATING SYSTEM. HVAC DESIGNS LTD. IS NOT LIABLE FOR ANY CLAIMS ARISING FROM UNAUTHORIZED USE OF THE DRAWINGS OR FROM ANY CHANGES TO ACCEPTED STANDARDS AND/OR THE ONTARIO BUILDING CODE.

Client GREENPARK HOMES		HVACDESIGNS LTD. 375 Finley Ave. Suite 202 - Ajax, Ontario L1S 2E2 Tel. 905.619.2300 - 905.420.5300 Fax 905.619.2375 Email: info@hvacdesigns.ca Web: www.hvacdesigns.ca Specializing in Residential Mechanical Design Services Installation to comply with the latest Ontario Building Code. All supply branch outlets shall be equipped with a manual balancing damper. Ductwork which passes through the garage or unheated spaces shall be adequately insulated and be gas-proofed.	Sheet Title FIRST FLOOR HEATING LAYOUT	
Project Name RUSSEL GARDENS PHASE 3 HAMILTON, ONTARIO			Date OCT/2020	Scale 3/16" = 1'-0"
LOT 258 MOUNTAINASH 5 3288 sqft			BCIN# 19669	
			LO#	87759



SECOND FLOOR PLAN '1'
(5 BEDROOM PLAN)

LOT 258
CSA-F280-12
PACKAGE A1

I MICHAEL O'Rourke HAVE REVIEWED AND TAKE RESPONSIBILITY FOR THE DESIGN WORK AND AM QUALIFIED UNDER DIVISION C, 3.2.5 OF THE BUILDING CODE.
Michael O'Rourke
Michael O'Rourke, BCIN# 19669
HVAC DESIGNS LTD.

HVAC LEGEND								3.		
SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION	2.		
	SUPPLY AIR GRILLE		6" SUPPLY AIR BOOT ABOVE		14"x8" RETURN AIR GRILLE		RETURN AIR STACK ABOVE	1.		
	SUPPLY AIR GRILLE 6" BOOT		SUPPLY AIR STACK FROM 2nd FLOOR		30"x8" RETURN AIR GRILLE		RETURN AIR STACK 2nd FLOOR	No.	Description	Date
	SUPPLY AIR BOOT ABOVE		6" SUPPLY AIR STACK 2nd FLOOR		FRA- FLOOR RETURN AIR GRILLE		REDUCER	REVISIONS		

ALL DRAWINGS, CALCULATIONS AND SPECIFICATIONS ARE THE PROPERTY OF HVAC DESIGNS LTD.© AND MAY NOT BE REPRODUCED, MODIFIED OR ALTERED WITHOUT EXPRESSED WRITTEN CONSENT. THE DRAWINGS ARE DATED AND USE OF THESE DRAWINGS AFTER ONE YEAR FROM THE DATED NOTED IS NOT AUTHORIZED. CONTRACTOR SHALL CHECK ALL CONDITIONS BEFORE PROCEEDING WITH WORK. LATEST MUNICIPAL APPROVED DRAWINGS ONLY TO BE USED DURING INSTALLATION OF HEATING SYSTEM. HVAC DESIGNS LTD. IS NOT LIABLE FOR ANY CLAIMS ARISING FROM UNAUTHORIZED USE OF THE DRAWINGS OR FROM ANY CHANGES TO ACCEPTED STANDARDS AND/OR THE ONTARIO BUILDING CODE.

Client		HVACDESIGNS LTD. 375 Finley Ave. Suite 202 - Ajax, Ontario L1S 2E2 Tel. 905.619.2300 - 905.420.5300 Fax 905.619.2375 Email: info@hvacdesigns.ca Web: www.hvacdesigns.ca Specializing in Residential Mechanical Design Services Installation to comply with the latest Ontario Building Code. All supply branch outlets shall be equipped with a manual balancing damper. Ductwork which passes through the garage or unheated spaces shall be adequately insulated and be gas-proofed.	Sheet Title	
GREENPARK HOMES			SECOND FLOOR HEATING LAYOUT	
Project Name			Date	OCT/2020
RUSSEL GARDENS PHASE 3 HAMILTON, ONTARIO			Scale	3/16" = 1'-0"
LOT 258 MOUNTAINASH 5 3288 sqft			BCIN# 19669	
			LO#	87759