



Engineering Notes: FWP-Floors

MHP 23032



PLEASE READ ALL NOTES PRIOR TO INSTALLATION OF THE COMPONENT

RESPONSIBILITIES

THE RESPONSIBILITY OF THE UNDERSIGNED ENGINEER IS ONLY LIMITED TO THE CALCULATION OF THIS BUILDING COMPONENT FOR THE LOADS AND CONDITIONS SHOWN ON THIS DRAWING.

THE RESPONSIBILITY OF THE UNDERSIGNED IS LIMITED TO THE VERIFICATION OF THE STRUCTURAL CAPACITY OF THE FLOOR JOISTS AND LVL BEAMS BASED ON PLACEMENT AS SHOWN ON THE LAYOUT. THE LOADS APPLIED ARE LIMITED TO THE GRAVITY EFFECTS OF THE SPECIFIED LOADS. THE STRUCTURAL INTEGRITY OF THE BUILDING AND THE EFFECT OF WIND, UPLIFT, SEISMIC, LATERAL OR OTHER FORCES, CALCULATION OF ADEQUATE SUPPORT AND ANCHORAGE OF COMPONENTS, AS WELL AS THE DIMENSIONS AND DESIGN LOADS USED TO CALCULATE COMPONENTS ARE THE RESPONSIBILITY OF THE OVERALL BUILDING DESIGNER. FLOOR JOISTS AND OSB RIM BOARD ARE DESIGNED TO CARRY UNIFORMLY DISTRIBUTED LOADS ONLY. POINT LOADS SHOULD BE TRANSFERRED THROUGH THE FLOOR CAVITY WITH TRANSFER BLOCKS. STRUCTURAL ELEMENTS SUCH AS WALLS, POSTS, CONNECTORS, AND TRANSFER BLOCKS ARE THE RESPONSIBILITY OF THE OVERALL BUILDING DESIGNER.

THE UNDERSIGNED ENGINEER DISCLAIMS ANY RESPONSIBILITY FOR DAMAGES AS A RESULT OF BEING FURNISHED FAULTY OR INCORRECT INFORMATION, SPECIFICATIONS AND/OR DESIGNS.

COMPONENT DESIGN INFORMATION

1. THIS BUILDING COMPONENT IS CERTIFIED AS AN INDIVIDUAL COMPONENT FOR THE LOADS AND CONDITIONS SHOWN ON THE CALCULATION PAGE BASED ON INFORMATION PROVIDED BY KOTT DESIGN.
2. THE BUILDING COMPONENT USED IN CONSTRUCTION MUST BE THE SAME AS INDICATED ON THE DRAWINGS.
3. UNLESS NOTED OTHERWISE ON THE LAYOUT OR BEAM CALCULATION SHEET, MEMBERS CONSISTING OF MULTIPLE PLIES MUST BE CONNECTED AS PER THE DOCUMENT "MULTIPLE MEMBER CONNECTION DETAILS" SHOWN ON PAGE 2 OF THIS DOCUMENT.
4. PASS-THRU TRANSFER BLOCK FRAMING IS REQUIRED AT ALL POINT LOADS OVER BEARINGS.
5. IT IS ASSUMED THAT EACH LVL BEAM WHERE NOT SEATED IN A HANGER IS ATTACHED USING (4) FOUR 3-1/4" COMMON SPIRAL NAILS FOR UP TO 5.5" LONG BEARINGS AND USING (6) SIX 3-1/4" COMMON SPIRAL NAILS FOR BEARINGS EQUAL TO OR LONGER THAN 5.5", UNLESS INDICATED OTHERWISE.

CODE

THIS BUILDING COMPONENT IS DESIGNED IN ACCORDANCE WITH THE NATIONAL BUILDING CODE OF CANADA, THE ONTARIO BUILDING CODE, CCMC AND CANADIAN STANDARDS ASSOCIATION GUIDELINES.


HANDLING AND INSTALLATION

1. DO NOT DRILL ANY HOLE, CUT OR NOTCH A CERTIFIED BUILDING COMPONENT WITHOUT A WRITTEN PRE-AUTHORIZATION.
2. INSTALLATION AND ASSEMBLY OF FLOOR JOISTS AND LVL BEAMS IS TO BE CARRIED OUT IN ACCORDANCE WITH THE CURRENT EDITION OF THE MANUFACTURER'S LITERATURE.

MULTIPLE MEMBER CONNECTIONS FOR BEAMS SHOWN ON KOTT LAYOUTS



MULTIPLE MEMBER CONNECTIONS FOR UNIFORMLY DISTRIBUTED TOP & SIDE LOADED LVL BEAMS SHOWN ON KOTT LAYOUTS



LVL Connection Notes:

- LVL ply width is 1-3/4"
- Nails to be 3 1/2" common wire nails.
- Nails to be located 2 1/2" min. from the top and bottom of the member. Start all nails 2 1/2" min. from ends.
- Minimum 3 1/4" spacing between rows.
- Number of rows and spacing as per details shown, unless noted otherwise.
- "X" represents nail driven from the opposite side.
- Head of all specified screws must be on the loaded side.

FOR 4 PLY BEAMS*, ATTACH PLYS TOGETHER USING 6-3/4" SDW SCREWS IN 3 ROWS @ 16" C/C.

USE AN ADDITIONAL THREE (3) 6-3/4" SDW SCREWS ON EACH SIDE (OF EACH FACE) AT POINT LOAD LOCATIONS @ 1/2 SPACING, WHERE APPLICABLE.

*UNLESS NOTED OTHERWISE ON LAYOUT OR CALCULATION SHEET OF BEAM IN THE FLOOR PACKAGE

FOR MULTIPLE MEMBER CONNECTION OF BOISE ALLJOISTS REFER TO THE BOISE CASCADE INSTALLATION GUIDE

Installation Guide




(Open your phone's camera and hover over this QR code to access it)

Last Revised January 13, 2023

ENG-M0723-103-KTF-GREENPARK-ZADORRA ESTATES-ROSE 12-2

Page 3 of 53

Ground Floor



Ground Floor										JOB INFORMATION	
LVL/LSL (Flush)										Builder	
Label	Description	Width	Depth	Qty	Piles	Pcs	Length			GREENPARK	
F8	Versa-Lam LVL 2.1E 3100 SP	1.75	11.875	1	2	2	18-0-0			Project	
F11	Versa-Lam LVL 2.1E 3100 SP	1.75	11.875	2	2	4	12-0-0			Shipping	
F6	Versa-Lam LVL 2.1E 3100 SP	1.75	11.875	1	2	2	10-0-0			ZADORRA ESTATES OSHAWA, ON	
F5	Versa-Lam LVL 2.1E 3100 SP	1.75	11.875	1	2	2	8-0-0			Sales Rep	
F4	Versa-Lam LVL 2.1E 3100 SP	1.75	11.875	3	2	6	6-0-0			RALPH MIRIGELLO	
FH2	Versa-Lam LVL 2.1E 3100 SP	1.75	11.875	1	2	2	4-0-0			Designer	
Joist (Flush)										Plotted	
Label	Description	Width	Depth	Pcs	Length					June 16, 2023	
F12	AJS 140	2.5	11.875	3	18-0-0					Layout Name	
F2	AJS 140	2.5	11.875	1	14-0-0					ROSE 12-2 STD	
F1	AJS 140	2.5	11.875	8	2-0-0					Job Path	
J4	AJS 140	2.5	11.875	35	18-0-0					S:\CUSTOMERS\GREENPARK\ZADORRA ESTATES	
J5	AJS 140	2.5	11.875	9	14-0-0					MODELS\ROSE 12\ROSE 12-2\ROSE 12-2\ROSE	
J3	AJS 140	2.5	11.875	11	12-0-0					12-2\JL	
J2	AJS 140	2.5	11.875	3	8-0-0						
J1	AJS 140	2.5	11.875	4	4-0-0						
Rim Board										DESIGN CRITERIA	
Label	Description	Width	Depth	Pcs	Length					Ground Floor	
R1	Norbord Rimboard Plus 1.125 X 11.875	1.125	11.875	13	12-0-0					Design Method	
Blocking										LSD (Canada)	
Label	Description	Width	Depth	Qty	Pcs	Length				NBCC 2015	
BLK1	AJS 140	2.5	11.875	1	53-0-0					OBC 2012(2020 Update)	
Hanger										Floor	
Label	Pcs	Description	fasteners	fasteners						Live	
H1	34	LP2511	12 10x1 1/2	1 #5x1 1/4WS						Dead	
H3	5	LP3511	12 10x1	2 #5x1 1/4WS						Deflection Joist	
Legend										LL Span /	
										TL Span /	
										Deflection Flush Girder	
										LL Span /	
										TL Span /	
										Deflection Dropped Girder	
										LL Span /	
										TL Span /	
										Deflection Header	
										LL Span /	
										TL Span /	
										Decking	
										OSB	
										Thickness	
										3/4"	
										Fastener	
										Nailed & Glued	
										CCMC References	
										Boise - 12472-R, 12787-R	
										LP - 12412-R, Roseburg - 13310-R	
										Forex - 14035-R	
										Kott Inc.	
										3228 Woodle Dr, Ottawa	
										14 Anderson Blvd, Uxbridge	
										Ontario	
										613-838-2775 /	
										905-642-4400	
										1. All blocking to be cut from 12" joists	
										2. 2' & 4' Lengths to be cut from 8' Length, 6' lengths to be cut from 12' Length	
										3. Ends of joists to be laterally supported	
										4. Pacing of steel beams and attachment by others	
										5. Shower and water closet flange locations are approximate only, consult architectural drawing for exact locations	
										6. Beams identified as "B1" are dropped and supplied by others	
										7. Install 2x4 blocking @ 24" o/c under parallel non-loadbearing walls	
										8. Load transfer blocks to be installed under all point loads	
										9. Refer to Multiple Member Connection Detail for ply to ply nailing or bolting requirements	
										10. Hangers and Fasteners to be installed as per manufacturer	
										11. Framing shown on this layout may deviate from architectural drawings, Arch / Eng to review and approve the deviation prior to construction,	
										12. Multi ply beams with side loading to have all fasteners installed with the head on the side of the applied load	
										13. Confirmation of adequate support & anchorage of components is the responsibility of the building designer, suggested up/lift connectors are as shown	
										here, where beam hangs on side of 3-ply member, it is recommended that the equivalent quantity and size of nails required for the hanger attachment also be installed on opposite side of the 3-ply member	

Installation Guide





(Open your phone's camera and
hover over this QR code to access it)

Hatch Area represents where
additional load has been applied.
(e.g. 5 psf for ceramic tile)

ENG-M0723-103-KTF-GREENPARK-ZADORRA ESTATES-ROSE 12-2

Page 30 of 51

Ground Floor



Installation Guide



(Open your phone's camera and
hover over this QR code to access it)

Hatch Area represents where
additional load has been applied.
(e.g. 5 psf for ceramic tile)

Ground Floor										JOB INFORMATION	
LVL/LSL (Flush)										Builder	
Label	Description	Width	Depth	Qty	Pieces	Pcs	Len...			GREENPARK	
F8	Versa-Lam LVL 2.1E 3100 SP	1.75	11.875	1	2	2	18-0			Project	
F11	Versa-Lam LVL 2.1E 3100 SP	1.75	11.875	2	2	4	12-0			Shipping	
F6	Versa-Lam LVL 2.1E 3100 SP	1.75	11.875	1	2	2	10-0			ZADORRA ESTATES OSHAWA, ON	
F5	Versa-Lam LVL 2.1E 3100 SP	1.75	11.875	1	2	2	8-0			Sales Rep	
F4	Versa-Lam LVL 2.1E 3100 SP	1.75	11.875	3	2	6	6-0			Designer	
FH2	Versa-Lam LVL 2.1E 3100 SP	1.75	11.875	3	2	6	4-0			Plotted	
Joist (Flush)										July 14, 2023	
Label	Description	Width	Depth	Pcs	Length					Layout Name	
F12	AJS 140	2.5	11.875	1	18-0					ROSE 12-2 DC	
F2	AJS 140	2.5	11.875	1	14-0					Job Path	
F1	AJS 140	2.5	11.875	4	2-0					S:\CUSTOMERS\GREENPARK\ZADORRA ESTATES	
J4	AJS 140	2.5	11.875	37	18-0					MODEL\ROSE 12\ROSE 12-2F-ROSE 12-2DC	
J5	AJS 140	2.5	11.875	9	14-0					ROSE 12-2 DC.H	
J3	AJS 140	2.5	11.875	11	12-0					DESIGN CRITERIA	
J2	AJS 140	2.5	11.875	3	8-0					Ground Floor	
J1	AJS 140	2.5	11.875	4	4-0					Design Method	
Rim Board										LSD (Canada)	
Label	Description	Width	Depth	Pcs	Length					NBCC 2015	
R1	Norbord Rimboard Plus 1.125 X 11.875	1.125	11.875	13	12-0					OBCC 2012(2020 Update)	
Blocking										Floor	
Label	Description	Width	Depth	Qty	Pcs	Length				Loads	
BLK1	AJS 140	2.5	11.875	1	36-0					Live	
Hanger										Dead	
										Deflection Joist	
Label	Pcs	Description	fasteners	fasteners						LL Span /	
H1	35	LP2511	12 10dX1 1/2	1 8dX1 1/4WS						TL Span /	
H3	5	LP3511	12 10d	2 8dX1 1/4WS						Deflection Flush Girder	
										LL Span /	
										Deflection Dropped Girder	
										LL Span /	
										Deflection Header	
										LL Span /	
										Decking	
										Decking	
										Thickness	
										3/4"	
										Fastener	
										Nailed & Glued	
										CCMC References	
										Boise - 12472-R, 12787-R	
										LP - 12412-R, Roseburg - 13310-R	
										Forex - 14035-R	
										Kott Inc.	
										3228 Woodle Dr, Ottawa	
										14 Anderson Blvd, Unbridge	
										Ontario	
										613-838-2775 /	
										905-642-4400	


1. All blocking to be cut from 12" joists
2. Z & 4 Lengths to be cut from 8' Length, 6' lengths to be cut from 12' Length
3. Ends of joists to be laterally supported
4. Packing of Steel beams and attachment by others
5. Shower and water closet flange locations are approximate only, consult architectural drawing for exact locations
6. Beams identified as "B" are dropped and supplied by others
7. Install 2x4 blocking @ 24" o/c under parallel non-loadbearing walls
8. Load transfer blocks to be installed under all point loads
9. Refer to Multiple Member Connection Detail for ply to ply nailing or bolting requirements
10. Hangers and Fasteners to be installed as per manufacturer
11. Framing shown on this layout may deviate from architectural drawings, Arch / Eng to review and approve the deviation prior to construction
12. Multi ply beams with side loading to have all fasteners installed with the head on the side of the applied load
13. Confirmation of adequate support & anchorage of components is the responsibility of the building designer, suggested up/lift connectors are as shown
14. Where beam hangs on side of 3-ply member, it is recommended that the equivalent quantity and size of nails required for the hanger attachment also be installed on opposite side of the 3-ply member



ENG-M0723-103-KTF-GREENPARK-ZADORRA ESTATES-ROSE 12-2

Page 18 of 51

Second Floor



Second Floor										JOB INFORMATION	
LVL/LSL (Flush)										Builder	
F8	Versa-Lam LVL 2.1E 3100 SP	1.75	11.875	1	2	2	18-0			GREENPARK	
F11	Versa-Lam LVL 2.1E 3100 SP	1.75	11.875	2	2	4	12-0			Project	
F8	Versa-Lam LVL 2.1E 3100 SP	1.75	11.875	1	2	2	10-0			Shipping	
F5	Versa-Lam LVL 2.1E 3100 SP	1.75	11.875	1	2	2	8-0			Sales Rep	
F10	Versa-Lam LVL 2.1E 3100 SP	1.75	11.875	1	2	2	2-0			Designer	
LVL/LSL (Dropped)										Plotted	
B7	Versa-Lam LVL 2.1E 3100 SP	1.75	9.5	2	2	4	12-0			June 16, 2023	
B4	Versa-Lam LVL 2.1E 3100 SP	1.75	9.5	1	2	2	8-0			Layout Name	
										ROSE 12-2 STD & DC	
Joist (Flush)										Job Path	
J7	AJS 140	2.5	11.875	17			20-0			8\CUSTOMER\GREENPARK\ZADORRA ESTATES	
J4	AJS 140	2.5	11.875	30			18-0			MODELS\ROSE 12\ROSE 12-2\ROSE 12-2\ROSE	
J6	AJS 140	2.5	11.875	11			16-0			12-2\J1	
J5	AJS 140	2.5	11.875	11			14-0			DESIGN CRITERIA	
J3	AJS 140	2.5	11.875	15			12-0			Second Floor	
J2	AJS 140	2.5	11.875	4			8-0			Design Method	
Rim Board										Building Code	
R1	Norford Rimboard Plus 1.125 X 11.875	1.125	11.875	15			12-0			LSD (Canada)	
Blocking										Floor	
BLK1	AJS 140	2.5	11.875	1			12-0			Live	
Hanger										Dead	
H1	2B	2.5	12.104	1			12-0			Deflection Joist	
H2	1	14.166	6.103							LL Span /	
H3	3	12.104	2 #8x1 1/4WS							TL Span /	
										Deflection Flush Girder	
										LL Span /	
										TL Span /	
										Deflection Dropped Girder	
										LL Span /	
										TL Span /	
										Deflection Header	
										LL Span /	
										TL Span /	
										Decking	
										Thickness	
										Fastener	
										Nailed & Glued	
Legend										CCMC References	
										Boise - 12472-R, 12787-R	
										LP - 12412-R, Roseburg - 13310-R	
										Forex - 14095-R	
										Kott Inc.	
										3228 Wood Dr. Ottawa	
										14 Anderson Blvd. Unbridge	
										Ontario	
										613-838-2775 /	
										805-542-1400	
										KOTT	
										1. All blocking to be cut from 12' joists	
										2. 2' & 4' Lengths to be cut from 8' Length, 6' lengths to be cut from 12' Length	
										3. Ends of joists to be laterally supported	
										4. Packing of Steel beams and attachment by others	
										5. Shower and water closet flange locations are approximate only, consult architectural drawing for exact locations	
										6. Beams identified as "B" are dropped and supplied by others	
										7. Install 2x4 blocking @ 24" o/c under parallel non-loadbearing walls	
										8. Load transfer blocks to be installed under all point loads	
										9. Refer to Multiple Member Connection Detail for ply to ply nailing or bolting requirements	
										10. Hangers and Fasteners to be installed as per manufacturer	
										11. Framing shown on this layout may deviate from architectural drawings. Arch / Eng to review and approve the deviation prior to construction.	
										12. Multi ply beams with side loading to have all fasteners installed with the head on the side of the applied load	
										13. Confirmation of adequate support & anchorage of components is the responsibility of the building designer, suggested uplift connectors are as shown	
										14. Where beam hangs on side of 3-ply member, it is recommended that the equivalent quantity and size of nails required for the hanger attachment also be installed on opposite side of the 3-ply member	

Installation Guide



(Open your phone's camera and
hover over this QR code to access it)

Hatch Area represents where
additional load has been applied.
(e.g. 5 psf for ceramic tile)

CORPORATION OF THE CITY OF OSHAWA
TRUE COPY
OF PERMIT PLANS
NOV 03 2023


Client: GREENPARK
Project:
Address: ZADORRA ESTATES
OSHAWA, ON

Date: 7/14/2023
Input by: W C
Job Name: ROSE 12-2 STD
Project #:


Page 1 of 41

F1 A. *C. Morris* 375" - PASSED
CHIEF BUILDING OFFICIAL

Level: Ground Floor



1 Hanger (LF2511) 0-2-0
2 SPF 0-2-6
1'4 15/16"
1'4 15/16"



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2015 OBC 2012(2020 Update)
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal - II	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Direction	Live	Dead	Snow	Wind
1	Vertical	44	16	0	0
2	Vertical	46	17	0	0

Bearings and Factored Reactions

Bearing	Length	Dir.	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - Hanger	2.000"	Vert	5%	20 / 66	86	L	1.25D+1.5L
2 - SPF	2.375"	Vert	5%	21 / 69	90	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	21 ft-lb	8 1/4"	5305 ft-lb	0.004 (0%)	1.25D+1.5L	L
Unbraced	21 ft-lb	8 1/4"	5305 ft-lb	0.004 (0%)	1.25D+1.5L	L
Shear	73 lb	1 1/4"	2350 lb	0.031 (3%)	1.25D+1.5L	L
Perm Defl in. (L/224856)	0.000	8 5/16"	0.039 (L/360)	0.002 (0%)	D	Uniform
LL Defl inch (L/84321)	0.000	8 5/16"	0.039 (L/360)	0.004 (0%)	L	L
TL Defl inch (L/61324)	0.000	8 5/16"	0.059 (L/240)	0.004 (0%)	D+L	L



JULY 14, 2023

Design Notes

- Provide support to prevent lateral movement and rotation at the end bearings. Lateral support may also be required at the interior bearings by the building code.
- Fill all hanger nailing holes.
- Left Header: SPF, Thickness: 2 1/2"
- Girders are designed to be supported on the bottom edge only.
- If sheathing is not attached to the top flange, top flange must be laterally braced at maximum 2' o.c.
- If sheathing is not attached to the bottom flange, bottom flange must be laterally braced at maximum 2' o.c.

READ ALL NOTES ON THIS PAGE AND ON THE
ENGINEERING NOTES: EWP-FLOORS. THE NOTE
PAGE IS AN INTEGRAL PART OF THIS DRAWING
AS IT CONTAINS SPECIFICATIONS AND CRITERIA
USED IN THE DESIGN OF THIS COMPONENT.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 1-4-15	1-7-0	Top	15 PSF	40 PSF	0 PSF	0 PSF	

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

- Dry service conditions, unless noted otherwise
- Ljoist not to be treated with fire retardant or corrosive chemicals

chemicals

Handling & Installation

- Ljoist flanges must not be cut or drilled
- Refer to latest copy of the Ljoist product information details for framing details, stiffener tables, web hole chart, bridging details, multi-ply fastening details and handling/erection details
- Damaged Ljoists must not be used
- Design assumes top flange to be laterally restrained by attached sheathing or as specified in engineering notes,

- Provide lateral support at bearing points to avoid lateral displacement and rotation
- Web stiffeners for point load as shown Minimum point load bearing length >= 3.5 inches
- For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Boise Cascade Wood Products
1111 W. Jefferson St.
Boise, ID 83702
(800) 232-0788
www.bc.com
CCMC: 12787

Kott Inc.

3228 Moodie Dr, Ottawa, Ontario
613-838-2775 / 905-642-4400



This design is valid until 4/17/2026

CORPORATION OF THE CITY OF OSHAWA
TRUE COPY
OF PERMIT PLANS
NOV 03 2023

Client: GREENPARK

Date: 7/14/2023

Project:

Input by: W C


Address: ZADORRA ESTATES
OSHAWA, ON

Job Name: ROSE 12-2 STD

Project #:

F11-B vC Morris 1E 3100 SP 1.750" X 11.875" 2-Ply - PASSED Level: Ground Floor

PER: CHIEF BUILDING OFFICIAL



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	2	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2015 OBC 2012(2020 Update)
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal - II	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Direction	Live	Dead	Snow	Wind
1	Vertical	1703	802	0	0
2	Vertical	1829	821	0	0

Bearings and Factored Reactions

Bearing	Length	Dir.	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	2.375"	Vert	70%	1002 / 2555	3557	L	1.25D+1.5L
2 - SPF	5.699"	Vert	31%	1026 / 2743	3769	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	10000 ft-lb	5'6 1/4"	35392 ft-lb	0.283 (28%)	1.25D+1.5L	L
Unbraced	10000 ft-lb	5'6 1/4"	35392 ft-lb	0.283 (28%)	1.25D+1.5L	L
Shear	4146 lb	1'2 1/4"	13217 lb	0.314 (31%)	1.25D+1.5L	L
Perm Defl in.	0.046 (L/2806)	5'6 3/16"	0.359 (L/360)	0.128 (13%)	D	Uniform
LL Defl inch	0.099 (L/1303)	5'6 3/8"	0.359 (L/360)	0.276 (28%)	L	
TL Defl inch	0.145 (L/890)	5'6 5/16"	0.539 (L/240)	0.270 (27%)	D+L	L

Design Notes

- 1 Provide support to prevent lateral movement and rotation at the end bearings. Lateral support may also be required at the interior bearings by the building code.
- 2 Girders are designed to be supported on the bottom edge only.
- 3 Multiple plies must be fastened together as per manufacturer's details.
- 4 Top loads must be supported equally by all plies.
- 5 Top must be continuously laterally braced.
- 6 Bottom must have sheathing attached or be continuously braced.
- 7 Lateral slenderness ratio based on full section width.



READ ALL NOTES ON THIS PAGE AND ON THE
ENGINEERING NOTES: EWP-FLOORS. THE NOTE
PAGE IS AN INTEGRAL PART OF THIS DRAWING
AS IT CONTAINS SPECIFICATIONS AND CRITERIA
USED IN THE DESIGN OF THIS COMPONENT.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 11-4-0	0-3-5	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Part. Uniform	0-4-14 to 8-7-2		Top	8 PLF	0 PLF	0 PLF	0 PLF	
3	Point	1-0-9		Far Face	174 lb	421 lb	0 lb	0 lb	J4
4	Part. Uniform	1-8-9 to 8-4-9		Far Face	132 PLF	320 PLF	0 PLF	0 PLF	
5	Part. Uniform	8-4-9 to 11-0-9		Far Face	121 PLF	320 PLF	0 PLF	0 PLF	
	Self Weight				12 PLF				

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

This design is valid until 4/17/2026

Manufacturer Info


Boise Cascade Wood Products
1111 W. Jefferson St.
Boise, ID 83702
(800) 232-0788
www.bc.com
CCMC: 12472

Kott Inc.
3228 Moodie Dr, Ottawa, Ontario
613-838-2775 / 905-642-4400



Client:	GREENPARK	Date:	7/14/2023
Project:		Input by:	W C
Address:	ZADORRVE SFATES OSHAWA ON	Job Name:	ROSE 12-2 STD
		Project #:	

F11-C	V	<i>C. Morris</i>	1E 3100 SP	1.750" X 11.875"	2-Ply - PASSED	Level: Ground Floor
-------	---	------------------	------------	------------------	----------------	---------------------



Unfactored Reactions UNPATTERNED lb (Uplift)


Type:	Girder	Application:	Floor (Residential)	Brg	Direction	Live	Dead	Snow	Wind
Plies:	2	Design Method:	LSD	1	Vertical	140	93	0	0
Moisture Condition:	Dry	Building Code:	NBCC 2015	2	Vertical	466	267	0	0
Deflection LL:	360		OBC 2012(2020 Update)	3	Vertical	152	65	0	0
Deflection TL:	240	Load Sharing:	No						
Importance:	Normal - II	Deck:	Not Checked						
General Load:		Vibration:	Not Checked						

Bearings and Factored Reactions

Bearing	Length	Dir.	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	5.250"	Vert	3%	116 / 223	339	L_	1.25D+1.5L
2 - SPF	6.000"	Vert	5%	335 / 702	1037	LL	1.25D+1.5L
End Grain							
3 - Hanger	2.000"	Vert	5%	80 / 308 388 (-20)		_L	1.25D+1.5L (0.9D+1.5L)

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Neg Moment	-616 ft-lb	7'10 3/4"	35392 ft-lb	0.017 (2%)	1.25D+1.5L	LL
Unbraced	-616 ft-lb	7'10 3/4"	32757 ft-lb	0.019 (2%)	1.25D+1.5L	LL
Pos Moment	475 ft-lb	3'5 7/16"	33622 ft-lb	0.014 (1%)	1.25D+1.5L	L_
Unbraced	475 ft-lb	3'5 7/16"	33622 ft-lb	0.014 (1%)	1.25D+1.5L	L_
Shear	349 lb	6'7 7/8"	13217 lb	0.026 (3%)	1.25D+1.5L	LL
Perm Defl in.	0.001 (L/84101)	3'8 3/4"	0.251 (L/360)	0.004 (0%)	D	Uniform
LL Defl inch	0.002 (L/46508)	3'10 1/8"	0.251 (L/360)	0.008 (1%)	L	L_
TL Defl inch	0.003 (L/29956)	3'9 5/8"	0.376 (L/240)	0.008 (1%)	D+L	L_



**READ ALL NOTES ON THIS PAGE AND ON THE
ENGINEERING NOTES: EWP-FLOORS. THE NOTE
PAGE IS AN INTEGRAL PART OF THIS DRAWING
AS IT CONTAINS SPECIFICATIONS AND CRITERIA
USED IN THE DESIGN OF THIS COMPONENT.**

Design Notes

- 1 Provide support to prevent lateral movement and rotation at the end bearings. Lateral support may also be required at the interior bearings by the building code.
- 2 Fill all hanger nailing holes.
- 3 Right Header: DF, Thickness: 3 1/2"
- 4 Girders are designed to be supported on the bottom edge only.
- 5 Multiple plies must be fastened together as per manufacturer's details.
- 6 Top loads must be supported equally by all plies.
- 7 Negligible uplift at end of short span.
- 8 Top must be continuously laterally braced.
- 9 Bottom must be laterally braced at bearings.
- 10 Lateral slenderness ratio based on full section width.

Notes

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Boise Cascade Wood Products
1111 W. Jefferson St.
Boise, ID 83702
(800) 232-0788
www.bc.com
CCMC: 12472

Kott Inc.
3228 Moodie Dr, Ottawa, Ontario
613-838-2775 / 905-642-4400



This design is valid until 4/17/2026

CORPORATION OF THE CITY OF OSHAWA



Client: GREENPARK

Project:

Address: ZADORRA ESTATES
OSHAWA, ON

Date: 7/14/2023


Input by: W C

Job Name: ROSE 12-2 STD

Project #:

MHP 23032

F11-C 1E 3100 SP 1.750" X 11.875" 2-Ply - PASSED Level: Ground Floor



ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 0-2-10	0-4-1	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Tie-In	0-0-0 to 0-2-10	0-3-15	Top	15 PSF	40 PSF	0 PSF	0 PSF	
3	Tie-In	0-2-10 to 7-9-0	0-6-1	Top	15 PSF	40 PSF	0 PSF	0 PSF	
4	Tie-In	0-2-10 to 11-9-1	0-6-15	Top	15 PSF	40 PSF	0 PSF	0 PSF	
5	Part. Uniform	8-1-12 to 11-7-13		Top	36 PLF	95 PLF	0 PLF	0 PLF	
	Self Weight				12 PLF				



READ ALL NOTES ON THIS PAGE AND ON THE
ENGINEERING NOTES: EWP-FLOORS. THE NOTE
PAGE IS AN INTEGRAL PART OF THIS DRAWING
AS IT CONTAINS SPECIFICATIONS AND CRITERIA
USED IN THE DESIGN OF THIS COMPONENT.

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Boise Cascade Wood Products
1111 W. Jefferson St.
Boise, ID 83702
(800) 232-0788
www.bc.com
CCMC: 12472

Kott Inc.

3228 Moodie Dr, Ottawa, Ontario
613-838-2775 / 905-642-4400



This design is valid until 4/17/2026

CORPORATION OF THE CITY OF OSHAWA
TRUE COPY
OF PERMIT PLANS
NOV 03 2023


Client: GREENPARK
Project:
Address: ZADORRA ESTATES
OSHAWA, ON

Date: 7/14/2023
Input by: W C
Job Name: ROSE 12-2 STD
Project #:

MHP 23032

F12 PER 875" - PASSED

Level: Ground Floor



11 7/8"
2 1/2"

Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2015 OBC 2012(2020 Update)
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal - II	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Direction	Live	Dead	Snow	Wind
1	Vertical	516	209	0	0
2	Vertical	451	169	0	0

Bearings and Factored Reactions

Bearing	Length	Dir.	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	2.875"	Vert	58%	262 / 774	1036	L	1.25D+1.5L
2 - SPF	2.388"	Vert	53%	211 / 676	887	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	3603 ft-lb	8' 11/16"	5305 ft-lb	0.679 (68%)	1.25D+1.5L	L
Unbraced	3603 ft-lb	8' 11/16"	5305 ft-lb	0.679 (68%)	1.25D+1.5L	L
Shear	876 lb	2 1/8"	2350 lb	0.373 (37%)	1.25D+1.5L	L
Perm Defl in.	0.108 (L/1754)	8' 9/16"	0.525 (L/360)	0.205 (21%)	D	Uniform
LL Defl inch	0.288 (L/657)	8' 9/16"	0.525 (L/360)	0.548 (55%)	L	L
TL Defl inch	0.395 (L/478)	8' 9/16"	0.787 (L/240)	0.502 (50%)	D+L	L



Design Notes

- Provide support to prevent lateral movement and rotation at the end bearings. Lateral support may also be required at the interior bearings by the building code.
- Girders are designed to be supported on the bottom edge only.
- If sheathing is not attached to the top flange, top flange must be laterally braced at maximum 2' o.c.
- Bottom flange must be laterally braced at a maximum of 6'6 5/16" o.c.

READ ALL NOTES ON THIS PAGE AND ON THE
ENGINEERING NOTES: EWP-FLOORS. THE NOTE
PAGE IS AN INTEGRAL PART OF THIS DRAWING
AS IT CONTAINS SPECIFICATIONS AND CRITERIA
USED IN THE DESIGN OF THIS COMPONENT.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 0-2-6	1-1-13	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Tie-In	0-0-4 to 16-0-11	0-7-13	Top	15 PSF	40 PSF	0 PSF	0 PSF	
3	Point	0-0-12		Top	12 lb	29 lb	0 lb	0 lb	J4
	Bearing Length	0-1-8							
4	Point	0-0-12		Top	12 lb	30 lb	0 lb	0 lb	J6
	Bearing Length	0-1-8							
5	Point	0-0-12		Top	14 lb	0 lb	0 lb	0 lb	Wall Self Weight

Continued on page 2...

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

- Dry service conditions, unless noted otherwise
- Joist not to be treated with fire retardant or corrosive

chemicals

Handling & Installation

- Joist flanges must not be cut or drilled
- Refer to latest copy of the Joist product information details for framing details, stiffener tables, web hole chart, bridging details, multi-ply fastening details and handling/erection details
- Damaged Joists must not be used
- Design assumes top flange to be laterally restrained by attached sheathing or as specified in engineering notes.

- Provide lateral support at bearing points to avoid lateral displacement and rotation
- Web stiffeners for point load as shown Minimum point load bearing length >= 3.5 inches
- For flat roofs provide proper drainage to prevent ponding

This design is valid until 4/17/2026

Manufacturer Info

Boise Cascade Wood Products
1111 W. Jefferson St.
Boise, ID 83702
(800) 232-0788
www.bc.com
CCMC: 12787

Kott Inc.
3228 Moodie Dr, Ottawa, Ontario
613-838-2775 / 905-642-4400



CORPORATION OF THE CITY OF OSHAWA



Client: GREENPARK

Date: 7/14/2023

Project:

Input by: W C



Address: ZADORRA ESTATES
OSHAWA, ON

Job Name: ROSE 12-2 STD

Project #:

F12 PERMIT 875" - PASSED

Level: Ground Floor



...Continued from page 1

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
	Bearing Length	0-1-8							
6	Tie-In	0-2-6 to 16-0-11	0-7-13	Top	15 PSF	40 PSF	0 PSF	0 PSF	
7	Point	6-4-6		Near Face	13 lb	35 lb	0 lb	0 lb	F1
8	Point	9-6-6		Near Face	13 lb	35 lb	0 lb	0 lb	F1



READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTES: EWP-FLOORS. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. Joist not to be treated with fire retardant or corrosive chemicals

Handling & Installation

1. Joist flanges must not be cut or drilled
2. Refer to latest copy of the Joist product information details for framing details, stiffener tables, web hole chart, bridging details, multi-ply fastening details and handling/erection details
3. Damaged Joists must not be used
4. Design assumes top flange to be laterally restrained by attached sheathing or as specified in engineering notes,

5. Provide lateral support at bearing points to avoid lateral displacement and rotation
6. Web stiffeners for point load as shown Minimum point load bearing length >= 3.5 inches
7. For flat roofs provide proper drainage to prevent ponding

This design is valid until 4/17/2026

Manufacturer Info

Boise Cascade Wood Products
1111 W. Jefferson St.
Boise, ID 83702
(800) 232-0788
www.bc.com
CCMC: 12787

Kott Inc.

3228 Moodie Dr, Ottawa, Ontario
613-838-2775 / 905-642-4400






Client: GREENPARK
Project:
Address: ZADORRA ESTATES
OSHAWA, ON

Date: 7/14/2023
Input by: W C
Job Name: ROSE 12-2 STD
Project #:

MHP 23032

F12-A 11.875" - PASSED

Level: Ground Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2015 OBC 2012(2020 Update)
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal - II	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Direction	Live	Dead	Snow	Wind
1	Vertical	420	158	0	0
2	Vertical	481	197	0	0

Bearings and Factored Reactions

Bearing	Length	Dir.	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	2.375"	Vert	49%	198 / 630	828	L	1.25D+1.5L
2 - SPF	2.625"	Vert	56%	246 / 722	968	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	3564 ft-lb	8'3 3/4"	5305 ft-lb	0.672 (67%)	1.25D+1.5L	L
Unbraced	3564 ft-lb	8'3 3/4"	5305 ft-lb	0.672 (67%)	1.25D+1.5L	L
Shear	818 lb	16'6 3/16"	2350 lb	0.348 (35%)	1.25D+1.5L	L
Perm Defl in.	0.115 (L/1714)	8'3 15/16"	0.546 (L/360)	0.210 (21%)	D	Uniform
LL Defl inch	0.304 (L/646)	8'3 15/16"	0.546 (L/360)	0.557 (56%)	L	
TL Defl inch	0.419 (L/469)	8'3 15/16"	0.819 (L/240)	0.512 (51%)	D+L	L



JULY 14, 2023

Design Notes

- 1 Provide support to prevent lateral movement and rotation at the end bearings. Lateral support may also be required at the interior bearings by the building code.
- 2 Girders are designed to be supported on the bottom edge only.
- 3 If sheathing is not attached to the top flange, top flange must be laterally braced at maximum 2' o.c.
- 4 Bottom flange must be laterally braced at a maximum of 6'9 15/16" o.c.

READ ALL NOTES ON THIS PAGE AND ON THE
ENGINEERING NOTES: EWP-FLOORS. THE NOTE
PAGE IS AN INTEGRAL PART OF THIS DRAWING
AS IT CONTAINS SPECIFICATIONS AND CRITERIA
USED IN THE DESIGN OF THIS COMPONENT.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 16-8-1	0-9-7	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Tie-In	0-0-0 to 16-8-1	0-4-2	Top	15 PSF	40 PSF	0 PSF	0 PSF	
3	Point	6-9-15		Near Face	17 lb	44 lb	0 lb	0 lb	F1
4	Point	9-11-15		Near Face	17 lb	44 lb	0 lb	0 lb	F1
5	Point	16-8-1		Top	12 lb	29 lb	0 lb	0 lb	J4
	Bearing Length	0-1-8							
6	Point	16-8-1		Top	12 lb	30 lb	0 lb	0 lb	J6

Continued on page 2...

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. Joist not to be treated with fire retardant or corrosive chemicals

chemicals

Handling & Installation

1. Joist flanges must not be cut or drilled
2. Refer to latest copy of the Joist product information details for framing details, stiffener tables, web hole chart, bridging details, multi-ply fastening details and handling/erection details
3. Damaged Joists must not be used
4. Design assumes top flange to be laterally restrained by attached sheathing or as specified in engineering notes.

5. Provide lateral support at bearing points to avoid lateral displacement and rotation
6. Web stiffeners for point load as shown Minimum point load bearing length >= 3.5 inches
7. For flat roofs provide proper drainage to prevent ponding

This design is valid until 4/17/2026

Manufacturer Info

Boise Cascade Wood Products
1111 W. Jefferson St.
Boise, ID 83702
(800) 232-0788
www.bc.com
CCMC: 12787

Kott Inc.

3228 Moodie Dr, Ottawa, Ontario
613-838-2775 / 905-642-4400



CORPORATION OF THE CITY OF OSHAWA



Client: GREENPARK

Project:

Address: ZADORRA ESTATES
OSHAWA, ON

Date: 7/14/2023

Input by: W C


Job Name: ROSE 12-2 STD

Project #:

MHP 23032

F12-A 11.875" - PASSED

Level: Ground Floor



...Continued from page 1

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
	Bearing Length	0-1-8							
7	Point	16-8-1		Top	14 lb	0 lb	0 lb	0 lb	Wall Self Weight
	Bearing Length	0-1-8							



READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTES: EWP-FLOORS. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. Joist not to be treated with fire retardant or corrosive chemicals

Handling & Installation

1. Joist flanges must not be cut or drilled
2. Refer to latest copy of the Joist product information details for framing details, stiffener tables, web hole chart, bridging details, multi-ply fastening details and handling/erection details
3. Damaged Joists must not be used
4. Design assumes top flange to be laterally restrained by attached sheathing or as specified in engineering notes,

5. Provide lateral support at bearing points to avoid lateral displacement and rotation
6. Web stiffeners for point load as shown Minimum point load bearing length >= 3.5 inches
7. For flat roofs provide proper drainage to prevent ponding

This design is valid until 4/17/2026

Manufacturer Info

Boise Cascade Wood Products
1111 W. Jefferson St.
Boise, ID 83702
(800) 232-0788
www.bc.com
CCMC: 12787

Kott Inc.

3228 Moodie Dr, Ottawa, Ontario
613-838-2775 / 905-642-4400






Client: GREENPARK
 Project: ZADORRA ESTATES
 Address: OSHAWA, ON
 Date: 7/14/2023
 Input by: W C
 Job Name: ROSE 12-2 STD
 Project #:

MHP 23032

F12-B 11.875" - PASSED

Level: Ground Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2015 OBC 2012(2020 Update)
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal - II	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Direction	Live	Dead	Snow	Wind
1	Vertical	208	99	0	0
2	Vertical	211	101	0	0

Bearings and Factored Reactions

Bearing	Length	Dir.	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	2.375"	Vert	26%	123 / 313	436	L	1.25D+1.5L
2 - SPF	2.625"	Vert	25%	126 / 316	442	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	2001 ft-lb	8'3 5/16"	5305 ft-lb	0.377 (38%)	1.25D+1.5L	L
Unbraced	2001 ft-lb	8'3 5/16"	5305 ft-lb	0.377 (38%)	1.25D+1.5L	L
Shear	435 lb	16'6 3/16"	2350 lb	0.185 (19%)	1.25D+1.5L	L
Perm Defl in.	0.076 (L/2578)	8'4"	0.546 (L/360)	0.140 (14%)	D	Uniform
LL Defl inch	0.159 (L/1235)	8'4"	0.546 (L/360)	0.292 (29%)	L	
TL Defl inch	0.235 (L/835)	8'4"	0.819 (L/240)	0.287 (29%)	D+L	L



Design Notes

- 1 Provide support to prevent lateral movement and rotation at the end bearings. Lateral support may also be required at the interior bearings by the building code.
- 2 Girders are designed to be supported on the bottom edge only.
- 3 If sheathing is not attached to the top flange, top flange must be laterally braced at maximum 2' o.c.
- 4 Bottom flange must be laterally braced at a maximum of 6'10 15/16" o.c.

READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTES: EWP-FLOORS. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 16-8-1	0-6-0	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Part. Uniform	0-4-15 to 16-8-1		Top	2 PLF	0 PLF	0 PLF	0 PLF	
3	Point	6-10-15		Far Face	21 lb	43 lb	0 lb	0 lb	F1
4	Point	10-1-0		Far Face	21 lb	43 lb	0 lb	0 lb	F1

Notes

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. Joist not to be treated with fire retardant or corrosive chemicals

chemicals

Handling & Installation

1. Joist flanges must not be cut or drilled
2. Refer to latest copy of the Joist product information details for framing details, stiffener tables, web hole chart, bridging details, multi-ply fastening details and handling/erection details
3. Damaged Joists must not be used
4. Design assumes top flange to be laterally restrained by attached sheathing or as specified in engineering notes.

5. Provide lateral support at bearing points to avoid lateral displacement and rotation
6. Web stiffeners for point load as shown Minimum point load bearing length >= 3.5 inches
7. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Boise Cascade Wood Products
 1111 W. Jefferson St.
 Boise, ID 83702
 (800) 232-0788
 www.bc.com
 CCMC: 12787

Kott Inc.
 3228 Moodie Dr, Ottawa, Ontario
 613-838-2775 / 905-642-4400



This design is valid until 4/17/2026

CORPORATION OF THE CITY OF OSHAWA



Client: GREENPARK

Date: 7/14/2023

Project:

Input by: W C



Address: ZADORRA ESTATES
OSHAWA, ON

Job Name: ROSE 12-2 STD

Project #:

F1-A PER: 1.875" - PASSED

Level: Ground Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2015 OBC 2012(2020 Update)
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal - II	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Direction	Live	Dead	Snow	Wind
1	Vertical	38	14	0	0
2	Vertical	35	13	0	0

Bearings and Factored Reactions

Bearing	Length	Dir.	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	2.442"	Vert	4%	18 / 56	74	L	1.25D+1.5L
2 - Hanger	2.000"	Vert	4%	17 / 53	70	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	13 ft-lb	7 1/8"	5305 ft-lb	0.002 (0%)	1.25D+1.5L	L
Unbraced	13 ft-lb	7 1/8"	5305 ft-lb	0.002 (0%)	1.25D+1.5L	L
Shear	57 lb	1 11/16"	2350 lb	0.024 (2%)	1.25D+1.5L	L
Perm Defl in. (L/295574)	0.000	7 3/16"	0.030 (L/360)	0.001 (0%)	D	Uniform
LL Defl inch (L/110840)	0.000	7 3/16"	0.030 (L/360)	0.003 (0%)	L	L
TL Defl inch (L/80611)	0.000	7 3/16"	0.046 (L/240)	0.003 (0%)	D+L	L



Design Notes

- Provide support to prevent lateral movement and rotation at the end bearings. Lateral support may also be required at the interior bearings by the building code.
- Fill all hanger nailing holes.
- Right Header: SPF, Thickness: 2 1/2"
- Girders are designed to be supported on the bottom edge only.
- If sheathing is not attached to the top flange, top flange must be laterally braced at maximum 2' o.c.
- If sheathing is not attached to the bottom flange, bottom flange must be laterally braced at maximum 2' o.c.

READ ALL NOTES ON THIS PAGE AND ON THE
ENGINEERING NOTES: EWP-FLOORS. THE NOTE
PAGE IS AN INTEGRAL PART OF THIS DRAWING
AS IT CONTAINS SPECIFICATIONS AND CRITERIA
USED IN THE DESIGN OF THIS COMPONENT.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 1-1-14	1-7-0	Top	15 PSF	40 PSF	0 PSF	0 PSF	

Notes

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

- Dry service conditions, unless noted otherwise
- Ljoist not to be treated with fire retardant or corrosive chemicals

chemicals

Handling & Installation

- Ljoist flanges must not be cut or drilled
- Refer to latest copy of the Ljoist product information details for framing details, stiffener tables, web hole chart, bridging details, multi-ply fastening details and handling/erection details
- Damaged Ljoists must not be used
- Design assumes top flange to be laterally restrained by attached sheathing or as specified in engineering notes.

- Provide lateral support at bearing points to avoid lateral displacement and rotation
- Web stiffeners for point load as shown Minimum point load bearing length >= 3.5 inches
- For flat roofs provide proper drainage to prevent ponding

This design is valid until 4/17/2026

Manufacturer Info

Boise Cascade Wood Products
1111 W. Jefferson St.
Boise, ID 83702
(800) 232-0788
www.bc.com
CCMC: 12787

Kott Inc.

3228 Moodie Dr, Ottawa, Ontario
613-838-2775 / 905-642-4400



CORPORATION OF THE CITY OF OSHAWA



Client: GREENPARK

Date: 7/14/2023

Project:

Input by: W C


Address: ZADORRA ESTATES
OSHAWA, ON

Job Name: ROSE 12-2 STD

Project #:

F1-B PER: *C. Morris* 1.875" - PASSED

Level: Ground Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2015 OBC 2012(2020 Update)
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal - II	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Direction	Live	Dead	Snow	Wind
1	Vertical	46	17	0	0
2	Vertical	44	17	0	0

Bearings and Factored Reactions

Bearing	Length	Dir.	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	2.375"	Vert	5%	22 / 69	91	L	1.25D+1.5L
2 - Hanger	2.000"	Vert	5%	21 / 66	87	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	22 ft-lb	8 11/16"	5305 ft-lb	0.004 (0%)	1.25D+1.5L	L
Unbraced	22 ft-lb	8 11/16"	5305 ft-lb	0.004 (0%)	1.25D+1.5L	L
Shear	74 lb	1 5/8"	2350 lb	0.031 (3%)	1.25D+1.5L	L
Perm Defl in. (L/222704)	0.000	8 3/4"	0.039 (L/360)	0.002 (0%)	D	Uniform
LL Defl inch (L/83514)	0.000	8 3/4"	0.039 (L/360)	0.004 (0%)	L	L
TL Defl inch (L/60737)	0.000	8 3/4"	0.059 (L/240)	0.004 (0%)	D+L	L



Design Notes

- Provide support to prevent lateral movement and rotation at the end bearings. Lateral support may also be required at the interior bearings by the building code.
- Fill all hanger nailing holes.
- Right Header: SPF, Thickness: 2 1/2"
- Girders are designed to be supported on the bottom edge only.
- If sheathing is not attached to the top flange, top flange must be laterally braced at maximum 2' o.c.
- If sheathing is not attached to the bottom flange, bottom flange must be laterally braced at maximum 2' o.c.

READ ALL NOTES ON THIS PAGE AND ON THE
ENGINEERING NOTES: EWP-FLOORS. THE NOTE
PAGE IS AN INTEGRAL PART OF THIS DRAWING
AS IT CONTAINS SPECIFICATIONS AND CRITERIA
USED IN THE DESIGN OF THIS COMPONENT.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 1-5-1	1-7-0	Top	15 PSF	40 PSF	0 PSF	0 PSF	

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

- Dry service conditions, unless noted otherwise
- Ljoist not to be treated with fire retardant or corrosive chemicals

chemicals

Handling & Installation

- Ljoist flanges must not be cut or drilled
- Refer to latest copy of the Ljoist product information details for framing details, stiffener tables, web hole chart, bridging details, multi-ply fastening details and handling/erection details
- Damaged Ljoists must not be used
- Design assumes top flange to be laterally restrained by attached sheathing or as specified in engineering notes.

- Provide lateral support at bearing points to avoid lateral displacement and rotation
- Web stiffeners for point load as shown Minimum point load bearing length >= 3.5 inches
- For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Boise Cascade Wood Products
1111 W. Jefferson St.
Boise, ID 83702
(800) 232-0788
www.bc.com
CCMC: 12787

Kott Inc.

3228 Moodie Dr, Ottawa, Ontario
613-838-2775 / 905-642-4400



This design is valid until 4/17/2026

CORPORATION OF THE CITY OF OSHAWA
TRUE COPY
OF PERMIT PLANS
NOV 03 2023
isDesign

Client: GREENPARK

Date: 7/14/2023

Project:

Input by: W C

Address: ZADORRA ESTATES
OSHAWA, ON

Job Name: ROSE 12-2 STD


Project #:

F1-C PER: *C. Morris* 1.875" - PASSED
CHIEF BUILDING OFFICIAL

Level: Ground Floor



1 Hanger (LF2511) 0-2-0
2 SPF 0-2-6
1'4 5/8"
1'4 5/8"



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2015 OBC 2012(2020 Update)
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal - II	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Direction	Live	Dead	Snow	Wind
1	Vertical	43	21	0	0
2	Vertical	45	20	0	0

Bearings and Factored Reactions

Bearing	Length	Dir.	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - Hanger	2.000"	Vert	6%	27 / 64	91	L	1.25D+1.5L
2 - SPF	2.375"	Vert	5%	24 / 68	92	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	22 ft-lb	8 1/8"	5305 ft-lb	0.004 (0%)	1.25D+1.5L	L
Unbraced	22 ft-lb	8 1/8"	5305 ft-lb	0.004 (0%)	1.25D+1.5L	L
Shear	77 lb	1 1/4"	2350 lb	0.033 (3%)	1.25D+1.5L	L
Perm Defl in. (L/176712)	0.000	8 1/16"	0.038 (L/360)	0.002 (0%)	D	Uniform
LL Defl inch (L/86028)	0.000	8 3/16"	0.038 (L/360)	0.004 (0%)	L	L
TL Defl inch (L/57862)	0.000	8 1/8"	0.057 (L/240)	0.004 (0%)	D+L	L



READ ALL NOTES ON THIS PAGE AND ON THE
ENGINEERING NOTES: EWP-FLOORS. THE NOTE
PAGE IS AN INTEGRAL PART OF THIS DRAWING
AS IT CONTAINS SPECIFICATIONS AND CRITERIA
USED IN THE DESIGN OF THIS COMPONENT.

Design Notes

- 1 Provide support to prevent lateral movement and rotation at the end bearings. Lateral support may also be required at the interior bearings by the building code.
- 2 Fill all hanger nailing holes.
- 3 Left Header: SPF, Thickness: 2 1/2"
- 4 Girders are designed to be supported on the bottom edge only.
- 5 If sheathing is not attached to the top flange, top flange must be laterally braced at maximum 2' o.c.
- 6 If sheathing is not attached to the bottom flange, bottom flange must be laterally braced at maximum 2' o.c.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 1-4-10	1-7-1	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Part. Uniform	0-0-0 to 0-11-12		Top	8 PLF	0 PLF	0 PLF	0 PLF	

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. Joist not to be treated with fire retardant or corrosive

chemicals

Handling & Installation

1. Joist flanges must not be cut or drilled
2. Refer to latest copy of the Joist product information details for framing details, stiffener tables, web hole chart, bridging details, multi-ply fastening details and handling/erection details
3. Damaged Joists must not be used
4. Design assumes top flange to be laterally restrained by attached sheathing or as specified in engineering notes.

5. Provide lateral support at bearing points to avoid lateral displacement and rotation
6. Web stiffeners for point load as shown Minimum point load bearing length >= 3.5 inches
7. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Boise Cascade Wood Products
1111 W. Jefferson St.
Boise, ID 83702
(800) 232-0788
www.bc.com
CCMC: 12787

Kott Inc.

3228 Moodie Dr, Ottawa, Ontario
613-838-2775 / 905-642-4400



This design is valid until 4/17/2026

CORPORATION OF THE CITY OF OSHAWA
TRUE COPY
OF PERMIT PLANS
NOV 03 2023



Client: GREENPARK
Project:
Address: ZADORRA ESTATES
OSHAWA, ON

Date: 7/14/2023
Input by: W C
Job Name: ROSE 12-2 STD
Project #:

MHP 23032

F2 A. *C. Morris* 375" - PASSED
CHIEF BUILDING OFFICIAL

Level: Ground Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2015 OBC 2012(2020 Update)
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal - II	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Direction	Live	Dead	Snow	Wind
1	Vertical	393	147	0	0
2	Vertical	400	149	0	0

Bearings and Factored Reactions

Bearing	Length	Dir.	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	2.375"	Vert	46%	184 / 590	774	L	1.25D+1.5L
2 - SPF	5.699"	Vert	41%	187 / 599	786	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	2352 ft-lb	6' 3/8"	5305 ft-lb	0.443 (44%)	1.25D+1.5L	L
Unbraced	2352 ft-lb	6' 3/8"	5305 ft-lb	0.443 (44%)	1.25D+1.5L	L
Shear	758 lb	11'11 1/8"	2350 lb	0.323 (32%)	1.25D+1.5L	L
Perm Defl in.	0.042 (L/3343)	6' 3/8"	0.393 (L/360)	0.108 (11%)	D	Uniform
LL Defl inch	0.113 (L/1248)	6' 3/8"	0.393 (L/360)	0.289 (29%)	L	
TL Defl inch	0.156 (L/909)	6' 3/8"	0.590 (L/240)	0.264 (26%)	D+L	L



Design Notes

- Provide support to prevent lateral movement and rotation at the end bearings. Lateral support may also be required at the interior bearings by the building code.
- Girders are designed to be supported on the bottom edge only.
- If sheathing is not attached to the top flange, top flange must be laterally braced at maximum 2' o.c.
- Bottom flange must be laterally braced at a maximum of 4'8 5/8" o.c.

READ ALL NOTES ON THIS PAGE AND ON THE
ENGINEERING NOTES: EWP-FLOORS. THE NOTE
PAGE IS AN INTEGRAL PART OF THIS DRAWING
AS IT CONTAINS SPECIFICATIONS AND CRITERIA
USED IN THE DESIGN OF THIS COMPONENT.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 11-11-11	0-8-0	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Tie-In	0-0-0 to 12-4-1	0-9-6	Top	15 PSF	40 PSF	0 PSF	0 PSF	
3	Point	4-5-7		Near Face	16 lb	44 lb	0 lb	0 lb	F1
4	Point	7-7-7		Near Face	16 lb	44 lb	0 lb	0 lb	F1

Notes

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

- Dry service conditions, unless noted otherwise
- Joist not to be treated with fire retardant or corrosive chemicals

chemicals

Handling & Installation

- Joist flanges must not be cut or drilled
- Refer to latest copy of the Joist product information details for framing details, stiffener tables, web hole chart, bridging details, multi-ply fastening details and handling/erection details
- Damaged Joists must not be used
- Design assumes top flange to be laterally restrained by attached sheathing or as specified in engineering notes.

- Provide lateral support at bearing points to avoid lateral displacement and rotation
- Web stiffeners for point load as shown Minimum point load bearing length >= 3.5 inches
- For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Boise Cascade Wood Products
1111 W. Jefferson St.
Boise, ID 83702
(800) 232-0788
www.bc.com
CCMC: 12787

Kott Inc.

3228 Moodie Dr, Ottawa, Ontario
613-838-2775 / 905-642-4400



This design is valid until 4/17/2026

CORPORATION OF THE CITY OF OSHAWA
TRUE COPY
OF PERMIT PLANS
NOV 03 2023

Client: GREENPARK

Date: 7/14/2023

Project:

Input by: W C

Address:

ZADORRA ESTATES
OSHAWA, ON

Job Name:

ROSE 12-2 STD

Project #:

F4 Vers: *Chieff* 3' 00 SP 1.750" X 11.875" 2-Ply - PASSED Level: Ground Floor

1 2 3



1 Hanger (LF3511) 0-2-0

2 SPF End Grain 0-6-0

5' 5/16"

7/16"

5' 3/4"

11 7/8"

3 1/2"

Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	2	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2015 OBC 2012(2020 Update)
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal - II	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Direction	Live	Dead	Snow	Wind
1	Vertical	463	202	0	0
2	Vertical	408	184	0	0

Bearings and Factored Reactions

Bearing	Length	Dir.	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - Hanger	2.000"	Vert	12%	253 / 695	947	L_	1.25D+1.5L
2 - SPF End Grain	6.000"	Vert	4%	230 / 612	841	L_	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	1292 ft-lb	2'3 3/8"	35392 ft-lb	0.036 (4%)	1.25D+1.5L	L_
Unbraced	1292 ft-lb	2'3 3/8"	35392 ft-lb	0.036 (4%)	1.25D+1.5L	L_
Shear	945 lb	1'1 7/8"	13217 lb	0.071 (7%)	1.25D+1.5L	L_
Perm Defl in.	0.001 (L/53080)	2'4 13/16"	0.156 (L/360)	0.007 (1%)	D	Uniform
LL Defl inch	0.002 (L/22725)	2'4 3/4"	0.156 (L/360)	0.016 (2%)	L	LL
TL Defl inch	0.004 (L/15912)	2'4 3/4"	0.233 (L/240)	0.015 (2%)	D+L	LL
LL Cant	-0.000 (2L/15438)	Rt Cant	0.200 (2L/360)	0.000 (0%)	L	LL
TL Cant	-0.000 (2L/10803)	Rt Cant	0.300 (2L/240)	0.000 (0%)	D+L	LL

Design Notes

- 1 Provide support to prevent lateral movement and rotation at the end bearings. Lateral support may also be required at the interior bearings by the building code.
- 2 Fill all hanger nailing holes.
- 3 Left Header: DF, Thickness: 3 1/2"
- 4 Girders are designed to be supported on the bottom edge only.
- 5 Multiple plies must be fastened together as per manufacturer's details.
- 6 Top must be continuously laterally braced.
- 7 Bottom must have sheathing attached or be continuously braced.
- 8 Lateral slenderness ratio based on full section width.



READ ALL NOTES ON THIS PAGE AND ON THE
ENGINEERING NOTES: EWP-FLOORS. THE NOTE
PAGE IS AN INTEGRAL PART OF THIS DRAWING
AS IT CONTAINS SPECIFICATIONS AND CRITERIA
USED IN THE DESIGN OF THIS COMPONENT.

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Boise Cascade Wood Products
1111 W. Jefferson St.
Boise, ID 83702
(800) 232-0788
www.bc.com
CCMC: 12472

Kott Inc.
3228 Moodie Dr, Ottawa, Ontario
613-838-2775 / 905-642-4400



This design is valid until 4/17/2026

CORPORATION OF THE CITY OF OSHAWA



Client: GREENPARK

Date: 7/14/2023

Project:

Input by: W C



Address:

ZADORRA ESTATES
OSHAWA, ON

Job Name:

ROSE 12-2 STD

Project #:

F4 Vers: *C. Morris* 3' 00 SP 1.750" X 11.875" 2-Ply - PASSED Level: Ground Floor

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Point	0-11-6		Far Face	104 lb	279 lb	0 lb	0 lb	J3
2	Point	2-3-6		Far Face	115 lb	306 lb	0 lb	0 lb	J3
3	Point	3-7-6		Far Face	107 lb	286 lb	0 lb	0 lb	J3
	Self Weight				12 PLF				



READ ALL NOTES ON THIS PAGE AND ON THE
ENGINEERING NOTES: EWP-FLOORS. THE NOTE
PAGE IS AN INTEGRAL PART OF THIS DRAWING
AS IT CONTAINS SPECIFICATIONS AND CRITERIA
USED IN THE DESIGN OF THIS COMPONENT.

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Boise Cascade Wood Products
1111 W. Jefferson St.
Boise, ID 83702
(800) 232-0788
www.bc.com
CCMC: 12472

Kott Inc.

3228 Moodie Dr, Ottawa, Ontario
613-838-2775 / 905-642-4400



This design is valid until 4/17/2026





Client: GREENPARK
Project:
Address: ZADORRA ESTATES
OSHAWA, ON

Date: 7/14/2023
Input by: W C
Job Name: ROSE 12-2 STD
Project #:

MHP 23032

F4-A Ve [Signature] E 3100 SP 1.750" X 11.875" 2-Ply - PASSED Level: Ground Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	2	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2015 OBC 2012(2020 Update)
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal - II	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Direction	Live	Dead	Snow	Wind
1	Vertical	286	135	0	0
2	Vertical	274	131	0	0

Bearings and Factored Reactions

Bearing	Length	Dir.	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - Hanger	2.000"	Vert	8%	169 / 430	599	L	1.25D+1.5L
2 - Hanger	2.000"	Vert	8%	163 / 410	574	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	755 ft-lb	2'2 5/16"	35392 ft-lb	0.021 (2%)	1.25D+1.5L	L
Unbraced	755 ft-lb	2'2 5/16"	35392 ft-lb	0.021 (2%)	1.25D+1.5L	L
Shear	596 lb	1'1 7/8"	13217 lb	0.045 (5%)	1.25D+1.5L	L
Perm Defl in.	0.001 (L/92395)	2'2 7/8"	0.144 (L/360)	0.004 (0%)	D	Uniform
LL Defl inch	0.001 (L/42380)	2'2 3/4"	0.144 (L/360)	0.008 (1%)	L	L
TL Defl inch	0.002 (L/29054)	2'2 3/4"	0.217 (L/240)	0.008 (1%)	D+L	L

Design Notes

- Provide support to prevent lateral movement and rotation at the end bearings. Lateral support may also be required at the interior bearings by the building code.
- Fill all hanger nailing holes.
- Left Header: DF, Thickness: 3 1/2"
- Right Header: DF, Thickness: 3 1/2"
- Girders are designed to be supported on the bottom edge only.
- Multiple plies must be fastened together as per manufacturer's details.
- Top must be continuously laterally braced.
- Bottom must have sheathing attached or be continuously braced.
- Lateral slenderness ratio based on full section width.



READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTES: EWP-FLOORS. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

Notes

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

- Dry service conditions, unless noted otherwise
- LVL not to be treated with fire retardant or corrosive chemicals

chemicals

Handling & Installation

- LVL beams must not be cut or drilled
- Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
- Damaged Beams must not be used
- Design assumes top edge is laterally restrained
- Provide lateral support at bearing points to avoid lateral displacement and rotation

- For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Boise Cascade Wood Products
1111 W. Jefferson St.
Boise, ID 83702
(800) 232-0788
www.bc.com
CCMC: 12472

Kott Inc.
3228 Moodie Dr, Ottawa, Ontario
613-838-2775 / 905-642-4400



This design is valid until 4/17/2026

CORPORATION OF THE CITY OF OSHAWA

TRUE COPY

OF PERMIT PLANS

NOV 03 2023

Client: GREENPARK

Date: 7/14/2023

Project:

Input by: W C



Address: ZADORRA ESTATES
OSHAWA, ON

Job Name: ROSE 12-2 STD

Project #:

F4-A Ve *Ch Monte* E 3100 SP 1.750" X 11.875" 2-Ply - PASSED Level: Ground Floor

PER: CHIEF BUILDING OFFICIAL



ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Point	0-10-5		Far Face	66 lb	175 lb	0 lb	0 lb	J2
2	Point	2-2-5		Far Face	75 lb	199 lb	0 lb	0 lb	J2
3	Point	3-6-5		Far Face	71 lb	186 lb	0 lb	0 lb	J2
	Self Weight				12 PLF				



READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTES: EWP-FLOORS. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

Notes

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive chemicals

chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Boise Cascade Wood Products
1111 W. Jefferson St.
Boise, ID 83702
(800) 232-0788
www.bc.com
CCMC: 12472

Kott Inc.

3228 Moodie Dr, Ottawa, Ontario
613-838-2775 / 905-642-4400



This design is valid until 4/17/2026




Client: GREENPARK
Project:
Address: ZADORRA ESTATES
OSHAWA, ON

Date: 7/14/2023
Input by: W C
Job Name: ROSE 12-2 STD
Project #:

MHP 23032

F4-B Ve C Morris E 3100 SP 1.750" X 11.875" 2-Ply - PASSED Level: Ground Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	2	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2015 OBC 2012(2020 Update)
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal - II	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Direction	Live	Dead	Snow	Wind
1	Vertical	1809	1273	396	0
2	Vertical	1770	1220	348	0

Bearings and Factored Reactions

Bearing	Length	Dir.	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	2.375"	Vert	92%	1591 / 3110	4701	L	1.25D+1.5L +S
2 - SPF	3.500"	Vert	60%	1525 / 3003	4527	L	1.25D+1.5L +S

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	1874 ft-lb	2'3 7/16"	35392 ft-lb	0.053 (5%)	1.25D+1.5L +S	L
Unbraced	1874 ft-lb	2'3 7/16"	35392 ft-lb	0.053 (5%)	1.25D+1.5L +S	L
Shear	2637 lb	1'2 1/4"	13217 lb	0.200 (20%)	1.25D+1.5L +S	L
Perm Defl in.	0.001 (L/36002)	2'3 9/16"	0.146 (L/360)	0.010 (1%)	D	Uniform
LL Defl inch	0.003 (L/15670)	2'3 13/16"	0.146 (L/360)	0.023 (2%)	L+0.5S	L
TL Defl inch	0.005 (L/10918)	2'3 13/16"	0.220 (L/240)	0.022 (2%)	D+L+0.5S	L

Design Notes

- 1 Performed Secondary Bearing Check (CSA 086-14 6.5.7.3). Assumed point load size: beam width X 2.375.
- 2 Performed Secondary Bearing Check (CSA 086-14 6.5.7.3). Assumed point load size: beam width X 3.5.
- 3 Provide support to prevent lateral movement and rotation at the end bearings. Lateral support may also be required at the interior bearings by the building code.
- 4 Girders are designed to be supported on the bottom edge only.
- 5 Multiple plies must be fastened together as per manufacturer's details.
- 6 Top loads must be supported equally by all plies.
- 7 Top must be continuously laterally braced.
- 8 Bottom must have sheathing attached or be continuously braced.
- 9 Lateral slenderness ratio based on full section width.



READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTES: EWP-FLOORS. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Boise Cascade Wood Products
1111 W. Jefferson St.
Boise, ID 83702
(800) 232-0788
www.bc.com
CCMC: 12472

Kott Inc.
3228 Moodie Dr, Ottawa, Ontario
613-838-2775 / 905-642-4400



This design is valid until 4/17/2026





Client: GREENPARK
Project:
Address: ZADORRA ESTATES
OSHAWA, ON

Date: 7/14/2023
Input by: W C
Job Name: ROSE 12-2 STD
Project #:

MHIP 23032

F4-B Ve [Signature] E 3100 SP 1.750" X 11.875" 2-Ply - PASSED Level: Ground Floor



ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 4-7-15	0-7-9	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Part. Uniform	0-0-0 to 0-0-9		Top	157 PLF	338 PLF	0 PLF	0 PLF	J4
3	Part. Uniform	0-0-0 to 0-1-9		Top	30 PLF	0 PLF	79 PLF	0 PLF	
4	Part. Uniform	0-0-0 to 0-4-6		Top	45 PLF	0 PLF	0 PLF	0 PLF	Wall Self Weight
6	Part. Uniform	0-0-0 to 0-4-6		Top	2 PLF	0 PLF	0 PLF	0 PLF	Rim Board Self Weight
7	Part. Uniform	0-0-0 to 0-4-6		Top	80 PLF	0 PLF	0 PLF	0 PLF	Wall Self Weight
8	Point	0-2-10		Top	765 lb	766 lb	365 lb	0 lb	B9 Header Column
	Bearing Length	0-5-8							
9	Point	0-3-9		Near Face	237 lb	501 lb	29 lb	0 lb	J4
10	Part. Uniform	0-11-9 to 4-9-1		Near Face	130 PLF	346 PLF	0 PLF	0 PLF	
11	Point	4-6-5		Top	23 lb	50 lb	0 lb	0 lb	J4
	Bearing Length	0-5-8							
12	Point	4-6-5		Top	19 lb	0 lb	0 lb	0 lb	Wall Self Weight
	Bearing Length	0-5-8							
13	Point	4-6-5		Top	706 lb	697 lb	340 lb	0 lb	B9
	Bearing Length	0-5-8							
14	Point	4-6-5		Top	26 lb	57 lb	0 lb	0 lb	J4
	Bearing Length	0-5-8							
17	Point	4-6-5		Top	18 lb	0 lb	0 lb	0 lb	Wall Self Weight
	Bearing Length	0-5-8							
18	Point	4-6-5		Top	29 lb	62 lb	0 lb	0 lb	J4
	Bearing Length	0-5-8							
19	Point	4-6-5		Top	19 lb	0 lb	0 lb	0 lb	Wall Self Weight
	Bearing Length	0-5-8							
	Self Weight				12 PLF				

READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTES: EWP-FLOORS. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.



Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive chemicals

chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Boise Cascade Wood Products
1111 W. Jefferson St.
Boise, ID 83702
(800) 232-0788
www.bc.com
CCMC: 12472

This design is valid until 4/17/2026

Kott Inc.
3228 Moodie Dr, Ottawa, Ontario
613-838-2775 / 905-642-4400





Client: GREENPARK

Date: 7/14/2023



Project:

Input by: W C

Address: ZADORRA ESTATES
OSHAWA, ON

Job Name: ROSE 12-2 STD

Project #:

F5-A Ve *Chen* E 3100 SP 1.750" X 11.875" 2-Ply - PASSED Level: Ground Floor

Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	2	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2015 OBC 2012(2020 Update)
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal - II	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Direction	Live	Dead	Snow	Wind
1	Vertical	239	150	0	0
2	Vertical	234	146	0	0

Bearings and Factored Reactions

Bearing	Length	Dir.	Cap. React	D/L lb	Total	Ld. Case	Ld. Comb.
1 - Hanger	2.000"	Vert	7%	187 / 358	545	L	1.25D+1.5L
2 - SPF	2.375"	Vert	10%	183 / 351	534	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	820 ft-lb	3' 15/16"	35392 ft-lb	0.023 (2%)	1.25D+1.5L	L
Unbraced	820 ft-lb	3' 15/16"	35392 ft-lb	0.023 (2%)	1.25D+1.5L	L
Shear	484 lb	1'1 7/8"	13217 lb	0.037 (4%)	1.25D+1.5L	L
Perm Defl in. (L/49332)	0.001	3' 7/8"	0.198 (L/360)	0.007 (1%)	D	Uniform
LL Defl inch (L/30633)	0.002	3' 7/8"	0.198 (L/360)	0.012 (1%)	L	L
TL Defl inch (L/18898)	0.004	3' 7/8"	0.297 (L/240)	0.013 (1%)	D+L	L

Design Notes

- Provide support to prevent lateral movement and rotation at the end bearings. Lateral support may also be required at the interior bearings by the building code.
- Fill all hanger nailing holes.
- Left Header: DF, Thickness: 3 1/2"
- Girders are designed to be supported on the bottom edge only.
- Multiple plies must be fastened together as per manufacturer's details.
- Top loads must be supported equally by all plies.
- Top must be continuously laterally braced.
- Bottom must have sheathing attached or be continuously braced.
- Lateral slenderness ratio based on full section width.



JULY 14, 2023

READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTES: EWP-FLOORS. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

- Dry service conditions, unless noted otherwise
- LVL not to be treated with fire retardant or corrosive chemicals

chemicals

Handling & Installation

- LVL beams must not be cut or drilled
- Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
- Damaged Beams must not be used
- Design assumes top edge is laterally restrained
- Provide lateral support at bearing points to avoid lateral displacement and rotation

- For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Boise Cascade Wood Products
1111 W. Jefferson St.
Boise, ID 83702
(800) 232-0788
www.bc.com
CCMC: 12472

Kott Inc.
3228 Moodie Dr, Ottawa, Ontario
613-838-2775 / 905-642-4400



This design is valid until 4/17/2026



Client: GREENPARK

Date: 7/14/2023

Project:

Input by: W C



Address: ZADORRA ESTATES
OSHAWA, ON

Job Name: ROSE 12-2 STD

Project #:

F5-A Ve *Monte* E 3100 SP 1.750" X 11.875" 2-Ply - PASSED

Level: Ground Floor



ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 4-8-5	1-1-0	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Part. Uniform	0-0-0 to 4-8-5		Top	4 PLF	0 PLF	0 PLF	0 PLF	
3	Point	0-11-6		Far Face	23 lb	48 lb	0 lb	0 lb	J1
4	Part. Uniform	1-7-6 to 5-7-6		Far Face	19 PLF	39 PLF	0 PLF	0 PLF	
5	Tie-In	4-8-5 to 6-2-4	1-1-0	Top	15 PSF	40 PSF	0 PSF	0 PSF	
6	Part. Uniform	4-8-5 to 5-9-5		Top	4 PLF	0 PLF	0 PLF	0 PLF	
	Self Weight				12 PLF				



JULY 14, 2023

READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTES: EWP-FLOORS. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

This design is valid until 4/17/2026

Manufacturer Info

Boise Cascade Wood Products
1111 W. Jefferson St.
Boise, ID 83702
(800) 232-0788
www.bc.com
CCMC: 12472

Kott Inc.

3228 Moodie Dr, Ottawa, Ontario
613-838-2775 / 905-642-4400





Client: GREENPARK

Date: 7/14/2023

Project:



Input by: W C

Address: ZADORRA ESTATES
OSHAWA, ON

Job Name: ROSE 12-2 STD

Project #:

F6-A Ve [Signature] E 3100 SP 1.750" X 11.875" 2-Ply - PASSED Level: Ground Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	2	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2015 OBC 2012(2020 Update)
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal - II	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Direction	Live	Dead	Snow	Wind
1	Vertical	304	217	0	0
2	Vertical	802	490	0	0

Bearings and Factored Reactions

Bearing	Length	Dir.	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	5.250"	Vert	6%	271 / 456	727	L	1.25D+1.5L
2 - SPF	6.000"	Vert	8%	613 / 1203	1815	L	1.25D+1.5L
End Grain							

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	1184 ft-lb	2'4 11/16"	35392 ft-lb	0.033 (3%)	1.25D+1.5L	L
Unbraced	1184 ft-lb	2'4 11/16"	35392 ft-lb	0.033 (3%)	1.25D+1.5L	L
Shear	597 lb	1'5 1/8"	13217 lb	0.045 (5%)	1.25D+1.5L	L
Perm Defl in.	0.003 (L/28699)	3'9 1/2"	0.244 (L/360)	0.013 (1%)	D	Uniform
LL Defl inch	0.004 (L/20616)	3'9"	0.244 (L/360)	0.017 (2%)	L	L
TL Defl inch	0.007 (L/11998)	3'9 1/4"	0.367 (L/240)	0.020 (2%)	D+L	L

Design Notes

- 1 Provide support to prevent lateral movement and rotation at the end bearings. Lateral support may also be required at the interior bearings by the building code.
- 2 Girders are designed to be supported on the bottom edge only.
- 3 Multiple plies must be fastened together as per manufacturer's details.
- 4 Top loads must be supported equally by all plies.
- 5 Top must be continuously laterally braced.
- 6 Bottom must be laterally braced at a maximum of 5'6 1/16" o.c.
- 7 Lateral slenderness ratio based on full section width.



JULY 14, 2023

READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTES: EWP-FLOORS. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 0-2-10	0-4-9	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Part. Uniform	0-0-0 to 0-2-10		Top	2 PLF	0 PLF	0 PLF	0 PLF	
3	Part. Uniform	0-0-0 to 0-2-10		Top	1 PLF	0 PLF	0 PLF	0 PLF	
4	Tie-In	0-2-10 to 2-2-15	0-6-9	Top	15 PSF	40 PSF	0 PSF	0 PSF	

Continued on page 2...

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Boise Cascade Wood Products
1111 W. Jefferson St.
Boise, ID 83702
(800) 232-0788
www.bc.com
CCMC: 12472

Kott Inc.
3228 Moodie Dr, Ottawa, Ontario
613-838-2775 / 905-642-4400



This design is valid until 4/17/2026