

Engineering Note Page (ENP-2)

REVISION 2018-10-17

Please read all notes prior to installation of the component**DESIGN INFORMATION**

This building component is certified as an individual component for the loads and conditions shown on the calculation and drawing page.

The responsibility of the undersigned engineer is only limited to the calculation of this building component for the loads and conditions shown on this drawing.

The responsibility of the undersigned is limited to the verification of the structural capacity of the floor joists and LVL beams based on placement as shown on the layout. The loads applied are limited to the gravity effects of the specified loads. The structural integrity of the building and the effect of wind, uplift, seismic, lateral or other forces, calculation of adequate support and anchorage of components, as well as the dimensions and design loads used to calculate components are the responsibility of the overall building designer.

Floor joists and OSB rim board are designed to carry uniformly distributed loads only. Point loads should be transferred through the floor cavity with transfer blocks. Structural elements such as walls, posts, connectors, and transfer blocks are the responsibility of the overall building designer.

The undersigned engineer disclaims any responsibility for damages as a result of being furnished faulty or incorrect information, specifications and/or designs.

Installation of floor joists is to be carried out in accordance with the current edition of the manufacturer's literature available at <http://www.kottgroup.com>.

CODE

This building component is designed in accordance with the National Building Code of Canada, the Ontario Building Code, CCMC and Canadian Standards Association guidelines.


COMPONENT

1. The building component used in construction must be the same as indicated on the drawings.
2. The building component must be installed and assembled as per specification shown on the drawing and in accordance with the manufacturer's assembly and installation.
3. Members consisting of multiple plies must be connected as per the document "Multi-ply Connection Details".
4. Pass-thru transfer block framing is required at all point loads over bearings.

HANDLING AND INSTALLATION

Do not drill any hole, cut or notch a certified building component without a written pre-authorization.


Conventional Connections



Conventional connection notes:

- Nails to be 3" long wire nails.
- Nails to be located 2" min. from the top and bottom of the member. Start all nails 2 1/2" min. from ends.
- Number of rows and spacing as per details shown, unless noted otherwise.
- "X" represents nail driven from the opposite side.

LVL Connections



LVL connection notes:

- LVL ply width is 1-3/4"
- Nails to be 3 1/2" common wire nails.
- Nails to be located 2 1/2" min. from the top and bottom of the member. Start all nails 2 1/2" min. from ends.
- Minimum 3 1/4" spacing between rows.
- Number of rows and spacing as per details shown, unless noted otherwise.
- "X" represents nail or screw driven from the opposite side.

For side-loaded 4-ply LVL Connections, please consult the engineering calculation page for the component and the KOTT floor layout

Multiple Member Connections

All connections are for uniformly distributed loads.

For multi-ply connections of I-joists, refer to Manufacturer's Installation Guide



KOTT Inc.
3228 Moodie Drive
Ottawa, ON
K2H 7V1
613-838-2775


Structural floor plan showing various framing members and components. Key labels include:

- Joists:** J1-AQ @ 16", J1-AT, J1-AW, J6-P @ 16"
- Beams:** F10-A - 2 ply, F14-A - 1 ply, F15-A - 1 ply, F15-B - 1 ply, F15-C - 1 ply, F15-D - 1 ply, F6-B - 1 ply, F7-B - 1 ply, F8-A - 1 ply, F9-A - 1 ply
- Other Components:** BBO-DROP, PS, BLOCKING, 2 X J6-R, 2 X J1-AI, 3 X J1-AT, 2 X J1-AW
- Notes:** FRAMING BY OTHERS (indicated by a white arrow pointing to a specific area)

JARDIN DESIGN GROUP
64 JARDIN DR, SUITE 3A
VAUGHAN, ON L4K 3P3
Project # 17-55
Model: LOT-9 (AMELIA 3 EL-2)
Date: AUG 30, 2018

1. OBC 2012 O.Reg 332/12 as amended
2. Nascor CCMC - 13535-R
3. LVL CCMC -12904-R
4. CAN/CSA-O86-09
5. CCMC -12787-R APA PR-L310(C)

1. The loads used in the calculation of the attached approved components conform to the floor assembly shown on this layout.
2. The floor joists comply with the KOTT span table for the loads and spacing shown on this layout. The floor system must be assembled in accordance to the KOTT Specifier Guide. Multi-ply members must be attached together as per the included multiple member connection detail.



Label	Description	Width	Depth	Qty	Plies	Pcs	Length
F9	Forex 2.0E-3000Fb LVL	1.75	11.875			1	12-0-0
F8	Forex 2.0E-3000Fb LVL	1.75	11.875			1	10-0-0
F11	Forex 2.0E-3000Fb LVL	1.75	11.875	1	2	2	8-0-0
F7	Forex 2.0E-3000Fb LVL	1.75	11.875			1	8-0-0
F10	Forex 2.0E-3000Fb LVL	1.75	11.875	1	2	2	6-0-0
F6	Forex 2.0E-3000Fb LVL	1.75	11.875			1	4-0-0

Label	Description	Width	Depth	Qty	Plies	Pcs	Length
F15	LPI 20Plus	2.5	11.875			4	16-0-0
F14	LPI 20Plus	2.5	11.875			2	4-0-0
J1	LPI 20Plus	2.5	11.875			30	16-0-0
J6	LPI 20Plus	2.5	11.875			18	14-0-0
J5	LPI 20Plus	2.5	11.875			4	12-0-0
J4	LPI 20Plus	2.5	11.875			1	10-0-0
J10	LPI 20Plus	2.5	11.875			7	8-0-0
J2	LPI 20Plus	2.5	11.875			1	6-0-0
J7	NJ60H	2.5	11.875			3	16-0-0

Label	Description	Width	Depth	Qty	Plies	Pcs	Length
R1	Norbord Rimboard Plus 1.125 X 11.875	1.125	11.875			16	12

					Beam/Girder	Supported Member
Label	Pcs	Description	Skew	Slope	fasteners	fasteners
H1	1	Unknown Hanger				
H2	2	HUS1.81/10			30 10dx1 1/2	10 16d
H3	25	LF2511			12 10d	1 #8x1 1/4WS
H5	1	HUS1.81/10				

Label	Description	Width	Depth	Qty	Plies	Pcs	Length
BLK1	LPI 20 Plus	2.5	11.875	LinFt		Varies	46-0-0

1. Framer to verify dimensions on the architectural drawings.
2. Double joist only require filler/backer ply when supporting another member using a face-mounted hanger.
3. Install 2x4 blocking @ 24" o/c under parallel non-loadbearing walls.
4. Install single-ply flush window header along inside face of rimboard/rimjoist
5. Refer to Nascor specifier guide for installation details.
6. Squash blocks recommended to be installed at end bearing on all first level joists which support loading from above exceeding two levels floor or roof.
7. Load transfer blocks to be installed under all point loads.
8. It shall be the framer's responsibility that floor joists and beams are fastened as per the hanger manufacturer's standards.

Rim parallel to joists: 1-1/8" rimboard with 2"x4" block (1/16" longer than rim depth) @ 16" o/c.

All other components and structural elements supporting the floor system such as beams, walls, columns and foundation walls and footings including anchorage of components and bracing for lateral stability are the responsibility of others.

The framing shown on this layout may be deviate from the architectural drawings. Project Engineer to review and approve the deviation prior to construction.

PS	Point Load Support
◇	Load from Above
	Wall
	Norbord Rimboard Plus 1.125 X 11.875
	LPI 20Plus 11.875
	NJ60H 11.875
	Forex 2.0E-3000FB LVL 1.75 X 11.875
	5.25 X 10.25 (Dropped)



Fastener	Nailed & Glued
Vibration	







Client:
Project:
Address:

Date: 12/18/2018
Designer: S B
Job Name: LOT 9 (AMELIA 3 EL-2)
Project #:

Page 1 of 1

F10-A Forex 2.0E-3000Fb LVL 1.750" X 11.875" 2-Ply - PASSED Level: Ground Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	2	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	776	314	0	0
2	759	308	0	0

Bearings and Factored Reactions

Bearing	Length	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	3.500"	21%	393 / 1165	1557	L	1.25D+1.5L
2 - SPF	3.500"	20%	385 / 1139	1524	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	1247 ft-lb	2'3 11/16"	34261 ft-lb	0.036 (4%)	1.25D+1.5L	L
Unbraced	1247 ft-lb	2'3 11/16"	34261 ft-lb	0.036 (4%)	1.25D+1.5L	L
Shear	1546 lb	1'2 5/8"	11596 lb	0.133 (13%)	1.25D+1.5L	L
Perm Defl in. (L/33117)	0.002	2'3 13/16"	0.140 (L/360)	0.010 (1%)	D	Uniform
LL Defl inch (L/13619)	0.004	2'3 13/16"	0.140 (L/360)	0.030 (3%)	L	L
TL Defl inch (L/9650)	0.005	2'3 13/16"	0.210 (L/240)	0.020 (2%)	D+L	L

Design Notes

- Girders are designed to be supported on the bottom edge only.
- Multiple plies must be fastened together as per manufacturer's details.
- Top loads must be supported equally by all plies.
- Top braced at bearings.
- Bottom braced at bearings.
- Lateral slenderness ratio based on full section width.



January 02, 2019

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 4-2-8	(Span)1-2-0	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Point	0-4-10		Near Face	139 lb	371 lb	0 lb	0 lb	J1
3	Part. Uniform	1-0-10 to 3-8-10		Near Face	106 PLF	281 PLF	0 PLF	0 PLF	J1
4	Point	4-4-10		Near Face	119 lb	317 lb	0 lb	0 lb	J1
	Self Weight				10 PLF				

Pass Thru Framing Squash Block is required at all point loads over bearings

Refer to Multiple Member Connection Detail for ply to ply nailing or bolting requirements

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

- Dry service conditions, unless noted otherwise
- LVL not to be treated with fire retardant or corrosive chemicals

Handling & Installation

- LVL beams must not be cut or drilled
- Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
- Damaged Beams must not be used
- Design assumes top edge is laterally restrained
- Provide lateral support at bearing points to avoid lateral displacement and rotation

- For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318

Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400



This design is valid until 10/18/2021







Client:
Project:
Address:

Date: 12/18/2018
Designer: S B
Job Name: LOT 9 (AMELIA 3 EL-2)
Project #:

Page 1 of 1

F11-C Forex 2.0E-3000Fb LVL 1.750" X 11.875" 2-Ply - PASSED Level: Ground Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	2	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	837	383	0	0
2	823	385	0	0

Bearings and Factored Reactions

Bearing	Length	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	5.500"	15%	479 / 1256	1735	L	1.25D+1.5L
2 - SPF	4.375"	18%	482 / 1234	1716	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	2763 ft-lb	3'2 11/16"	34261 ft-lb	0.081 (8%)	1.25D+1.5L	L
Unbraced	2763 ft-lb	3'2 11/16"	32711 ft-lb	0.084 (8%)	1.25D+1.5L	L
Shear	1902 lb	5'2 1/8"	11596 lb	0.164 (16%)	1.25D+1.5L	L
Perm Defl in.	0.005 (L/12838)	3'3 1/4"	0.192 (L/360)	0.030 (3%)	D	Uniform
LL Defl inch	0.012 (L/5833)	3'3 1/16"	0.192 (L/360)	0.060 (6%)	L	L
TL Defl inch	0.017 (L/4011)	3'3 1/8"	0.289 (L/240)	0.060 (6%)	D+L	L

Design Notes

- 1 Performed Secondary Bearing Check (CSA 086-14 6.5.7.3). Assumed point load size: beam width X 4.5.
- 2 Girders are designed to be supported on the bottom edge only.
- 3 Multiple plies must be fastened together as per manufacturer's details.
- 4 Top loads must be supported equally by all plies.
- 5 Top braced at bearings.
- 6 Bottom braced at bearings.
- 7 Lateral slenderness ratio based on full section width.

READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTE PAGE ENP-2. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.



January 02, 2019

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Part. Uniform	0-0-0 to 6-5-10		Top	15 PLF	40 PLF	0 PLF	0 PLF	
2	Point	0-2-12		Top	1 lb	0 lb	0 lb	0 lb	Wall Self Weight
3	Part. Uniform	0-10-12 to 3-6-12		Near Face	129 PLF	305 PLF	0 PLF	0 PLF	Pass-Thru Framing Squash Block is required at all point loads over bearings
4	Point	4-2-12		Near Face	171 lb	387 lb	0 lb	0 lb	J7
5	Point	5-6-12		Near Face	94 lb	201 lb	0 lb	0 lb	J4
	Self Weight				10 PLF				

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318

Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400



This design is valid until 10/18/2021






Client:
Project:
Address:

Date: 12/18/2018
Designer: S B
Job Name: LOT 9 (AMELIA 3 EL-2)
Project #:


Page 1 of 1

F14-A LPI 20Plus 11.875" - PASSED

Level: Ground Floor



1 Hanger (LF2511)
2 Hanger (LF2511)
2'6 1/2"
2'6 1/2"


Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	266	99	0	0
2	328	123	0	0

Bearings and Factored Reactions

Bearing	Length	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - Hanger	2.000"	33%	124 / 399	523	L	1.25D+1.5L
2 - Hanger	2.000"	41%	154 / 493	646	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	353 ft-lb	9 3/4"	6250 ft-lb	0.056 (6%)	1.25D+1.5L	L
Shear	641 lb	2'5 1/4"	2345 lb	0.273 (27%)	1.25D+1.5L	L
Perm Defl in. (L/20184)	0.001	9 3/4"	0.078 (L/360)	0.020 (2%)	D	Uniform
LL Defl inch	0.004 (L/7547)	9 3/4"	0.078 (L/360)	0.050 (5%)	L	L
TL Defl inch	0.005 (L/5493)	9 3/4"	0.117 (L/240)	0.040 (4%)	D+L	L

Design Notes

- 1 Provide restraint at supports to ensure lateral stability.
- 2 Dead Load Deflection: Instant = 0.001", Long Term = 0.002"
- 3 Fill all hanger nailing holes.
- 4 See manufacture installation guide note E4 for installation details
- 5 Girders are designed to be supported on the bottom edge only.
- 6 Top flange braced at bearings.
- 7 Bottom flange braced at bearings.



January 02, 2019

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 2-6-8	(Span)1-4-9	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Point	0-9-12		Near Face	108 lb	289 lb	0 lb	0 lb	J6
3	Point	2-1-12		Near Face	88 lb	235 lb	0 lb	0 lb	J6

READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTE PAGE ENP-2. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

Pass-Thru Framing Squash Block is required at all point loads over bearings

Refer to Multiple Member Connection Detail for ply to ply nailing or bolting requirements

Notes

This component analysis is based on the loads, geometry and other conditions as entered by the user and listed in this report. The user is responsible to ensure the accuracy of the input and the applicability to the actual conditions of the structure for which this component is intended. This analysis is valid only for the product listed.

Copyright 2016 All rights reserved by Louisiana Pacific Corp. 414 Union St Suite 2000, Nashville, TN 37219

This design is valid until 10/31/2020

Manufacturer Info

Louisiana-Pacific Corp
414 Union Street, Suite 2000
Nashville, TN 37219
(888) 820-0325
www.lpcorp.com
CCMC: 12412-R APA: PR-L238C

Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400








Client:
Project:
Address:

Date: 12/18/2018
Designer: S B
Job Name: LOT 9 (AMELIA 3 EL-2)
Project #:

Page 1 of 1

F14-B LPI 20Plus 11.875" - PASSED

Level: Ground Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	304	148	0	0
2	328	161	0	0

Bearings and Factored Reactions

Bearing	Length	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - Hanger	2.000"	40%	185 / 455	640	L	1.25D+1.5L
2 - Hanger	2.000"	44%	202 / 492	694	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	436 ft-lb	9 3/4"	6250 ft-lb	0.070 (7%)	1.25D+1.5L	L
Shear	689 lb	2'8 1/4"	2345 lb	0.294 (29%)	1.25D+1.5L	L
Perm Defl in. (L/14174)	0.002	1'1 9/16"	0.086 (L/360)	0.030 (3%)	D	Uniform
LL Defl inch	0.004 (L/6920)	1'1 3/8"	0.086 (L/360)	0.050 (5%)	L	L
TL Defl inch	0.007 (L/4650)	1'1 7/16"	0.129 (L/240)	0.050 (5%)	D+L	L

Design Notes

- 1 Provide restraint at supports to ensure lateral stability.
- 2 Dead Load Deflection: Instant = 0.002", Long Term = 0.003"
- 3 Fill all hanger nailing holes.
- 4 See manufacture installation guide note E4 for installation details
- 5 Girders are designed to be supported on the bottom edge only.
- 6 Top flange braced at bearings.
- 7 Bottom flange braced at bearings.



January 02, 2019

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 2-9-8	(Span)1-3-7	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Part. Uniform	0-0-0 to 2-9-8		Top	3 PLF	0 PLF	0 PLF	0 PLF	
3	Point	0-9-12		Far Face	141 lb	291 lb	0 lb	0 lb	J6
4	Point	2-1-12		Far Face	133 lb	269 lb	0 lb	0 lb	J6

READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTE PAGE ENP-2. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

Pass-Thru Framing Squash Block is required at all point loads over bearings

Refer to Multiple Member Connection Detail for ply to ply nailing or bolting requirements

Notes

This component analysis is based on the loads, geometry and other conditions as entered by the user and listed in this report. The user is responsible to ensure the accuracy of the input and the applicability to the actual conditions of the structure for which this component is intended. This analysis is valid only for the product listed.

Copyright 2016 All rights reserved by Louisiana Pacific Corp. 414 Union St Suite 2000, Nashville, TN 37219



This design is valid until
10/31/2020

Manufacturer Info

Louisiana-Pacific Corp
414 Union Street, Suite 2000
Nashville, TN 37219
(888) 820-0325
www.lpcorp.com
CCMC: 12412-R APA: PR-L238C

Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400






Client:
Project:
Address:

Date: 12/18/2018
Designer: S B
Job Name: LOT 9 (AMELIA 3 EL-2)
Project #:

Page 1 of 1

F15-A LPI 20Plus 11.875" - PASSED

Level: Ground Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	544	203	0	0
2	280	105	0	0

Bearings and Factored Reactions

Bearing	Length	Cap. React D/L lb	Total Ld. Case	Ld. Comb.
1 - SPF	2.375"	65% 254 / 816	1070 L	1.25D+1.5L
2 - SPF	4.125"	30% 131 / 420	552 L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	2057 ft-lb	6'5 1/4"	6250 ft-lb	0.329 (33%)	1.25D+1.5L	L
Shear	1051 lb	1 5/8"	2345 lb	0.448 (45%)	1.25D+1.5L	L
Perm Defl in.	0.052 (L/3252)	6'10 7/8"	0.468 (L/360)	0.110 (11%)	D	Uniform
LL Defl inch	0.138 (L/1218)	6'10 7/8"	0.468 (L/360)	0.300 (30%)	L	L
TL Defl inch	0.190 (L/886)	6'10 7/8"	0.702 (L/240)	0.270 (27%)	D+L	L

Design Notes

- 1 Provide restraint at supports to ensure lateral stability.
- 2 Dead Load Deflection: Instant = 0.052", Long Term = 0.078"
- 3 See manufacture installation guide note E4 for installation details
- 4 Girders are designed to be supported on the bottom edge only.
- 5 Top flange must be laterally braced at a maximum of 7'3" o.c.
- 6 Bottom flange braced at bearings.



January 02, 2019

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 1-5-4	(Span)2-9-0	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Tie-In	0-0-0 to 14-5-6	(Span)0-10-0	Top	15 PSF	40 PSF	0 PSF	0 PSF	
3	Point	1-4-0		Far Face	99 lb	266 lb	0 lb	0 lb	F14
4	Tie-In	1-5-4 to 14-5-6	(Span)0-11-0	Top	15 PSF	40 PSF	0 PSF	0 PSF	

READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTE PAGE ENP-2. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

Pass-Thru Framing Squash Block is required at all point loads over bearings

Refer to Multiple Member Connection Detail for ply to ply nailing or bolting requirements

Notes

This component analysis is based on the loads, geometry and other conditions as entered by the user and listed in this report. The user is responsible to ensure the accuracy of the input and the applicability to the actual conditions of the structure for which this component is intended. This analysis is valid only for the product listed.

Copyright 2016 All rights reserved by Louisiana Pacific Corp. 414 Union St Suite 2000, Nashville, TN 37219



This design is valid until
10/31/2020

Manufacturer Info

Louisiana-Pacific Corp
414 Union Street, Suite 2000
Nashville, TN 37219
(888) 820-0325
www.lpcorp.com
CCMC: 12412-R APA: PR-L238C

Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400






Client:
Project:
Address:

Date: 12/18/2018
Designer: S B
Job Name: LOT 9 (AMELIA 3 EL-2)
Project #:

Page 1 of 1

F15-B LPI 20Plus 11.875" - PASSED

Level: Ground Floor


Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	576	216	0	0
2	250	94	0	0

Bearings and Factored Reactions

Bearing	Length	Cap. React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	2.375"	69%	270 / 864	1134 L	1.25D+1.5L
2 - SPF	4.500"	27%	117 / 375	493 L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	1902 ft-lb	6'1 5/16"	6250 ft-lb	0.304 (30%)	1.25D+1.5L	L
Shear	1114 lb	1 5/8"	2345 lb	0.475 (48%)	1.25D+1.5L	L
Perm Defl in.	0.048 (L/3510)	6'9 5/8"	0.467 (L/360)	0.100 (10%)	D	Uniform
LL Defl inch	0.128 (L/1316)	6'9 5/8"	0.467 (L/360)	0.270 (27%)	L	L
TL Defl inch	0.176 (L/957)	6'9 5/8"	0.700 (L/240)	0.250 (25%)	D+L	L

Design Notes

- 1 Provide restraint at supports to ensure lateral stability.
- 2 Dead Load Deflection: Instant = 0.048", Long Term = 0.072"
- 3 See manufacture installation guide note E4 for installation details
- 4 Girders are designed to be supported on the bottom edge only.
- 5 Top flange must be laterally braced at a maximum of 7'6" o.c.
- 6 Bottom flange braced at bearings.



January 02, 2019

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 14-5-6	(Span)1-0-0	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Tie-In	0-0-0 to 1-5-4	(Span)2-9-0	Top	15 PSF	40 PSF	0 PSF	0 PSF	
3	Point	1-4-0		Near Face	123 lb	328 lb	0 lb	0 lb	F14
4	Tie-In	1-5-4 to 14-5-6	(Span)0-6-0	Top	15 PSF	40 PSF	0 PSF	0 PSF	

READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTE PAGE ENP-2. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

Pass-Thru Framing Squash Block is required at all point loads over bearings

Refer to Multiple Member Connection Detail for ply to ply nailing or bolting requirements

Notes

This component analysis is based on the loads, geometry and other conditions as entered by the user and listed in this report. The user is responsible to ensure the accuracy of the input and the applicability to the actual conditions of the structure for which this component is intended. This analysis is valid only for the product listed.

Copyright 2016 All rights reserved by Louisiana Pacific Corp. 414 Union St Suite 2000, Nashville, TN 37219



This design is valid until
10/31/2020

Manufacturer Info

Louisiana-Pacific Corp
414 Union Street, Suite 2000
Nashville, TN 37219
(888) 820-0325
www.lpcorp.com
CCMC: 12412-R APA: PR-L238C

Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400






Client:
Project:
Address:

Date: 12/18/2018
Designer: S B
Job Name: LOT 9 (AMELIA 3 EL-2)
Project #:

Page 1 of 2

F15-C LPI 20Plus 11.875" - PASSED

Level: Ground Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	551	270	0	0
2	522	267	0	0

Bearings and Factored Reactions

Bearing	Length	Cap. React	D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	2.375"	71%	338 / 827	1164	L	1.25D+1.5L
2 - SPF	5.250"	61%	333 / 783	1117	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	1834 ft-lb	6'1 1/8"	6250 ft-lb	0.293 (29%)	1.25D+1.5L	L
Shear	1144 lb	1 5/8"	2345 lb	0.488 (49%)	1.25D+1.5L	L
Perm Defl in.	0.056 (L/2990)	6'9 3/4"	0.468 (L/360)	0.120 (12%)	D	Uniform
LL Defl inch	0.115 (L/1461)	6'9 3/4"	0.468 (L/360)	0.250 (25%)	L	L
TL Defl inch	0.172 (L/982)	6'9 3/4"	0.702 (L/240)	0.240 (24%)	D+L	L

Design Notes

- 1 Provide restraint at supports to ensure lateral stability.
- 2 Applied loads over end bearings and loads exceeding 250 lbs over intermediate bearings must be transferred directly to the support by rim board, blocking, squash blocks, or other device.
- 3 Dead Load Deflection: Instant = 0.056", Long Term = 0.084"
- 4 See manufacture installation guide note E4 for installation details
- 5 Girders are designed to be supported on the bottom edge only.
- 6 Top flange must be laterally braced at a maximum of 7'7" o.c.
- 7 Bottom flange braced at bearings.



January 02, 2019

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 1-4-2	(Span)3-0-0 to 3-0-0	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Tie-In	0-0-0 to 14-1-4	(Span)0-7-0	Top	15 PSF	40 PSF	0 PSF	0 PSF	
3	Part. Uniform	0-0-10 to 14-1-4		Top	1 PLF	0 PLF	0 PLF	0 PLF	Pass-Thru Framing Squash Block is required at all point loads over bearings
4	Part. Uniform	0-0-12 to 1-4-2		Top	8 PLF	0 PLF	0 PLF	0 PLF	Refer to Multiple Member Connection Detail for ply to ply nailing or bolting requirements
5	Point	1-2-14		Far Face	161 lb	328 lb	0 lb	0 lb	

Continued on page 2...

READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTE PAGE ENP-2. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

Notes

This component analysis is based on the loads, geometry and other conditions as entered by the user and listed in this report. The user is responsible to ensure the accuracy of the input and the applicability to the actual conditions of the structure for which this component is intended. This analysis is valid only for the product listed.

Copyright 2016 All rights reserved by Louisiana Pacific Corp. 414 Union St Suite 2000, Nashville, TN 37219



This design is valid until
10/31/2020

Manufacturer Info

Louisiana-Pacific Corp
414 Union Street, Suite 2000
Nashville, TN 37219
(888) 820-0325
www.lpcorp.com
CCMC: 12412-R APA: PR-L238C

Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400






Client:
Project:
Address:

Date: 12/18/2018
Designer: S B
Job Name: LOT 9 (AMELIA 3 EL-2)
Project #:

Page 2 of 2

F15-C LPI 20Plus 11.875" - PASSED

Level: Ground Floor



...Continued from page 1

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
6	Tie-In	1-4-2 to 14-6-8	(Span)0-9-0	Top	15 PSF	40 PSF	0 PSF	0 PSF	
7	Part. Uniform	1-4-2 to 14-5-1		Top	2 PLF	0 PLF	0 PLF	0 PLF	
8	Tie-In	14-1-4 to 14-6-8	(Span)0-4-0	Top	15 PSF	40 PSF	0 PSF	0 PSF	
9	Part. Uniform	14-1-4 to 14-5-1		Top	1 PLF	0 PLF	0 PLF	0 PLF	
10	Point	14-3-14		Top	61 lb	155 lb	0 lb	0 lb	J1
	Bearing Length	0-1-8							
11	Point	14-3-14		Top	4 lb	10 lb	0 lb	0 lb	J6
	Bearing Length	0-1-8							
12	Point	14-3-14		Top	50 lb	134 lb	0 lb	0 lb	J6
	Bearing Length	0-1-8							
13	Point	14-3-14		Top	43 lb	0 lb	0 lb	0 lb	Wall Self Weight
	Bearing Length	0-1-8							



January 02, 2019

READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTE PAGE ENP-2. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

Pass-Thru Framing Squash Block is required at all point loads over bearings

Refer to Multiple Member Connection Detail for ply to ply nailing or bolting requirements

Notes

This component analysis is based on the loads, geometry and other conditions as entered by the user and listed in this report. The user is responsible to ensure the accuracy of the input and the applicability to the actual conditions of the structure for which this component is intended. This analysis is valid only for the product listed.

Copyright 2016 All rights reserved by Louisiana Pacific Corp. 414 Union St Suite 2000, Nashville, TN 37219



This design is valid until
10/31/2020

Manufacturer Info

Louisiana-Pacific Corp
414 Union Street, Suite 2000
Nashville, TN 37219
(888) 820-0325
www.lpcorp.com
CCMC: 12412-R APA: PR-L238C

Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400






Client:
Project:
Address:

Date: 12/18/2018
Designer: S B
Job Name: LOT 9 (AMELIA 3 EL-2)
Project #:

Page 1 of 2

F15-D LPI 20Plus 11.875" - PASSED

Level: Ground Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	632	311	0	0
2	698	354	0	0

Bearings and Factored Reactions


Bearing	Length	Cap. React	D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	2.375"	82%	389 / 948	1336	L	1.25D+1.5L
2 - SPF	5.250"	81%	442 / 1048	1490	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	2576 ft-lb	6'6 5/16"	6250 ft-lb	0.412 (41%)	1.25D+1.5L	L
Shear	1313 lb	1 5/8"	2345 lb	0.560 (56%)	1.25D+1.5L	L
Perm Defl in.	0.079 (L/2119)	6'11 3/16"	0.468 (L/360)	0.170 (17%)	D	Uniform
LL Defl inch	0.161 (L/1047)	6'11 3/16"	0.468 (L/360)	0.340 (34%)	L	L
TL Defl inch	0.240 (L/701)	6'11 3/16"	0.702 (L/240)	0.340 (34%)	D+L	L

Design Notes

- 1 Provide restraint at supports to ensure lateral stability.
- 2 Applied loads over end bearings and loads exceeding 250 lbs over intermediate bearings must be transferred directly to the support by rim board, blocking, squash blocks, or other device.
- 3 Dead Load Deflection: Instant = 0.079", Long Term = 0.119"
- 4 See manufacture installation guide note E4 for installation details
- 5 Girders are designed to be supported on the bottom edge only.
- 6 Top flange must be laterally braced at a maximum of 6'6" o.c.
- 7 Bottom flange braced at bearings.



ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 14-1-4	(Span)1-2-0 to 1-2-0	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Tie-In	0-0-0 to 1-4-2	(Span)3-0-0 to 3-0-0	Top	15 PSF	40 PSF	0 PSF	0 PSF	
3	Part. Uniform	0-0-14 to 1-4-2		Top	8 PLF	0 PLF	0 PLF	0 PLF	Pass-Thru Framing Squash Block is required at all point loads over bearings
4	Part. Uniform	0-0-15 to 14-1-4		Top	3 PLF	0 PLF	0 PLF	0 PLF	Refer to Multiple Member Connection Detail for ply to ply nailing or bolting requirements

Continued on page 2...

Notes

This component analysis is based on the loads, geometry and other conditions as entered by the user and listed in this report. The user is responsible to ensure the accuracy of the input and the applicability to the actual conditions of the structure for which this component is intended. This analysis is valid only for the product listed.

Copyright 2016 All rights reserved by Louisiana Pacific Corp. 414 Union St Suite 2000, Nashville, TN 37219

READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTE PAGE ENP-2. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.



This design is valid until
10/31/2020

Manufacturer Info

Louisiana-Pacific Corp
414 Union Street, Suite 2000
Nashville, TN 37219
(888) 820-0325
www.lpcorp.com
CCMC: 12412-R APA: PR-L238C

Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400






Client:
Project:
Address:

Date: 12/18/2018
Designer: S B
Job Name: LOT 9 (AMELIA 3 EL-2)
Project #:

Page 2 of 2

F15-D LPI 20Plus 11.875" - PASSED

Level: Ground Floor



...Continued from page 1

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
5	Point	1-2-14		Near Face	148 lb	304 lb	0 lb	0 lb	F14
6	Tie-In	1-4-2 to 14-1-4	(Span)0-11-0 to 0-11-0	Top	15 PSF	40 PSF	0 PSF	0 PSF	
7	Part. Uniform	1-4-2 to 14-1-4		Top	2 PLF	0 PLF	0 PLF	0 PLF	
8	Tie-In	14-1-4 to 14-6-8	(Span)0-8-0	Top	15 PSF	40 PSF	0 PSF	0 PSF	
9	Tie-In	14-1-4 to 14-6-8	(Span)0-8-0	Top	15 PSF	40 PSF	0 PSF	0 PSF	
10	Part. Uniform	14-1-4 to 14-5-5		Top	2 PLF	0 PLF	0 PLF	0 PLF	
11	Part. Uniform	14-1-4 to 14-5-4		Top	2 PLF	0 PLF	0 PLF	0 PLF	
12	Point	14-3-14		Top	69 lb	185 lb	0 lb	0 lb	J1
	Bearing Length	0-1-8							
13	Point	14-3-14		Top	41 lb	109 lb	0 lb	0 lb	J6
	Bearing Length	0-1-8							
14	Point	14-3-14		Top	29 lb	77 lb	0 lb	0 lb	J6
	Bearing Length	0-1-8							
15	Point	14-3-14		Top	53 lb	0 lb	0 lb	0 lb	Wall Self Weight
	Bearing Length	0-1-8							

Pass-Thru Framing Squash Block is required at all point loads over bearings

Refer to Multiple Member Connection Detail for ply to ply nailing or bolting requirements

READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTE PAGE ENP-2. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.



January 02, 2019

Notes

This component analysis is based on the loads, geometry and other conditions as entered by the user and listed in this report. The user is responsible to ensure the accuracy of the input and the applicability to the actual conditions of the structure for which this component is intended. This analysis is valid only for the product listed.

Copyright 2016 All rights reserved by Louisiana Pacific Corp. 414 Union St Suite 2000, Nashville, TN 37219



This design is valid until
10/31/2020

Manufacturer Info

Louisiana-Pacific Corp
414 Union Street, Suite 2000
Nashville, TN 37219
(888) 820-0325
www.lpcorp.com
CCMC: 12412-R APA: PR-L238C

Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400







Client:
Project:
Address:

Date: 12/18/2018
Designer: S B
Job Name: LOT 9 (AMELIA 3 EL-2)
Project #:

Page 1 of 1

F6-B Forex 2.0E-3000Fb LVL 1.750" X 11.875" - PASSED

Level: Ground Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	360	170	0	0
2	259	122	0	0

Bearings and Factored Reactions

Bearing	Length	Cap. React	D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	5.500"	13%	213 / 540	753	L	1.25D+1.5L
2 - Hanger	3.000"	14%	152 / 389	541	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	485 ft-lb	1'11 1/4"	17130 ft-lb	0.028 (3%)	1.25D+1.5L	L
Unbraced	485 ft-lb	1'11 1/4"	13987 ft-lb	0.035 (3%)	1.25D+1.5L	L
Shear	526 lb	1'4 5/8"	5798 lb	0.091 (9%)	1.25D+1.5L	L
Perm Defl in. (L/36212)	0.001	1'10 7/16"	0.097 (L/360)	0.010 (1%)	D	Uniform
LL Defl inch (L/17367)	0.002	1'10 5/16"	0.097 (L/360)	0.020 (2%)	L	L
TL Defl inch (L/11738)	0.003	1'10 5/16"	0.145 (L/240)	0.020 (2%)	D+L	L

Design Notes

- 1 Fill all hanger nailing holes.
- 2 Girders are designed to be supported on the bottom edge only.
- 3 Top braced at bearings.
- 4 Bottom braced at bearings.



January 02, 2019

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Part. Uniform	0-0-0 to 3-5-14		Top	30 PLF	80 PLF	0 PLF	0 PLF	
2	Point	1-0-12		Far Face	102 lb	206 lb	0 lb	0 lb	J4
3	Point	2-1-12		Far Face	69 lb	134 lb	0 lb	0 lb	J2
	Self Weight				5 PLF				

READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTE PAGE ENP-2. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

Pass-Thru Framing Squash Block is required at all point loads over bearings

Refer to Multiple Member Connection Detail for ply to ply nailing or bolting requirements

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318

Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400



This design is valid until 10/18/2021







Client:
Project:
Address:

Date: 12/18/2018
Designer: S B
Job Name: LOT 9 (AMELIA 3 EL-2)
Project #:

Page 1 of 2

F7-B Forex 2.0E-3000Fb LVL 1.750" X 11.875" - PASSED

Level: Ground Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	410	199	0	0
2	295	156	0	0

Bearings and Factored Reactions

Bearing	Length	Cap. React	D/L lb	Total	Ld. Case	Ld. Comb.
1 - Hanger	3.000"	22%	248 / 615	864	L	1.25D+1.5L
2 - SPF	6.438"	9%	195 / 442	637	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	1478 ft-lb	2' 7 7/16"	17130 ft-lb	0.086 (9%)	1.25D+1.5L	L
Unbraced	1478 ft-lb	2' 7 7/16"	7067 ft-lb	0.209 (21%)	1.25D+1.5L	L
Shear	649 lb	1' 2 1/8"	5798 lb	0.112 (11%)	1.25D+1.5L	L
Perm Defl in.	0.006 (L/11753)	3' 11/16"	0.212 (L/360)	0.030 (3%)	D	Uniform
LL Defl inch	0.013 (L/5910)	3' 1/8"	0.212 (L/360)	0.060 (6%)	L	L
TL Defl inch	0.019 (L/3933)	3' 5/16"	0.318 (L/240)	0.060 (6%)	D+L	L

Design Notes

- Fill all hanger nailing holes.
- Girders are designed to be supported on the bottom edge only.
- Top braced at bearings.
- Bottom braced at bearings.

READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTE PAGE ENP-2. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.



January 02, 2019

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind
1	Tie-In	0-0-0 to 2-6-9	(Span)3-1-13	Top	15 PSF	40 PSF	0 PSF	0 PSF
2	Tie-In	0-0-0 to 6-4-2	(Span)1-3-0	Top	15 PSF	40 PSF	0 PSF	0 PSF
3	Part. Uniform	0-3-4 to 2-8-10		Top	3 PLF	0 PLF	0 PLF	0 PLF
4	Point	2-7-7		Far Face	122 lb	259 lb	0 lb	0 lb F6
5	Tie-In	2-8-5 to 7-0-5	(Span)1-5-0	Top	15 PSF	40 PSF	0 PSF	0 PSF
6	Part. Uniform	2-8-10 to 6-5-14		Top	4 PLF	0 PLF	0 PLF	0 PLF
7	Tapered Start	2-8-10		Top	3 PLF	0 PLF	0 PLF	0 PLF

Continued on page 2...

PASS Thru Framing Squash Block is required at all point loads over bearings

Refer to Multiple Member Connection Detail for ply to ply nailing or bolting requirements

Notes

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

- Dry service conditions, unless noted otherwise
- LVL not to be treated with fire retardant or corrosive chemicals

Handling & Installation

- LVL beams must not be cut or drilled
- Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
- Damaged Beams must not be used
- Design assumes top edge is laterally restrained
- Provide lateral support at bearing points to avoid lateral displacement and rotation

- For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318

Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400



This design is valid until 10/18/2021







Client:
Project:
Address:

Date: 12/18/2018
Designer: S B
Job Name: LOT 9 (AMELIA 3 EL-2)
Project #:

Page 2 of 2

F7-B Forex 2.0E-3000Fb LVL 1.750" X 11.875" - PASSED

Level: Ground Floor



...Continued from page 1

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
	End	5-11-10			2 PLF	0 PLF	0 PLF	0 PLF	
8	Tapered Start	5-11-10		Top	2 PLF	0 PLF	0 PLF	0 PLF	
	End	6-4-2			0 PLF	0 PLF	0 PLF	0 PLF	
9	Tie-In	6-5-4 to 7-0-5	(Span)0-7-13 to 0-0-13	Top	15 PSF	40 PSF	0 PSF	0 PSF	
10	Tapered Start	6-5-14		Top	4 PLF	0 PLF	0 PLF	0 PLF	
	End	7-0-5			1 PLF	0 PLF	0 PLF	0 PLF	
	Self Weight				5 PLF				



January 02, 2019

READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTE PAGE ENP-2. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

Pass-Thru Framing Squash Block is required at all point loads over bearings

Refer to Multiple Member Connection Detail for ply to ply nailing or bolting requirements

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318

Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400



This design is valid until 10/18/2021







Client:
Project:
Address:

Date: 12/18/2018
Designer: S B
Job Name: LOT 9 (AMELIA 3 EL-2)
Project #:

Page 1 of 2

F8-A Forex 2.0E-3000Fb LVL 1.750" X 11.875" - PASSED

Level: Ground Floor

**Member Information**

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	1200	535	0	0
2	1290	544	0	0

Bearings and Factored Reactions

Bearing	Length	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF End Grain	3.500"	54%	668 / 1800	2468	L	1.25D+1.5L
2 - Hanger	3.000"	67%	680 / 1936	2616	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	5061 ft-lb	5'4 3/4"	17130 ft-lb	0.295 (30%)	1.25D+1.5L	L
Unbraced	5061 ft-lb	5'4 3/4"	5210 ft-lb	0.971 (97%)	1.25D+1.5L	L
Shear	2425 lb	7'10 7/16"	5798 lb	0.418 (42%)	1.25D+1.5L	L
Perm Defl in.	0.035 (L/2951)	4'8 1/8"	0.288 (L/360)	0.120 (12%)	D	Uniform
LL Defl inch	0.081 (L/1283)	4'8 9/16"	0.288 (L/360)	0.280 (28%)	L	L
TL Defl inch	0.116 (L/894)	4'8 7/16"	0.432 (L/240)	0.270 (27%)	D+L	L

Design Notes

- 1 Performed Secondary Bearing Check (CSA 086-14 6.5.7.3). Assumed point load size: beam width X 4.5.
- 2 Fill all hanger nailing holes.
- 3 Girders are designed to be supported on the bottom edge only.
- 4 Top braced at bearings.
- 5 Bottom braced at bearings.

READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTE PAGE ENP-2. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.



January 02, 2019

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind
1	Tie-In	0-0-0 to 9-0-9	(Span)3-11-7 to 3-11-7	Top	15 PSF	40 PSF	0 PSF	0 PSF
2	Point	0-1-12		Top	110 lb	248 lb	0 lb	0 lb C4
3	Point	1-4-12		Far Face	77 lb	158 lb	0 lb	0 lb J10
4	Part. Uniform	2-0-12 to 4-8-12		Far Face	59 PLF	123 PLF	0 PLF	0 PLF
6	Point	5-4-12		Far Face	126 lb	296 lb	0 lb	0 lb J10
7	Point	6-8-12		Far Face	156 lb	393 lb	0 lb	

Pass Thru Framing Squash Block is required at all point loads over bearings

Refer to Multiple Member Connection Detail for ply to ply nailing or bolting requirements

Continued on page 2...

Notes

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals**Handling & Installation**

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318

Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400



This design is valid until 10/18/2021






Client:
Project:
Address:

Date: 12/18/2018
Designer: S B
Job Name: LOT 9 (AMELIA 3 EL-2)
Project #:

Page 2 of 2

F8-A Forex 2.0E-3000Fb LVL 1.750" X 11.875" - PASSED

Level: Ground Floor



...Continued from page 1

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
8	Point	8-0-12		Far Face	141 lb	352 lb	0 lb	0 lb	J10
	Self Weight				5 PLF				



January 02, 2019

READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTE PAGE ENP-2. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

Pass-Thru Framing Squash Block is required at all point loads over bearings

Refer to Multiple Member Connection Detail for ply to ply nailing or bolting requirements

Notes

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals**Handling & Installation**

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318

Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400



This design is valid until 10/18/2021






Client:
Project:
Address:

Date: 12/18/2018
Designer: S B
Job Name: LOT 9 (AMELIA 3 EL-2)
Project #:

Page 1 of 1

F9-A Forex 2.0E-3000Fb LVL 1.750" X 11.875" - PASSED

Level: Ground Floor

**Member Information**

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	949	425	0	0
2	722	334	0	0

Bearings and Factored Reactions

Bearing	Length	Cap. React	D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	2.375"	76%	531 / 1424	1955	L	1.25D+1.5L
2 - SPF	4.500"	31%	417 / 1083	1501	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	7161 ft-lb	3'10 7/8"	17130 ft-lb	0.418 (42%)	1.25D+1.5L	L
Unbraced	7161 ft-lb	3'10 7/8"	7194 ft-lb	0.995 (100%)	1.25D+1.5L	L
Shear	1924 lb	1'1 1/2"	5798 lb	0.332 (33%)	1.25D+1.5L	L
Perm Defl in.	0.054 (L/2188)	4'7 7/8"	0.329 (L/360)	0.160 (16%)	D	Uniform
LL Defl inch	0.123 (L/965)	4'7 11/16"	0.329 (L/360)	0.370 (37%)	L	L
TL Defl inch	0.177 (L/670)	4'7 3/4"	0.494 (L/240)	0.360 (36%)	D+L	L

Design Notes

- Girders are designed to be supported on the bottom edge only.
- Top must be laterally braced at a maximum of 6'3" o.c.
- Bottom braced at bearings.

READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTE PAGE ENP-2. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.



January 02, 2019

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind
1	Tie-In	0-0-0 to 10-3-14	(Span)0-6-5	Top	15 PSF	40 PSF	0 PSF	0 PSF
2	Part. Uniform	0-2-1 to 2-3-1		Top	1 PLF	0 PLF	0 PLF	0 PLF
3	Part. Uniform	2-3-1 to 10-0-4		Top	1 PLF	0 PLF	0 PLF	0 PLF
4	Point	3-10-14		Far Face	544 lb	1290 lb	0 lb	0 lb F8
5	Tie-In	3-11-12 to 10-3-14	(Span)1-0-11	Top	15 PSF	40 PSF	0 PSF	0 PSF
6	Point	5-9-3		Top	48 lb	127 lb	0 lb	0 lb
7	Point	5-9-3		Top	4 lb	12 lb	0 lb	0 lb
8	Part. Uniform	5-9-5 to 10-0-3		Top	3 PLF	0 PLF	0 PLF	0 PLF
	Self Weight				5 PLF			

Pass-Through Framing Squash Block is required at all point loads over bearings

Refer to Multiple Member Connection Detail for ply to ply nailing or bolting requirements

Notes

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

- Dry service conditions, unless noted otherwise
- LVL not to be treated with fire retardant or corrosive

chemicals**Handling & Installation**

- LVL beams must not be cut or drilled
- Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
- Damaged Beams must not be used
- Design assumes top edge is laterally restrained
- Provide lateral support at bearing points to avoid lateral displacement and rotation

- For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318


Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400



This design is valid until 10/18/2021



Second Floor



Architectural Drawing Info

JARDIN DESIGN GROUP
64 JARDIN DR, SUITE 3A
VAUGHAN, ON L4K 3P3
Project # 17-55
Model: LOT 9 (AMELIA 3 EL-2)
Date: AUG 30, 2018

JOISTS SPACING 16\"O/C
UNLESS
NOTED OTHERWISE

1. OBC 2012 O.Reg 332/12 as amended
2. Nascor CCMC - 13535-R
3. LVL CCMC -12904-R
4. CAN/CSA-O86-09
5. CCMC -12787-R APA PR-L310(C)

This certification is to confirm that:

1. The loads used in the calculation of the attached approved components conform to the floor assembly shown on this layout.
2. The floor joists comply with the KOTT span table for the loads and spacing shown on this layout. The floor system must be assembled in accordance to the KOTT Specifier Guide. Multi-ply members must be attached together as per the included multiple member connection detail.



January 02, 2019

Second Floor
LVL/LSL

Label	Description	Width	Depth	Qty	Plies	Pcs	Length
F13	Forex 2.0E-3000Fb LVL	1.75	11.875	1	3	3	16-0-0
F12	Forex 2.0E-3000Fb LVL	1.75	11.875	1	2	2	12-0-0
F11	Forex 2.0E-3000Fb LVL	1.75	11.875	2	2	4	8-0-0
F7	Forex 2.0E-3000Fb LVL	1.75	11.875			1	8-0-0
F6	Forex 2.0E-3000Fb LVL	1.75	11.875			1	4-0-0

I Joist							
Label	Description	Width	Depth	Qty	Plies	Pcs	Length
J8	LPI 20Plus	2.5	11.875			18	20-0-0
J1	LPI 20Plus	2.5	11.875			50	16-0-0
J6	LPI 20Plus	2.5	11.875			14	14-0-0
J5	LPI 20Plus	2.5	11.875			5	12-0-0
J10	LPI 20Plus	2.5	11.875			1	8-0-0
J9	LPI 20Plus	2.5	11.875			2	4-0-0
F16	LPI 20Plus	2.5	11.875			1	20-0-0

Rim Board							
Label	Description	Width	Depth	Qty	Plies	Pcs	Length
R1	Norbord Rimboard Plus 1.125 X 11.875	1.125	11.875			18	12

Blocking							
Label	Description	Width	Depth	Qty	Plies	Pcs	Length
BLK1	LPI 20 Plus	2.5	11.875	LinFt		Varies	34-0-0

Hanger							
				Beam/Girder		Supported Member	
Label	Pcs	Description	Skew	Slope	fasteners	fasteners	
H2	2	HUS1.81/10			30 16d	10 16d	
H3	26	LF2511			12 10d	1 #8x1 1/4WS	
H4	1	HGUS410			46 16d	16 16d	

NOTES:

1. Framers to verify dimensions on the architectural drawings.
2. Double joist only require filler/backer ply when supporting another member using a face-mounted hanger.
3. Install 2x4 blocking @ 24" o/c under parallel non-loadbearing walls.
4. Install single-ply flush window header along inside face of rimboard/rimjoist
5. Refer to Nascor specifier guide for installation details.
6. Squash blocks recommended to be installed at end bearing on all first level joists which support loading from above exceeding two levels floor or roof.
7. Load transfer blocks to be installed under all point loads.
8. It shall be the framer's responsibility that floor joists and beams are fastened as per the hanger manufacturer's standards.

Refer to Multiple Member Connection Detail to ply to ply nailing or bolting requirements.

Rim parallel to joists: 1-1/8" rimboard with 2"x4" block (1/16" longer than rim depth) @ 16" o/c. All other components and structural elements supporting the floor system such as beams, walls, columns and foundation walls and footings including anchorage of components and bracing for lateral stability are the responsibility of others.

Hatch area represents ceramic tiled floor with an additional dead load of 5 PSF.

The framing shown on this layout may be deviate from the architectural drawings. Project Engineer to review and approve the deviation prior to construction.

Legend

PS	Point Load Support
◇	Load from Above
Wall	Wall
Norbord Rimboard Plus 1.125 X 11.875	Norbord Rimboard Plus 1.125 X 11.875
LPI 20Plus 11.875	LPI 20Plus 11.875
Forex 2.0E-3000Fb LVL 1.75 X 11.875	Forex 2.0E-3000Fb LVL 1.75 X 11.875
1.75 X 9.5 (Dropped)	1.75 X 9.5 (Dropped)
5 X 10.25 (Dropped)	5 X 10.25 (Dropped)



Layout Name		LOT 9 (AMELIA 3 EL-2)
Design Method		LSD
Description		GREEN YORK HOMES GRANELLI HOMES PROJECT BRAMPTON, ON
Created		May 29, 2018
Builder		
Sales Rep		RM
Designer		S B
Shipping		
Project		
Builder's Project		Kott Lumber Company
		14 Anderson Blvd Stouffville, Ontario Canada L4A 7X4 905-642-4400

Second Floor		
Design Method		LSD
Building Code		NBCC 2010 / OBC 2012
Floor		
Loads		
Live		40
Dead		15
Deflection Joist		
LL Span L/		480
TL Span L/		360
LL Cant 2L/		480
TL Cant 2L/		360
Deflection Girder		
LL Span L/		360
TL Span L/		240
LL Cant 2L/		480
TL Cant 2L/		360
Decking		
Deck		OSB
Thickness		5/8"
Fastener		Nailed & Glued
Vibration		
Ceiling:		Gypsum 1/2"





Client:
Project:
Address:

Date: 12/18/2018
Designer: S B
Job Name: LOT 9 (AMELIA 3 EL-2)
Project #:

Page 1 of 1

F11-A Forex 2.0E-3000Fb LVL 1.750" X 11.875" 2-Ply - PASSED Level: Second Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	2	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	489	224	0	0
2	372	179	0	0

Bearings and Factored Reactions

Bearing	Length	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	4.467"	11%	280 / 733	1013	L	1.25D+1.5L
2 - Hanger	4.000"	8%	224 / 558	782	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	2402 ft-lb	3'7 11/16"	34261 ft-lb	0.070 (7%)	1.25D+1.5L	L
Unbraced	2402 ft-lb	3'7 11/16"	31940 ft-lb	0.075 (8%)	1.25D+1.5L	L
Shear	838 lb	1'3 9/16"	11596 lb	0.072 (7%)	1.25D+1.5L	L
Perm Defl in. (L/15375)	0.006	3'7 3/4"	0.235 (L/360)	0.020 (2%)	D	Uniform
LL Defl inch	0.012 (L/6820)	3'7 3/4"	0.235 (L/360)	0.050 (5%)	L	L
TL Defl inch	0.018 (L/4725)	3'7 3/4"	0.353 (L/240)	0.050 (5%)	D+L	L

Design Notes

- 1 Fill all hanger nailing holes.
- 2 Girders are designed to be supported on the bottom edge only.
- 3 Multiple plies must be fastened together as per manufacturer's details.
- 4 Top loads must be supported equally by all plies.
- 5 Top braced at bearings.
- 6 Bottom braced at bearings.
- 7 Lateral slenderness ratio based on full section width.

READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTE PAGE ENP-2. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.



January 02, 2019

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 7-7-11	(Span)0-9-0	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Tie-In	0-4-7 to 3-8-9	(Span)3-4-0	Top	15 PSF	40 PSF	0 PSF	0 PSF	
3	Point	3-7-11		Near Face	187 lb	477 lb	0 lb	0 lb	Pass-Thru Framing Squash Block is required at all point loads over bearings
4	Tie-In	3-8-9 to 7-7-11	(Span)0-7-0	Top	15 PSF	40 PSF	0 PSF	0 PSF	
	Self Weight				10 PLF				Refer to Multiple Member Connection Detail for ply to ply nailing or bolting requirements

Notes

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318

Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400



This design is valid until 10/18/2021






Client:
Project:
Address:

Date: 12/18/2018
Designer: S B
Job Name: LOT 9 (AMELIA 3 EL-2)
Project #:

Page 1 of 2

F11-B Forex 2.0E-3000Fb LVL 1.750" X 11.875" 2-Ply - PASSED Level: Second Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	2	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	1641	720	0	0
2	1474	667	0	0

Bearings and Factored Reactions

Bearing	Length	Cap. React D/L lb	Total Ld. Case	Ld. Comb.
1 - SPF	5.250"	30% 900 / 2461	3361 L	1.25D+1.5L
2 - SPF	5.500"	26% 834 / 2211	3044 L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	4871 ft-lb	3'3 5/8"	34261 ft-lb	0.142 (14%)	1.25D+1.5L	L
Unbraced	4871 ft-lb	3'3 5/8"	32706 ft-lb	0.149 (15%)	1.25D+1.5L	L
Shear	3590 lb	5'2"	11596 lb	0.310 (31%)	1.25D+1.5L	L
Perm Defl in.	0.009 (L/7417)	3'3 5/8"	0.193 (L/360)	0.050 (5%)	D	Uniform
LL Defl inch	0.021 (L/3252)	3'3 7/16"	0.193 (L/360)	0.110 (11%)	L	L
TL Defl inch	0.031 (L/2261)	3'3 1/2"	0.289 (L/240)	0.110 (11%)	D+L	L

Design Notes

- Girders are designed to be supported on the bottom edge only.
- Multiple plies must be fastened together as per manufacturer's details.
- Top loads must be supported equally by all plies.
- Top braced at bearings.
- Bottom braced at bearings.
- Lateral slenderness ratio based on full section width.

READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTE PAGE ENP-2. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.



January 02, 2019

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Point	0-6-10		Far Face	116 lb	256 lb	0 lb	0 lb	J1
2	Part. Uniform	0-7-10 to 3-3-10		Near Face	105 PLF	280 PLF	0 PLF	0 PLF	
3	Part. Uniform	1-0-10 to 5-0-10		Far Face	127 PLF	286 PLF	0 PLF	0 PLF	
4	Point	3-11-10		Near Face	111 lb	296 lb	0 lb	0 lb	J1
5	Point	4-8-10		Near Face	179 lb	372 lb	0 lb	0 lb	F11
6	Point	5-3-10		Near Face	25 lb	67 lb	0 lb	0 lb	

Pass-Thru Framing Squash Block is required at all point loads over bearings

Refer to Multiple Member Connection Detail for ply to ply nailing or bolting requirements

Continued on page 2...

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

- Dry service conditions, unless noted otherwise
- LVL not to be treated with fire retardant or corrosive chemicals

chemicals

Handling & Installation

- LVL beams must not be cut or drilled
- Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
- Damaged Beams must not be used
- Design assumes top edge is laterally restrained
- Provide lateral support at bearing points to avoid lateral displacement and rotation

- For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318

Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400



This design is valid until 10/18/2021







Client:
Project:
Address:

Date: 12/18/2018
Designer: S B
Job Name: LOT 9 (AMELIA 3 EL-2)
Project #:

Page 2 of 2

F11-B Forex 2.0E-3000Fb LVL 1.750" X 11.875" 2-Ply - PASSED Level: Second Floor



...Continued from page 1

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
7	Point	5-6-10		Far Face	101 lb	221 lb	0 lb	0 lb	J1
8	Tie-In	6-1-2 to 6-6-10	(Span)1-0-1	Top	15 PSF	40 PSF	0 PSF	0 PSF	
9	Tie-In	6-1-11 to 6-6-10	(Span)0-3-15	Top	15 PSF	40 PSF	0 PSF	0 PSF	
	Self Weight				10 PLF				



January 02, 2019

READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTE PAGE ENP-2. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

Pass-Thru Framing Squash Block is required at all point loads over bearings

Refer to Multiple Member Connection Detail for ply to ply nailing or bolting requirements

Notes

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals**Handling & Installation**

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318

Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400



This design is valid until 10/18/2021






Client:
Project:
Address:

Date: 12/18/2018
Designer: S B
Job Name: LOT 9 (AMELIA 3 EL-2)
Project #:

Page 1 of 1

F12-A Forex 2.0E-3000Fb LVL 1.750" X 11.875" 2-Ply - PASSED Level: Second Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	2	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	97	91	0	0
2	97	91	0	0

Bearings and Factored Reactions

Bearing	Length	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	4.375"	3%	113 / 146	259	L	1.25D+1.5L
2 - SPF	4.375"	3%	113 / 146	259	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	592 ft-lb	5'1 7/8"	34261 ft-lb	0.017 (2%)	1.25D+1.5L	L
Unbraced	592 ft-lb	5'1 7/8"	29876 ft-lb	0.020 (2%)	1.25D+1.5L	L
Shear	194 lb	9' 1/4"	11596 lb	0.017 (2%)	1.25D+1.5L	L
Perm Defl in. (L/27908)	0.004	5'1 7/8"	0.324 (L/360)	0.010 (1%)	D	Uniform
LL Defl inch (L/26047)	0.004	5'1 7/8"	0.324 (L/360)	0.010 (1%)	L	L
TL Defl inch (L/13473)	0.009	5'1 7/8"	0.485 (L/240)	0.020 (2%)	D+L	L

Design Notes

- Girders are designed to be supported on the bottom edge only.
- Multiple plies must be fastened together as per manufacturer's details.
- Top loads must be supported equally by all plies.
- Top braced at bearings.
- Bottom braced at bearings.
- Lateral slenderness ratio based on full section width.



January 02, 2019

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 10-3-12	(Span)0-11-5	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Part. Uniform	0-2-5 to 10-3-12		Top	1 PLF	0 PLF	0 PLF	0 PLF	
	Self Weight				10 PLF				

READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTE PAGE ENP-2. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

Pass-Thru Framing Squash Block is required at all point loads over bearings

Refer to Multiple Member Connection Detail for ply to ply nailing or bolting requirements

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

- Dry service conditions, unless noted otherwise
- LVL not to be treated with fire retardant or corrosive

chemicals

Handling & Installation

- LVL beams must not be cut or drilled
- Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
- Damaged Beams must not be used
- Design assumes top edge is laterally restrained
- Provide lateral support at bearing points to avoid lateral displacement and rotation

- For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318

Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400






Client:
Project:
Address:

Date: 12/18/2018
Designer: S B
Job Name: LOT 9 (AMELIA 3 EL-2)
Project #:

Page 1 of 2

F13-A Forex 2.0E-3000Fb LVL 1.750" X 11.875" 3-Ply - PASSED Level: Second Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	3	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	Yes
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	2085	972	0	0
2	2008	911	0	0

Bearings and Factored Reactions

Bearing	Length	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	4.375"	31%	1215 / 3127	4342	L	1.25D+1.5L
2 - SPF	5.500"	23%	1139 / 3012	4151	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	14769 ft-lb	7'2 13/16"	53447 ft-lb	0.276 (28%)	1.25D+1.5L	L
Unbraced	14769 ft-lb	7'2 13/16"	50470 ft-lb	0.293 (29%)	1.25D+1.5L	L
Shear	4273 lb	1'3 1/2"	17394 lb	0.246 (25%)	1.25D+1.5L	L
Perm Defl in.	0.083 (L/1993)	7'2 5/8"	0.462 (L/360)	0.180 (18%)	D	Uniform
LL Defl inch	0.181 (L/920)	7'2 7/8"	0.462 (L/360)	0.390 (39%)	L	L
TL Defl inch	0.264 (L/629)	7'2 13/16"	0.693 (L/240)	0.380 (38%)	D+L	L

Design Notes

- Girders are designed to be supported on the bottom edge only.
- Multiple plies must be fastened together as per manufacturer's details.
- Top loads must be supported equally by all plies.
- Top braced at bearings.
- Bottom braced at bearings.
- Lateral slenderness ratio based on full section width.

READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTE PAGE ENP-2. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.



January 02, 2019

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 14-1-4	(Span)0-11-0	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Point	0-5-13		Far Face	81 lb	190 lb	0 lb	0 lb	J1
3	Point	1-3-13		Far Face	108 lb	255 lb	0 lb	0 lb	J1
4	Part. Uniform	1-9-13 to 10-9-13		Far Face	117 PLF	278 PLF	0 PLF	0 PLF	
5	Point	11-3-13		Far Face	91 lb	232 lb	0 lb	0 lb	J1
6	Point	11-11-13		Far Face	104 lb	278 lb	0 lb	0 lb	J1

Pass-Thru Framing Squash Block is required at all point loads over bearings

Refer to Multiple Member Connection Detail for ply to ply nailing or bolting requirements

Continued on page 2...

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

- Dry service conditions, unless noted otherwise
- LVL not to be treated with fire retardant or corrosive chemicals

Handling & Installation

- LVL beams must not be cut or drilled
- Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
- Damaged Beams must not be used
- Design assumes top edge is laterally restrained
- Provide lateral support at bearing points to avoid lateral displacement and rotation

- For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318

Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400



This design is valid until 10/18/2021






Client:
Project:
Address:

Date: 12/18/2018
Designer: S B
Job Name: LOT 9 (AMELIA 3 EL-2)
Project #:

Page 2 of 2

F13-A Forex 2.0E-3000Fb LVL 1.750" X 11.875" 3-Ply - PASSED Level: Second Floor



...Continued from page 1

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
7	Point	13-3-13		Far Face	139 lb	371 lb	0 lb	0 lb	J1
8	Tie-In	14-1-4 to 14-6-10	(Span)0-8-8	Top	15 PSF	40 PSF	0 PSF	0 PSF	
	Self Weight				14 PLF				



January 02, 2019

READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTE PAGE ENP-2. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

Pass-Thru Framing Squash Block is required at all point loads over bearings

Refer to Multiple Member Connection Detail for ply to ply nailing or bolting requirements

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals**Handling & Installation**

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318

Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400



This design is valid until 10/18/2021






Client:
Project:
Address:

Date: 12/18/2018
Designer: S B
Job Name: LOT 9 (AMELIA 3 EL-2)
Project #:

Page 1 of 2

F16-A LPI 20Plus 11.875" - PASSED

Level: Second Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	116	55	1	0
2	322	118	0 (-4)	0
3	331	337	201	0

Bearings and Factored Reactions

Bearing	Length	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	5.500"	14%	67 / 193	260	L__	1.25D+1.5L
2 - SPF	5.000"	16%	150 / 502	652	LL__	1.25D+1.5L
3 - SPF	5.000"	34%	421 / 617	1038	_LL	1.25D+1.5L +0.5S

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Neg Moment	-578 ft-lb	9'3 1/2"	6250 ft-lb	0.092 (9%)	1.25D+1.5L	LL__
Pos Moment	433 ft-lb	4'1 11/16"	5500 ft-lb	0.079 (8%)	1.25D+1.5L	L__
Shear	656 lb	18'7 1/4"	1853 lb	0.354 (35%)	1.25D+1.5S	_L
Perm Defl in.	0.005 (L/21091)	4'5 1/4"	0.297 (L/360)	0.020 (2%)	D	Uniform
LL Defl inch	0.015 (L/6927)	4'8 1/2"	0.297 (L/360)	0.050 (5%)	L+0.5S	L_L
TL Defl inch	0.020 (L/5219)	4'7 11/16"	0.445 (L/240)	0.050 (5%)	D+L+0.5S	L_L
LL Cant	-0.002 (2L/5898)	Rt Cant	0.200 (2L/480)	0.011 (1%)	L	_L
TL Cant	0.002 (2L/5508)	Rt Cant	0.300 (2L/360)	0.008 (1%)	D+L+0.5S	L_L

Design Notes

- 1 Provide restraint at supports to ensure lateral stability.
- 2 Applied loads over end bearings and loads exceeding 250 lbs over intermediate bearings must be transferred directly to the support by rim board, blocking, squash blocks, or other device.
- 3 Dead Load Deflection: Instant = 0.005", Long Term = 0.008"
- 4 Girders are designed to be supported on the bottom edge only.
- 5 Top flange braced at bearings.
- 6 Bottom flange braced at bearings.

READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTE PAGE ENP-2. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.



January 02, 2019

Pass-Thru Framing Squash Block is required at all point loads over bearings

Refer to Multiple Member Connection Detail for ply to ply nailing or bolting requirements

Notes

This component analysis is based on the loads, geometry and other conditions as entered by the user and listed in this report. The user is responsible to ensure the accuracy of the input and the applicability to the actual conditions of the structure for which this component is intended. This analysis is valid only for the product listed.

Copyright 2016 All rights reserved by Louisiana Pacific Corp. 414 Union St Suite 2000, Nashville, TN 37219



This design is valid until
10/31/2020

Manufacturer Info

Louisiana-Pacific Corp
414 Union Street, Suite 2000
Nashville, TN 37219
(888) 820-0325
www.lpcorp.com
CCMC: 12412-R APA: PR-L238C

Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400






Client:
Project:
Address:

Date: 12/18/2018
Designer: S B
Job Name: LOT 9 (AMELIA 3 EL-2)
Project #:

Page 2 of 2

F16-A LPI 20Plus 11.875" - PASSED

Level: Second Floor



ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 18-7-3	(Span)0-9-11	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Tie-In	0-0-0 to 19-2-0	(Span)0-8-5	Top	15 PSF	40 PSF	0 PSF	0 PSF	
3	Part. Uniform	0-0-0 to 3-2-5		Top	2 PLF	0 PLF	0 PLF	0 PLF	
4	Part. Uniform	0-0-0 to 3-2-6		Top	2 PLF	0 PLF	0 PLF	0 PLF	
5	Point	18-4-12		Top	199 lb	204 lb	197 lb	0 lb	F2 F2
	Bearing Length	0-1-8							
6	Point	18-4-12		Top	7 lb	0 lb	0 lb	0 lb	Wall Self Weight
	Bearing Length	0-1-8							
7	Point	18-4-12		Top	36 lb	0 lb	0 lb	0 lb	Wall Self Weight
	Bearing Length	0-1-8							
8	Part. Uniform	18-7-8 to 19-2-0		Top	80 PLF	0 PLF	0 PLF	0 PLF	Wall Self Weight



January 02, 2019

Pass-Thru Framing Squash Block is required at all point loads over bearings

Refer to Multiple Member Connection Detail for ply to ply nailing or bolting requirements

READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTE PAGE ENP-2. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

Notes

This component analysis is based on the loads, geometry and other conditions as entered by the user and listed in this report. The user is responsible to ensure the accuracy of the input and the applicability to the actual conditions of the structure for which this component is intended. This analysis is valid only for the product listed.

Copyright 2016 All rights reserved by Louisiana Pacific Corp. 414 Union St Suite 2000, Nashville, TN 37219



This design is valid until
10/31/2020

Manufacturer Info

Louisiana-Pacific Corp
414 Union Street, Suite 2000
Nashville, TN 37219
(888) 820-0325
www.lpcorp.com
CCMC: 12412-R APA: PR-L238C

Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400







Client:
Project:
Address:

Date: 12/18/2018
Designer: S B
Job Name: LOT 9 (AMELIA 3 EL-2)
Project #:

Page 1 of 1

F6-A Forex 2.0E-3000Fb LVL 1.750" X 11.875" - PASSED

Level: Second Floor

**Member Information**

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	477	187	0	0
2	449	176	0	0

Bearings and Factored Reactions

Bearing	Length	Cap. React D/L lb	Total	Ld. Case	Ld. Comb.
1 - Hanger	3.000"	24%	233 / 716	949 L	1.25D+1.5L
2 - Hanger	3.000"	23%	220 / 674	894 L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	568 ft-lb	1'8 1/8"	17130 ft-lb	0.033 (3%)	1.25D+1.5L	L
Unbraced	568 ft-lb	1'8 1/8"	14337 ft-lb	0.040 (4%)	1.25D+1.5L	L
Shear	386 lb	1'2 1/8"	5798 lb	0.067 (7%)	1.25D+1.5L	L
Perm Defl in. (L/35583)	0.001	1'7 9/16"	0.091 (L/360)	0.010 (1%)	D	Uniform
LL Defl inch (L/13914)	0.002	1'7 9/16"	0.091 (L/360)	0.030 (3%)	L	L
TL Defl inch (L/10003)	0.003	1'7 9/16"	0.137 (L/240)	0.020 (2%)	D+L	L

Design Notes

READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTE PAGE ENP-2. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

- 1 Fill all hanger nailing holes.
- 2 Girders are designed to be supported on the bottom edge only.
- 3 Top braced at bearings.
- 4 Bottom braced at bearings.



January 02, 2019

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Part. Uniform	0-0-0 to 3-1-6		Top	90 PLF	240 PLF	0 PLF	0 PLF	
2	Point	0-5-4		Far Face	28 lb	74 lb	0 lb	0 lb	J9
3	Tie-In	1-9-4 to 1-11-14	(Span)3-1-11 to 3-1-11	Top	15 PSF	40 PSF	0 PSF	0 PSF	
4	Point	1-9-4		Far Face	23 lb	61 lb	0 lb	0 lb	
5	Tie-In	1-11-14 to 2-5-0	(Span)1-9-11	Top	15 PSF	40 PSF	0 PSF	0 PSF	
6	Tie-In	2-5-0 to 3-1-6	(Span)1-0-11	Top	15 PSF	40 PSF	0 PSF	0 PSF	
	Self Weight				5 PLF				

Pass-Thru Framing Squash Block is required at all point loads over bearings

Refer to Multiple Member Connection Detail for ply to ply nailing or bolting requirements

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318

Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400



This design is valid until 10/18/2021







Client:
Project:
Address:

Date: 12/18/2018
Designer: S B
Job Name: LOT 9 (AMELIA 3 EL-2)
Project #:

Page 1 of 1

F7-A Forex 2.0E-3000Fb LVL 1.750" X 11.875" - PASSED

Level: Second Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	248	110	0	0
2	643	266	0	0

Bearings and Factored Reactions

Bearing	Length	Cap. React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF End Grain	3.500"	11%	138 / 372	510 L	1.25D+1.5L
2 - SPF	6.438"	19%	333 / 965	1298 L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	884 ft-lb	3'10 9/16"	17130 ft-lb	0.052 (5%)	1.25D+1.5L	L
Unbraced	884 ft-lb	3'10 9/16"	6876 ft-lb	0.129 (13%)	1.25D+1.5L	L
Shear	1154 lb	5'9 3/8"	5798 lb	0.199 (20%)	1.25D+1.5L	L
Perm Defl in. (L/19225)	0.004	3'7 3/4"	0.218 (L/360)	0.020 (2%)	D	Uniform
LL Defl inch	0.009 (L/8390)	3'7 15/16"	0.218 (L/360)	0.040 (4%)	L	L
TL Defl inch	0.013 (L/5841)	3'7 7/8"	0.327 (L/240)	0.040 (4%)	D+L	L

Design Notes

- Girders are designed to be supported on the bottom edge only.
- Top braced at bearings.
- Bottom braced at bearings.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind
1	Tie-In	0-0-0 to 3-1-12	(Span)3-1-13	Top	15 PSF	40 PSF	0 PSF	0 PSF
2	Tie-In	3-1-12 to 6-5-14	(Span)3-4-0	Top	15 PSF	40 PSF	0 PSF	0 PSF
3	Point	6-5-0		Far Face	176 lb	449 lb	0 lb	0 lb F6
4	Tie-In	6-5-14 to 7-2-15	(Span)1-5-0	Top	15 PSF	40 PSF	0 PSF	0 PSF
	Self Weight				5 PLF			

READ ALL NOTES ON THIS PAGE AND ON THE ENGINEERING NOTE PAGE ENP-2. THE NOTE PAGE IS AN INTEGRAL PART OF THIS DRAWING AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.



January 02, 2019

Pass-Thru Framing Squash Block is required at all point loads over bearings

Refer to Multiple Member Connection Detail for ply to ply nailing or bolting requirements

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

- Dry service conditions, unless noted otherwise
- LVL not to be treated with fire retardant or corrosive

chemicals

Handling & Installation

- LVL beams must not be cut or drilled
- Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
- Damaged Beams must not be used
- Design assumes top edge is laterally restrained
- Provide lateral support at bearing points to avoid lateral displacement and rotation

- For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318

Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400



This design is valid until 10/18/2021

