

Please read all notes prior to installation of the component

DESIGN INFORMATION

This building component is certified as an individual component for the loads and conditions shown on the calculation and drawing page.

The responsibility of the undersigned engineer is only limited to the calculation of this building component for the loads and conditions shown on this drawing.

The responsibility of the undersigned is limited to the verification of the structural capacity of the NASCOR floor joists and LVL beams based on placement as shown on the layout. The loads applied are limited to the gravity effects of the specified loads. The structural integrity of the building and the effect of wind, uplift, seismic, lateral or other forces, calculation of adequate support and anchorage of components, as well as the dimensions and design loads used to calculate components are the responsibility of the overall building designer.

Floor joists and OSB rim board are designed to carry uniformly distributed loads only. Point loads should be transferred through the floor cavity with squash blocks. Structural elements such as walls, posts, connectors, and squash blocks are the responsibility of the overall building designer.

The undersigned engineer disclaims any responsibility for damages as a result of being furnished faulty or incorrect information, specifications and/or designs.

Installation of NASCOR joists is to be carried out in accordance with the current edition of the manufacturer's approved literature available at <http://www.nascor.ca>.

CODE

This building component is designed in accordance with the National Building Code of Canada, the Ontario Building Code, CCMC and Canadian Standards Association guidelines.

COMPONENT

1. The building component used in construction must be the same as indicated on the drawings.
2. The building component must be installed and assembled as per specification shown on the drawing and in accordance with the manufacturer's assembly and installation.
3. Members consisting of multiple plies must be connected as per the document "Multi-ply Connection Details".
4. Pass-thru squash block framing is required at all point loads over bearings.


HANDLING AND INSTALLATION

Do not drill any hole, cut or notch a certified building component without a written pre-authorization.

MULTIPLE MEMBER CONNECTIONS


GREEN YORK HOMES-GRANELLI
HOME CORP-LIANA 2 (ELEV.1&2

Conventional Connections (for uniform distributed loads)




- Conventional connection notes:**
- Nails to be 3" 10d spiral wire nails.
 - Nails to be located a minimum of 2" from the top and bottom of the member. Start all nails a minimum of 2 1/2" in from ends.
 - Number of rows and spacing as per details shown, unless noted otherwise.
 - "X" represents nail driven from the opposite side.

LVL Connections (for uniform distributed loads)



- LVL connection notes:**
- Nails to be 3 1/2" spiral wire nails.
 - Nails to be located a minimum of 2 1/2" from the top and bottom of the member. Start all nails a minimum of 2 1/2" in from ends.
 - Minimum 3 1/4" spacing between rows.
 - Number of rows and spacing as per details shown, unless noted otherwise.
 - "X" represents nail or screw driven from the opposite side.

Vertical I-Joist Connections (for uniform distributed loads)



- Vertical I-Joist connection notes:**
- Nails to be 3" spiral wire nails.
 - Nails to be located at centre of top and bottom flanges. Start all nails a minimum of 2 1/2" in from ends.
 - Number of rows and spacing as per details shown, unless noted otherwise.
 - "X" represents nail driven from the opposite side.

MULTI -PLY CONNECTION DETAILS


Date: November 30, 2016

Scale: NTS



KOTT
3228 Moodie Drive
Ottawa, ON
K2H 7V1
Ph: 613-838-2775
Fx: 613-838-4751

Ground Floor



THIS CERTIFICATION IS TO CONFIRM THAT:

- 1. THE LOADS USED IN THE CALCULATION OF THE ATTACHED APPROVED COMPONENTS CONFORM TO THE FLOOR ASSEMBLY SHOWN ON THIS LAYOUT.
- 2. THE FLOOR JOISTS COMPLY WITH THE NASCOR SPAN TABLE FOR THE LOADS AND SPACING SHOWN ON THIS LAYOUT.

THE FLOOR SYSTEM MUST BE ASSEMBLED IN ACCORDANCE TO THE NASCOR SPECIFIER GUIDE. MULTI-PLY MEMBERS MUST BE ATTACHED TOGETHER AS PER THE INCLUDED MULTIPLE MEMBER CONNECTION DETAIL.

ALL OTHER COMPONENTS AND STRUCTURAL ELEMENTS SUPPORTING THE FLOOR SYSTEM SUCH AS BEAMS, WALLS, COLUMNS AND FOUNDATION WALLS AND FOOTINGS INCLUDING ANCHORAGE OF COMPONENTS AND BRACING FOR LATERAL STABILITY ARE THE RESPONSIBILITY OF OTHERS.

READ ALL NOTES ON THIS PAGE AND ON ENGINEERING NOTE PAGE ENP-2. THIS NOTE PAGE IS AN INTEGRAL PART OF THIS CALCULATION SUMMARY PAGE AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

REFER TO MULTIPLE MEMBER TO MEMB CONNECTION DETAIL FOR PLY TO PLY NAILING OR BOLTING REQUIREMENTS.

PASS THRU FRAMING SQUASH BLOCK IS REQUIRED AT ALL POINT LOADS OVER BEARINGS.



Legend	
	Load from Above
	Wall
	Wall Opening
	Norbord Rimboard Plus 1.125 X 9.5
	NJH 9.5
	Forex 2.0E-3000Fb LVL 1.75 X 9.5

- 1. OBC 2012 O.Reg 332/12 as amended
- 2. Nascor CCMC - 13535-R
- 3. LVL CCMC -14056-R
- 4. CAN/CSA-O86-09
- 5. CCMC -12787-R APA PR-L310(C)

Ground Floor LVL/LSL (Flush)							
Label	Description	Width	Depth	Qty	Plies	Pcs	Length
F4	Forex 2.0E-3000Fb LVL	1.75	9.5	2	2	4	14-0-0
F2	Forex 2.0E-3000Fb LVL	1.75	9.5			1	8-0-0
F3	Forex 2.0E-3000Fb LVL	1.75	9.5	1	2	2	4-0-0
F1	Forex 2.0E-3000Fb LVL	1.75	9.5			1	4-0-0
I Joist (Flush)							
Label	Description	Width	Depth	Qty	Plies	Pcs	Length
F7	NJH	2.5	9.5			2	14-0-0
F8	NJH	2.5	9.5	2	2	4	12-0-0
F6	NJH	2.5	9.5			1	4-0-0
F5	NJH	2.5	9.5			4	2-0-0
J6	NJH	2.5	9.5			11	16-0-0
J5	NJH	2.5	9.5			20	14-0-0
J4	NJH	2.5	9.5			8	12-0-0
J3	NJH	2.5	9.5			4	10-0-0
J2	NJH	2.5	9.5			4	6-0-0
J1	NJH	2.5	9.5			1	4-0-0
Rim Board							
Label	Description	Width	Depth	Qty	Plies	Pcs	Length
R1	Norbord Rimboard Plus 1.125 X 9.5	1.125	9.5			13	12
Blocking							
Label	Description	Width	Depth	Qty	Plies	Pcs	Length
BLK1	NJH	2.5	9.5	LinFt		Varies	29-0-0
Hanger							
				Beam/Girder		Supported Member	
Label	Pcs	Description	Skew	Slope	fasteners	fasteners	
H1	1	Unknown Hanger					
H2	25	LT259			4 10dx1 1/2	2 10dx1 1/2	
H3	1	HUS1.81/10			30 16d	10 16d	

NOTES:

1. Framer to verify dimensions on the architectural drawings.
2. Double joist only require filler/backer ply when supporting another member using a face-mounted hanger.
3. Install 2x4 blocking @ 24" o/c under parallel non-load bearing walls.
4. Install single-ply flush window header along inside face of rimboard/rimjoist.
5. Refer to Nascor specifier guide for installation works.
6. Squash blocks recommended to be installed at end bearing on all first level joists which support loading from above exceeding two levels floor or roof.
7. Load transfer blocks to be installed under all point loads.
8. It shall be the framer's responsibility that floor joists and beams are fastened as per the hanger manufacturer's standards.

Refer to Multiple Member Connection Detail to ply to ply nailing or bolting requirements.

Rim parallel to joists: 1-1/8" rimboard with 2"x 4" block (1/16" longer than rim depth @ 16" o/c). All other components and structural elements supporting the floor system such as beams, walls, columns, and foundation walls and footings including anchorage of components and bracing for lateral stability are the responsibility of Others.

Hatch area represents ceramic tiled floor with an additional dead load of 5 PSF

The framing shown on this layout may deviate from the architectural and structural drawings. Project Engineer to review and approve the deviation prior to construction.

ARCHITECTURAL DRAWINGS:

JARDIN DESIGN GROUP INC.
64 Jardin Dr., Suite 3A, Vaughan, ON
Date: Rev.1; May 22,2018
Project No: 17-55
Model: Liana 2





Layout Name	LIANA 2 (ELEV.1BG)
Design Method	LSD
Description	GRANELLI HOMES CORP. BRAMPTON, ONT.
Created	May 29, 2018
Builder	GREEN YORK HOMES
Sales Rep	RM
Designer	RCO
Shipping	
Project	
Builder's Project	
Kott Lumber Company	
14 Anderson Blvd	
Stouffville, Ontario	
Canada	
L4A 7X4	
905-642-4400	
Job Path	D:\Users\rochavillo\WORK FROM HOME\GREEN YORK HOMES\GRANELLI HOME CORP\MODELS\LIANA 2\LIANA 2 ELEV 1\FLOOR

Design Method	LSD
Building Code	NBCC 2010 / OBC 2012
Floor	
Loads	
Live	40
Dead	15
Deflection Joist	
LL Span L/	480
TL Span L/	360
LL Cant 2L/	480
TL Cant 2L/	360
Deflection Girder	
LL Span L/	360
TL Span L/	240
LL Cant 2L/	480
TL Cant 2L/	360
Decking	
Deck	OSB
Thickness	3/4"
Fastener	Nailed & Glued
Vibration	

F1-A Forex 2.0E-3000Fb LVL 1.750" X 9.500" - PASSED

Level: Ground Floor

**Member Information**

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	299	116	0	0
2	258	101	0	0

Bearings and Factored Reactions

Bearing	Length	Cap. React D/L lb	Total	Ld. Case	Ld. Comb.
1 - Hanger	3.000"	15%	145 / 449	594 L	1.25D+1.5L
2 - SPF End Grain	3.625"	11%	127 / 387	514 L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	214 ft-lb	1'6 7/8"	11362 ft-lb	0.019 (2%)	1.25D+1.5L	L
Unbraced	214 ft-lb	1'6 7/8"	10729 ft-lb	0.020 (2%)	1.25D+1.5L	L
Shear	438 lb	11 3/4"	4638 lb	0.094 (9%)	1.25D+1.5L	L
Perm Defl in. (L/58713)	0.000	1'4 3/8"	0.067 (L/360)	0.010 (1%)	D	Uniform
LL Defl inch (L/23005)	0.001	1'4 9/16"	0.067 (L/360)	0.020 (2%)	L	L
TL Defl inch (L/16529)	0.001	1'4 7/16"	0.100 (L/240)	0.010 (1%)	D+L	L

READ ALL NOTES ON THIS PAGE AND ON ENGINEERING NOTE PAGE ENP-2. THIS NOTE PAGE IS AN INTEGRAL PART OF THIS CALCULATION SUMMARY PAGE AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

REFER TO MULTIPLE MEMBER TO MEMBER CONNECTION DETAIL FOR PLY TO PLY NAILING OR BOLTING REQUIREMENTS.

PASS THRU FRAMING SQUASH BLOCK IS REQUIRED AT ALL POINT LOADS OVER BEARINGS.

**Design Notes**

- 1 Fill all hanger nailing holes.
- 2 Girders are designed to be supported on the bottom edge only.
- 3 Top braced at bearings.
- 4 Bottom braced at bearings.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 2-5-2	(Span)3-11-0	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Point	0-4-6		Far Face	65 lb	175 lb	0 lb	0 lb	J3
3	Point	1-8-6		Far Face	72 lb	192 lb	0 lb	0 lb	J3
	Self Weight				4 PLF				

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals**Handling & Installation**

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318





Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400



F2-A Forex 2.0E-3000Fb LVL 1.750" X 9.500" - PASSED

Level: Ground Floor

**Member Information**

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	156	72	0	0
2	84	45	0	0

Bearings and Factored Reactions

Bearing	Length	Cap. React	D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	1.750"	17%	90 / 234	324	L	1.25D+1.5L
2 - SPF	1.875"	7%	56 / 125	182	L	1.25D+1.5L
End Grain						

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	453 ft-lb	2'11 9/16"	11362 ft-lb	0.040 (4%)	1.25D+1.5L	L
Unbraced	453 ft-lb	2'11 9/16"	5389 ft-lb	0.084 (8%)	1.25D+1.5L	L
Shear	228 lb	10 1/2"	4638 lb	0.049 (5%)	1.25D+1.5L	L
Perm Defl in. (L/20045)	0.004	3'4 1/8"	0.231 (L/360)	0.020 (2%)	D	Uniform
LL Defl inch	0.009 (L/9718)	3'3 1/2"	0.231 (L/360)	0.040 (4%)	L	L
TL Defl inch	0.013 (L/6545)	3'3 11/16"	0.346 (L/240)	0.040 (4%)	D+L	L

READ ALL NOTES ON THIS PAGE AND ON ENGINEERING NOTE PAGE ENP-2. THIS NOTE PAGE IS AN INTEGRAL PART OF THIS CALCULATION SUMMARY PAGE AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

REFER TO MULTIPLE MEMBER TO MEMBER CONNECTION DETAIL FOR PLY TO PLY NAILING OR BOLTING REQUIREMENTS.

PASS THRU FRAMING SQUASH BLOCK IS REQUIRED AT ALL POINT LOADS OVER BEARINGS.

**Design Notes**

- Girders are designed to be supported on the bottom edge only.
- Top braced at bearings.
- Bottom braced at bearings.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 7-1-2	(Span)0-7-14	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Part. Uniform	0-0-0 to 3-8-0		Top	15 PLF	40 PLF	0 PLF	0 PLF	
	Self Weight				4 PLF				

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

- Dry service conditions, unless noted otherwise
- LVL not to be treated with fire retardant or corrosive

chemicals**Handling & Installation**

- LVL beams must not be cut or drilled
- Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
- Damaged Beams must not be used
- Design assumes top edge is laterally restrained
- Provide lateral support at bearing points to avoid lateral displacement and rotation

- For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318



Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400







EWP Studio
Simpson Strong-Tie®
Component Solutions™

Client: GREEN YORK HOMES
Project:
Address:

Date: 5/31/2018
Designer: RCO
Job Name: LIANA 2 (ELEV.1)
Project #:

F3-A Forex 2.0E-3000Fb LVL 1.750" X 9.500" 2-Ply - PASSED

Level: Ground Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	2	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	669	380	0	0
2	523	292	0	0

Bearings and Factored Reactions

Bearing	Length	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	5.500"	12%	475 / 1003	1478	L	1.25D+1.5L
2 - SPF	2.375"	22%	365 / 784	1150	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	607 ft-lb	1'4 1/8"	22724 ft-lb	0.027 (3%)	1.25D+1.5L	L
Unbraced	607 ft-lb	1'4 1/8"	22724 ft-lb	0.027 (3%)	1.25D+1.5L	L
Shear	729 lb	1'2 1/4"	9277 lb	0.079 (8%)	1.25D+1.5L	L
Perm Defl in.	0.001 (L/32357)	1'5 1/8"	0.072 (L/360)	0.010 (1%)	D	Uniform
LL Defl inch	0.001 (L/18072)	1'4 11/16"	0.072 (L/360)	0.020 (2%)	L	L
TL Defl inch	0.002 (L/11598)	1'4 13/16"	0.108 (L/240)	0.020 (2%)	D+L	L

READ ALL NOTES ON THIS PAGE AND ON ENGINEERING NOTE PAGE ENP-2. THIS NOTE PAGE IS AN INTEGRAL PART OF THIS CALCULATION SUMMARY PAGE AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

REFER TO MULTIPLE MEMBER TO MEMBER CONNECTION DETAIL FOR PLY TO PLY NAILING OR BOLTING REQUIREMENTS.

PASS THRU FRAMING SQUASH BLOCK IS REQUIRED AT ALL POINT LOADS OVER BEARINGS.



Design Notes

- Girders are designed to be supported on the bottom edge only.
- Multiple plies must be fastened together as per manufacturer's details.
- Top loads must be supported equally by all plies.
- Top braced at bearings.
- Bottom braced at bearings.
- Lateral slenderness ratio based on full section width.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 0-4-4	(Span)0-10-7	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Part. Uniform	0-0-0 to 0-0-2		Top	46 PLF	123 PLF	0 PLF	0 PLF	J5
3	Part. Uniform	0-0-0 to 0-0-2		Top	40 PLF	0 PLF	0 PLF	0 PLF	Wall Self Weight
4	Part. Uniform	0-0-2 to 2-5-2		Top	92 PLF	246 PLF	0 PLF	0 PLF	J5
5	Part. Uniform	0-0-2 to 2-6-12		Top	80 PLF	0 PLF	0 PLF	0 PLF	Wall Self Weight

Continued on page 2...

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

- Dry service conditions, unless noted otherwise
- LVL not to be treated with fire retardant or corrosive chemicals

chemicals

Handling & Installation

- LVL beams must not be cut or drilled
- Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
- Damaged Beams must not be used
- Design assumes top edge is laterally restrained
- Provide lateral support at bearing points to avoid lateral displacement and rotation

- For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318



Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400





EWP Studio
Simpson Strong-Tie®
Component Solutions™



Client: GREEN YORK HOMES
Project:
Address:

Date: 5/31/2018
Designer: RCO
Job Name: LIANA 2 (ELEV.1)
Project #:

Page 2 of 2

F3-A Forex 2.0E-3000Fb LVL 1.750" X 9.500" 2-Ply - PASSED

Level: Ground Floor



...Continued from page 1

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
6	Tie-In	0-4-4 to 2-8-6	(Span)1-0-15	Top	15 PSF	40 PSF	0 PSF	0 PSF	
7	Point	0-10-14		Far Face	120 lb	319 lb	0 lb	0 lb	J5
8	Point	2-2-14		Far Face	83 lb	220 lb	0 lb	0 lb	J5
	Self Weight				8 PLF				

REFER TO MULTIPLE MEMBER TO MEMBER
CONNECTION DETAIL FOR PLY TO PLY
NAILING OR BOLTING REQUIREMENTS.

PASS THRU FRAMING SQUASH
BLOCK IS REQUIRED AT ALL
POINT LOADS OVER BEARINGS.

Notes

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318



Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400






EWP Studio
Simpson Strong-Tie®
Component Solutions™

Client: GREEN YORK HOMES
Project:
Address:

Date: 5/31/2018
Designer: RCO
Job Name: LIANA 2 (ELEV.1)
Project #:

F4-C Forex 2.0E-3000Fb LVL 1.750" X 9.500" 2-Ply - PASSED

Level: Ground Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	2	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	374	193	0	0
2	1087	464	0	0

Bearings and Factored Reactions

Bearing	Length	Cap. React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	4.125"	9%	241 / 560	801 L	1.25D+1.5L
2 - SPF	6.875"	15%	580 / 1631	2211 L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	4654 ft-lb	9'8 1/2"	22724 ft-lb	0.205 (20%)	1.25D+1.5L	L
Unbraced	4654 ft-lb	9'8 1/2"	19392 ft-lb	0.240 (24%)	1.25D+1.5L	L
Shear	1816 lb	12'5 3/4"	9277 lb	0.196 (20%)	1.25D+1.5L	L
Perm Defl in.	0.058 (L/2669)	7'3 7/8"	0.433 (L/360)	0.130 (13%)	D	Uniform
LL Defl inch	0.127 (L/1225)	7'5 1/4"	0.433 (L/360)	0.290 (29%)	L	
TL Defl inch	0.186 (L/840)	7'4 13/16"	0.649 (L/240)	0.290 (29%)	D+L	L

READ ALL NOTES ON THIS PAGE AND ON ENGINEERING NOTE PAGE ENP-2. THIS NOTE PAGE IS AN INTEGRAL PART OF THIS CALCULATION SUMMARY PAGE AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

REFER TO MULTIPLE MEMBER TO MEMBER CONNECTION DETAIL FOR PLY TO PLY NAILING OR BOLTING REQUIREMENTS.

PASS THRU FRAMING SQUASH BLOCK IS REQUIRED AT ALL POINT LOADS OVER BEARINGS.



Design Notes

- Girders are designed to be supported on the bottom edge only.
- Multiple plies must be fastened together as per manufacturer's details.
- Top loads must be supported equally by all plies.
- Top braced at bearings.
- Bottom braced at bearings.
- Lateral slenderness ratio based on full section width.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 9-7-10	(Span)0-6-2	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Tie-In	0-0-0 to 0-3-0	(Span)0-7-6	Top	15 PSF	40 PSF	0 PSF	0 PSF	
3	Tie-In	0-3-0 to 13-7-15	(Span)0-9-14	Top	15 PSF	40 PSF	0 PSF	0 PSF	
4	Part. Uniform	9-8-8 to 13-2-8		Top	90 PLF	240 PLF	0 PLF	0 PLF	
5	Point	9-8-8		Far Face	116 lb	299 lb	0 lb	0 lb	F1
	Self Weight				8 PLF				

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

- Dry service conditions, unless noted otherwise
- LVL not to be treated with fire retardant or corrosive chemicals

chemicals

Handling & Installation

- LVL beams must not be cut or drilled
- Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
- Damaged Beams must not be used
- Design assumes top edge is laterally restrained
- Provide lateral support at bearing points to avoid lateral displacement and rotation

- For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318



Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400






EWP Studio
Simpson Strong-Tie®
Component Solutions™

Client: GREEN YORK HOMES
Project:
Address:

Date: 5/31/2018
Designer: RCO
Job Name: LIANA 2 (ELEV.1)
Project #:

F4-D Forex 2.0E-3000Fb LVL 1.750" X 9.500" 2-Ply - PASSED

Level: Ground Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	2	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	1545	622	0	0
2	1762	732	0	0

Bearings and Factored Reactions

Bearing	Length	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	2.375"	61%	777 / 2317	3094	L	1.25D+1.5L
2 - SPF	7.754"	21%	915 / 2643	3559	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	9242 ft-lb	5'9 9/16"	22724 ft-lb	0.407 (41%)	1.25D+1.5L	L
Unbraced	9242 ft-lb	5'9 9/16"	20195 ft-lb	0.458 (46%)	1.25D+1.5L	L
Shear	3271 lb	11 1/8"	9277 lb	0.353 (35%)	1.25D+1.5L	L
Perm Defl in.	0.092 (L/1482)	5'9 9/16"	0.377 (L/360)	0.240 (24%)	D	Uniform
LL Defl inch	0.229 (L/594)	5'9 9/16"	0.377 (L/360)	0.610 (61%)	L	
TL Defl inch	0.320 (L/424)	5'9 9/16"	0.566 (L/240)	0.570 (57%)	D+L	L

READ ALL NOTES ON THIS PAGE AND ON ENGINEERING NOTE PAGE ENP-2. THIS NOTE PAGE IS AN INTEGRAL PART OF THIS CALCULATION SUMMARY PAGE AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

REFER TO MULTIPLE MEMBER TO MEMBER CONNECTION DETAIL FOR PLY TO PLY NAILING OR BOLTING REQUIREMENTS.

PASS THRU FRAMING SQUASH BLOCK IS REQUIRED AT ALL POINT LOADS OVER BEARINGS.



Design Notes

- 1 Performed Secondary Bearing Check (CSA 086-14 6.5.7.3). Assumed point load size: beam width X 4.5.
- 2 Girders are designed to be supported on the bottom edge only.
- 3 Multiple plies must be fastened together as per manufacturer's details.
- 4 Top loads must be supported equally by all plies.
- 5 Top braced at bearings.
- 6 Bottom braced at bearings.
- 7 Lateral slenderness ratio based on full section width.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 11-2-3	(Span)1-0-4	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Point	1-0-15		Far Face	124 lb	332 lb	0 lb	0 lb	J5
3	Part. Uniform	1-8-15 to 11-0-15		Far Face	101 PLF	270 PLF	0 PLF	0 PLF	
4	Tie-In	11-2-3 to 12-0-7	(Span)1-1-0 to 0-2-12	Top	15 PSF	40 PSF	0 PSF	0 PSF	
5	Point	11-8-15		Far Face	48 lb	128 lb	0 lb	0 lb	J5

Continued on page 2...

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318



Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400





EWP Studio
Simpson Strong-Tie®
Component Solutions™


Client: GREEN YORK HOMES
Project:
Address:

Date: 5/31/2018
Designer: RCO
Job Name: LIANA 2 (ELEV.1)
Project #:

Page 2 of 2

F4-D Forex 2.0E-3000Fb LVL 1.750" X 9.500" 2-Ply - PASSED

Level: Ground Floor



...Continued from page 1

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
6	Point	11-11-5		Top	16 lb	34 lb	0 lb	0 lb	J4
7	Point	11-11-5		Top	20 lb	54 lb	0 lb	0 lb	J5
8	Point	11-11-5		Top	22 lb	0 lb	0 lb	0 lb	Wall Self Weight
	Self Weight				8 PLF				

REFER TO MULTIPLE MEMBER TO MEMBER
CONNECTION DETAIL FOR PLY TO PLY
NAILING OR BOLTING REQUIREMENTS.

PASS THRU FRAMING SQUASH
BLOCK IS REQUIRED AT ALL
POINT LOADS OVER BEARINGS.

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318





Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400



F5-A NJH 9.500" - PASSED

Level: Ground Floor

**Member Information**

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	65	31	0	0
2	135	67	0	0

Bearings and Factored Reactions

Bearing	Length	Cap. React	D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	2.375"	9%	39 / 98	136	L	1.25D+1.5L
2 - Hanger	2.000"	18%	84 / 202	286	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	52 ft-lb	1' 1/8"	3830 ft-lb	0.014 (1%)	1.25D+1.5L	L
Unbraced	52 ft-lb	1' 1/8"	3779 ft-lb	0.014 (1%)	1.25D+1.5L	L
Shear	272 lb	1'5 5/8"	1580 lb	0.172 (17%)	1.25D+1.5L	L
Perm Defl in. (L/56622)	0.000	11 7/8"	0.044 (L/360)	0.010 (1%)	D	Uniform
LL Defl inch (L/28154)	0.001	11 7/8"	0.044 (L/360)	0.010 (1%)	L	L
TL Defl inch (L/18804)	0.001	11 7/8"	0.067 (L/240)	0.010 (1%)	D+L	L

READ ALL NOTES ON THIS PAGE AND ON ENGINEERING NOTE PAGE ENP-2. THIS NOTE PAGE IS AN INTEGRAL PART OF THIS CALCULATION SUMMARY PAGE AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

REFER TO MULTIPLE MEMBER TO MEMBER CONNECTION DETAIL FOR PLY TO PLY NAILING OR BOLTING REQUIREMENTS.

PASS THRU FRAMING SQUASH BLOCK IS REQUIRED AT ALL POINT LOADS OVER BEARINGS.

**Design Notes**

- 1 Fill all hanger nailing holes.
- 2 Girders are designed to be supported on the bottom edge only.
- 3 Top flange unbraced.
- 4 Bottom flange braced at bearings.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 1-6-14	(Span)3-2-8	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Part. Uniform	0-2-6 to 1-6-14		Top	8 PLF	0 PLF	0 PLF	0 PLF	
3	Point	1-3-7		Near Face	49 lb	99 lb	0 lb	0 lb	J2

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. Ljoist not to be treated with fire retardant or corrosive chemicals

chemicals**Handling & Installation**

1. Ljoist flanges must not be cut or drilled
2. Refer to latest copy of the Ljoist product information details for framing details, stiffener tables, web hole chart, bridging details, multi-ply fastening details and handling/erection details
3. Damaged Ljoists must not be used
4. Design assumes top flange to be laterally restrained by attached sheathing or as specified in engineering notes.

5. Provide lateral support at bearing points to avoid lateral displacement and rotation
6. Web stiffeners for point load as shown Minimum point load bearing length >= 3.5 inches
7. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Nascor by Kott



Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400







EWP Studio
Simpson Strong-Tie®
Component Solutions™

Client: GREEN YORK HOMES
Project:
Address:

Date: 5/31/2018
Designer: RCO
Job Name: LIANA 2 (ELEV.1)
Project #:

F5-B NJH 9.500" - PASSED

Level: Ground Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	63	30	0	0
2	120	59	0	0

Bearings and Factored Reactions

Bearing	Length	Cap. React	D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	2.375"	8%	37 / 94	131	L	1.25D+1.5L
2 - Hanger	2.000"	16%	74 / 180	254	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	48 ft-lb	11 11/16"	3830 ft-lb	0.013 (1%)	1.25D+1.5L	L
Unbraced	48 ft-lb	11 11/16"	3779 ft-lb	0.013 (1%)	1.25D+1.5L	L
Shear	240 lb	1'5 5/8"	1580 lb	0.152 (15%)	1.25D+1.5L	L
Perm Defl in. (L/61792)	0.000	11 7/16"	0.044 (L/360)	0.010 (1%)	D	Uniform
LL Defl inch (L/30562)	0.001	11 1/2"	0.044 (L/360)	0.010 (1%)	L	L
TL Defl inch (L/20448)	0.001	11 1/2"	0.067 (L/240)	0.010 (1%)	D+L	L

READ ALL NOTES ON THIS PAGE AND ON ENGINEERING NOTE PAGE ENP-2. THIS NOTE PAGE IS AN INTEGRAL PART OF THIS CALCULATION SUMMARY PAGE AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

REFER TO MULTIPLE MEMBER TO MEMBER CONNECTION DETAIL FOR PLY TO PLY NAILING OR BOLTING REQUIREMENTS.

PASS THRU FRAMING SQUASH BLOCK IS REQUIRED AT ALL POINT LOADS OVER BEARINGS.



Design Notes

- 1 Fill all hanger nailing holes.
- 2 Girders are designed to be supported on the bottom edge only.
- 3 Top flange unbraced.
- 4 Bottom flange braced at bearings.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 1-6-14	(Span)3-2-8	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Part. Uniform	0-2-6 to 1-6-14		Top	8 PLF	0 PLF	0 PLF	0 PLF	
3	Point	1-3-7		Far Face	40 lb	82 lb	0 lb	0 lb	J2

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. Joist not to be treated with fire retardant or corrosive chemicals

chemicals

Handling & Installation

1. Joist flanges must not be cut or drilled
2. Refer to latest copy of the Joist product information details for framing details, stiffener tables, web hole chart, bridging details, multi-ply fastening details and handling/erection details
3. Damaged Joists must not be used
4. Design assumes top flange to be laterally restrained by attached sheathing or as specified in engineering notes.

5. Provide lateral support at bearing points to avoid lateral displacement and rotation
6. Web stiffeners for point load as shown Minimum point load bearing length >= 3.5 inches
7. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Nascor by Kott



Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400







EWP Studio
Simpson Strong-Tie®
Component Solutions™

Client: GREEN YORK HOMES
Project:
Address:

Date: 5/31/2018
Designer: RCO
Job Name: LIANA 2 (ELEV.1)
Project #:

F5-C NJH 9.500" - PASSED

Level: Ground Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	59	22	0	0
2	115	44	0	0

Bearings and Factored Reactions

Bearing	Length	Cap. React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	2.375"	7%	28 / 88	116 L	1.25D+1.5L
2 - Hanger	2.000"	14%	55 / 173	227 L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	39 ft-lb	11"	3830 ft-lb	0.010 (1%)	1.25D+1.5L	L
Unbraced	39 ft-lb	11"	3779 ft-lb	0.010 (1%)	1.25D+1.5L	L
Shear	214 lb	1'5 5/8"	1580 lb	0.135 (14%)	1.25D+1.5L	L
Perm Defl in.	0.000 (L/999)	0	999.000 (L/0)	0.000 (0%)		
LL Defl inch	0.000 (L/35261)	10 7/8"	0.044 (L/360)	0.010 (1%)	L	L
TL Defl inch	0.001 (L/25598)	10 7/8"	0.067 (L/240)	0.010 (1%)	D+L	L

READ ALL NOTES ON THIS PAGE AND ON ENGINEERING NOTE PAGE ENP-2. THIS NOTE PAGE IS AN INTEGRAL PART OF THIS CALCULATION SUMMARY PAGE AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

REFER TO MULTIPLE MEMBER TO MEMBER CONNECTION DETAIL FOR PLY TO PLY NAILING OR BOLTING REQUIREMENTS.

PASS THRU FRAMING SQUASH BLOCK IS REQUIRED AT ALL POINT LOADS OVER BEARINGS.



Design Notes

- 1 Fill all hanger nailing holes.
- 2 Girders are designed to be supported on the bottom edge only.
- 3 Top flange unbraced.
- 4 Bottom flange braced at bearings.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 1-6-14	(Span)3-2-8	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Point	1-4-0		Near Face	28 lb	73 lb	0 lb	0 lb	J2

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. Joist not to be treated with fire retardant or corrosive chemicals

chemicals

Handling & Installation

1. Joist flanges must not be cut or drilled
2. Refer to latest copy of the Joist product information details for framing details, stiffener tables, web hole chart, bridging details, multi-ply fastening details and handling/erection details
3. Damaged Joists must not be used
4. Design assumes top flange to be laterally restrained by attached sheathing or as specified in engineering notes.

5. Provide lateral support at bearing points to avoid lateral displacement and rotation
6. Web stiffeners for point load as shown Minimum point load bearing length >= 3.5 inches
7. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Nascor by Kott



Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400







EWP Studio
Simpson Strong-Tie®
Component Solutions™

Client: GREEN YORK HOMES
Project:
Address:

Date: 5/31/2018
Designer: RCO
Job Name: LIANA 2 (ELEV.1)
Project #:

F5-D NJH 9.500" - PASSED

Level: Ground Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	59	22	0	0
2	118	44	0	0

Bearings and Factored Reactions

Bearing	Length	Cap. React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	2.375"	7%	28 / 89	116 L	1.25D+1.5L
2 - Hanger	2.000"	15%	55 / 177	231 L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	39 ft-lb	11 1/16"	3830 ft-lb	0.010 (1%)	1.25D+1.5L	L
Unbraced	39 ft-lb	11 1/16"	3779 ft-lb	0.010 (1%)	1.25D+1.5L	L
Shear	218 lb	1'5 5/8"	1580 lb	0.138 (14%)	1.25D+1.5L	L
Perm Defl in.	0.000 (L/999)	0	999.000 (L/0)	0.000 (0%)		
LL Defl inch	0.000 (L/34841)	10 15/16"	0.044 (L/360)	0.010 (1%)	L	L
TL Defl inch	0.001 (L/25376)	10 15/16"	0.067 (L/240)	0.010 (1%)	D+L	L

READ ALL NOTES ON THIS PAGE AND ON ENGINEERING NOTE PAGE ENP-2. THIS NOTE PAGE IS AN INTEGRAL PART OF THIS CALCULATION SUMMARY PAGE AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

REFER TO MULTIPLE MEMBER TO MEMBER CONNECTION DETAIL FOR PLY TO PLY NAILING OR BOLTING REQUIREMENTS.

PASS THRU FRAMING SQUASH BLOCK IS REQUIRED AT ALL POINT LOADS OVER BEARINGS.



Design Notes

- Fill all hanger nailing holes.
- Girders are designed to be supported on the bottom edge only.
- Top flange unbraced.
- Bottom flange braced at bearings.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 1-6-14	(Span)3-2-8	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Point	1-4-0		Far Face	28 lb	76 lb	0 lb	0 lb	J2

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

- Dry service conditions, unless noted otherwise
- Joist not to be treated with fire retardant or corrosive chemicals

chemicals

Handling & Installation

- Joist flanges must not be cut or drilled
- Refer to latest copy of the Joist product information details for framing details, stiffener tables, web hole chart, bridging details, multi-ply fastening details and handling/erection details
- Damaged Joists must not be used
- Design assumes top flange to be laterally restrained by attached sheathing or as specified in engineering notes.

- Provide lateral support at bearing points to avoid lateral displacement and rotation
- Web stiffeners for point load as shown Minimum point load bearing length >= 3.5 inches
- For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Nascor by Kott




Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400



F6-A NJH 9.500" - PASSED

Level: Ground Floor

**Member Information**

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	274	135	0	0
2	215	105	0	0

Bearings and Factored Reactions

Bearing	Length	Cap. React D/L lb	Total	Ld. Case	Ld. Comb.
1 - Hanger	2.000"	37%	169 / 411	581 L	1.25D+1.5L
2 - Hanger	2.000"	29%	132 / 323	455 L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	420 ft-lb	1'10 7/16"	3830 ft-lb	0.110 (11%)	1.25D+1.5L	L
Unbraced	420 ft-lb	1'10 7/16"	3411 ft-lb	0.123 (12%)	1.25D+1.5L	L
Shear	573 lb	1 1/4"	1580 lb	0.363 (36%)	1.25D+1.5L	L
Perm Defl in. (L/12262)	0.003	1'10 7/16"	0.093 (L/360)	0.030 (3%)	D	Uniform
LL Defl inch	0.006 (L/6011)	1'10 7/16"	0.093 (L/360)	0.060 (6%)	L	L
TL Defl inch	0.008 (L/4033)	1'10 7/16"	0.140 (L/240)	0.060 (6%)	D+L	L

READ ALL NOTES ON THIS PAGE AND ON ENGINEERING NOTE PAGE ENP-2. THIS NOTE PAGE IS AN INTEGRAL PART OF THIS CALCULATION SUMMARY PAGE AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

REFER TO MULTIPLE MEMBER TO MEMBER CONNECTION DETAIL FOR PLY TO PLY NAILING OR BOLTING REQUIREMENTS.

PASS THRU FRAMING SQUASH BLOCK IS REQUIRED AT ALL POINT LOADS OVER BEARINGS.

**Design Notes**

- 1 Fill all hanger nailing holes.
- 2 Girders are designed to be supported on the bottom edge only.
- 3 Top flange unbraced.
- 4 Bottom flange braced at bearings.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 3-0-0	(Span)1-8-11	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Part. Uniform	0-0-0 to 3-0-0		Top	4 PLF	0 PLF	0 PLF	0 PLF	
3	Point	0-6-7		Far Face	84 lb	169 lb	0 lb	0 lb	J3
4	Point	1-10-7		Far Face	106 lb	217 lb	0 lb	0 lb	J3

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. Joist not to be treated with fire retardant or corrosive chemicals

Handling & Installation

1. Joist flanges must not be cut or drilled
2. Refer to latest copy of the Joist product information details for framing details, stiffener tables, web hole chart, bridging details, multi-ply fastening details and handling/erection details
3. Damaged Joists must not be used
4. Design assumes top flange to be laterally restrained by attached sheathing or as specified in engineering notes.

5. Provide lateral support at bearing points to avoid lateral displacement and rotation
6. Web stiffeners for point load as shown Minimum point load bearing length>= 3.5 inches
7. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Nascor by Kott




Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400



F7-A NJH 9.500" - PASSED

Level: Ground Floor

**Member Information**

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	370	181	0	0
2	533	273	0	0

Bearings and Factored Reactions

Bearing	Length	Cap. React	D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	2.375"	49%	226 / 555	781	L	1.25D+1.5L
2 - SPF	2.625"	72%	342 / 800	1141	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	3313 ft-lb	7'1"	3830 ft-lb	0.865 (87%)	1.25D+1.5L	L
Unbraced	3313 ft-lb	7'1"	3323 ft-lb	0.997 (100%)	1.25D+1.5L	L
Shear	774 lb	1 5/8"	1580 lb	0.490 (49%)	1.25D+1.5L	L
Perm Defl in.	0.155 (L/1064)	6'11 3/8"	0.457 (L/360)	0.340 (34%)	D	Uniform
LL Defl inch	0.315 (L/522)	6'11 3/8"	0.457 (L/360)	0.690 (69%)	L	L
TL Defl inch	0.470 (L/350)	6'11 3/8"	0.685 (L/240)	0.690 (69%)	D+L	L

READ ALL NOTES ON THIS PAGE AND ON ENGINEERING NOTE PAGE ENP-2. THIS NOTE PAGE IS AN INTEGRAL PART OF THIS CALCULATION SUMMARY PAGE AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

REFER TO MULTIPLE MEMBER TO MEMBER CONNECTION DETAIL FOR PLY TO PLY NAILING OR BOLTING REQUIREMENTS.

PASS THRU FRAMING SQUASH BLOCK IS REQUIRED AT ALL POINT LOADS OVER BEARINGS.

**Design Notes**

- Girders are designed to be supported on the bottom edge only.
- Top flange must be laterally braced at a maximum of 3' o.c.
- Bottom flange braced at bearings.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 13-11-14	(Span)0-11-5	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Tie-In	0-0-0 to 4-9-6	(Span)0-4-11	Top	15 PSF	40 PSF	0 PSF	0 PSF	
3	Part. Uniform	0-2-6 to 4-9-6		Top	1 PLF	0 PLF	0 PLF	0 PLF	
4	Part. Uniform	0-2-6 to 13-9-2		Top	2 PLF	0 PLF	0 PLF	0 PLF	
5	Tie-In	4-9-6 to 8-2-6	(Span)1-8-11 to 1-8-11	Top	15 PSF	40 PSF	0 PSF	0 PSF	
6	Part. Uniform	4-9-6 to 8-2-6		Top	4 PLF	0 PLF	0 PLF	0 PLF	
7	Point	4-10-10		Near Face	59 lb	120 lb	0 lb	0 lb	F5

Continued on page 2...

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

- Dry service conditions, unless noted otherwise
- IJoist not to be treated with fire retardant or corrosive chemicals

chemicals**Handling & Installation**

- IJoist flanges must not be cut or drilled
- Refer to latest copy of the IJoist product information details for framing details, stiffener tables, web hole chart, bridging details, multi-ply fastening details and handling/erection details
- Damaged IJoists must not be used
- Design assumes top flange to be laterally restrained by attached sheathing or as specified in engineering notes.

- Provide lateral support at bearing points to avoid lateral displacement and rotation
- Web stiffeners for point load as shown Minimum point load bearing length >= 3.5 inches
- For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Nascor by Kott




Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400



F7-A NJH 9.500" - PASSED

Level: Ground Floor



...Continued from page 1

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
8	Point	8-1-2		Near Face	67 lb	135 lb	0 lb	0 lb	F5
9	Tie-In	8-2-6 to 13-11-14	(Span)0-4-11	Top	15 PSF	40 PSF	0 PSF	0 PSF	
10	Part. Uniform	8-2-6 to 13-9-2		Top	1 PLF	0 PLF	0 PLF	0 PLF	
11	Point	13-11-14		Top	35 lb	91 lb	0 lb	0 lb	J5
12	Point	13-11-14		Top	41 lb	93 lb	0 lb	0 lb	J5
13	Point	13-11-14		Top	27 lb	0 lb	0 lb	0 lb	Wall Self Weight

REFER TO MULTIPLE MEMBER TO MEMBER
CONNECTION DETAIL FOR PLY TO PLY
NAILING OR BOLTING REQUIREMENTS.

PASS THRU FRAMING SQUASH
BLOCK IS REQUIRED AT ALL
POINT LOADS OVER BEARINGS.

Notes

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. Ljoist not to be treated with fire retardant or corrosive

chemicals**Handling & Installation**

1. Ljoist flanges must not be cut or drilled
2. Refer to latest copy of the Ljoist product information details for framing details, stiffener tables, web hole chart, bridging details, multi-ply fastening details and handling/erection details
3. Damaged Ljoists must not be used
4. Design assumes top flange to be laterally restrained by attached sheathing or as specified in engineering notes.

5. Provide lateral support at bearing points to avoid lateral displacement and rotation
6. Web stiffeners for point load as shown Minimum point load bearing length>= 3.5 inches
7. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Nascor by Kott




Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400



F7-B NJH 9.500" - PASSED

Level: Ground Floor

**Member Information**

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	331	125	0	0
2	324	122	0	0

Bearings and Factored Reactions

Bearing	Length	Cap. React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	4.125"	41%	156 / 496	652 L	1.25D+1.5L
2 - SPF	2.375"	40%	152 / 486	638 L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	2390 ft-lb	6'2 3/4"	3830 ft-lb	0.624 (62%)	1.25D+1.5L	L
Unbraced	2390 ft-lb	6'2 3/4"	2404 ft-lb	0.994 (99%)	1.25D+1.5L	L
Shear	637 lb	3 3/8"	1580 lb	0.403 (40%)	1.25D+1.5L	L
Perm Defl in.	0.072 (L/1978)	6'2 1/2"	0.395 (L/360)	0.180 (18%)	D	Uniform
LL Defl inch	0.191 (L/744)	6'2 9/16"	0.395 (L/360)	0.480 (48%)	L	
TL Defl inch	0.263 (L/541)	6'2 9/16"	0.593 (L/240)	0.440 (44%)	D+L	L

READ ALL NOTES ON THIS PAGE AND ON ENGINEERING NOTE PAGE ENP-2. THIS NOTE PAGE IS AN INTEGRAL PART OF THIS CALCULATION SUMMARY PAGE AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

REFER TO MULTIPLE MEMBER TO MEMBER CONNECTION DETAIL FOR PLY TO PLY NAILING OR BOLTING REQUIREMENTS.

PASS THRU FRAMING SQUASH BLOCK IS REQUIRED AT ALL POINT LOADS OVER BEARINGS.

**Design Notes**

- Girders are designed to be supported on the bottom edge only.
- Top flange must be laterally braced at a maximum of 4'9" o.c.
- Bottom flange braced at bearings.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 4-5-3	(Span)0-4-2	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Tie-In	0-0-0 to 12-3-6	(Span)0-11-14	Top	15 PSF	40 PSF	0 PSF	0 PSF	
3	Tie-In	4-5-3 to 7-10-3	(Span)1-8-11	Top	15 PSF	40 PSF	0 PSF	0 PSF	
4	Point	4-6-7		Far Face	44 lb	115 lb	0 lb	0 lb	F5
5	Point	7-8-15		Far Face	44 lb	118 lb	0 lb	0 lb	F5
6	Tie-In	7-10-3 to 12-3-6	(Span)0-4-2	Top	15 PSF	40 PSF	0 PSF	0 PSF	

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

- Dry service conditions, unless noted otherwise
- Joist not to be treated with fire retardant or corrosive chemicals

chemicals**Handling & Installation**

- Joist flanges must not be cut or drilled
- Refer to latest copy of the Joist product information details for framing details, stiffener tables, web hole chart, bridging details, multi-ply fastening details and handling/erection details
- Damaged Joists must not be used
- Design assumes top flange to be laterally restrained by attached sheathing or as specified in engineering notes.

- Provide lateral support at bearing points to avoid lateral displacement and rotation
- Web stiffeners for point load as shown Minimum point load bearing length>= 3.5 inches
- For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Nascor by Kott





Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400



F8-A NJH 9.500" 2-Ply - PASSED

Level: Ground Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	2	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	514	250	0	0
2	325	155	0	0

Bearings and Factored Reactions

Bearing	Length	Cap. React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	2.375"	34%	313 / 771	1084 L	1.25D+1.5L
2 - SPF	6.875"	22%	194 / 488	682 L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	1756 ft-lb	4'2 9/16"	7660 ft-lb	0.229 (23%)	1.25D+1.5L	L
Unbraced	1756 ft-lb	4'2 9/16"	1759 ft-lb	0.999 (100%)	1.25D+1.5L	L
Shear	1059 lb	1 5/8"	3160 lb	0.335 (34%)	1.25D+1.5L	L
Perm Defl in.	0.024 (L/4916)	4'8 11/16"	0.322 (L/360)	0.070 (7%)	D	Uniform
LL Defl inch	0.048 (L/2404)	4'8 11/16"	0.322 (L/360)	0.150 (15%)	L	L
TL Defl inch	0.072 (L/1614)	4'8 11/16"	0.483 (L/240)	0.150 (15%)	D+L	L

READ ALL NOTES ON THIS PAGE AND ON ENGINEERING NOTE PAGE ENP-2. THIS NOTE PAGE IS AN INTEGRAL PART OF THIS CALCULATION SUMMARY PAGE AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

REFER TO MULTIPLE MEMBER TO MEMBER CONNECTION DETAIL FOR PLY TO PLY NAILING OR BOLTING REQUIREMENTS.

PASS THRU FRAMING SQUASH BLOCK IS REQUIRED AT ALL POINT LOADS OVER BEARINGS.



Design Notes

- Girders are designed to be supported on the bottom edge only.
- Multiple plies must be fastened together as per manufacturer's details.
- Top loads must be supported equally by all plies.
- Top flange must be laterally braced at a maximum of 8'5" o.c.
- Bottom flange braced at bearings.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 1-9-6	(Span)3-5-0	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Tie-In	0-0-0 to 10-3-12	(Span)1-3-15	Top	15 PSF	40 PSF	0 PSF	0 PSF	
3	Part. Uniform	0-2-6 to 1-9-6		Top	9 PLF	0 PLF	0 PLF	0 PLF	
4	Part. Uniform	0-2-6 to 9-8-15		Top	3 PLF	0 PLF	0 PLF	0 PLF	
5	Point	1-8-2		Far Face	105 lb	215 lb	0 lb	0 lb	F6
6	Tie-In	1-9-6 to 10-3-12	(Span)1-4-1	Top	15 PSF	40 PSF	0 PSF	0 PSF	
7	Part. Uniform	1-9-6 to 9-8-15		Top	3 PLF	0 PLF	0 PLF	0 PLF	

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

- Dry service conditions, unless noted otherwise
- Joist not to be treated with fire retardant or corrosive chemicals

chemicals

Handling & Installation

- Joist flanges must not be cut or drilled
- Refer to latest copy of the Joist product information details for framing details, stiffener tables, web hole chart, bridging details, multi-ply fastening details and handling/erection details
- Damaged Joists must not be used
- Design assumes top flange to be laterally restrained by attached sheathing or as specified in engineering notes.

- Provide lateral support at bearing points to avoid lateral displacement and rotation
- Web stiffeners for point load as shown Minimum point load bearing length >= 3.5 inches
- For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Nascor by Kott




Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400



F8-B NJH 9.500" 2-Ply - PASSED

Level: Ground Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	2	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	451	220	0	0
2	194	93	0	0

Bearings and Factored Reactions

Bearing	Length	Cap. React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	2.375"	30%	276 / 676	951 L	1.25D+1.5L
2 - SPF	6.875"	13%	116 / 291	407 L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	1286 ft-lb	3' 1/2"	7660 ft-lb	0.168 (17%)	1.25D+1.5L	L
Unbraced	1286 ft-lb	3' 1/2"	1290 ft-lb	0.997 (100%)	1.25D+1.5L	L
Shear	930 lb	1 5/8"	3160 lb	0.294 (29%)	1.25D+1.5L	L
Perm Defl in.	0.017 (L/6925)	4'6"	0.322 (L/360)	0.050 (5%)	D	Uniform
LL Defl inch	0.034 (L/3400)	4'6"	0.322 (L/360)	0.110 (11%)	L	L
TL Defl inch	0.051 (L/2280)	4'6"	0.483 (L/240)	0.110 (11%)	D+L	L

READ ALL NOTES ON THIS PAGE AND ON ENGINEERING NOTE PAGE ENP-2. THIS NOTE PAGE IS AN INTEGRAL PART OF THIS CALCULATION SUMMARY PAGE AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

REFER TO MULTIPLE MEMBER TO MEMBER CONNECTION DETAIL FOR PLY TO PLY NAILING OR BOLTING REQUIREMENTS.

PASS THRU FRAMING SQUASH BLOCK IS REQUIRED AT ALL POINT LOADS OVER BEARINGS.



Design Notes

- Girders are designed to be supported on the bottom edge only.
- Multiple plies must be fastened together as per manufacturer's details.
- Top loads must be supported equally by all plies.
- Top flange must be laterally braced at a maximum of 9'7" o.c.
- Bottom flange braced at bearings.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 10-3-12	(Span)0-7-1	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Tie-In	0-0-0 to 1-9-6	(Span)3-5-0	Top	15 PSF	40 PSF	0 PSF	0 PSF	
3	Part. Uniform	0-2-6 to 9-9-0		Top	1 PLF	0 PLF	0 PLF	0 PLF	
4	Part. Uniform	0-2-6 to 1-9-6		Top	9 PLF	0 PLF	0 PLF	0 PLF	
5	Point	1-8-2		Near Face	135 lb	274 lb	0 lb	0 lb	F6
6	Tie-In	1-9-6 to 10-3-12	(Span)0-8-15	Top	15 PSF	40 PSF	0 PSF	0 PSF	
7	Part. Uniform	1-9-6 to 9-9-0		Top	2 PLF	0 PLF	0 PLF	0 PLF	

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

- Dry service conditions, unless noted otherwise
- Ljoist not to be treated with fire retardant or corrosive chemicals

chemicals

Handling & Installation

- Ljoist flanges must not be cut or drilled
- Refer to latest copy of the Ljoist product information details for framing details, stiffener tables, web hole chart, bridging details, multi-ply fastening details and handling/erection details
- Damaged Ljoists must not be used
- Design assumes top flange to be laterally restrained by attached sheathing or as specified in engineering notes.

- Provide lateral support at bearing points to avoid lateral displacement and rotation
- Web stiffeners for point load as shown Minimum point load bearing length >= 3.5 inches
- For flat roofs provide proper drainage to prevent ponding

Manufacturer Info


Nascor by Kott



Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400



Second Floor



THIS CERTIFICATION IS TO CONFIRM THAT:

1. THE LOADS USED IN THE CALCULATION OF THE ATTACHED APPROVED COMPONENTS CONFORM TO THE FLOOR ASSEMBLY SHOWN ON THIS LAYOUT.

2. THE FLOOR JOISTS COMPLY WITH THE NASCOR SPAN TABLE FOR THE LOADS AND SPACING SHOWN ON THIS LAYOUT.

THE FLOOR SYSTEM MUST BE ASSEMBLED IN ACCORDANCE TO THE NASCOR SPECIFIER GUIDE. MULTI-PLY MEMBERS MUST BE ATTACHED TOGETHER AS PER THE INCLUDED MULTIPLE MEMBER CONNECTION DETAIL.

ALL OTHER COMPONENTS AND STRUCTURAL ELEMENTS SUPPORTING THE FLOOR SYSTEM SUCH AS BEAMS, WALLS, COLUMNS AND FOUNDATION WALLS AND FOOTINGS INCLUDING ANCHORAGE OF COMPONENTS AND BRACING FOR LATERAL STABILITY ARE THE RESPONSIBILITY OF OTHERS.

READ ALL NOTES ON THIS PAGE AND ON ENGINEERING NOTE PAGE ENP-2. THIS NOTE PAGE IS AN INTEGRAL PART OF THIS CALCULATION SUMMARY PAGE AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.


REFER TO MULTIPLE MEMBER TO MEMBER CONNECTION DETAIL FOR PLY TO PLY NAILING OR BOLTING REQUIREMENTS.

PASS THRU FRAMING SQUASH BLOCK IS REQUIRED AT ALL POINT LOADS OVER BEARINGS.

Legend

- Load from Above
- Wall
- Norbord Rimboard Plus 1.125 X 9.5
- NJH 9.5
- Forex 2.0E-3000Fb LVL 1.75 X 9.5 (Dropped)
- Forex 2.0E-3000Fb LVL 1.75 X 9.5

- 1. OBC 2012 O.Reg 332/12 as amended
- 2. Nascor CCMC - 13535-R
- 3. LVL CCMC -14056-R
- 4. CAN/CSA-O86-09
- 5. CCMC -12787-R APA PR-L310(C)



Second Floor LVL/LSL (Flush)							
Label	Description	Width	Depth	Qty	Plies	Pcs	Length
F4	Forex 2.0E-3000Fb LVL	1.75	9.5	2	2	4	14-0-0
F10	Forex 2.0E-3000Fb LVL	1.75	9.5	1	2	2	6-0-0
F9	Forex 2.0E-3000Fb LVL	1.75	9.5			1	2-0-0
LVL/LSL (Dropped)							
Label	Description	Width	Depth	Qty	Plies	Pcs	Length
BBO4	Forex 2.0E-3000Fb LVL	1.75	9.5	1	2	2	12-0-0
I Joist (Flush)							
Label	Description	Width	Depth	Qty	Plies	Pcs	Length
J5	NJH	2.5	9.5			45	14-0-0
J4	NJH	2.5	9.5			28	12-0-0
J1	NJH	2.5	9.5			1	4-0-0
Rim Board							
Label	Description	Width	Depth	Qty	Plies	Pcs	Length
R1	Norbord Rimboard Plus 1.125 X 9.5	1.125	9.5			17	12
Blocking							
Label	Description	Width	Depth	Qty	Plies	Pcs	Length
BLK1	NJH	2.5	9.5	LinFt		Varies	5-0-0
Hanger							
				Beam/Girder		Supported Member	
Label	Pcs	Description	Skew	Slope	fasteners	fasteners	
H2	21	LT259			4 10dx1 1/2	2 10dx1 1/2	
H4	1	HGUS410			46 16d	16 16d	

NOTES:

1. Framer to verify dimensions on the architectural drawings.
2. Double joist only require filler/backer ply when supporting another member using a face-mounted hanger.
3. Install 2x4 blocking @ 24" o/c under parallel non-load bearing walls.
4. Install single-ply flush window header along inside face of rimboard/rimjoist.
5. Refer to Nascor specifier guide for installation works.
6. Squash blocks recommended to be installed at end bearing on all first level joists which support loading from above exceeding two levels floor or roof.
7. Load transfer blocks to be installed under all point loads.
8. It shall be the framer's responsibility that floor joists and beams are fastened as per the hanger manufacturer's standards.

Refer to Multiple Member Connection Detail to ply to ply nailing or bolting requirements.

Rim parallel to joists: 1-1/8" rimboard with 2"x 4" block (1/16" longer than rim depth @ 16" o/c). All other components and structural elements supporting the floor system such as beams, walls, columns, and foundation walls and footings including anchorage of components and bracing for lateral stability are the responsibility of Others.

Hatch area represents ceramic tiled floor with an additional dead load of 5 PSF

The framing shown on this layout may deviate from the architectural and structural drawings. Project Engineer to review and approve the deviation prior to construction.

ARCHITECTURAL DRAWINGS:

JARDIN DESIGN GROUP INC.
64 Jardin Dr., Suite 3A, Vaughan, ON
Date: Rev.1; May 22,2018
Project No: 17-55
Model: Liana 2

Layout Name
LIANA 2 (ELEV.1)

Design Method
LSD

Description
GRANELLI HOMES CORP.
BRAMPTON, ONT.

Created
May 29, 2018

Builder
GREEN YORK HOMES

Sales Rep
RM

Designer
RCO

Shipping
Project

Builder's Project
Kott Lumber Company
14 Anderson Blvd
Stouffville, Ontario
Canada
L4A 7X4
905-642-4400

Job Path
D:\Users\rochavillo\WORK FROM HOME\GREEN YORK HOMES\GRANELLI HOME CORP\MODELS\LIANA 2\LIANA 2 ELEV 1\FLOOR

Second Floor

Design Method
LSD

Building Code
NBCC 2010 / OBC 2012

Floor

Loads

Live	40
Dead	15

Deflection Joist

LL Span L/	480
TL Span L/	360
LL Cant 2L/	480
TL Cant 2L/	360

Deflection Girder

LL Span L/	360
TL Span L/	240
LL Cant 2L/	480
TL Cant 2L/	360

Decking

Deck
OSB


Thickness
5/8"

Fastener
Nailed & Glued

Vibration

Ceiling:
Gypsum 1/2"






Client: GREEN YORK HOMES
 Project:
 Address:

Date: 5/31/2018
 Designer: RCO
 Job Name: LIANA 2 (ELEV.1)
 Project #:

BBO4-A Forex 2.0E-3000Fb LVL 1.750" X 9.500" 2-Ply - PASSED

Level: Second Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	2	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	1378	565	0	0
2	1362	559	0	0

Bearings and Factored Reactions

Bearing	Length	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	5.500"	23%	706 / 2068	2774	L	1.25D+1.5L
2 - SPF	5.500"	23%	699 / 2043	2742	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	7560 ft-lb	5'11 5/8"	22724 ft-lb	0.333 (33%)	1.25D+1.5L	L
Unbraced	7560 ft-lb	5'11 5/8"	20280 ft-lb	0.373 (37%)	1.25D+1.5L	L
Shear	2345 lb	1'2 1/4"	9277 lb	0.253 (25%)	1.25D+1.5L	L
Perm Defl in.	0.074 (L/1812)	5'11 9/16"	0.371 (L/360)	0.200 (20%)	D	Uniform
LL Defl inch	0.180 (L/740)	5'11 9/16"	0.371 (L/360)	0.490 (49%)	L	L
TL Defl inch	0.254 (L/525)	5'11 9/16"	0.556 (L/240)	0.460 (46%)	D+L	L

READ ALL NOTES ON THIS PAGE AND ON ENGINEERING NOTE PAGE ENP-2. THIS NOTE PAGE IS AN INTEGRAL PART OF THIS CALCULATION SUMMARY PAGE AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

REFER TO MULTIPLE MEMBER TO MEMBER CONNECTION DETAIL FOR PLY TO PLY NAILING OR BOLTING REQUIREMENTS.

PASS THRU FRAMING SQUASH BLOCK IS REQUIRED AT ALL POINT LOADS OVER BEARINGS.



Design Notes

- 1 Performed Secondary Bearing Check (CSA 086-14 6.5.7.3). Assumed point load size: beam width X 4.5.
- 2 Girders are designed to be supported on the bottom edge only.
- 3 Multiple plies must be fastened together as per manufacturer's details.
- 4 Top loads must be supported equally by all plies.
- 5 Top braced at bearings.
- 6 Bottom braced at bearings.
- 7 Lateral slenderness ratio based on full section width.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Point	0-2-10		Top	52 lb	138 lb	0 lb	0 lb	J5
2	Part. Uniform	0-10-10 to 11-6-10		Top	92 PLF	244 PLF	0 PLF	0 PLF	
	Self Weight				8 PLF				

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive chemicals

chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding


Manufacturer Info

Forex
 APA: PR-L318





Kott Lumber Company
 14 Anderson Blvd, Ontario
 Canada
 L4A 7X4
 905-642-4400



 EWP Studio Simpson Strong-Tie® Component Solutions™	Client: GREEN YORK HOMES	Date: 5/31/2018
	Project:	Designer: RCO
	Address:	Job Name: LIANA 2 (ELEV.1)
		Project #:

F10-A Forex 2.0E-3000Fb LVL 1.750" X 9.500" 2-Ply - PASSED Level: Second Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	2	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	1315	519	0	0
2	1964	809	0	0

Bearings and Factored Reactions

Bearing	Length	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	5.500"	22%	649 / 1973	2622	L	1.25D+1.5L
2 - SPF	5.500"	33%	1012 / 2947	3959	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	3183 ft-lb	3' 9/16"	22724 ft-lb	0.140 (14%)	1.25D+1.5L	L
Unbraced	3183 ft-lb	3' 9/16"	22724 ft-lb	0.140 (14%)	1.25D+1.5L	L
Shear	3768 lb	4' 3/4"	9277 lb	0.406 (41%)	1.25D+1.5L	L
Perm Defl in.	0.007 (L/7855)	2'10 1/8"	0.160 (L/360)	0.050 (5%)	D	Uniform
LL Defl inch	0.019 (L/3082)	2'10 1/8"	0.160 (L/360)	0.120 (12%)	L	
TL Defl inch	0.026 (L/2214)	2'10 1/8"	0.240 (L/240)	0.110 (11%)	D+L	L

READ ALL NOTES ON THIS PAGE AND ON ENGINEERING NOTE PAGE ENP-2. THIS NOTE PAGE IS AN INTEGRAL PART OF THIS CALCULATION SUMMARY PAGE AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

REFER TO MULTIPLE MEMBER TO MEMBER CONNECTION DETAIL FOR PLY TO PLY NAILING OR BOLTING REQUIREMENTS.

PASS THRU FRAMING SQUASH BLOCK IS REQUIRED AT ALL POINT LOADS OVER BEARINGS.



Design Notes

- Girders are designed to be supported on the bottom edge only.
- Multiple plies must be fastened together as per manufacturer's details.
- Top loads must be supported equally by all plies.
- Top braced at bearings.
- Bottom braced at bearings.
- Lateral slenderness ratio based on full section width.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Part. Uniform	0-5-1 to 5-5-1		Far Face	104 PLF	276 PLF	0 PLF	0 PLF	
2	Point	0-11-1		Near Face	112 lb	292 lb	0 lb	0 lb	J5
3	Point	1-11-1		Near Face	105 lb	281 lb	0 lb	0 lb	J5
4	Point	3-0-9		Near Face	123 lb	327 lb	0 lb	0 lb	J5
5	Point	4-4-9		Near Face	100 lb	268 lb	0 lb	0 lb	J5
6	Point	5-0-12		Near Face	319 lb	713 lb	0 lb	0 lb	F4

Continued on page 2...

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

- Dry service conditions, unless noted otherwise
- LVL not to be treated with fire retardant or corrosive chemicals

chemicals

Handling & Installation

- LVL beams must not be cut or drilled
- Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
- Damaged Beams must not be used
- Design assumes top edge is laterally restrained
- Provide lateral support at bearing points to avoid lateral displacement and rotation

- For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318



Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400





EWP Studio
Simpson Strong-Tie®
Component Solutions™



Client: GREEN YORK HOMES
Project:
Address:

Date: 5/31/2018
Designer: RCO
Job Name: LIANA 2 (ELEV.1)
Project #:

Page 2 of 2

F10-A Forex 2.0E-3000Fb LVL 1.750" X 9.500" 2-Ply - PASSED

Level: Second Floor



...Continued from page 1

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
7	Tie-In	5-2-8 to 5-7-0	(Span)2-6-3	Top	15 PSF	40 PSF	0 PSF	0 PSF	
	Self Weight				8 PLF				

**REFER TO MULTIPLE MEMBER TO MEMBER
CONNECTION DETAIL FOR PLY TO PLY
NAILING OR BOLTING REQUIREMENTS.**

**PASS THRU FRAMING SQUASH
BLOCK IS REQUIRED AT ALL
POINT LOADS OVER BEARINGS.**

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318



Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400






EWP Studio
Simpson Strong-Tie®
Component Solutions™

Client: GREEN YORK HOMES
Project:
Address:

Date: 5/31/2018
Designer: RCO
Job Name: LIANA 2 (ELEV.1)
Project #:

F4-A Forex 2.0E-3000Fb LVL 1.750" X 9.500" 2-Ply - PASSED

Level: Second Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	2	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	1567	722	0	0
2	1790	804	0	0

Bearings and Factored Reactions

Bearing	Length	Cap. React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	2.375"	64%	902 / 2351	3253 L	1.25D+1.5L
2 - SPF	9.714"	18%	1005 / 2685	3690 L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	9822 ft-lb	6'	22724 ft-lb	0.432 (43%)	1.25D+1.5L	L
Unbraced	9822 ft-lb	6'	20006 ft-lb	0.491 (49%)	1.25D+1.5L	L
Shear	3223 lb	11 1/8"	9277 lb	0.347 (35%)	1.25D+1.5L	L
Perm Defl in.	0.115 (L/1224)	6' 1/16"	0.391 (L/360)	0.290 (29%)	D	Uniform
LL Defl inch	0.251 (L/561)	6'	0.391 (L/360)	0.640 (64%)	L	L
TL Defl inch	0.366 (L/385)	6' 1/16"	0.587 (L/240)	0.620 (62%)	D+L	L

READ ALL NOTES ON THIS PAGE AND ON ENGINEERING NOTE PAGE ENP-2. THIS NOTE PAGE IS AN INTEGRAL PART OF THIS CALCULATION SUMMARY PAGE AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

REFER TO MULTIPLE MEMBER TO MEMBER CONNECTION DETAIL FOR PLY TO PLY NAILING OR BOLTING REQUIREMENTS.

PASS THRU FRAMING SQUASH BLOCK IS REQUIRED AT ALL POINT LOADS OVER BEARINGS.



Design Notes

- Girders are designed to be supported on the bottom edge only.
- Multiple plies must be fastened together as per manufacturer's details.
- Top loads must be supported equally by all plies.
- Top braced at bearings.
- Bottom braced at bearings.
- Lateral slenderness ratio based on full section width.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 11-7-2	(Span)0-6-7	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Part. Uniform	0-2-7 to 11-1-5		Top	1 PLF	0 PLF	0 PLF	0 PLF	
3	Point	0-8-15		Far Face	104 lb	238 lb	0 lb	0 lb	J5
4	Part. Uniform	1-2-15 to 9-2-15		Far Face	114 PLF	266 PLF	0 PLF	0 PLF	
5	Point	9-8-15		Far Face	128 lb	294 lb	0 lb	0 lb	J5
6	Point	10-11-7		Far Face	123 lb	292 lb	0 lb	0 lb	J5

Continued on page 2...

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

- Dry service conditions, unless noted otherwise
- LVL not to be treated with fire retardant or corrosive

chemicals

Handling & Installation

- LVL beams must not be cut or drilled
- Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
- Damaged Beams must not be used
- Design assumes top edge is laterally restrained
- Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318



Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400





EWP Studio
Simpson Strong-Tie®
Component Solutions™


Client: GREEN YORK HOMES
Project:
Address:

Date: 5/31/2018
Designer: RCO
Job Name: LIANA 2 (ELEV.1)
Project #:

Page 2 of 2

F4-A Forex 2.0E-3000Fb LVL 1.750" X 9.500" 2-Ply - PASSED

Level: Second Floor



...Continued from page 1

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
7	Point	11-11-7		Far Face	105 lb	281 lb	0 lb	0 lb	J5
	Self Weight				8 PLF				

REFER TO MULTIPLE MEMBER TO MEMBER
CONNECTION DETAIL FOR PLY TO PLY
NAILING OR BOLTING REQUIREMENTS.

PASS THRU FRAMING SQUASH
BLOCK IS REQUIRED AT ALL
POINT LOADS OVER BEARINGS.

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318




Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400



F4-B Forex 2.0E-3000Fb LVL 1.750" X 9.500" 2-Ply - PASSED

Level: Second Floor

**Member Information**

Type:	Girder	Application:	Floor (Residential)
Plies:	2	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	713	319	0	0
2	357	186	0	0

Bearings and Factored Reactions

Bearing	Length	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - Hanger	4.000"	14%	398 / 1070	1468	L	1.25D+1.5L
2 - SPF	5.500"	6%	233 / 535	768	L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	4658 ft-lb	5' 1/8"	22724 ft-lb	0.205 (20%)	1.25D+1.5L	L
Unbraced	4658 ft-lb	5' 1/8"	19429 ft-lb	0.240 (24%)	1.25D+1.5L	L
Shear	1393 lb	1' 3/4"	9277 lb	0.150 (15%)	1.25D+1.5L	L
Perm Defl in.	0.058 (L/2674)	6'2 5/8"	0.431 (L/360)	0.130 (13%)	D	Uniform
LL Defl inch	0.128 (L/1212)	6'1 5/16"	0.431 (L/360)	0.300 (30%)	L	
TL Defl inch	0.186 (L/834)	6'1 3/4"	0.646 (L/240)	0.290 (29%)	D+L	L

READ ALL NOTES ON THIS PAGE AND ON ENGINEERING NOTE PAGE ENP-2. THIS NOTE PAGE IS AN INTEGRAL PART OF THIS CALCULATION SUMMARY PAGE AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

REFER TO MULTIPLE MEMBER TO MEMBER CONNECTION DETAIL FOR PLY TO PLY NAILING OR BOLTING REQUIREMENTS.

PASS THRU FRAMING SQUASH BLOCK IS REQUIRED AT ALL POINT LOADS OVER BEARINGS.

**Design Notes**

- 1 Fill all hanger nailing holes.
- 2 Girders are designed to be supported on the bottom edge only.
- 3 Multiple plies must be fastened together as per manufacturer's details.
- 4 Top loads must be supported equally by all plies.
- 5 Top braced at bearings.
- 6 Bottom braced at bearings.
- 7 Lateral slenderness ratio based on full section width.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 2-3-14	(Span)0-10-5	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Tie-In	0-0-0 to 13-2-12	(Span)0-8-3	Top	15 PSF	40 PSF	0 PSF	0 PSF	
3	Part. Uniform	2-5-7 to 5-11-7		Top	90 PLF	240 PLF	0 PLF	0 PLF	
4	Tie-In	13-2-10 to 13-7-0	(Span)0-10-5	Top	15 PSF	40 PSF	0 PSF	0 PSF	
5	Tie-In	13-2-12 to 13-7-0	(Span)0-5-11	Top	15 PSF	40 PSF	0 PSF	0 PSF	
	Self Weight				8 PLF				

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive chemicals

chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318



Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400





EWP Studio
Simpson Strong-Tie®
Component Solutions™



Client: GREEN YORK HOMES
Project:
Address:

Date: 5/31/2018
Designer: RCO
Job Name: LIANA 2 (ELEV.1)
Project #:

Page 1 of 2

F9-A Forex 2.0E-3000Fb LVL 1.750" X 9.500" - PASSED

Level: Second Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	283	457	566	0
2	20	43	0	0

Bearings and Factored Reactions

Bearing	Length	Cap. React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	5.250"	37%	571 / 991	1561 L	1.25D+1.5S +0.5L
2 - SPF	4.125"	2%	53 / 29	83 L	1.25D+1.5L

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	10 ft-lb	9 5/8"	7385 ft-lb	0.001 (0%)	1.4D	Uniform
Unbraced	10 ft-lb	9 5/8"	7385 ft-lb	0.001 (0%)	1.4D	Uniform
Shear	40 lb	5 1/4"	3015 lb	0.013 (1%)	1.4D	Uniform
Perm Defl in.	0.000 (L/999)	0	999.000 (L/0)	0.000 (0%)		
LL Defl inch	0.000 (L/999)	0	999.000 (L/0)	0.000 (0%)		
TL Defl inch	0.000 (L/999)	0	999.000 (L/0)	0.000 (0%)		

Design Notes

- 1 Performed Secondary Bearing Check (CSA 086-14 6.5.7.3). Assumed point load size: beam width X 4.5.
- 2 Girders are designed to be supported on the bottom edge only.
- 3 Top braced at bearings.
- 4 Bottom braced at bearings.

READ ALL NOTES ON THIS PAGE AND ON ENGINEERING NOTE PAGE ENP-2. THIS NOTE PAGE IS AN INTEGRAL PART OF THIS CALCULATION SUMMARY PAGE AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

REFER TO MULTIPLE MEMBER TO MEMBER CONNECTION DETAIL FOR PLY TO PLY NAILING OR BOLTING REQUIREMENTS.

PASS THRU FRAMING SQUASH BLOCK IS REQUIRED AT ALL POINT LOADS OVER BEARINGS.



ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 0-4-2	(Span)1-3-7	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Point	0-3-8		Top	10 lb	0 lb	23 lb	0 lb	
3	Point	0-3-8		Top	18 lb	0 lb	0 lb	0 lb	Wall Self Weight
4	Point	0-3-8		Top	386 lb	262 lb	537 lb	0 lb	F12 F12
5	Point	0-3-8		Top	2 lb	0 lb	6 lb	0 lb	
6	Point	0-3-8		Top	6 lb	0 lb	0 lb	0 lb	Wall Self Weight
7	Tie-In	0-4-2 to 1-6-2	(Span)1-4-9	Top	15 PSF	40 PSF	0 PSF	0 PSF	

Continued on page 2...

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318





Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400



F9-A Forex 2.0E-3000Fb LVL 1.750" X 9.500" - PASSED

Level: Second Floor



...Continued from page 1

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
8	Part. Uniform	0-5-4 to 1-3-12		Top	64 PLF	0 PLF	0 PLF	0 PLF	Wall Self Weight
	Self Weight				4 PLF				

REFER TO MULTIPLE MEMBER TO MEMBER
CONNECTION DETAIL FOR PLY TO PLY
NAILING OR BOLTING REQUIREMENTS.

PASS THRU FRAMING SQUASH
BLOCK IS REQUIRED AT ALL
POINT LOADS OVER BEARINGS.

Notes

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info


Forex
APA: PR-L318



Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400



Second Floor



THIS CERTIFICATION IS TO CONFIRM THAT:

1. THE LOADS USED IN THE CALCULATION OF THE ATTACHED APPROVED COMPONENTS CONFORM TO THE FLOOR ASSEMBLY SHOWN ON THIS LAYOUT.

2. THE FLOOR JOISTS COMPLY WITH THE NASCOR SPAN TABLE FOR THE LOADS AND SPACING SHOWN ON THIS LAYOUT.

THE FLOOR SYSTEM MUST BE ASSEMBLED IN ACCORDANCE TO THE NASCOR SPECIFIER GUIDE. MULTI-PLY MEMBERS MUST BE ATTACHED TOGETHER AS PER THE INCLUDED MULTIPLE MEMBER CONNECTION DETAIL.

ALL OTHER COMPONENTS AND STRUCTURAL ELEMENTS SUPPORTING THE FLOOR SYSTEM SUCH AS BEAMS, WALLS, COLUMNS AND FOUNDATION WALLS AND FOOTINGS INCLUDING ANCHORAGE OF COMPONENTS AND BRACING FOR LATERAL STABILITY ARE THE RESPONSIBILITY OF OTHERS.

READ ALL NOTES ON THIS PAGE AND ON ENGINEERING NOTE PAGE ENP-2. THIS NOTE PAGE IS AN INTEGRAL PART OF THIS CALCULATION SUMMARY PAGE AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

REFER TO MULTIPLE MEMBER TO MEMBER CONNECTION DETAIL FOR PLY TO PLY NAILING OR BOLTING REQUIREMENTS.

PASS THRU FRAMING SQUASH BLOCK IS REQUIRED AT ALL POINT LOADS OVER BEARINGS.

Legend

Load from Above

Wall

Norbord Rimboard Plus 1.125 X 9.5

NJH 9.5

Forex 2.0E-3000Fb LVL 1.75 X 9.5 (Dropped)

Forex 2.0E-3000Fb LVL 1.75 X 9.5

1. OBC 2012 O.Reg 332/12 as amended

2. Nascor CCMC - 13535-R

3. LVL CCMC -14056-R

4. CAN/CSA-O86-09

5. CCMC -12787-R APA PR-L310(C)

LICENSED PROFESSIONAL ENGINEER
N.A. EL-MASRI
PROVINCE OF ONTARIO
Jun 04, 2018
NE0618-021

Second Floor
LVL/LSL (Flush)

Label	Description	Width	Depth	Qty	Plies	Pcs	Length
F4	Forex 2.0E-3000Fb LVL	1.75	9.5	2	2	4	14-0-0
F10	Forex 2.0E-3000Fb LVL	1.75	9.5	1	2	2	6-0-0
F9	Forex 2.0E-3000Fb LVL	1.75	9.5			2	2-0-0

LVL/LSL (Dropped)

Label	Description	Width	Depth	Qty	Plies	Pcs	Length
BBO4	Forex 2.0E-3000Fb LVL	1.75	9.5	1	2	2	12-0-0

I Joist (Flush)

Label	Description	Width	Depth	Qty	Plies	Pcs	Length
J6	NJH	2.5	9.5			5	16-0-0
J5	NJH	2.5	9.5			50	14-0-0
J4	NJH	2.5	9.5			18	12-0-0
J1	NJH	2.5	9.5			1	4-0-0

Rim Board

Label	Description	Width	Depth	Qty	Plies	Pcs	Length
R1	Norbord Rimboard Plus 1.125 X 9.5	1.125	9.5			17	12

Blocking

Label	Description	Width	Depth	Qty	Plies	Pcs	Length
BLK1	NJH	2.5	9.5	LinFt		Varies	7-0-0

Hanger

Label	Pcs	Description	Skew	Slope	fasteners	Supported Member
H2	21	LT259			4 10dx1 1/2	2 10dx1 1/2
H4	1	HGUS410			46 16d	16 16d

NOTES:

1. Framers to verify dimensions on the architectural drawings.

2. Double joist only require filler/backer ply when supporting another member using a face-mounted hanger.

3. Install 2x4 blocking @ 24" o/c under parallel non-load bearing walls.

4. Install single-ply flush window header along inside face of rimboard/rimjoist.

5. Refer to Nascor specifier guide for installation works.

6. Squash blocks recommended to be installed at end bearing on all first level joists which support loading from above exceeding two levels floor or roof.

7. Load transfer blocks to be installed under all point loads.

8. It shall be the framer's responsibility that floor joists and beams are fastened as per the hanger manufacturer's standards.

Refer to Multiple Member Connection Detail to ply to ply nailing or bolting requirements.

Rim parallel to joists: 1-1/8" rimboard with 2"x 4" block (1/16" longer than rim depth @ 16" o/c). All other components and structural elements supporting the floor system such as beams, walls, columns, and foundation walls and footings including anchorage of components and bracing for lateral stability are the responsibility of Others.

Hatch area represents ceramic tiled floor with an additional dead load of 5 PSF

The framing shown on this layout may deviate from the architectural and structural drawings. Project Engineer to review and approve the deviation prior to construction.

ARCHITECTURAL DRAWINGS:

JARDIN DESIGN GROUP INC.
64 Jardin Dr., Suite 3A, Vaughan, ON
Date: Rev.1; May 22,2018
Project No: 17-55
Model: Liana 2

NASCOR

Layout Name
LIANA 2 (ELEV.2)

Design Method
LSD

Description
GRANELLI HOMES CORP.
BRAMPTON, ONT.

Created
May 29, 2018

Builder
GREEN YORK HOMES

Sales Rep
RM

Designer
RCO

Shipping

Project

Builder's Project

Kott Lumber Company

14 Anderson Blvd
Stouffville, Ontario
Canada
L4A 7X4
905-642-4400

Job Path
D:\Users\rochavillo\WORK FROM HOME\GREEN YORK HOMES \GRANELLI HOME CORP\MODELS \LIANA 2\LIANA 2 ELEV 2\FLOOR

Second Floor

Design Method
LSD

Building Code
NBCC 2010 / OBC 2012

Floor

Loads

Live
40

Dead
15

Deflection Joist

LL Span L/
480

TL Span L/
360

LL Cant 2L/
480

TL Cant 2L/
360

Deflection Girder

LL Span L/
360

TL Span L/
240

LL Cant 2L/
480

TL Cant 2L/
360

Decking

Deck
OSB

Thickness
5/8"

Fastener
Nailed & Glued

Vibration

Ceiling:
Gypsum 1/2"

EWP Studio
Simpson Strong-Tie®
Component Solutions™

EWP Studio Version 18.32.085 Powered by iStruct™

This layout is to be used as an installation guide only. It is meant to be used in conjunction with the architectural and structural drawings, not to replace them

SIMPSON
Strong-Tie



EWP Studio
Simpson Strong-Tie®
Component Solutions™



Client: GREEN YORK HOMES
Project:
Address:

Date: 5/31/2018
Designer: RCO
Job Name: LIANA 2 (ELEV.2)
Project #:

Page 1 of 1

F9-A Forex 2.0E-3000Fb LVL 1.750" X 9.500" - PASSED

Level: Second Floor



Member Information

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	184	324	365	0
2	31	90	19	0

Bearings and Factored Reactions

Bearing	Length	Cap. React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	2.625"	41%	406 / 639	1045 L	1.25D+1.5S +0.5L
2 - SPF	4.125"	4%	126 / 0	126 Uniform	1.4D

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	35 ft-lb	11 1/16"	7385 ft-lb	0.005 (0%)	1.4D	Uniform
Unbraced	35 ft-lb	11 1/16"	7285 ft-lb	0.005 (0%)	1.4D	Uniform
Shear	8 lb	10 5/8"	4638 lb	0.002 (0%)	1.25D+1.5S L +0.5L	
Perm Defl in.	0.000 (L/999)	0	999.000 (L/0)	0.000 (0%)		
LL Defl inch	0.000 (L/999)	0	999.000 (L/0)	0.000 (0%)		
TL Defl inch	0.000 (L/999)	0	999.000 (L/0)	0.000 (0%)		

READ ALL NOTES ON THIS PAGE AND ON ENGINEERING NOTE PAGE ENP-2. THIS NOTE PAGE IS AN INTEGRAL PART OF THIS CALCULATION SUMMARY PAGE AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

REFER TO MULTIPLE MEMBER TO MEMBER CONNECTION DETAIL FOR PLY TO PLY NAILING OR BOLTING REQUIREMENTS.

PASS THRU FRAMING SQUASH BLOCK IS REQUIRED AT ALL POINT LOADS OVER BEARINGS.



Design Notes

- 1 Performed Secondary Bearing Check (CSA 086-14 6.5.7.3). Assumed point load size: beam width X 4.5.
- 2 Girders are designed to be supported on the bottom edge only.
- 3 Bottom braced at bearings.
- 4 Bottom braced at bearings.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 1-11-8	(Span)1-5-11	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Part. Uniform	0-0-0 to 1-11-8		Top	64 PLF	0 PLF	0 PLF	0 PLF	Wall Self Weight
3	Point	0-0-14		Top	248 lb	157 lb	355 lb	0 lb	F11 F11
4	Part. Uniform	0-6-10 to 1-9-2		Top	10 PLF	0 PLF	24 PLF	0 PLF	
	Self Weight				4 PLF				

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318





Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400



F9-B Forex 2.0E-3000Fb LVL 1.750" X 9.500" - PASSED

Level: Second Floor

**Member Information**

Type:	Girder	Application:	Floor (Residential)
Plies:	1	Design Method:	LSD
Moisture Condition:	Dry	Building Code:	NBCC 2010 / OBC 2012
Deflection LL:	360	Load Sharing:	No
Deflection TL:	240	Deck:	Not Checked
Importance:	Normal	Vibration:	Not Checked
General Load			
Floor Live:	40 PSF		
Dead:	15 PSF		

Unfactored Reactions UNPATTERNED lb (Uplift)

Brg	Live	Dead	Snow	Wind
1	173	318	370	0
2	18	73	19	0

Bearings and Factored Reactions

Bearing	Length	Cap. React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	2.625"	41%	398 / 642	1040 L	1.25D+1.5S +0.5L
2 - SPF	4.125"	4%	102 / 0	102 Uniform	1.4D

Analysis Results

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	34 ft-lb	11 1/16"	7385 ft-lb	0.005 (0%)	1.4D	Uniform
Unbraced	34 ft-lb	11 1/16"	7285 ft-lb	0.005 (0%)	1.4D	Uniform
Shear	7 lb	10 5/8"	4638 lb	0.002 (0%)	1.25D+1.5S L +0.5L	
Perm Defl in.	0.000 (L/999)	0	999.000 (L/0)	0.000 (0%)		
LL Defl inch	0.000 (L/999)	0	999.000 (L/0)	0.000 (0%)		
TL Defl inch	0.000 (L/999)	0	999.000 (L/0)	0.000 (0%)		

READ ALL NOTES ON THIS PAGE AND ON ENGINEERING NOTE PAGE ENP-2. THIS NOTE PAGE IS AN INTEGRAL PART OF THIS CALCULATION SUMMARY PAGE AS IT CONTAINS SPECIFICATIONS AND CRITERIA USED IN THE DESIGN OF THIS COMPONENT.

REFER TO MULTIPLE MEMBER TO MEMBER CONNECTION DETAIL FOR PLY TO PLY NAILING OR BOLTING REQUIREMENTS.

PASS THRU FRAMING SQUASH BLOCK IS REQUIRED AT ALL POINT LOADS OVER BEARINGS.

**Design Notes**

- 1 Performed Secondary Bearing Check (CSA 086-14 6.5.7.3). Assumed point load size: beam width X 4.5.
- 2 Girders are designed to be supported on the bottom edge only.
- 3 Top braced at bearings.
- 4 Bottom braced at bearings.

ID	Load Type	Location	Trib Width	Side	Dead	Live	Snow	Wind	Comments
1	Tie-In	0-0-0 to 1-11-8	(Span)0-10-9	Top	15 PSF	40 PSF	0 PSF	0 PSF	
2	Point	0-0-14		Top	250 lb	157 lb	360 lb	0 lb	F11 F11
3	Point	0-0-14		Top	5 lb	0 lb	0 lb	0 lb	Wall Self Weight
4	Point	0-0-14		Top	5 lb	0 lb	0 lb	0 lb	Wall Self Weight
5	Part. Uniform	0-2-10 to 1-9-2		Top	64 PLF	0 PLF	0 PLF	0 PLF	Wall Self Weight
6	Part. Uniform	0-6-10 to 1-9-2		Top	10 PLF	0 PLF	24 PLF	0 PLF	
	Self Weight				4 PLF				

Notes

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

Manufacturer Info

Forex
APA: PR-L318



Kott Lumber Company
14 Anderson Blvd, Ontario
Canada
L4A 7X4
905-642-4400

