HEATHWOOD

01-Sep-21

PRE-Sales Selection Sheet
CHECKLIST

7 OF 41 CU

LOT	004-4	* REVISED *	20-2212 ELEV A THE ROSLYN
PURCHASERS:	HEMA BHARATBHAI SHAH ZUBIN MUKESHBHAI MISTRY	CONTACT NO: 647-870-7843	
VENDOR:	**HEATHWOOD HOMES (UPCOUNTRY) LIMITED**		

DO NOT SUPPLY OR INSTALL PLANK AND POLE IN ANY CLOSETS THROUGHOUT *

DO NOT SUPPLY OR INSTALL SHELVING IN WALK IN KITCHEN PANTRY *

- ☐ **FINISHED BASEMENT**
- ☐ **COLD CELLAR**

UPGRADED / MODIFIED ELEVATION

- ☐ **CORNER UPGRADE**
- ☐ **SIDE UPGRADE**
- ☐ **REAR UPGRADE**
- ☐ **WALK OUT DECK**
- ☐ **WALK OUT BASEMENT**

CEILING UPGRADE - SMOOTH

- ☐ **MAIN FLOOR**
- ☐ **SECOND FLOOR**
- ☐ **BASEMENT**

ADDITIONAL ROUGH-INS

- ☑ **200 AMP SERVICE**
- ☐ **WET BAR ROUGH IN**
- ☐ **HUMIDIFIER**
- ☑ **AIRCON**

GAS ROUGH-IN

- ☑ **STOVE** *
- ☐ **BBQ**
- ☐ **DRYER**
- ☐ **ADDITIONAL FIREPLACE**

HOODFAN VENTING

- ☑ **6" ROUND DUCT** *
- ☐ **7" ROUND DUCT**

FULL BASEMENT STAIRS:	PAINT GRADE
UPPER BASEMENT STAIRS:	N/A
LOWER BASEMENT STAIRS:	N/A
STAIRS TO LOWER LEVEL:	ALL OAK
STAIRS TO UPPER LEVEL:	N/A
MAIN STAIRS:	ALL OAK
MEDIA STAIRS (if applicable):	N/A

SEPT 1/21	Signatures on file	SEPT 1/21	IRIT SALEM
Date	**Purchaser**	**Date**	**Décor Consultant**
		- APPROVED -	
Date	**Purchaser**		
		Date Approved	**HEATHWOOD HOMES (UPCOUNTRY) LIMITED**

HEATHWOOD

Interior Finishing Selection Sheet

8 of 11

17-Aug-21

LOT 004-4 — 20-2212 ELEV A THE ROSLYN

PURCHASERS: HEMA BHARATBHAI SHAH — CONTACT NO: 647-870-7843
ZUBIN MUKESHBHAI MISTRY

VENDOR: **HEATHWOOD HOMES (UPCOUNTRY) LIMITED**

		UPG
Appliances		
6-9117	Kitchen HoodFan	☐ CYCLONE 30" STAINLESS CHIMNEY/CANOPY HOODFAN STAINLESS STEEL SCB51930 UPG 30" PAGE 27
Cabinetry		
1-9158	Kitchen Cabinet Colour/Style	☐ SIMCOE NAVY BLUE Viking III STD 3DL
3-2098	Kitchen Cabinet Hardware	☐ HARDWARE 12801 STD
25-9158	Main Bathroom Cabinet Colour/Style	☐ SIMCOE NAVY BLUE Viking III STD 3DL
29-2098	Main Bathroom Cabinet Hardware	☐ HARDWARE 12801 STD
28-8827	Main Bathroom Countertop	☐ Countertop CALCUTTA MARBLE 4925K-07 Wilsonart
20-9158	Master Ensuite Cabinet Colour/Style	☐ SIMCOE NAVY BLUE Viking III STD 3DL
22-2098	Master Ensuite Cabinet Hardware	☐ HARDWARE 12801 STD
21-8827	Master Ensuite Countertop	☐ Countertop CALCUTTA MARBLE 4925K-07 Wilsonart
414-9158	Powder Room Lower Level Cabinet Colour/Style	☐ SIMCOE NAVY BLUE Viking III STD 3DL
416-2098	Powder Room Lower Level Cabinet Hardware	☐ HARDWARE 12801 STD
415-8827	Powder Room Lower Level Countertop	☐ Countertop CALCUTTA MARBLE 4925K-07 Wilsonart
Carpet		
37-9250	Bedroom 2 Flooring	☐ Dynasty Tex 40 oz Poly PROVINCIAL WHITE DY 14253 STD
38-9250	Bedroom 3 Flooring	☐ Dynasty Tex 40 oz Poly PROVINCIAL WHITE DY 14253 STD
14-9250	Family Room Flooring	☐ Dynasty Tex 40 oz Poly PROVINCIAL WHITE DY 14253 STD
36-9250	Master Bedroom Flooring	☐ Dynasty Tex 40 oz Poly PROVINCIAL WHITE DY 14253 STD
52-1079	Throughout Underpad	☐ Underpad 500 Series STD
Ceramics		
16-9255	Foyer Flooring	☐ SEMPRE White Matte TR.SP.WHITE.1313 STD 13" x 13"
17-2225	Foyer Grout	☐ Grout (27) Silver STD

1. The Purchaser acknowledges these selections are subject to the terms and conditions of the applicable Agreement of Purchase and Sale.
2. The Purchaser acknowledges that the Vendor accepts no responsibility in the event the Vendor is unable to supply a selection. The Purchaser agrees to reselect from the currently available selections immediately upon request.
3. The Vendor reserves the right to substitute above materials and equipment with that of equal or better quality.
4. Purchaser acknowledges that items may not be exactly as shown. Variations from the Vendor's samples may occur in finished materials due to normal production processes. Vendor is not responsible for shade difference which may occur from different dye lots or wood grains. Variations from the Vendor's samples will occur with natural materials such as wood, marble, granite, hardwood and brick.
5. The Vendor reserves the right to select Grout & Thresholds that best suits the Tile selected.
6. Selections will not be processed unless signed by Heathwood Homes Head Office.
7. The colour selections made on the Colour Chart are final and cannot be changed once submitted.
8. The Purchaser has checked and acknowledges the accuracy of this Colour Chart.

Aug 17/21		Aug 17 21 — EFFECTIVE	
Date	Purchaser	Date	Décor Consultant
Aug/17/21	Hema	Aug 17/21	
Date	Purchaser	Date Approved	HEATHWOOD HOMES (UPCOUNTRY) LIMITED

HEATHWOOD

Interior Finishing Selection Sheet 9 of 11

17-Aug-21

LOT 004-4 20-2212 ELEV A THE ROSLYN

PURCHASERS: HEMA BHARATBHAI SHAH CONTACT NO: 647-870-7843
ZUBIN MUKESHBHAI MISTRY

VENDOR: **HEATHWOOD HOMES (UPCOUNTRY) LIMITED**

Ceramics

		UPG
4-5721	Kitchen Backsplash	☑ Colour and Dimension Bright Arctic White QT.CD.ARW.0306.BR UPG_1 3 x 6 TO BE INSTALLED IN A BRICK DESIGN
5-2226	Kitchen Backsplash Grout	☐ Grout (00) White STD
7-9255	Kitchen/Breakfast Flooring	☐ SEMPRE White Matte TR.SP.WHITE.1313 STD 13" x 13"
8-2225	Kitchen/Breakfast Grout	☐ Grout (27) Silver STD
66-9255	Laundry Room Flooring	☐ SEMPRE White Matte TR.SP.WHITE.1313 STD 13" x 13"
67-2225	Laundry Room Grout	☐ Grout (27) Silver STD
30-9255	Main Bathroom Flooring	☐ SEMPRE White Matte TR.SP.WHITE.1313 STD 13" x 13"
31-2225	Main Bathroom Grout	☐ Grout (27) Silver STD
27-9020	Main Bathroom Tub Wall Tile	☐ Weave White QT.WV.WHT.0810 STD 8 x 10 TO BE INSTALLED VERTICALLY
26-2226	Main Bathroom Tub Wall Tile Grout	☐ Grout (00) White STD
23-9255	Master Ensuite Floor Tile	☐ SEMPRE White Matte TR.SP.WHITE.1313 STD 13" x 13"
24-2225	Master Ensuite Floor Tile Grout	☐ Grout (27) Silver STD
73-8661	Master Ensuite Shower Floor Tile	☐ Ontario Series Mosaic Snow White Matte OD.ON.SWT.0202.MT.N STD 2 x 2
74-2226	Master Ensuite Shower Floor Tile Grout	☐ Grout (00) White STD
147-8923	Master Ensuite Shower Jamb(s) and Sill(s)	☐ Shower Jamb / Sill Thassos White STD
104-9020	Master Ensuite Shower Wall Tile	☐ Weave White QT.WV.WHT.0810 STD 8 x 10 TO BE INSTALLED VERTICALLY
105-2226	Master Ensuite Shower Wall Tile Grout	☐ Grout (00) White STD
191-9255	Mud Room Flooring	☐ SEMPRE White Matte TR.SP.WHITE.1313 STD 13" x 13"
190-2225	Mud Room Grout	☐ Grout (27) Silver STD
32-9255	Powder Room Flooring	☐ SEMPRE White Matte TR.SP.WHITE.1313 STD 13" x 13"
33-2225	Powder Room Grout	☐ Grout (27) Silver STD

1. The Purchaser acknowledges these selections are subject to the terms and conditions of the applicable Agreement of Purchase and Sale.
2. The Purchaser acknowledges that the Vendor accepts no responsibility in the event the Vendor is unable to supply a selection. The Purchaser agrees to reselect from the currently available selections immediately upon request.
3. The Vendor reserves the right to substitute above materials and equipment with that of equal or better quality.
4. Purchaser acknowledges that items may not be exactly as shown. Variations from the Vendor's samples may occur in finished materials due to normal production processes. Vendor is not responsible for shade difference which may occur from different dye lots or wood grains. Variations from the Vendor's samples will occur with natural materials such as wood, marble, granite, hardwood and brick.
5. The Vendor reserves the right to select Grout & Thresholds that best suits the Tile selected.
6. Selections will not be processed unless signed by Heathwood Homes Head Office.
7. The colour selections made on the Colour Chart are final and cannot be changed once submitted.
8. The Purchaser has checked and acknowledges the accuracy of this Colour Chart.

Aug/17/2021 Date — Purchaser

Aug 17 21 Date — Décor Consultant

Date — Purchaser

Date Approved — HEATHWOOD HOMES (UPCOUNTRY) LIMITED

HEATHWOOD

Interior Finishing Selection Sheet

10 of 14

17-Aug-21

LOT 004-4 20-2212 ELEV A THE ROSLYN

PURCHASERS: HEMA BHARATBHAI SHAH CONTACT NO: 647-870-7843
ZUBIN MUKESHBHAI MISTRY

VENDOR: **HEATHWOOD HOMES (UPCOUNTRY) LIMITED**

		UPG
Ceramics		
369-9255 Powder Room Lower Level Flooring	☐ **SEMPRE White Matte TR.SP.WHITE.1313 STD 13" x 13"**	
370-2225 Powder Room Lower Level Grout	☐ **Grout (27) Silver STD**	
53-2232 Throughout Thresholds	☐ **Metal Thresholds STD**	
Electrical		
90-5796 Throughout Switches and Plug	☐ **Decora White Switches and Plugs STD**	
Fireplace		
136-9114 Great Room Fireplace Mantle	☐ **Paint Grade Mantel- Cabinet (Per Plan) WHITE NF 15 STD**	
135-8865 Great Room Fireplace Type	☑ **Dimplex FP3033HL Electric Fireplace** PAGE 20	
Granite		
2-9069 Kitchen Countertop	☐ **MSI Quartz ICED WHITE Group 1 STD 3/4"**	
Hardwood		
11-9358 Great Room Flooring	☐ **Vintage Pioneered Solid Collection Select V : Red Oak Pearl TITANIUM Red Oak Pearl 3/4" X 3 1/4"**	
367-9358 Lower Level Hall Flooring	☐ **Vintage Pioneered Solid Collection Select V : Red Oak Pearl TITANIUM Red Oak Pearl 3/4" X 3 1/4"**	
100-9059 Main Stairs Landing(s) Flooring	☐ **Red Oak-Vintage 3 1/4 inch Pre-Sanded Smooth Unfinished Red Oak-Unfinished-3/4 inch x 3 1/4inch 3/4" x 3 1/4" STAIN SAMBUCA**	
78-9059 Stair Landing to Lower Level Flooring	☑ **Red Oak-Vintage 3 1/4 inch Pre-Sanded Smooth Unfinished Red Oak-Unfinished-3/4 inch x 3 1/4inch 3/4" x 3 1/4" STAIN SAMBUCA**	
35-9358 Upper Hall Flooring	☐ **Vintage Pioneered Solid Collection Select V : Red Oak Pearl TITANIUM Red Oak Pearl 3/4" X 3 1/4"**	
Interior Railings		
145-7654 Main Stairs Handrail/Pickets/Posts Type	☐ **1 3/4" Square pickets with 3 1/2" Square/Cap Post(s) ALL OAK STD**	
49-7654 Stairs to Lower Level Handrail/Pickets/Posts Type	☐ **1 3/4" Square pickets with 3 1/2" Square/Cap Post(s) ALL OAK STD**	
Interior Stairs		
116-1713 Basement Stairs Type	☐ **Paint Grade Stairs STD**	

1. The Purchaser acknowledges these selections are subject to the terms and conditions of the applicable Agreement of Purchase and Sale.
2. The Purchaser acknowledges that the Vendor accepts no responsibility in the event the Vendor is unable to supply a selection. The Purchaser agrees to reselect from the currently available selections immediately upon request.
3. The Vendor reserves the right to substitute above materials and equipment with that of equal or better quality.
4. Purchaser acknowledges that items may not be exactly as shown. Variations from the Vendor's samples may occur in finished materials due to normal production processes. Vendor is not responsible for shade difference which may occur from different dye lots or wood grains. Variations from the Vendor's samples will occur with natural materials such as wood, marble, granite, hardwood and brick.
5. The Vendor reserves the right to select Grout & Thresholds that best suits the Tile selected.
6. Selections will not be processed unless signed by Heathwood Homes Head Office.
7. The colour selections made on the Colour Chart are final and cannot be changed once submitted.
8. The Purchaser has checked and acknowledges the accuracy of this Colour Chart.

Aug/17/21 — Date — Purchaser

Aug 17 21 — Date — Décor Consultant

Date — Purchaser

Date Approved — HEATHWOOD HOMES (UPCOUNTRY) LIMITED

HEATHWOOD

Interior Finishing Selection Sheet

17-Aug-21

LOT **004-4** 20-2212 ELEV A THE ROSLYN

PURCHASERS: HEMA BHARATBHAI SHAH CONTACT NO: 647-870-7843
ZUBIN MUKESHBHAI MISTRY

VENDOR: **HEATHWOOD HOMES (UPCOUNTRY) LIMITED**

		UPG
Interior Stairs		
142-1712 Main Stairs Type	☐ **Oak Stairs**	**UPG_1**
45-1712 Stairs to Lower Level Type	☐ **Oak Stairs**	**UPG_1**
Interior Trim		
91-9374 Throughout Trim Size	☐ **4 1/4" Baseboards and 2 3/4" Integrated Backbend Casings STD-Towns**	
Painting		
143-1728 Main Stairs Colour	☐ **Stain handrail, pickets, stringers, treads,risers, nosing & posts. STAIN SAMBUCA-COLOR IS DIFFERENT THEN HARDWOOD FLOOR**	
46-1728 Stairs to Lower Level Colour	☐ **Stain handrail, pickets, stringers, treads,risers, nosing & posts. STAIN SAMBUCA-COLOR IS DIFFERENT THEN HARDWOOD FLOOR**	
240-1716 Throughout Trim - Paint Colour	☐ **Trim WHITE STD**	
51-1717 Throughout Walls - Paint Colour	☐ **Wall WARM GREY 22 STD**	
Plumbing		
266-1737 Main Bathroom Plumbing Fixture (Colour)	☐ **Plumbing Fixtures WHITE STD**	
149-1737 Master Ensuite Plumbing Fixture (colour)	☐ **Plumbing Fixtures WHITE STD**	
34-1737 Powder Room Plumbing Fixture (Colour)	☐ **Plumbing Fixtures WHITE STD**	
371-1737 Powder Room Lower Level Plumbing Fixture (Colour)	☐ **Plumbing Fixtures WHITE STD**	

1. The Purchaser acknowledges these selections are subject to the terms and conditions of the applicable Agreement of Purchase and Sale.
2. The Purchaser acknowledges that the Vendor accepts no responsibility in the event the Vendor is unable to supply a selection. The Purchaser agrees to reselect from the currently available selections immediately upon request.
3. The Vendor reserves the right to substitute above materials and equipment with that of equal or better quality.
4. Purchaser acknowledges that items may not be exactly as shown. Variations from the Vendor's samples may occur in finished materials due to normal production processes. Vendor is not responsible for shade difference which may occur from different dye lots or wood grains. Variations from the Vendor's samples will occur with natural materials such as wood, marble, granite, hardwood and brick.
5. The Vendor reserves the right to select Grout & Thresholds that best suits the Tile selected.
6. Selections will not be processed unless signed by Heathwood Homes Head Office.
7. The colour selections made on the Colour Chart are final and cannot be changed once submitted.
8. The Purchaser has checked and acknowledges the accuracy of this Colour Chart.

Aug 17 21 — Date — Purchaser

Aug 17 21 — Date — Décor Consultant

Date — Purchaser

Date Approved — **HEATHWOOD HOMES (UPCOUNTRY) LIMITED**

HEATHWOOD

Sales Selection Sheet

17-Aug-21

LOT **004-4** 20-2212 ELEV A THE ROSLYN

PURCHASERS: HEMA BHARATBHAI SHAH CONTACT NO: 647-870-7843
ZUBIN MUKESHBHAI MISTRY

VENDOR: **HEATHWOOD HOMES (UPCOUNTRY) LIMITED** **HST #**

It is herein understood and agreed between the undersigned parties hereto that the following changes shall be made to the above mentioned Agreement of Purchase and Sale in accordance with the agreement and except for such changes noted below, all other terms and conditions in the Agreement of Purchase and Sale shall remain as stated herein: It is further understood that and agreed that all changes and additions shall be installed as per builder's specifications, location and available selections. The Purchaser hereby agrees to purchase the following extras:

AMOUNT:

Appliances

792 **Cyclone 30" Wall Mount Chimney Hood SS** **KITCHEN** Qty: 1
SCB51930 PAGE 27

Cabinetry

405 **Optional Extras** **KITCHEN** Qty: 2
12B- Pots and pans drawers (width min. 60cm/max. 90cm) (size subject to floor plan) Viking
TO BE ON SIDE OF THE STOVE
SEE SKETCH # 8 PAGE 18

403 **Optional Extras** **KITCHEN** Qty: 10
10B- Upgrade levels 1-4, 5-7 drawers from Metabox to Tandembox per drawer. BD x 4, BPP x 3, BT x 1 (Partial conversions on rooms not allowed, pull-outs must also be converted.) Viking INSTALL 4 TOP DRAWERS IN LIEU OF BANK OF DRAWERS
SEE SKETCH # 8 PAGE 18

470 **Optional Extras** **KITCHEN** Qty: 18
05G- Integreated Blumotion (softclose) hinge for doors
SEE SKETCH # 8 PAGE 18

406 **Optional Extras** **KITCHEN** Qty: 1
19B- 45cm wide pull-out door base cabinet waste/recycle centre with soft-close ([2] 35L bins) (available only with 45cm wide cabinet) Viking 2 TOP DRAWER
SEE SKETCH # 8 PAGE# 18

Ceramics

1. This Sales Selection Sheet when properly executed forms part of our Agreement of Purchase and Sale.
2. All extras and upgrades listed above are subject to Construction Progress and Architectural and Municipal requirements.
3. In the event the Vendor is unable to incorporate the work approved above in the construction of the house for any reason whatsoever, the Vendor will not be liable to the Purchaser in any way. The monies paid for any changes or optional extras not proceeded with shall be returned to the Purchaser, without interest. The cost of options or extras is non-refundable in all other circumstances. If for any reason whatsoever the Agreement of Purchase and Sale is not completed, the total cost of work approved above will be retained by the Vendor.
4. The Vendor reserves the right to substitute above materials and equipment with that of equal or better quality.
5. Purchaser acknowledges that items may not be exactly as shown. Variations from the Vendor's samples may occur in finished materials due to normal production processes. Vendor is not responsible for shade difference which may occur from different dye lots or wood grains. Variations from the Vendor's samples will occur with natural materials such as wood, marble, granite, hardwood and brick.
6. The Vendor reserves the right to select Grout & Thresholds that best suits the Tile selected.
7. Selections will not be processed unless signed by Heathwood Homes Head Office.
8. The selections made on this schedule are final and cannot be changed once submitted.
9. The Purchaser has checked and acknowledges the accuracy of this schedule.

Aug/17/21 Date — Purchaser

Aug 18.21 Date — APPROVED — Décor Consultant

Aug/17/21 Date — Hema Purchaser

Date Approved — **HEATHWOOD HOMES (UPCOUNTRY) LIMITED**

HEATHWOOD

17-Aug-21

Sales Selection Sheet 3 OF 4

LOT **004-4** 20-2212 ELEV A THE ROSLYN

PURCHASERS: HEMA BHARATBHAI SHAH CONTACT NO: 647-870-7843
ZUBIN MUKESHBHAI MISTRY

VENDOR: **HEATHWOOD HOMES (UPCOUNTRY) LIMITED** HST #

It is herein understood and agreed between the undersigned parties hereto that the following changes shall be made to the above mentioned Agreement of Purchase and Sale in accordance with the agreement and except for such changes noted below, all other terms and conditions in the Agreement of Purchase and Sale shall remain as stated herein: It is further understood that and agreed that all changes and additions shall be installed as per builder's specifications, location and available selections. The Purchaser hereby agrees to purchase the following extras:

				AMOUNT:
493	**Optional Extras** Supply and install additional backsplash due to chimney hoodfan installation Upgrade 1	**Kitchen**	Qty: 1	
870	Upgrade 1 Tile	**Kitchen Optional Backsplash**	Qty: 1	

Electrical

286	**Optional Extras** Ceiling rough-in (Capped) USE EXISTING SWITCH PLUG SEE SKETCH # 7 PAGE 17	**GREAT ROOM**	Qty: 1	
284	**Optional Extras** Extra wall interior outlet on Existing Circuit (does not include kitchen outlets) TO BE INSTALLED 70 " FROM FLOOR ABOVE THE FIRE PLACE SEE SKETCH # 7 PAGE 17	**GREAT ROOM**	Qty: 1	
284	**Optional Extras** Extra wall interior outlet on Existing Circuit (does not include kitchen outlets) TO BE INSTALLED 1' +- FROM THE CORNER STD. HIGHT SEE SKETCH # 7 PAGE 17	**MAIN FLOOR HALL**	Qty: 1	

Heating / Air

277	**Optional Extras** ROUGH-IN GAS LINE FOR GAS STOVE AT MAIN FLOOR (See specs) (Hook-up not included)Leave standard 120 volt electrical outlet on a separate circuit. STANDARD 240 V 40AMP TO REMAIN	**KITCHEN**	Qty: 1	

Interior Trim

1. This Sales Selection Sheet when properly executed forms part of our Agreement of Purchase and Sale.
2. All extras and upgrades listed above are subject to Construction Progress and Architectural and Municipal requirements.
3. In the event the Vendor is unable to incorporate the work approved above in the construction of the house for any reason whatsoever, the Vendor will not be liable to the Purchaser in any way. The monies paid for any changes or optional extras not proceeded with shall be returned to the Purchaser, without interest. The cost of options or extras is non-refundable in all other circumstances. If for any reason whatsoever the Agreement of Purchase and Sale is not completed, the total cost of work approved above will be retained by the Vendor.
4. The Vendor reserves the right to substitute above materials and equipment with that of equal or better quality.
5. Purchaser acknowledges that items may not be exactly as shown. Variations from the Vendor's samples may occur in finished materials due to normal production processes. Vendor is not responsible for shade difference which may occur from different dye lots or wood grains. Variations from the Vendor's samples will occur with natural materials such as wood, marble, granite, hardwood and brick.
6. The Vendor reserves the right to select Grout & Thresholds that best suits the Tile selected.
7. Selections will not be processed unless signed by Heathwood Homes Head Office.
8. The selections made on this schedule are final and cannot be changed once submitted.
9. The Purchaser has checked and acknowledges the accuracy of this schedule.

Aug/17/21 Date — Purchaser

Aug 17, 21 Date — Décor Consultant

Aug/17/21 Date — Purchaser

Date Approved — **HEATHWOOD HOMES (UPCOUNTRY) LIMITED**

HEATHWOOD

17-Aug-21

Sales Selection Sheet of

LOT **004-4** 20-2212 ELEV A THE ROSLYN

PURCHASERS: HEMA BHARATBHAI SHAH CONTACT NO: 647-870-7843
ZUBIN MUKESHBHAI MISTRY

VENDOR: **HEATHWOOD HOMES (UPCOUNTRY) LIMITED** **HST #**

It is herein understood and agreed between the undersigned parties hereto that the following changes shall be made to the above mentioned Agreement of Purchase and Sale in accordance with the agreement and except for such changes noted below, all other terms and conditions in the Agreement of Purchase and Sale shall remain as stated herein: It is further understood that and agreed that all changes and additions shall be installed as per builder's specifications, location and available selections. The Purchaser hereby agrees to purchase the following extras:

				AMOUNT:
1200		**ALL CLOSETS AND PANTRY**	Qty: 1	
	Delete Shelving in Walk-in Pantry (Do not supply) DO NOT SUPPLY AND INSTALL ANY SHELVING OR RODS IN ALL CLOSETS AND PANTRY			
Painting				
350	**Optional Extras - PAINT / STAIN - Custom**	**LANDING**	Qty: 2	
	Stain stair landing less than 25sq/ft in sambucca. For stair with metal or oak pickets only. Unfinished Pre-sanded smooth hardwood will be installed and to be stained in sambucca to match the stairs STAIN LANDING SAMBUCA- COLOUR DIFFERENT THEN HARDWOOD FLOOR			
Plumbing				
226	**STANDARD Kitchen Sink Option**	**KITCHEN**	Qty: 1	
	KINDRED Kitchen Sink Collection - Reginox NS1930U/9 Stainless Kitchen Single Bowl Undermount Sink (or equivalent) PAGE 21			

1. This Sales Selection Sheet when properly executed forms part of our Agreement of Purchase and Sale.
2. All extras and upgrades listed above are subject to Construction Progress and Architectural and Municipal requirements.
3. In the event the Vendor is unable to incorporate the work approved above in the construction of the house for any reason whatsoever, the Vendor will not be liable to the Purchaser in any way. The monies paid for any changes or optional extras not proceeded with shall be returned to the Purchaser, without interest. The cost of options or extras is non-refundable in all other circumstances. If for any reason whatsoever the Agreement of Purchase and Sale is not completed, the total cost of work approved above will be retained by the Vendor.
4. The Vendor reserves the right to substitute above materials and equipment with that of equal or better quality.
5. Purchaser acknowledges that items may not be exactly as shown. Variations from the Vendor's samples may occur in finished materials due to normal production processes. Vendor is not responsible for shade difference which may occur from different dye lots or wood grains. Variations from the Vendor's samples will occur with natural materials such as wood, marble, granite, hardwood and brick.
6. The Vendor reserves the right to select Grout & Thresholds that best suits the Tile selected.
7. Selections will not be processed unless signed by Heathwood Homes Head Office.
8. The selections made on this schedule are final and cannot be changed once submitted.
9. The Purchaser has checked and acknowledges the accuracy of this schedule.

Aug/17/21 Hema
Date Purchaser

Aug 17 21 - APPROVED -
Date Décor Consultant

Aug/17/21
Date Purchaser

Date Approved **HEATHWOOD HOMES (UPCOUNTRY) LIMITED**

CU UPCOUNTRY
LOT 4-4
20-2212 ELEV A
THE ROSLYN

15 of 41

The Roslyn

20-2212 ELEV. A

ELEVATION A: 2,212 SQ FT

Sketch #5



BASEMENT
ELEVATION A

Legal Plan: September 17, 2020

CU UPCOUNTRY
LOT 4-4
20-2212 ELEV A
THE ROSLYN

16 of 41

The Roslyn

20-2212 ELEV. A

ELEVATION A: 2,212 SQ FT

Sketch #6



LOWER LEVEL
ELEVATION A

Legal Plan: September 17, 2020

CU UPCOUNTRY
LOT 4-4
20-2212 ELEV A
THE ROSLYN

17 of 41

The Roslyn

20-2212 ELEV. A

ELEVATION A: 2,212 SQ FT

Sketch #7



POT & PAN (H)

±1'-ELECTRICAL PLUG (H)

R/I CAP LIGHT ON EXISTING SWITCH FOR SWITCHED PLUG (H)

ELECTRICAL PLUG 70" +/- FROM FLOOR (H)

MAIN LEVEL
ELEVATION A

Legal Plan: September 17, 2020

CU UPCOUNTRY
LOT 4-4
20-2212 ELEV A
THE ROSLYN





FRENDE KITCHENS LIMITED
1350 Shawson Drive, Mississauga, ON L4W 1C

HEATHWOOD HOMES
COUNTRY LANE, WHITB
MODEL: 20-2212 (2008)

STANDARD CONTRACT INCLUDES:

Appliance Openings
- Hood Opening: 30"W builder hoo
- Fridge Opening: 37 3/8 "W X 73 3
- Fridge cabinet: 30cm deep
- Stove Opening: 30" Freestanding
- Dishwasher Opening: 24"

Standard Kitchens Scope:
- 100cm H wall cabinets
- Std. Blum Hinges- **not soft close**
- Std. Metabox Drawers- **not soft close**
- Min 40cm W drawer
- Backing on all cabinets
- Countertop by others
- Upgrade applied paneled fridge & dishwashers supply only (appliance hardware by others)

Classic Collection
Optional Upgrade to Includes:
- Top Drawer Construction (In lieu of Standard bank of drawers)
- Tandem Box **Soft Close Drawers**
- Blumotion **Soft Close Hinges for Doors**
- Crown Moulding
- Deep Fridge Upper w/Deep Panel
- Tall upper Cabinets

Sketch #8

8 of 44

6/28/2021

THIS DRAWING IS FOR DESIGN PURPOSES ONLY.
IT IS NOT AN EXACT RENDITION.

CU UPCOUNTRY
LOT 4-4
20-2212 ELEV A
THE ROSLYN

19 of 41

The Roslyn

20-2212 ELEV. A

ELEVATION A: 2,212 SQ FT

Sketch #9



UPPER LEVEL
ELEVATION A

2 H

Legal Plan: September 17, 2020

CU UPCOUNTRY
LOT 4-4
20-2212 ELEV A
THE ROSLYN

20 of 41

NATIONAL
FIREPLACES & AIR SYSTEMS



'CABINET'

NFAS NF15 Mantel

Aug 17 21

(M)

CU UPCOUNTRY
LOT 4-4
20-2212 ELEV A
THE ROSLYN

21 OF 41

Stainless Steel | 122.0264.716

FAMILY : **Sinks** | SERIES : **Reginox** | MODEL : **NS1930U/9** | FINISH : **Stainless Steel** | INSTALLATION TYPE : **Undermount**





TECHNICAL DATA	
Width overall	18 3/4"
Length overall	29 3/4"
Width of large bowl	17"
Length of large bowl	28"
Depth of large bowl	8 1/2"
Cabinet Size	36"
Number of Bowls	1
Waste Outlet Diameter	3 1/2"
Cut-Out Template	Yes
Faucet Hole	None
Type of Material	18 Gauge Stainless Steel
Surface Finish	SILK
Special feature	Rear Drain Waste Hole Location
Waste Kit Included	YES

KINDRED

CU UPCOUNTRY
LOT 4-4
20-2212 ELEV A
THE ROSLYN

22 OF 41

STANDARD KITCHEN FAUCET

Align

Modern



Single Handle Pull-Down Kitchen Faucet‡

Model 7565†

CU UPCOUNTRY
LOT 4-4
20-2212 ELEV A
THE ROSLYN

23 of 41

American Standard

BOULEVARD® PEDESTAL SINK
VITREOUS CHINA

BOULEVARD® PEDESTAL SINK

- ☐ **0641.800** Faucet holes on 8" (203mm) centers (Illustrated)
- ☒ **0641.400** Faucet holes on 4" (102mm) centers
- ☐ **0641.100** Center hole only
  - Classic styled rectangular pedestal lavatory
  - Vitreous china
  - Rear overflow
  - Supplied with mounting kit
  - Right Height® for greater comfort during use
  - Faucet ledge with large deck area (faucet not included)
  - **Design coordinates with Boulevard® Toilet**
  - Basin has flat bottom to also allow use as an **above counter** sink or a **drop-in** sink (with u-shaped cut out)



Nominal Dimensions:
24" x 19" x 35-1/2"
(610 x 483 x 902mm)

SEE REVERSE FOR ROUGHING-IN DIMENSIONS

- ☐ **0641.008** Pedestal top-8" (203mm) centers
- ☐ **0641.004** Pedestal top-4" (102mm) centers
- ☐ **0641.001** Pedestal top-center hole only
- ☐ **0010.000** Pedestal only

Bowl sizes:
17" (432mm) wide,
12-1/2" (318mm) front to back,
5" (127mm) deep

Compliance Certifications -
Meets or Exceeds the Following Specifications:
• ASME A112.19.2 - 2008/CSA B45.1-08

To Be Specified:
- ☐ Color: ☐ White ☐ Linen
- ☐ Faucet Finish:
- ☐ Supplies:
- ☐ 1-1/4" Trap:
- ☐ Nipple:

* See faucet section for additional models available

© 2014 AS America Inc.

American Standard

CU UPCOUNTRY
LOT 4-4
20-2212 ELEV A
THE ROSLYN

24 of 41

COLONY™ COUNTERTOP SINK
VITREOUS CHINA

BARRIER FREE

COLONY COUNTERTOP SINK

- Vitreous china
- Self-rimming
- Front overflow
- Supplied with template
- Faucet deck
  (Faucet shown not included)

☑ **0346 803**
Faucet holes on 203mm (8") centres

☐ **0346 403** (Illustrated)
Faucet holes on 102mm (4") centres

☐ **0346 001**
Centre hole only



Nominal Dimensions:
521 x 448mm (20-1/2" x 17-5/8")

Bowl sizes:
422mm (16-5/8") wide, 279mm (11") front to back, 143mm (5-5/8") deep





COMPLIANCE CERTIFICATIONS –
Meets or exceeds the following Specifications:
- ASME A112.19.2M for Vitreous China Fixtures.
- CAN/CSA B45 Series.

To Be Specified

☐ Colour: ☑ White ☐ Bone ☐ Silver Gray ☐ Linen

☐ Faucet*:

☐ Faucet Finish:

☐ Supplies & Stops:

☐ Trap 1-1/4" (32 mm):

NOTES:
* DIMENSIONS SHOWN FOR LOCATION OF SUPPLIES AND "P" TRAP ARE SUGGESTED. FOR COUNTERTOP CUTOUT AND INSTALLATION INSTRUCTIONS USE TEMPLATE SUPPLIED WITH SINK.
FAUCETS NOT INCLUDED AND MUST BE ORDERED SEPARATELY.
IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ANSI Standard A112.19.2.
These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

* See faucet section for additional models available

© 2000 American Standard Inc.

CU UPCOUNTRY
LOT 4-4
20-2212 ELEV A
THE ROSLYN

25 of 41

Demi CF2007

CU UPCOUNTRY
LOT 4-4
20-2212 ELEV A
THE ROSLYN

26 OF 41

Chateau

Transitional



Lavatory Faucet with Pop-Up Drain
Model L4621†

VANITY SINKS AND PEDESTAL

Posi-Temp® Pressure Balancing Tub/Shower
Model 62320 / TL183†
OR
Posi-Temp Valve and Tub/Shower Trim with Eco-Performance Easy Clean® XL
Model 62320 / TL183EP†
(TL183EP not available in BC)

SHOWER AND 5' TUB FAUCETS

2 Handle Roman Tub with 9" Spout
Model 4796 / T990†

FREESTANDING TUB FAUCETS

CU UPCOUNTRY
LOT 4-4
20-2212 ELEV A
THE ROSLYN

27 of 41

SC(B)500 | ALITO Collection

Cyclone®
Breathe Better

Features

- Wall mount range hood
- 6" round duct adapter
- Non-stick aluminum fan blades
- 3 speed push button control
- 2 LED lights (2 x 1.4W)
- Dishwasher-safe mesh or baffle filters
- Standard chimney fits up to 9 ft. ceiling
- Up to 9 minute time-delay OFF feature
- Plug-in connection





Options

- Filters: SC500 - Quick ~~Release~~ Aluminum Mesh Filters
  SCB500 - Quick Release Stainless Steel Baffle Filters ✓
- Available Chimney Flues:
  Short (7 ft. - 8 ft. A1. CH10)
  Standard (8 ft. - 9 ft. A1.CH18)
  Extended (9 ft. - 11 ft. A1.CH30)
- Widths: ~~24"~~, (30"), ~~36"~~

H Aug/17/21

Specifications

- Air Flow Volume: 550 CFM
- Electrical Connection: 120V/60Hz
- Power Consumption: 210 Watts
- Current: 2.5 Amps
- Fan Speed: 1600RPM
- Fan Type: Centrifugal Blower

- Finishes: Stainless Steel
- Ducting: 6" Round
- Dimensions: Width: 24" (30") 36"
  Height: 46"
  Depth: 18"

- Noise Level: Min. 2 Sones
  Max. 6 Sones

C SP US

CU UPCOUNTRY
LOT 4-4
20-2212 ELEV A
THE ROSLYN

28 OF 41

Whirlpool® Top Mount Refrigerator

PRODUCT MODEL NUMBERS

WRT311FZD
WRT511SZD
WRT541SZD

Electrical: A 115-volt, 60-Hz, AC-only, 15- or 20-amp fused, grounded electrical supply is required. It is recommended that a separate circuit serving only your refrigerator be provided. Use an outlet that cannot be turned off by a switch. Do not use an extension cord.

NOTE: Before performing any type of installation, cleaning, or removing a light bulb, turn the control (Thermostat, Refrigerator or Freezer Control depending on the model) to OFF and then disconnect the refrigerator from the electrical source. When you are finished, reconnect the refrigerator to the electrical source and reset the control (Thermostat, Refrigerator or Freezer Control depending on the model) to the desired setting. See "Using the Controls."

Water: A cold water supply with water pressure between 30 and 120 psi (207 and 827 kPa) is required to operate ice maker and water dispenser. If you have questions about your water pressure, call a licensed, qualified plumber.

IMPORTANT: The pressure of the water coming out of a reverse osmosis system going to the water inlet valve of the refrigerator needs to be between 30 and 120 psi (207 and 827 kPa).

Reverse Osmosis Water Supply: If a reverse osmosis water filtration system is connected to your cold water supply, the water pressure to the reverse osmosis system needs to be a minimum of 40 to 60 psi (276 to 414 kPa).

PRODUCT DIMENSIONS





Model Number	Model Size	Reversible Door	Height - Overall "A"	Height - Top of Cabinet "B"	Depth - Door Open 90° "C"	Depth - With Handles "D"	Depth - Without Handles "E"	Depth - Cabinet Only "F"	Width - Cabinet "G"
WRT311FZD	20.5 cu. ft.	Yes	66¼" (168.3 cm)	65½" (166.4 cm)	62¼" (158.1 cm)	32⅞" (83.5 cm)	30⅝" (77.8 cm)	28½" (72.4 cm)	32¾" (83.2 cm)
WRT511SZD WRT541SZD	21.3 cu. ft.	Yes	66¼" (168.3 cm)	65½" (166.4 cm)	62¼" (158.1 cm)	34" (86.4 cm)	32½" (82.3 cm)	28⅛" (72.4 cm)	32¾" (83.2 cm)

LOCATION REQUIREMENTS



To ensure proper ventilation for your refrigerator, allow for a ½" (1.25 cm) space on each and between overhead cabinets and refrigerator top. Allow at least 1" (2.5 cm) between back of cabinet and the wall. If your refrigerator has an ice maker, make sure you leave some extra space at the back for the water line connections.

If you are installing your refrigerator next to a fixed wall, leave 2" (5 cm) minimum on the hinge side (depending on your model) to allow for the door to swing open.

NOTE: This refrigerator is intended for use in a location where the temperature ranges from a minimum of 55°F (13°C) to a maximum of 110°F (43°C). The preferred room temperature range for optimum performance, which reduces electricity usage and provides superior cooling, is between 60°F (15°C) and 90°F (32°C). It is recommended that you do not install the refrigerator near a heat source, such as an oven or radiator.

Because Whirlpool Corporation policy includes a continuous commitment to improve our products, we reserve the right to change materials and specifications without notice.

Dimensions are for planning purposes only. For complete details, see Installation Instructions packed with product. Specifications subject to change without notice.

Ref. W10674106
10/29/14

CU UPCOUNTRY
LOT 4-4
20-2212 ELEV A
THE ROSLYN

29 of 41

Refrigerator Door Swing Verification



When facing the refrigerator

☑ *RIGHT HAND DOOR OPENING*
- *Hinges on right*
- *Handle on left*

MK
INITIAL

LEFT HAND DOOR OPENING ☐
- *Hinges on left*
- *Handle on right*

INITIAL

PORCH RIGHT

Please check and INITIAL your door swing selection.

CU UPCOUNTRY
LOT 4-4
20-2212 ELEV A
THE ROSLYN

30 of 41

WHIRLPOOL 30" (76.0 CM) FREESTANDING ELECTRIC RANGES
Model YWFE515S0JS

5.3 cu. ft. Whirlpool® electric range with Frozen Bake™ technology

YWFE515S0JS

Whirlpool

Home › Kitchen Appliances › Cooking Appliances › Ranges › Single Oven Ranges › YWFE515S0JS





WHIRLPOOL 30" (76.0 CM) FREESTANDING ELECTRIC RANGES
Model YWFE515S0JS

Product Dimensions



A. 27¾" (70.5 cm) max. depth with handle
*B. 46⅞" (119.1 cm) overall height (max.) with leveling legs screwed all the way in**
*C. 36" (91.4 cm) cooktop height (max.) with leveling legs screwed all the way in**
D. 29⅞" (75.9 cm) width
*E. 25⅝" (64.3 cm) depth - back of range to front of cooktop***
F. Model/serial/rating plate (located on the frame behind a top corner of the door or either side of the drawer)

IMPORTANT: Range must be level after installation. Follow the instructions in the "Level Range" section. Using the cooktop as a reference for leveling the range is not recommended.

*Range can be raised approximately 1" (2.5 cm) by adjusting the leveling legs.

**Front of door and drawer may extend further forward depending on styling.

Cabinet Dimensions

Cabinet opening dimensions shown are for 25" (64.0 cm) countertop depth, 24" (61.0 cm) base cabinet depth and 36" (91.4 cm) countertop height.

IMPORTANT: If installing a range hood or microwave hood combination above the cooking surface, follow the range hood or microwave hood combination installation instructions for dimensional clearances above the cooktop surface.

A freestanding range may be installed next to combustible walls with zero clearance.



A. 13" (33.0 cm) max. upper cabinet depth
B. 30" (76.2 cm) min. opening width
*C. For minimum clearance to top of cooktop, see NOTE**
D. 30" (76.2 cm) min. opening width
E. Outlet - 8" (20.3 cm) to 22" (55.9 cm) from either cabinet, 7" (17.8 cm) max. from floor.
F. Cabinet door or hinges should not extend into the cutout.

***NOTE:** 24" (61.0 cm) minimum when bottom of wood or metal cabinet is covered by not less than 1/4" (6.4 mm) flame retardant millboard covered with not less than No. 28 MSG sheet steel, 0.015" (0.4 mm) stainless steel, 0.024" (0.6 mm) aluminum or 0.020" (0.5 mm) copper.

30" (76.2 cm) minimum clearance between the top of the cooking platform and the bottom of an uncovered wood or metal cabinet.

JAN 28/20

WHIRLPOOL 30" (76.0 CM) FREESTANDING ELECTRIC RANGES
Model YWFE515S0JS

Install Anti-Tip Bracket

⚠WARNING

Tip Over Hazard

A child or adult can tip the range and be killed.

Install anti-tip bracket to floor or wall per installation instructions.

Slide range back so rear range foot is engaged in the slot of the anti-tip bracket.

Re-engage anti-tip bracket if range is moved.

Do not operate range without anti-tip bracket installed and engaged.

Failure to follow these instructions can result in death or serious burns to children and adults.

1. Remove the anti-tip bracket from where it is taped inside the storage drawer or warming drawer.
2. Determine which mounting method to use: floor or wall.
   If you have a stone or masonry floor, you can use the wall mounting method. If you are installing the range in a mobile home, you must secure the range to the floor.
3. Determine and mark centerline of the cutout space. The mounting can be installed on either the left-side or right-side of the cutout. Position mounting bracket against the wall in the cutout so that the V-notch of the bracket is 12$^{9}/_{16}$" (31.9 cm) from centerline as shown.



A. 12$^{9}/_{16}$" (31.9 cm)
B. Bracket V-notch

4. Drill two 1/8" (3 mm) holes that correspond to the bracket holes of the determined mounting method. See the following illustrations.

Floor Mounting



Rear position *Front position* *Diagonal (2 options)*

Wall Mounting



5. Using the Phillips screwdriver, mount anti-tip bracket to the wall or floor with the two #12 x 1$^{5}/_{8}$" (4.1 cm) screws provided.
6. Move range close enough to opening to allow for final electrical connections. Remove shipping base, cardboard or hardboard from under range.
7. Move range into its final location, making sure rear leveling leg slides into anti-tip bracket.



8. Move range forward onto shipping base, cardboard or hardboard to continue installing the range using the following installation instructions.

CU UPCOUNTRY
LOT 4-4
20-2212 ELEV A
THE ROSLYN

33 OF 41

Whirlpool® Dishwasher with ENERGY STAR® qualification



WDF310PAAS
Black-on-Stainless

OTHER AVAILABLE COLORS

- Black — Model: WDF310PAAB
- Biscuit-on-Biscuit — Model: WDF310PAAT
- White — Model: WDF310PAAW
- Universal Silver — Model: WDF310PAAD

ENERGY STAR

DIMENSIONS	
Maximum Height	34 1/2 Inches
Minimum Height	33 1/2 Inches
Height	34 1/2 Inches
Depth	24 1/2 Inches
Width	23 7/8 Inches

Dimensions shown are for planning purposes only. For complete information, see installation instructions packaged with product.

ELECTRICAL

15 Amps Amps. 60 Hz. 120 V. 15,

Before purchasing this appliance, read important information about its estimated annual energy consumption or energy efficiency rating that is available from your dealer.

KEY FEATURES

ENERGY STAR® Qualified
No One Has Fewer Repairs 17 Years In A Row
Resource - Efficient Wash System
CEE Tier 1 qualified
Tall Tub Design
White Plastic Interior
Quiet Partner(TM) I Sound Package
Auto Soil Sensor
Electronic Controls
3 Automatic Cycles
1-Hour Wash Cycle
Heavy Wash Cycle
Normal Cycle
4 Options
High Temperature Wash System
Heated Dry Option
4 Hour Delay Wash Option
4-Tier SheerClean Direct Feed Wash System
Control Lock
Vinyl Racks
In-Rack Silverware Basket

CU UPCOUNTRY
LOT 4-4
20-2212 ELEV A
THE ROSLYN

34 of 41

Whirlpool® Undercounter Dishwasher

PRODUCT MODEL NUMBERS

WDF110PAB	~~WDF310PLA~~	WDF530PSY
WDF111PAB	WDF320PAD	WDF540PAD
WDF120PAF	~~WDF510PAY~~	WDF730PAY
WDF121PAF	WDF520PAD	WDT710PAY
WDF310PAA	WDF530PAY	WDT720PAD
WDF310PCA	WDF530PLY	WDT770PAY

Electrical Requirements: 120-volt, 60-Hz, AC only, 15- or 20-amp. fused electrical supply. Copper wire only. A time delay fuse or circuit breaker and separate circuit is recommended.

If direct wiring dishwasher: Use flexible, armored, or nonmetallic, sheathed copper wire with grounding wire that meets the wiring requirements for your home and local codes and ordinances. Use a UL listed or CSA approved conduit connector.

If connecting dishwasher with a power supply cord: Use Power Supply Cord Kit (Part No. 4317824) marked for use with dishwashers. Follow the kit instructions for installing the power supply cord.



Power supply cord must plug into a grounded 3 prong, outlet, located in the cabinet next to the dishwasher opening. Outlet must meet all local codes and ordinances.



Water Supply Requirements: A hot water line with 20 to 120 psi (138 to 862 kPa) water pressure. Water temperature must be 120°F (49°C) water at dishwasher. Use ⅜" O.D. copper tubing with compression fitting or flexible braided water supply line (½" minimum plastic tubing is not recommended). Use a 90° elbow with ¾" N.P.T. external pipe threads on one end. Do not solder within 6" (15.2 cm) from water inlet valve.

Drain Requirements: A new drain hose is supplied with your dishwasher. If this is not long enough, use a new drain hose with a maximum length of 12' (3.7 m) (Part No. 3385556) that meets all current AHAM/IAPMO test standards, is resistant to heat and detergent, and fits the 1" (2.5 cm) drain connector of the dishwasher.

Make sure to connect the drain hose to waste tee or disposer inlet above drain trap in house plumbing and 20" (50.8 cm) minimum above the floor. It is recommended that the drain hose either be looped up and securely fastened to the underside of the counter or be connected to an air gap.



Make sure to use an air gap if the drain hose is connected to house plumbing lower than 20" (50.8 cm) above subfloor or floor.

Use ½" (1.3 cm) minimum I.D. drain line fittings.

If required, the air gap should be installed in accordance with the air gap installation instructions. When connecting the air gap, a rubber hose (not provided) will be needed to connect to the waste tee or disposer inlet.

PRODUCT DIMENSIONS



*Insulation may be compressed (not used on all models)

Because Whirlpool Corporation policy includes a continuous commitment to improve our products, we reserve the right to change materials and specifications without notice.

Dimensions are for planning purposes only. For complete details, see installation instructions packed with product. Specifications subject to change without notice.

W10435040C-D-WH
5/1/16

CU UPCOUNTRY
LOT 4-4
20-2212 ELEV A
THE ROSLYN

35 of 41

CABINET CUTOUT DIMENSIONS

WDF320PAD

NOTE: Shaded areas of cabinet walls show where utility connections may be installed.

*Measure from the lowest point on the underside of the countertop. May be reduced to 33½" (85.1 cm) by removing the rear leveling legs from dishwasher.

**Minimum, measured from narrowest point of opening.



Because Whirlpool Corporation policy includes a continuous commitment to improve our products, we reserve the right to change materials and specifications without notice.

Dimensions are for planning purposes only. For complete details, see Installation Instructions packed with product. Specifications subject to change without notice.

W10435040C-D-WH
5/1/16

CU UPCOUNTRY
LOT 4-4
20-2212 ELEV A
THE ROSLYN

36 of 41

WHIRLPOOL WASHER Model #: WFW5620HW



5.2 cu. ft. I.E.C. Closet-Depth Front Load Washer with Load & Go™ Dispenser

Whirlpool

5.2 cu. ft. I.E.C. Closet-Depth Front Load Washer with Load & Go™ Dispenser

Model #: WFW5620HW

Dimensions

Depth	80.17 cm, 31-9/16 in
Depth With Door Open 90 Degree	143.51 cm, 56-1/2 in
Minimum Height	98.11 cm, 38-5/8 in
Width	68.58 cm, 27.0 in

Appearance

LCD Touch Screen	No
Window	Yes

Details

Drum Material	Stainless Steel

Cycles and Options

Number of Wash Cycles	37

Electrical

Hz	60
Power Cord Included	Yes

CU UPCOUNTRY
LOT 4-4
20-2212 ELEV A
THE ROSLYN

37 OF 41

WHIRLPOOL WASHER Model #: WFW5620HW

LOCATION REQUIREMENTS

Proper installation is your responsibility.

You will need:

- A water heater set to 120°F (49°C).
- A grounded electrical outlet located within 6 ft (1.8 m) of power cord on back of washer.
- Hot and cold water faucets located within 4 ft (1.2 m) of hot and cold water fill valves on washer, and water pressure of 20–100 psi (137.9–689.6 kPa).
- A level floor with maximum slope of 1" (25 mm) under entire washer. Installing on carpet or surfaces with foam backing is not recommended.
- Floor must support washer's total weight (with water and load) of 315 lbs (143 kgs).

IMPORTANT: Do not install, store, or operate washer where it will be exposed to weather or in temperatures below 32°F (0°C). Water remaining in washer after use may cause damage in low temperatures. See "Washer Care" in your Use and Care Guide for winterizing information.

Whirlpool Models*





*For additional details (or information) specific to your model, refer to the 'Dimensions' listed for your model at **www.whirlpool.com.**

Maytag Models





All dimensions show minimum spacing allowed.
For each arrangement, consider allowing more space for ease of installation and servicing, and spacing for companion appliances and clearances for walls, doors, and floor moldings.

Space must be large enough to allow door to fully open. Add spacing of 1" (25 mm) on all sides of washer to reduce noise transfer. If a closet door or louvered door is installed, top and bottom air openings in door are required.

Recessed area or closet installation (stacked washer and dryer):



CU UPCOUNTRY
LOT 4-4
20-2212 ELEV A
THE ROSLYN

38 of 41

WHIRLPOOL WASHER Model #: WFW5620HW

Custom under-counter installation:



Recessed area or closet installation:



Custom cabinet installation:



DRAIN SYSTEM

The drain system can be installed using a floor drain, wall standpipe, floor standpipe, or laundry tub. Select the method you need.

IMPORTANT: To avoid siphoning, only 4.5" (114 mm) of drain hose should be inside standpipe. Always secure drain hose with cable tie.

Floor standpipe drain system



Minimum diameter for a standpipe drain: 2" (51 mm). Minimum carry-away capacity: 17 gal. (64 L) per minute. A 1/4" (6 mm) diameter to 1" (25 mm) diameter Standpipe Adapter Kit is available (Part Number 3363920). Top of standpipe must be at least 30" (762 mm) high; install no higher than 96" (2.44 m) from bottom of washer. If you have an overhead sewer and need to pump higher than 96" (2.44 m), a sump pump and associated hardware are needed. See "Alternate parts."

Wall standpipe drain system



See requirements for floor standpipe drain system.

Laundry tub drain system



Minimum capacity: 20 gal. (76 L). Top of laundry tub must be at least 30" (762 mm) above floor; install no higher than 96" (2.44 m) from bottom of washer.

CU UPCOUNTRY
LOT 4-4
20-2212 ELEV A
THE ROSLYN

39 of 41

WHIRLPOOL DRYER Model #: YWED5620HW



Define Your Style

7.4 cu. ft. Front Load Electric Dryer with Intuitive Touch Controls

Whirlpool **7.4 cu. ft. Front Load Electric Dryer with Intuitive Touch Controls**

Model #: YWED5620HW

Dimensions

Depth	78.74 cm, 31.0 in
Depth With Door Open 90 Degree	138.43 cm, 54-1/2 in
Height	98.42 cm, 38-3/4 in
Width	68.58 cm, 27.0 in

Configuration and Overview

Fuel Type	Electric

Cycles and Options

Cycle Time Remaining	Yes
Lint Filter Indicator	No
Number of Dryer Cycles	36
Number of Dryness Levels	3

Ventilation System

Long Vent	No
Maximum Vent Length	64
Venting Direction	Left, Right, Bottom, Rear

Electrical

Hz	60
Power Cord Included	Yes

CU UPCOUNTRY
LOT 4-4
20-2212 ELEV A
THE ROSLYN

40 of 41

WHIRLPOOL DRYER Model #: YWED5620HW

Back view:



*Approx. measurement

NOTE: Most installations require a minimum of 5" (127 mm) clearance behind dryer for exhaust vent with elbow. See "Venting Requirements."

Installation Clearances

For each arrangement, consider allowing more space for ease of installation and servicing, spacing for companion appliances, and clearances for walls, doors, and floor moldings. Space must be large enough to allow door to fully open. Add spacing on all sides of dryer to reduce noise transfer. If a closet door or louvered door is installed, top and bottom air openings in door are required.

Check code requirements. Some codes limit, or do not permit, installation of the dryer in garages, closets, mobile homes, or sleeping quarters. Contact your local building inspector.

NOTE: No other fuel-burning appliance can be installed in the same closet as a dryer.

Installation spacing for recessed area or closet installation

All dimensions show recommended and minimum spacing allowed.

- Additional spacing should be considered for ease of installation and servicing.
- Additional clearances might be required for wall, door, floor moldings, dryer venting, and gas line.
- Additional spacing should be considered on all sides of the dryer to reduce noise transfer.
- For closet installation with a door, minimum ventilation openings in the top and bottom of the door are required. Louvered doors with equivalent ventilation openings are acceptable.
- Companion appliance spacing should also be considered.

Recommended installation clearances (dryer only):



0" (0 mm) rear spacing is allowed for straight back venting only. For steam models only, inlet hose must not be kinked.

Custom under-counter installation:



Mobile home – Additional installation requirements:

This dryer is suitable for mobile home installations. The installation must conform to the Manufactured Home Construction and Safety Standard, Title 24 CFR, Part 3280 (formerly the Federal Standard for Mobile home construction and Safety, Title 24, HUD Part 280) or Standard CAN/CSA-Z240 MH.

Mobile home installations require:

- Metal exhaust system hardware, available for purchase from your dealer. For further information, see "Assistance or Service" in your Use and Care Guide.
- Special provisions must be made in mobile homes to introduce outside air into dryer. Openings (such as a nearby window) should be at least twice as large as dryer exhaust opening.

For mobile home installation of gas dryers:

- Mobile Home Installation Hold-down Kit Part Number 346764 is available to order. For further information, see "Assistance or Service" in your Use and Care Guide.

CU UPCOUNTRY
LOT 4-4
20-2212 ELEV A
THE ROSLYN

41 OF 41

WHIRLPOOL DRYER Model #: YWED5620HW

Additional parts may be required, depending on your installation. Check local codes. Check existing electrical supply and venting. Read "Electrical Requirements" and "Venting Requirements" before purchasing parts.

If using a power supply cord:

Use a UL Listed power supply cord kit marked for use with clothes dryers. The kit should contain:

- A UL Listed 30 amp power supply cord, rated 120/240 volt minimum. The cord should be type SRD or SRDT and be at least 4 ft. (1.22 m) long. The wires that connect to the dryer must end in ring terminals or spade terminals with upturned ends.
- A UL Listed strain relief.

Optional Equipment (not supplied with dryer):

Refer to your Use and Care Guide for information about accessories available for your dryer.

LOCATION REQUIREMENTS

Check code requirements. Some codes limit, or do not permit, installing dryer in garages, closets, mobile homes, or sleeping quarters. Contact your local building inspector.

⚠WARNING

Explosion Hazard

Keep flammable materials and vapors, such as gasoline, away from dryer.

Place dryer at least 18 inches (460 mm) above the floor for a garage installation.

Failure to do so can result in death, explosion, or fire.

You will need:

- A location allowing for proper exhaust installation. See "Venting Requirements."
- A separate 15 or 20 amp circuit for a gas dryer or 30 amp circuit for an electric dryer.
- If using power supply cord, a grounded electrical outlet located within 2 ft. (610 mm) of either side of dryer. See "Electrical Requirements."
- Floor must support dryer weight of 200 lbs. (90.7 kg). Also consider weight of companion appliance.
- Cold water faucets located within 4 ft. (1.2 m) of the water fill valves, and water pressure of 20–120 psi (138–827 kPa). You may use your washer's water supply by purchasing the necessary parts noted in "Parts needed."
- Level floor with maximum slope of 1" (25 mm) under entire dryer. If slope is greater than 1" (25 mm), Install Extended Dryer Feet Kit, Part Number 279810. If not level, clothes may not tumble properly and automatic sensor cycles may not operate correctly.
- For garage installation, place dryer at least 18" (460 mm) above floor. If using a pedestal, you will need 18" (460 mm) to bottom of dryer.
- The dryer must not be installed or stored in an area where it will be exposed to water and/or weather.

IMPORTANT: Do not operate, install, or store dryer where it will be exposed to water, weather, or at temperatures below 40°F (4°C). Lower temperatures may cause dryer not to shut off at end of automatic sensor cycles, resulting in longer drying times.

DRYER DIMENSIONS

Front view:



Side view:

Whirlpool Models



*Approx. measurement

Maytag Models



*Approx. measurement