Sales Selection Sheet Checklist

1 of 45

LOT 697-6 Model: 20-2447 END B BARRINGTON PURCHASERS: SHOWMICA RAVINDRAN/ **Heathwood Homes (Whitby) Limited VENDOR:** OPTIONAL CLASSIC KITCHEN BALCONY OFF SECOND FLOOR MASTER BEDROOM OPTIONAL COFFERED CEILING IN GREAT ROOM OPTIONAL DOUBLE SINKS IN MASTER ENSUITE BATHROOM VANITY **WOB** Υ **DECK ON MAIN** FINISHED BASEMENT **COLD CELLAR UPGRADED / MODIFIED ELEVATION CORNER UPGRADE** REAR UPGRADE SIDE UPGRADE **CEILING UPGRADE - SMOOTH** MAIN FLOOR SECOND FLOOR **BASEMENT** LOWER LEVEL ADDITIONAL ROUGH-INS 200 AMP SERVICE (STD 200AMP TOWNS) WET BAR ROUGH-IN **HUMIDIFIER (STD in Singles)** AIR CONDITIONING (SITE STD) Y **GAS ROUGH-IN STOVE DRYER BBQ** ADDITIONAL FIREPLACE KITCHEN: HOODFAN VENTING SIZE **6 IN ROUND DUCT** Y 7 IN ROUND DUCT (STD FOR TOWNS) **FULL BASEMENT STAIRS:** Paint Grade **UPPER BASEMENT STAIRS:** N/A LOWER LEVEL STAIRS: All Oak LOWER BASEMENT STAIRS: N/A MAIN STAIRS: All Oak MEDIA STAIRS (if applicable): N/A LOFT STAIRS (if applicable): N/A Aug 11, 2022 Signature on file Aug 11, 2022 IRIT SALEM **Decor Consultant: Date** Purchaser: Date Aug 11, 2022 MARILYN ROSEN Purchaser: **Date Date Heathwood Homes (Whitby) Limited**

Floor Tile Pattern

SHOWMICA RAVINDRAN/ Project: Country Lane
Unit: 697-6, Phase: 6
Model: 20-2447 END B BARRINGTON

Locked: Closed:

en/Breakfast			
Cabinet Colour/Style	9111	Viking III-SIMCOE ORCHID 3DL ***STD***	
Island Cabinet Colour/Style	6319	Viking III-MANCHESTER-CAVIAR CL-MAPLE ***STD***	
Cabinet Hardware	9146	12877 MB BLACK-HARDWARE ***2***	
Countertop	8595	Group 2-Quartz-Caesarstone-OCEAN FOAM #6141-3/4 inch with built-up edge ***2***	
Island Countertop	8595	Group 2-Quartz-Caesarstone-OCEAN FOAM #6141-3/4 inch with built-up edge ***2***	
Countertop Edge	4005	DOUBLE MITRE 1 1/2 INCH ***UPG***	
Sink	9488	Plumbing-KINDRED Kitchen Sink Collection - Reginox NS1930 U/9-Single Bowl Undermount Sink (or equivalent)-Stainless Steel	
Crumb Vac Color	9482	Vacuum-Crumb Vac (Dust Pan)-White	
HoodFan	9393	SCB51930-CYCLONE 30 inch CANOPY CHIMNEY HOODFAN-SS	
Opt. Backsplash	5721	QT.CD.ARW.0306.BR-Colour and Dimension Bright-Arctic White-3 x 6 ***1***	
Opt. Backsplash Grout	2226	Grout-(00) White ***STD***	
Opt. Backsplash Tile Pattern	3060	HORIZONTAL BRICK ***STD***	
Flooring	9358	Red Oak Pearl-Vintage Engineered-TITANIUM-3/4 inch x 3 1/4 inch ***UPG***	
Floor Tile Grout	1111	N/A *****	

- Purchasers have been advised: standard fridge opening is a minimum 37 3/8 x 73 3/8 inches. Ice Waterline Rough-In is included.

N/A *****

1111

- Standard stove opening is 30 inches and standard dishwasher opening is 24 inches. Any gas stove will require backsplash or stainless steel backing to avoid fire hazards.
- Purchasers acknowledge: Heathwood Homes and its contractors will not be responsible for any kitchen cabinet changes due to appliances dimension changes after sign-off.

	-	
Comment		

Foyer			
Flooring	8913	UN.BL.BIA.1224-Biel-Bianco (White)-12 x 24 See Tile Direction on Sketch Page ***2***	S3P17
Floor Tile Grout	2225	Grout-(27) Silver ***STD***	
Floor Tile Pattern	3050	SIDE TO SIDE ***STD***	
Page 1 of 8			

SHOWMICA RAVINDRAN/ Project: Country Lane Unit: 697-6, Phase: 6 Model: 20-2447 END B BARRINGTON

_			
Comment			
wder Room			
		0050	TD CDW// UTE 4242 CEMPDE W/- 1/2 - M-4/2 - 42
Flooring		3050	TR.SP.WHITE.1313 SEMPRE White Matte 13
[] Til- O	.4	0005	C+ (07) C:1 ***CTD***
Floor Tile Grou		2225	Grout-(27) Silver ***STD***
Floor Tile Patte	ern	3000	STANDARD SQUARE ***STD***
Diumbin Ei (uno (Coloum)	4707	Diumbing Fixtures MUUTE ***CTD***
Plumbing Fixtu	ure (Colour)	1737	Plumbing Fixtures-WHITE ***STD***
Comment			
ving Room			
		0050	D. LO. I. D I.V. I E I. TITANIII IN 0/4 I 0
Flooring		9358	Red Oak Pearl-Vintage Engineered-TITANIUM-3/4 inch x 3 1/4 inch ***STD***
			W. W
Comment			
eat Room		0358	
		9358	Red Oak Pearl-Vintage Engineered-TITANIUM-3/4 inch x 3
eat Room Flooring		9358	
eat Room		9358	Red Oak Pearl-Vintage Engineered-TITANIUM-3/4 inch x 3
eat Room Flooring		9358	Red Oak Pearl-Vintage Engineered-TITANIUM-3/4 inch x 3
eat Room Flooring		9358	Red Oak Pearl-Vintage Engineered-TITANIUM-3/4 inch x 3
eat Room Flooring		9358	Red Oak Pearl-Vintage Engineered-TITANIUM-3/4 inch x 3
eat Room Flooring Comment	lace	9358	Red Oak Pearl-Vintage Engineered-TITANIUM-3/4 inch x 3
eat Room Flooring Comment	lace		Red Oak Pearl-Vintage Engineered-TITANIUM-3/4 inch x 3 1/4 inch ***STD***
eat Room Flooring Comment eat Room Firep Type	lace	8865	Red Oak Pearl-Vintage Engineered-TITANIUM-3/4 inch x 3 1/4 inch ***STD*** Dimplex-Electric Fireplace-PF3033HL ***STD***
eat Room Flooring Comment	lace		Red Oak Pearl-Vintage Engineered-TITANIUM-3/4 inch x 3 1/4 inch ***STD*** Dimplex-Electric Fireplace-PF3033HL ***STD*** NF-17-Paint Grade Mantle- Cabinet (Per Plan)-WHITE
eat Room Flooring Comment eat Room Firep Type Mantle		8865 8891	Red Oak Pearl-Vintage Engineered-TITANIUM-3/4 inch x 3 1/4 inch ***STD*** Dimplex-Electric Fireplace-PF3033HL ***STD*** NF-17-Paint Grade Mantle- Cabinet (Per Plan)-WHITE ***STD***
eat Room Flooring Comment eat Room Firep Type		8865	Red Oak Pearl-Vintage Engineered-TITANIUM-3/4 inch x 3 1/4 inch ***STD*** Dimplex-Electric Fireplace-PF3033HL ***STD*** NF-17-Paint Grade Mantle- Cabinet (Per Plan)-WHITE
eat Room Flooring Comment eat Room Firep Type Mantle Opt. Surround		8865 8891	Red Oak Pearl-Vintage Engineered-TITANIUM-3/4 inch x 3 1/4 inch ***STD*** Dimplex-Electric Fireplace-PF3033HL ***STD*** NF-17-Paint Grade Mantle- Cabinet (Per Plan)-WHITE ***STD***
eat Room Flooring Comment eat Room Firep Type Mantle Opt. Surround		8865 8891	Red Oak Pearl-Vintage Engineered-TITANIUM-3/4 inch x 3 1/4 inch ***STD*** Dimplex-Electric Fireplace-PF3033HL ***STD*** NF-17-Paint Grade Mantle- Cabinet (Per Plan)-WHITE ***STD***
eat Room Flooring Comment eat Room Firep Type Mantle Opt. Surround		8865 8891	Red Oak Pearl-Vintage Engineered-TITANIUM-3/4 inch x 3 1/4 inch ***STD*** Dimplex-Electric Fireplace-PF3033HL ***STD*** NF-17-Paint Grade Mantle- Cabinet (Per Plan)-WHITE ***STD*** N/A ******
eat Room Flooring Comment eat Room Firep Type Mantle Opt. Surround - Purchasers h - Heathwood a	nave been advised:	8865 8891 1111 : heat from the	Red Oak Pearl-Vintage Engineered-TITANIUM-3/4 inch x 3 1/4 inch ***STD*** Dimplex-Electric Fireplace-PF3033HL ***STD*** NF-17-Paint Grade Mantle- Cabinet (Per Plan)-WHITE ***STD***
eat Room Flooring Comment eat Room Firep Type Mantle Opt. Surround - Purchasers h	nave been advised:	8865 8891 1111 : heat from the	Red Oak Pearl-Vintage Engineered-TITANIUM-3/4 inch x 3 1/4 inch ***STD*** Dimplex-Electric Fireplace-PF3033HL ***STD*** NF-17-Paint Grade Mantle- Cabinet (Per Plan)-WHITE ***STD*** N/A ****** PF can damage TV above a FP and items placed on mantle.
eat Room Flooring Comment eat Room Firep Type Mantle Opt. Surround - Purchasers h - Heathwood a	nave been advised:	8865 8891 1111 : heat from the	Red Oak Pearl-Vintage Engineered-TITANIUM-3/4 inch x 3 1/4 inch ***STD*** Dimplex-Electric Fireplace-PF3033HL ***STD*** NF-17-Paint Grade Mantle- Cabinet (Per Plan)-WHITE ***STD*** N/A ****** PF can damage TV above a FP and items placed on mantle.
eat Room Flooring Comment eat Room Firep Type Mantle Opt. Surround - Purchasers h - Heathwood a Fireplace after	nave been advised:	8865 8891 1111 : heat from the	Red Oak Pearl-Vintage Engineered-TITANIUM-3/4 inch x 3 1/4 inch ***STD*** Dimplex-Electric Fireplace-PF3033HL ***STD*** NF-17-Paint Grade Mantle- Cabinet (Per Plan)-WHITE ***STD*** N/A ****** PFP can damage TV above a FP and items placed on mantle.
eat Room Flooring Comment eat Room Firep Type Mantle Opt. Surround - Purchasers h - Heathwood a Fireplace after	nave been advised:	8865 8891 1111 : heat from the	Red Oak Pearl-Vintage Engineered-TITANIUM-3/4 inch x 3 1/4 inch ***STD*** Dimplex-Electric Fireplace-PF3033HL ***STD*** NF-17-Paint Grade Mantle- Cabinet (Per Plan)-WHITE ***STD*** N/A ****** PFP can damage TV above a FP and items placed on mantle.
eat Room Flooring Comment eat Room Firep Type Mantle Opt. Surround - Purchasers h - Heathwood a Fireplace after	nave been advised:	8865 8891 1111 : heat from the	Red Oak Pearl-Vintage Engineered-TITANIUM-3/4 inch x 3 1/4 inch ***STD*** Dimplex-Electric Fireplace-PF3033HL ***STD*** NF-17-Paint Grade Mantle- Cabinet (Per Plan)-WHITE ***STD*** N/A ****** PFP can damage TV above a FP and items placed on mantle.
eat Room Flooring Comment eat Room Firep Type Mantle Opt. Surround - Purchasers h - Heathwood a Fireplace after Comment	nave been advised:	8865 8891 1111 : heat from the	Red Oak Pearl-Vintage Engineered-TITANIUM-3/4 inch x 3 1/4 inch ***STD*** Dimplex-Electric Fireplace-PF3033HL ***STD*** NF-17-Paint Grade Mantle- Cabinet (Per Plan)-WHITE ***STD*** N/A ****** PF can damage TV above a FP and items placed on mantle.
eat Room Flooring Comment eat Room Firep Type Mantle Opt. Surround - Purchasers h - Heathwood a Fireplace after	nave been advised:	8865 8891 1111 : heat from the	Red Oak Pearl-Vintage Engineered-TITANIUM-3/4 inch x 3 1/4 inch ***STD*** Dimplex-Electric Fireplace-PF3033HL ***STD*** NF-17-Paint Grade Mantle- Cabinet (Per Plan)-WHITE ***STD*** N/A ****** PFP can damage TV above a FP and items placed on mantle.
eat Room Flooring Comment eat Room Firep Type Mantle Opt. Surround - Purchasers h - Heathwood a Fireplace after Comment	nave been advised:	8865 8891 1111 : heat from the	Red Oak Pearl-Vintage Engineered-TITANIUM-3/4 inch x 3 1/4 inch ***STD*** Dimplex-Electric Fireplace-PF3033HL ***STD*** NF-17-Paint Grade Mantle- Cabinet (Per Plan)-WHITE ***STD*** N/A ****** PFP can damage TV above a FP and items placed on mantle. the for any damage on items placed and or installed above a Red Oak Pearl-Vintage Engineered-TITANIUM-3/4 inch x 3
eat Room Flooring Comment eat Room Firep Type Mantle Opt. Surround - Purchasers h - Heathwood a Fireplace after Comment	nave been advised:	8865 8891 1111 : heat from the	Red Oak Pearl-Vintage Engineered-TITANIUM-3/4 inch x 3 1/4 inch ***STD*** Dimplex-Electric Fireplace-PF3033HL ***STD*** NF-17-Paint Grade Mantle- Cabinet (Per Plan)-WHITE ***STD*** N/A ****** PF can damage TV above a FP and items placed on mantle.
eat Room Flooring Comment eat Room Firep Type Mantle Opt. Surround - Purchasers h - Heathwood a Fireplace after Comment	nave been advised:	8865 8891 1111 : heat from the	Red Oak Pearl-Vintage Engineered-TITANIUM-3/4 inch x 3 1/4 inch ***STD*** Dimplex-Electric Fireplace-PF3033HL ***STD*** NF-17-Paint Grade Mantle- Cabinet (Per Plan)-WHITE ***STD*** N/A ****** PFP can damage TV above a FP and items placed on mantle. the for any damage on items placed and or installed above a Red Oak Pearl-Vintage Engineered-TITANIUM-3/4 inch x 3

SHOWMICA RAVINDRAN/ Project: Country Lane Unit: 697-6, Phase: 6 Model: 20-2447 END B BARRINGTON

		Glosed.
Upper Hall	9358	Red Oak Pearl-Vintage Engineered-TITANIUM-3/4 inch x 3
Flooring	9330	1/4 inch ***STD***
Comment		
Master Bedroom		
Flooring	9248	DY 89418 -Dynasty Tex-BLACK ICE-40 oz Poly***STD ***
Comment		
Bedroom 2		
Flooring	9248	DY 89418 -Dynasty Tex-BLACK ICE-40 oz Poly***STD ***
Comment		
Bedroom 3		
Flooring	9248	DY 89418 -Dynasty Tex-BLACK ICE-40 oz Poly***STD ***
Comment		
Master Ensuite		
Cabinet Colour/Style	9248	Viking III-SILK TOUCH-WHITE CLOUD-3DL ***STD***
Cabinet Hardware	2086	9677-HARDWARE ***STD***
Countertop	8826	4926K-07-Countertop-BLACK ALICANTE-Wilsonart ***STD***
Countertop Edge	1111	N/A *****
, -		
Floor Tile	9441	TH.CT.BLK.1212.MT-Construct-Black Matte-12 x 12 STD ***STD***
Floor Tile Grout Floor Tile Pattern	2221 3000	Grout-(47) Charcoal ***UPG*** STANDARD SQUARE ***STD***
Floor file Falletti	3000	STANDARD SQUARE STD
Shower Wall Tile	9441	TH.CT.BLK.1212.MT-Construct-Black Matte-12 x 12 STD
		STD
Shower Wall Tile Grout	2221	Grout-(47) Charcoal ***UPG***
Page 3 of 8		

SHOWMICA RAVINDRAN/ Project: Country Lane Unit: 697-6, Phase: 6 Model: 20-2447 END B BARRINGTON

Shower Wall Tile Pattern	3000	STANDARD SQUARE ***STD***
Shower Floor Tile	8666	OD.ON.DGR.0202.MT.N-Ontario Series Mosaic-Dark
		Grey-2 x 2 ***1***
Shower Floor Tile Grout	2221	Grout-(47) Charcoal ***UPG***
Shower Floor Tile Pattern	3000	STANDARD SQUARE ***STD***
Shower lamb(a) and Sill(a)	8927	Chayor Jamb / Cill Moonlight Plank *** Ing***
Shower Jamb(s) and Sill(s)		Shower Jamb / Sill-Moonlight Black ***Upg***
Plumbing Fixture (colour)	1737	Plumbing Fixtures-WHITE ***STD***
Comment		
Main Bathroom		
Cabinet Colour/Style	9111	Viking III-SIMCOE ORCHID 3DL ***STD***
Cabinat Handusan	0000	0077 HADDWADE ***CTD***
Cabinet Hardware	2086	9677-HARDWARE ***STD***
Countertop	8796	6698-46-Countertop-PALOMA POLAR ETCHINGS FINISH-Formica ***STD***
Countertop Edge	1111	N/A *****
Countertop Lage	1111	
Floor Tile	9437	TH.CT.WHT.1212.MT-Construct-White Matte-12 x 12 STD
FIOOI THE	9437	***STD***
Floor Tile Grout	2225	Grout-(27) Silver ***STD***
Floor Tile Pattern	3000	STANDARD SQUARE ***STD***
Wall Tile	9020	QT.WV.WHT.0810-Weave-White-8 x 10 ***STD***
Wall Tile Grout	2226	Crot (00) \M\bito ***CTD***
		Grout-(00) White ***STD***
Wall Tile Pattern	3070	HORIZONTAL STACKED ***STD***
Opt. Shower Floor Tile	1111	N/A *****
Opt. Onowor Floor The	1111	
Opt. Shower Floor Tile Grout	1111	N/A *****
Opt. Shower Floor Tile Pattern	1111	N/A *****

SHOWMICA RAVINDRAN/ Project: Country Lane Unit: 697-6, Phase: 6 Model: 20-2447 END B BARRINGTON

Page 5 of 8

6	\ /		4	459	Λ	5
C	ed: 6	7	02		38:	

Opt. Shower Jamb(s) and Sill(s)	1111	N/A *****
Plumbing Fixture (colour)	1737	Plumbing Fixtures-WHITE ***STD***
Comment		
er Level Family Room and Hall	_	
Flooring	9248	DY 89418 -Dynasty Tex-BLACK ICE-40 oz Poly***STD
3		
Comment		
er Level Laundry Mud Room	_	
Flooring	9248	GE.SU.ATR.1313 Sauble Anthracite (Black) 13
riooning	9240	GE.30.ATN. 1313 Sauble Attitifacite (black) 13
Floor Tile Grout	2221	Grout-(47) Charcoal ***UPG***
Floor Tile Pattern	3000	STANDARD SQUARE ***STD***
Opt. Cabinet Colour/Style - Uppers	1111	N/A *****
	4444	N/A *****
Opt. Cabinet Hardware - Uppers Comment	1111	IWA
Comment	[1111]	ĮWA
er Level Powder Room		
Comment	1111	Viking II-GEORGIAN-MOONLIGHT-3DL ***STD***
er Level Powder Room		
Comment Ter Level Powder Room Cabinet Colour/Style	1111	Viking II-GEORGIAN-MOONLIGHT-3DL ***STD***
Comment Ter Level Powder Room Cabinet Colour/Style Cabinet Hardware	1111 2086	Viking II-GEORGIAN-MOONLIGHT-3DL ***STD*** 9677-HARDWARE ***STD*** 6698-46-Countertop-PALOMA POLAR ETCHINGS
Comment Ter Level Powder Room Cabinet Colour/Style Cabinet Hardware Countertop	1111 2086 8796	Viking II-GEORGIAN-MOONLIGHT-3DL ***STD*** 9677-HARDWARE ***STD*** 6698-46-Countertop-PALOMA POLAR ETCHINGS FINISH-Formica ***STD***
Cer Level Powder Room Cabinet Colour/Style Cabinet Hardware Countertop Countertop Edge	1111 2086 8796	Viking II-GEORGIAN-MOONLIGHT-3DL ***STD*** 9677-HARDWARE ***STD*** 6698-46-Countertop-PALOMA POLAR ETCHINGS FINISH-Formica ***STD*** N/A ******
Comment Cer Level Powder Room Cabinet Colour/Style Cabinet Hardware Countertop Countertop Edge Flooring	1111 2086 8796 1111	Viking II-GEORGIAN-MOONLIGHT-3DL ***STD*** 9677-HARDWARE ***STD*** 6698-46-Countertop-PALOMA POLAR ETCHINGS FINISH-Formica ***STD*** N/A ****** GE.SU.ATR.1313 Sauble Anthracite (Black) 13
Comment Ter Level Powder Room Cabinet Colour/Style Cabinet Hardware Countertop Countertop Edge Flooring Floor Tile Grout	1111 2086 8796 11111 1111	Viking II-GEORGIAN-MOONLIGHT-3DL ***STD*** 9677-HARDWARE ***STD*** 6698-46-Countertop-PALOMA POLAR ETCHINGS FINISH-Formica ***STD*** N/A ****** GE.SU.ATR.1313 Sauble Anthracite (Black) 13 Grout-(47) Charcoal ***UPG***
Comment Ter Level Powder Room Cabinet Colour/Style Cabinet Hardware Countertop Countertop Edge Flooring Floor Tile Grout	1111 2086 8796 11111 1111	Viking II-GEORGIAN-MOONLIGHT-3DL ***STD*** 9677-HARDWARE ***STD*** 6698-46-Countertop-PALOMA POLAR ETCHINGS FINISH-Formica ***STD*** N/A ****** GE.SU.ATR.1313 Sauble Anthracite (Black) 13 Grout-(47) Charcoal ***UPG***

SHOWMICA RAVINDRAN/ Project: Country Lane Unit: 697-6, Phase: 6 Model: 20-2447 END B BARRINGTON

Opt. Lower Level Bedroom 4		
Flooring	1111	N/A *****
Comment		
Opt. Lower Level Bedroom 4 Hallway		\\ \tag{\tag{\tag{\tag{\tag{\tag{\tag{
Flooring	1111	N/A *****
Comment		
Opt. Lower Level Bedroom 4 Laundry	Mu	
Flooring	1111	N/A *****
3		
Floor Tile Grout	1111	N/A *****
Floor Tile Pattern		
		7
Opt. Cabinet Colour/Style - Uppers	1111	N/A *****
Opt. Cabinet Hardware - Uppers	1111	N/A *****
Comment	1111	
Comment		
Out Lawer Lavel Badraam 4 Bathraam	-	
Opt. Lower Level Bedroom 4 Bathroom		N/A *****
Cabinet Colour/Style	1111	JIN/A
Cabinet Hardware	1111	N/A *****
Countertop	1111	N/A *****
Countertop	1111	
Countertop Edge	1111	N/A *****
. 3		
Floor Tile	1111	N/A *****
	_	
Floor Tile Grout	1111	N/A *****
Floor Tile Pattern	1111	N/A *****
		76
Wall Tile	1111	N/A *****
Page 6 of 8		

SHOWMICA RAVINDRAN/ Project: Country Lane Unit: 697-6, Phase: 6 Model: 20-2447 END B BARRINGTON

		Closed.
Wall Tile Grout	1111	N/A *****
Wall Tile Pattern	1111	N/A *****
Opt. Shower Floor Tile	1111	N/A *****
op. chewer riser rise		
Opt. Shower Floor Tile Grout	1111	N/A *****
Opt. Shower Floor Tile Pattern	1111	N/A *****

Opt. Shower Jamb(s) and Sill(s)	1111	N/A *****
Plumbing Fixture (colour)	1111	N/A *****
Comment		

ver Level and Main Stairs		
Туре	1111	Oak Stairs ***STD***
Colour	7940	Sambucca STAIN TO COMPLIMENT HARDWOOD AND WILL VARY FROM FLOORING ***99***
Handrail/Pickets/Posts Type	8148	Single Collar Alt. Plain w/ Shoes with 3 1/2" Square/Cap Post(s)-BLACK ***2***
Handrail/Pickets/Posts Colour	7940	Sambucca STAIN TO COMPLIMENT HARDWOOD AND WILL VARY FROM FLOORING ***99***
Custom Stain/Paint	1111	N/A *****
Landing(s)	9059	Red Oak-Vintage 3 1/4 inch Pre-Sanded Smooth Unfinished Red Oak-Unfinished-3/4 inch x 3 1/4inch
Opt. Carpet Runner	1111	N/A *****
Comment		

Basement Stairs	
Туре	Paint Grade Stairs ***STD BASEMENT STAIR ***
Comment	

Throughout		
Switches and Plug	5796	Decora White Switches and Plugs ***STD***
Thresholds	2232	Metal Thresholds ***STD***
Underpad	1079	500 Series-Underpad ***STD***
Trim Size	8705	4 ¼ Baseboard and 2 ¾ Casings ***STD***
Trim - Paint Colour	1716	Trim-WHITE ***STD***
Page 7 of 8		

SHOWMICA RAVINDRAN/ Project: Country Lane Unit: 697-6, Phase: 6 Model: 20-2447 END B BARRINGTON

0			£	459	1	5
			П		4	_ 1
	ed: 6	7/	022	09:3	8:57	

Walls - P	Paint Colour	1717	22-Wall-WA	ARM GREY	***STD***	
Commer	nt					
Purchaser:	SHOWMICA RAVINDRAN		Date	Decor	Consultant	Date
Purchaser:			Date	Country La	ane	Date Approved

10 of 45



CONSTRUCTION SUMMARY

Lot: 697-6

Model: 20-2447 END B BARRINGTON

Project/Phase: Country Lane / 6

ADMIN FEE

Invoice Qty. Description

APPI	JAN	CES
-------------	------------	-----

Invoice	Qty.	Description	
1095	1	KITCHEN - APPLIANCES - CYCLONE 30 INCH WALL MOUNT CHIMNEY HOOD SS - SCB51930	
335,497			
03Nov22			
		CABINETRY-delete stove uppers; ELECTRICAL-delete std range hood; HEATING/AIR CONDITIONING-Duct	
		change to 6 in	
CABIN	ET	RY	
Invoice	Otv.	Description	

1 RITCHEN - APPLIANCES - CYCLONE 30 INCH WALL MOUNT CHIMNEY HOOD SS - SCB51930 335,497 03Nov22 *** CABINETRY-delete stove uppers; ELECTRICAL-delete std range hood; HEATING/AIR CONDITIONING-Dichange to 6 in RITCHEN - Cabinetry - Opt. Light Valance Trim Only - UPG 336,966 03Nov22 SKETCH # 4 1095 336,941 03Nov22 SKETCH # 4 DRYWAL-Notify; FRAMING-Modify Bulkhead; PAINTING-Notify 1095 335,964 03Nov22 I KITCHEN - CABINETRY-G01-Upgrade hardware for kitchen in a CONDO, TOWNHOUSE & SEMI-DETACHED model (stacked upper hardware is an additional charge see line G04 if applicable) VIKING 1095 335,967 03Nov22 I KITCHEN - CABINETRY-H34-Wall cabinet with shelf for microwave (finished interior) (opening 24?W x 13 3/4?H x 17?D) (not available in some laminates) VIKING 1095 335,877 03Nov22 SKETCH # 4 1095 335,871 1095 335,871 1095 335,871 1095 335,871 1095 335,871 1095 335,871 1095 335,871 1095 336,004 1 KITCHEN - CABINETRY-H34-Wall cabinet with shelf for microwave (finished interior) (opening 24?W x 13 3/4?H x 17?D) (not available in some laminates) VIKING 1095 335,871 1095 335,871 1095 336,004 1 KITCHEN - CABINETRY-H34-Wall cabinet with SINK TO DOUBLE SINKS INCLUDING ONE ADDITIONAL STD CHATEAU FAUCET OVERMOUNT COLONY SINK ONE EXTRA VANITY LIGHT AND CABINET CONVERSION 2D VIKING 330Nov22 SKETCH # 5 CABINETRY-2D Convert Cabinetry Viking; ELECTRICAL-Additional Vanity Light 1095 336,004	Invoice		
335,497 03Nov22 *** CABINETRY-delete stove uppers; ELECTRICAL-delete std range hood; HEATING/AIR CONDITIONING-Dechange to 6 in	Invoice	Qty.	Description
CABINETRY-delete stove uppers; ELECTRICAL-delete std range hood; HEATING/AIR CONDITIONING-Dechange to 6 in 1095	335,497	1	KITCHEN - APPLIANCES - CYCLONE 30 INCH WALL MOUNT CHIMNEY HOOD SS - SCB51930
336,966 03Nov22 SKETCH # 4 1095 336,941 03Nov22 SKETCH # 4 DRYWAL-Notify; FRAMING-Modify Bulkhead; PAINTING-Notify 1095 335,964 03Nov22 SKETCH # 4 DRYWAL-Notify; FRAMING-Modify Bulkhead; PAINTING-Notify 1095 335,987 03Nov22 SKETCH # 4 1095 335,987 03Nov22 SKETCH # 4 1095 335,871 03Nov22 SKETCH # 5 CABINETRY-DOLONY SINK ONE EXTRA VANITY LIGHT AND CABINET CONVERSION 2D VIKING SKETCH # 5 CABINETRY-2D Convert Cabinetry Viking; ELECTRICAL-Additional Vanity Light 1095 336,004 1 KITCHEN - CABINETRY-L01-PER KITCHEN Two-tone colour/style selection for island (must be of equal or lower level to main selection) VIKING 1 KITCHEN - CABINETRY-L01-PER KITCHEN Two-tone colour/style selection for island (must be of equal or lower level to main selection) VIKING 1 KITCHEN - CABINETRY-L01-PER KITCHEN Two-tone colour/style selection for island (must be of equal or lower level to main selection) VIKING 1 KITCHEN - CABINETRY-L01-PER KITCHEN Two-tone colour/style selection for island (must be of equal or lower level to main selection) VIKING 1 KITCHEN - CABINETRY-L01-PER KITCHEN Two-tone colour/style selection for island (must be of equal or lower level to main selection) VIKING 1 KITCHEN - CABINETRY-L01-PER KITCHEN Two-tone colour/style selection for island (must be of equal or lower level to main selection) VIKING 1 KITCHEN - CABINETRY-L01-PER KITCHEN Two-tone colour/style selection for island (must be of equal or lower level to main selection) VIKING 1 KITCHEN - CABINETRY-L01-PER KITCHEN Two-tone colour/style selection for island (must be of equal or lower level to main selection) VIKING 1 KITCHEN - CABINETRY-L01-PER KITCHEN Two-tone colour/style selection for island (must be of equal or lower level to main selection) VIKING 1 KITCHEN - CABINETRY-L01-PER KITCHEN Two-tone colour/style selection for island (must be			CABINETRY-delete stove uppers; ELECTRICAL-delete std range hood; HEATING/AIR CONDITIONING-Duct change to 6 in
1095 336,941 03Nov22 SKETCH # 4 DRYWAL-Notify; FRAMING-Modify Bulkhead; PAINTING-Notify 1095 335,964 03Nov22 I KITCHEN - CABINETRY-G01-Upgrade hardware for kitchen in a CONDO, TOWNHOUSE & SEMI-DETACHED model (stacked upper hardware is an additional charge see line G04 if applicable) VIKING 1095 335,987 03Nov22 I KITCHEN - CABINETRY-H34-Wall cabinet with shelf for microwave (finished interior) (opening 24?W x 13 3/4?H x 17?D) (not available in some laminates) VIKING SKETCH # 4 1095 335,871 03Nov22 MASTER ENSUITE - PLUMBING - OPTION FROM ONE SINK TO DOUBLE SINKS INCLUDING ONE ADDITIONAL STD CHATEAU FAUCET OVERMOUNT COLONY SINK ONE EXTRA VANITY LIGHT AND CABINET CONVERSION 2D VIKING 03Nov22 ** CABINETRY-2D Convert Cabinetry Viking; ELECTRICAL-Additional Vanity Light 1 KITCHEN - CABINETRY-L01-PER KITCHEN Two-tone colour/style selection for island (must be of equal or lower level to main selection) VIKING		1	KITCHEN - Cabinetry - Opt. Light Valance Trim Only - UPG
336,941 03Nov22 SKETCH # 4 DRYWAL-Notify; FRAMING-Modify Bulkhead; PAINTING-Notify	03Nov22		SKETCH # 4
SKETCH # 4 DRYWAL-Notify; FRAMING-Modify Bulkhead; PAINTING-Notify		1	KITCHEN - Cabinetry - VIKING II/III - Kitchen Classic Collection Upgrade Package - UPG
DRYWAL-Notify; FRAMING-Modify Bulkhead; PAINTING-Notify 1095	I ' I		SKETCH# 4
upper hardware is an additional charge see line G04 if applicable) VIKING 1095	03110122		
available in some laminates) VIKING SKETCH # 4 MASTER ENSUITE - PLUMBING - OPTION FROM ONE SINK TO DOUBLE SINKS INCLUDING ONE ADDITIONAL STD CHATEAU FAUCET OVERMOUNT COLONY SINK ONE EXTRA VANITY LIGHT AND CABINET CONVERSION 2D VIKING SKETCH # 5 CABINETRY-2D Convert Cabinetry Viking; ELECTRICAL-Additional Vanity Light KITCHEN - CABINETRY-L01-PER KITCHEN Two-tone colour/style selection for island (must be of equal or lower level to main selection) VIKING	335,964	1	KITCHEN - CABINETRY-G01-Upgrade hardware for kitchen in a CONDO, TOWNHOUSE & SEMI-DETACHED model (stacked upper hardware is an additional charge see line G04 if applicable) VIKING
SKETCH # 4 1095 335,871 03Nov22 1 MASTER ENSUITE - PLUMBING - OPTION FROM ONE SINK TO DOUBLE SINKS INCLUDING ONE ADDITIONAL STD CHATEAU FAUCET OVERMOUNT COLONY SINK ONE EXTRA VANITY LIGHT AND CABINET CONVERSION 2D VIKING SKETCH # 5 CABINETRY-2D Convert Cabinetry Viking; ELECTRICAL-Additional Vanity Light 1095 336,004 1 KITCHEN - CABINETRY-L01-PER KITCHEN Two-tone colour/style selection for island (must be of equal or lower level to main selection) VIKING	1095	1	KITCHEN - CABINETRY-H34-Wall cabinet with shelf for microwave (finished interior) (opening 24?W x 13 3/4?H x 17?D) (not
335,871 CHATEAU FAUCET OVERMOUNT COLONY SINK ONE EXTRA VANITY LIGHT AND CABINET CONVERSION 2D VIKING 336,004 CHATEAU FAUCET OVERMOUNT COLONY SINK ONE EXTRA VANITY LIGHT AND CABINET CONVERSION 2D VIKING SKETCH # 5 CABINETRY-2D Convert Cabinetry Viking; ELECTRICAL-Additional Vanity Light KITCHEN - CABINETRY-L01-PER KITCHEN Two-tone colour/style selection for island (must be of equal or lower level to main selection) VIKING	1 1		
VIKING 03Nov22 ** CABINETRY-2D Convert Cabinetry Viking; ELECTRICAL-Additional Vanity Light 1095	1 1	1	
1095 1 KITCHEN - CABINETRY-L01-PER KITCHEN Two-tone colour/style selection for island (must be of equal or lower level to main selection) VIKING	03Nov22		VIKING SKETCH # 5
336,004 selection) VIKING	**		CABINETRY-2D Convert Cabinetry Viking; ELECTRICAL-Additional Vanity Light
ONL 32 SVETCH # 4		1	KITCHEN - CABINETRY-L01-PER KITCHEN Two-tone colour/style selection for island (must be of equal or lower level to main selection) VIKING
U3NOV22 SKETCH # 4	03Nov22		SKETCH # 4
1095 1 Kitchen/Breakfast - Hardwood - 3-1/4 in Vintage NSS Red Oak - Kitchen/Breakfast - UPG 336,125		1	Kitchen/Breakfast - Hardwood - 3-1/4 in Vintage NSS Red Oak - Kitchen/Breakfast - UPG
03Nov22 ** CABINETRY-Raise Cabinet; CERAMICS-Delete Std Ceramics	03Nov22		CARINETDY Daisa Cabinat: CEDAMICS Dalata Std Caramias

Page 1 of 5

Printed and Sent: 03-Nov-22

construction summary of 45



Lot: 697-6

Model: 20-2447 END B BARRINGTON Project/Phase: Country Lane / 6

CERAMICS

Invoice		
	Qıy.	Description
1095 335,537 03Nov22	1	KITCHEN - CERAMICS - ADDITIONAL BACKSPLASH DUE TO INSTALL CHIMNEY HOODFAN IN KITCHEN - KITCHEN - UPGRADE 1
1095 340,226 03Nov22	1	Kitchen Optional Backsplash - Ceramics - Upgrade 1 Tile - Kitchen Optional Backsplash - UPG
1095 340,251 03Nov22	1	Foyer Floor - Ceramics - Upgrade 2 Tile - Foyer Floor - UPG
1095 340,231 03Nov22	1	Master Ensuite Shower Floor - Ceramics - Upgrade 1 Tile - Master Ensuite Shower Floor - UPG
1095	1	Master Ensuite Shower Wall - Ceramics - Upgrade 1 Tile - Master Ensuite Shower Wall - UPG
340,230 03Nov22	•	INSTALL FLOOR TILE ON WALL
1095 335,552 03Nov22	1	MASTER ENSUITE - CERAMICS - UPGRADED SHOWER JAMB/SILL COLOUR MOONLIGHT BLACK #8927
1095 340,322 03Nov22	1	Master Ensuite Shower Floor - Ceramics - Upgrade Grout - Master Ensuite Shower Floor - UPG
1095 340,321 03Nov22	1	Master Ensuite Shower Wall - Ceramics - Upgrade Grout - Master Ensuite Shower Wall - UPG
1095 340,327 03Nov22	1	L. Flr.Pow Floor - Ceramics - Upgrade Grout - L. Flr.Pow Floor - UPG
1095 340,326 03Nov22	1	Laundry Floor - Ceramics - Upgrade Grout - Laundry Floor - UPG
1095 340,323 03Nov22	1	Master Ensuite Floor - Ceramics - Upgrade Grout - Master Ensuite Floor - UPG
1095	1	Kitchen Optional Backsplash - Ceramics - Install in Specified Pattern - Kitchen Optional Backsplash - UPG
340,330 03Nov22		IN BRICK PATTERN
1095 336,125 03Nov22 **	1	Kitchen/Breakfast - Hardwood - 3-1/4 in Vintage NSS Red Oak - Kitchen/Breakfast - UPG CABINETRY-Raise Cabinet; CERAMICS-Delete Std Ceramics

DisciplineMS.rpt 13dec21 Page 2 of 5 Printed and Sent: 03-Nov-22

12 of 45 construction summary



Lot: 697-6

Model: 20-2447 END B BARRINGTON

Project/Phase: Country Lane / 6

COFFERED CEILING

Invoice	Qty.	Description
1095	1	GREAT ROOM - Coffered Ceiling - Install Coffered Ceiling - GREAT ROOM - UPG
337,713		
03Nov22		SKETCH # 3

DRYWALL

Invoice	Qty.	Description
1095 336,941	1	KITCHEN - Cabinetry - VIKING II/III - Kitchen Classic Collection Upgrade Package - UPG
03Nov22 **		SKETCH # 4 DRYWAL-Notify; FRAMING-Modify Bulkhead; PAINTING-Notify
1095	1	GREAT ROOM - Coffered Ceiling - Install Coffered Ceiling - GREAT ROOM - UPG
337,713 03Nov22 **		SKETCH# 3
1095	1	- Drywall - Smooth Ceilings - Main Floor - UPG
337,754		
03Nov22		PAINTING-Notify

ELECTRICAL

ELECI		
Invoice	Qty.	Description
1095 335,497 03Nov22 **	1	KITCHEN - APPLIANCES - CYCLONE 30 INCH WALL MOUNT CHIMNEY HOOD SS - SCB51930 CABINETRY-delete stove uppers; ELECTRICAL-delete std range hood; HEATING/AIR CONDITIONING-Duct change to 6 in
1095 335,569 03Nov22	2	- ELECTRICAL - ADDITIONAL SWITCH 1 FOR CAPPED CEILING IN GREAT ROOM AND 1 FOR CAPPED CEILING ABOVE KITCHEN ISLAND SKETCH # 3
1095 335,570 03Nov22	2	- ELECTRICAL - CEILING ROUGH-IN (CAPPED) 1 IN GREAT ROOM AND 1 IN KITCHEN ABOVE CENTERED+/-ABOVE ISLAND SKETCH # 3
1095 335,575 03Nov22	1	KITCHEN - ELECTRICAL - EXTRA WALL INTERIOR OUTLET (120V/15A) ON A SEPARATE CIRCUIT (ON ARCFAULT) FOR MICROWAVE SHELF SKETCH # 4
1095 335,578 03Nov22	1	GREAT ROOM - ELECTRICAL - EXTRA WALL INTERIOR OUTLET ON EXISTING CIRCUIT (DOES NOT INCLUDE KITCHEN OUTLETS) LOCATE 70" +/- ABOVE FIREPLACE SKETCH # 3
1095 335,871 03Nov22 **	1	MASTER ENSUITE - PLUMBING - OPTION FROM ONE SINK TO DOUBLE SINKS INCLUDING ONE ADDITIONAL STD CHATEAU FAUCET OVERMOUNT COLONY SINK ONE EXTRA VANITY LIGHT AND CABINET CONVERSION 2D VIKING SKETCH # 5 CABINETRY-2D Convert Cabinetry Viking; ELECTRICAL-Additional Vanity Light

DisciplineMS.rpt 13dec21

Page 3 of 5

Printed and Sent: 03-Nov-22

13 of 45



CONSTRUCTION SUMMARY

Lot: 697-6

Model: 20-2447 END B BARRINGTON

Project/Phase: Country Lane / 6

FRAMING

Invoice	Qty.	Description
1095	1	KITCHEN - Cabinetry - VIKING II/III - Kitchen Classic Collection Upgrade Package - UPG
336,941		
03Nov22	ı	SKETCH # 4
**		DRYWAL-Notify; FRAMING-Modify Bulkhead; PAINTING-Notify

GRANITE

Invoice	Qty.	Description			
1095	1	Kitchen - Granite - Countertop - 3/4" GROUP 2 with double edge - Kitchen - UPG			
338,195					
03Nov22					

HARDWOOD

Invoice	Qty.	Description
1095	2	- PAINT - STAIN STAIR LANDING IN SAMBUCCA. LANDING UNDER 25 SQ.FT. EACH
335,692		
03Nov22		
**		HARDWOOD-Supply and Install smooth UNFINISHED pre-sanded red oak at stair landing(s)
1095	1	Kitchen/Breakfast - Hardwood - 3-1/4 in Vintage NSS Red Oak - Kitchen/Breakfast - UPG
336,125		
03Nov22		
		CABINETRY-Raise Cabinet; CERAMICS-Delete Std Ceramics

HEATING / AIR CONDITIONING

Invoice	Qty.	Description
1095	1	KITCHEN - APPLIANCES - CYCLONE 30 INCH WALL MOUNT CHIMNEY HOOD SS - SCB51930
335,497		
03Nov22 **	Nov22 CABINETRY-delete stove uppers; ELECTRICAL-delete std range hood; HEATING/AIR change to 6 in	
1095 335,680 03Nov22	1	KITCHEN - HEATING/AIR - ROUGH-IN GAS LINE FOR STOVE AT 2ND FLOOR UP TO 40 FT (HOOK UP NOT INCLUDED); LEAVE STANDARD 120 VOLT ELECTRICAL OUTLET ON A SEPARATE CIRCCUIT STANDARD 220V TO REMAIN(TOWNS) SKETCH #'s 3 AND 4
03110122		ELECTRICAL-Notify

MIRRORS/GLASS PRODUCTS				
Invoice	Qty. Description			
1095 338,688 03Nov22		MASTER ENSUITE - Mirrors/Glass Products - Upgrade to Frameless clear glass with D-Ring Handle in chrome - Master Ensuite - UPG SKETCH # 5		

DisciplineMS.rpt 13dec21 Page 4 of 5

Printed and Sent: 03-Nov-22

14 of 45 construction summary



Lot: 697-6

Model: 20-2447 END B BARRINGTON

Project/Phase: Country Lane / 6

PAINTING

Invoice	Qty.	Description	
1095 336,941	1	KITCHEN - Cabinetry - VIKING II/III - Kitchen Classic Collection Upgrade Package - UPG	
03Nov22 SKETCH # 4		SKETCH # 4 DRYWAL-Notify; FRAMING-Modify Bulkhead; PAINTING-Notify	
1095 337,713	1	GREAT ROOM - Coffered Ceiling - Install Coffered Ceiling - GREAT ROOM - UPG	
03Nov22 **		SKETCH # 3	
1095 337,754 03Nov22	1	- Drywall - Smooth Ceilings - Main Floor - UPG	
**		PAINTING-Notify	
1095 335,692	2	- PAINT - STAIN STAIR LANDING IN SAMBUCCA. LANDING UNDER 25 SQ.FT. EACH	
03Nov22		HARDWOOD-Supply and Install smooth UNFINISHED pre-sanded red oak at stair landing(s)	

PLUMBING

Invoice	Otv.	Description
IIIVOICC	Qıy.	Description

r			
-	1095	1	MASTER ENSUITE - PLUMBING - OPTION FROM ONE SINK TO DOUBLE SINKS INCLUDING ONE ADDITIONAL STD
	335,871	ı	CHATEAU FAUCET OVERMOUNT COLONY SINK ONE EXTRA VANITY LIGHT AND CABINET CONVERSION 2D
	333,671		VIKING
١	03Nov22		SKETCH # 5
ı			CABINETRY-2D Convert Cabinetry Viking; ELECTRICAL-Additional Vanity Light

STRUCTURED WIRING

Invoice	Qty.	Description	

1095 335,883	GREAT ROOM - STRUCTURED WIRING - CONDUIT PIPE TO ABOVE FIREPLACE ROUGH-IN LOCAATE 70" +/- FROM FLOOR ABOVE FIREPLACE
03Nov22	SKETCH # 3

DisciplineMS.rpt 13dec21 Page 5 of 5

20-2447 END ELEV. B

Model: 20-2447 END B BARRINGTON


15 of 45

The Barrington

ELEVATION A & B: 2,504 SQ. FT.
THE TRAILS OF

COUNTRY LANE

Sketch #1



BASEMENT ELEVATION A & B END

Legal Plan Jan. 22, 2021

Model: 20-2447 END B BARRINGTON

16 of 45

The Barrington


20-2447 END ELEV. B

ELEVATION A & B: 2,504 SQ. FT.

THE TRAILS OF

COUNTRY LANE

Sketch#2



LOWER LEVEL ELEVATION B END

Legal Plan Jan. 22, 2021

Model: 20-2447 END B BARRINGTON

17 of 45


The Barrington

20-2447 END ELEV. B

ELEVATION A & B: 2,504 SQ. FT.

THE TRAILS OF
COUNTRY LANE

Sketch #3



Project: Country Lane 197-6, Phase: 6 Model: 20-2447 END

20-2447 END B BARRINGTON

of 45 18

Z

CITCHENS LIMITED 1350 Shawson Drive, Mississauga, ON LAW 1C5

COUNTRY LANE, WHITBY HEATHWOOD HOMES

MODEL: 20-2447 (2006)

STANDARD CONTRACT INCLUDES:

Hood Opening: 30"W builder hood Appliance Openings

Fridge Opening: 37 3/8 "W X 73 3/8" Fridge cabinet: 30cm deep

Stove Opening: 30" Freestanding Dishwasher Opening: 24"

Standard Kitchens Scope: X - 100cm H wall cabinets

Std. Metabox Crawers- not soft close Std. Blum Hinges-not soft close

Backing on all cabinets Min 40cp W drawer

Upgrade applied paneled fridge & dishwashers supply only (appliance Countertop by others nardware by others)

Optional Upgrade to Includes: Classic Collection


Top Drawer Construction (In lieu of Tandem Box Soft Close Drawers Standard bank of drawers)

Blumotion Soft Close Hinges for Doors Deep Fridge Upper w/Deep Panel Crown Moulding

Tall upper Cabinets

THIS DRAWING IS FOR DESIGN PURPOSES ONLY.
IT IS NOT AN EXACT RENDITION.

6/28/2021



Model: 20-2447 END B BARRINGTON

19 of 45

The Barrington


20-2447 END ELEV. B

ELEVATION A & B: 2,504 SQ. FT.

THE TRAILS OF

COUNTRY LANE

Sketch #5



5× 1/2

Legal Plan Jan. 22, 2021

Project: Country Lane Unit: 697-6, Phase: 6 Model: 20-2447 END B BARRINGTON

20 of 45





NFAS NF17 Mantel


Model: 20-2447 END B BARRINGTON

21 of 45



NS1930U/9





NS1930U/9 SPECIFICATION

Model NS1930U/9 is a single bowl, undermount sink manufactured for Franke Kindred Canada Limited from 18 gauge, 18-10 stainless steel. Product has mirror finished rim and brush finished bowl. Sink is fully undercoated. Basket strainer waste fitting (3 1/2", 89 mm) are included. Sink is backed with a limited buyer lifetime warranty.

- O.D. 18 3/4" x 29 3/4" x 8 1/2" (48 x 76 x 22 cm)
- Recommended for minimum 36" cabinet

Franke Kindred Canada Limited

P.O. Box 190, 1000 Franke Kindred Road, Midland, Ontario, Canada, L4R 4K9 Phone: 866-687-7465 Fax: 800-361-8408

Model: 20-2447 END B BARRINGTON

22 of 45

MOEN

FAUCET DESCRIPTION

Reflex™ pulldown system offers smooth operation, easy movement and secure docking Power Clean™ spray technology Metal construction with various finishes identified by suffix

Quick connect installation

Pulldown spray with 68" braided hose Flexible supply lines with 3/8" compression fittings

High arc spout provides height and reach to fill or clean large pots while pulldown wand provides the maneuverability for cleaning or rinsing 360° rotating spout

Faucet designed for handle to be mounted on right side only

OPERATION

Lever style handle

Temperature controlled by 100° arc of handle travel

Operates with less than 5 lbs. of force

• Operates in stream or spray mode in the pullout or retracted position **FLOW**

Flow is limited to 1.5 gpm (5.7 L/min) max at 60 psi

CARTRIDGE

• 1255™ Duralast™ cartridge

STANDARDS


Third party certified to IAPMO Green, ASME A112.18.1/CSA B125.1 and all applicable requirements therein including NSF 61/9G & 372

- Meets CalGreen and Georgia SB370 requirements Complies with California Proposition 65 and with the Federal Safe Drinking
- The backflow protection system in the device consists of two independently operating check valves, a primary and a secondary which prevent backflow
- ADA 🖒 for lever handle

WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the
- 10 year limited warranty when used in a multifamily installation
- 5 year limited warranty when used in a commercial installation Visit www.moen.com/support for complete details and limitations

Specifications




ALIGN™ **Single Handle High Arc Pulldown Kitchen Faucet**

Models: 7565 series

NOTE: THIS FAUCET IS DESIGNED TO BE INSTALLED THROUGH 1 HOLE, 1-1/2" (38mm) MIN. DIA. (OPTIONAL 3-HOLE ESCUTCHEON 141002 AVAILABLE)





FOR MORE INFORMATION CALL: 1-800-BUY-MOEN

www.moen.com

Rev. 6/20



b BARRIER FREE (ABOVE COUNTER OR DROP-IN ONLY)

BOULEVARD® PEDESTAL SINK VITREOUS CHINA

BOULEVARD® PEDESTAL SINK

☐ 0641.800 Faucet holes on 8" (203mm) centers (Illustrated)

STD • 0641.400 Faucet holes on 4" (102mm) centers

☐ 0641.100 Center hole only

- Classic styled rectangular pedestal lavatory
- · Vitreous china
- Rear overflow
- Supplied with mounting kit
- Right Height® for greater comfort during use
- Faucet ledge with large deck area (faucet not included)
- Design coordinates with Boulevard® Toilet
- Basin has flat bottom to also allow use as an above counter sink or a drop-in sink (with u-shaped cut out)

Nominal Dimensions:

24" x 19" x 35-1/2" (610 x 483 x 902mm)

- ☐ 0641.008 Pedestal top-8" (203mm) centers
- ☐ 0641.004 Pedestal top-4" (102mm) centers
- ☐ 0641.001 Pedestal top-center hole only
- ☐ 0010.000 Pedestal only

Bowl sizes:

17" (432mm) wide, 12-1/2" (318mm) front to back, 5" (127mm) deep

Compliance Certifications -

Meets or Exceeds the Following Specifications:

• ASME A112.19.2 - 2008/CSA B45.1-08

To Be Specified:

- ☐ Color: ☐ White ☐ Linen
- ☐ Faucet Finish:
- Supplies:
- ☐ 1-1/4" Trap:
- □ Nipple:




SEE REVERSE FOR ROUGHING-IN DIMENSIONS

^{*} See faucet section for additional models available

Model: 20-2447 END B BARRINGTON



BOULEVARD® PEDESTAL SINK



ABOVE COUNTER AND DROP-IN SINK CONFIGURATIONS MEET THE AMERICANS WITH DISABILITIES ACT GUIDELINES AND ANSI A117.1 ACCESSIBLE AND USABLE BUILDINGS AND FACILITIES - CHECK LOCAL CODES.

Top of sink installed at 34" (864mm) height from finished floor. Sink installed 5" (127mm) minimum from front edge of countertop. Provide 27" (686mm) knee clearance area.

NOTES:

* DIMENSIONS SHOWN FOR LOCATION OF SUPPLIES AND "P" TRAPS ARE SUGGESTED.

▼ PEDESTAL ANCHORING SCREWS NOT INCLUDED.

■ SUITABLE FOR REINFORCEMENT ONLY. ACTUAL DIMENSIONS MUST BE TAKEN FROM FIXTURE.

FITTING NOT INCLUDED AND MUST BE ORDERED SEPARATELY.

PROVIDE SUITABLE REINFORCEMENT FOR ALL WALL SUPPORTS. INSTALLATION INSTRUCTIONS SUPPLIED WITH LAVATORY.

IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerance established by ANSI Standard A112.19.2 These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

© 2018 AS America Inc.

Model: 20-2447 END B BARRINGTON






BARRIER FREE

COLONY™ COUNTERTOP SINK

VITREOUS CHINA

COLONY COUNTERTOP SINK

- · Vitreous china
- Self-rimming
- · Front overflow
- · Supplied with template
- Faucet deck (Faucet shown not included)




Centre hole only


Nominal Dimensions: 521 x 448mm (20-1/2" x 17-5/8")


Bowl sizes:

422mm (16-5/8") wide, 279mm (11") front to back, 143mm (5-5/8") deep









COMPLIANCE CERTIFICATIONS -

Meets or exceeds the following Specifications:

- ASME A112.19.2M for Vitreous China Fixtures.
- · CAN/CSA B45 Series.

To Be Specified

- ☐ Colour: ☐ White ☐ Bone ☐ Silver Gray ☐ Linen
- □ Faucet*:
- □ Faucet Finish:
- Supplies & Stops:
- ☐ Trap 1-1/4" (32 mm):

* DIMENSIONS SHOWN FOR LOCATION OF SUPPLIES AND "P" TRAP ARE SUGGESTED. FOR COUNTERTOP CUTOUT AND INSTALLATION INSTRUCTIONS USE TEMPLATE SUPPLIED WITH SINK.

SUPPLIED WITH SINK.

FAUCETS NOT INCLUDED AND MUST BE ORDERED SEPARATELY.

IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ANSI Standard A112.19.2.

These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

BAS-198

^{*} See faucet section for additional models available

Model: 20-2447 END B BARRINGTON

26 of 45



DEMI™ **Product Specification Sheet**

Two Piece Freestanding Collection

CF2007 Two Piece Freestanding Soaker


Size: 60" x 32" x 22"

1524 mm x 813 mm x 559 mm




- Vacuum formed acrylic reinforced with fiberglass
- Scratch, stain and fade resistant high gloss finish
- Installation friendly two piece design
- Accepts deck mounted faucet
- Includes integral pop up drain and rectangular overflow
- Includes levelling feet


TWO PIECE ASSEMBLY



END VIEW



TOP VIEW



GENERAL SPECIFICATIONS

Average Weight 90 lb 41 kg Bathing Well at bottom 43"x 20" 1092 x 508 mm 195 litres Capacity Drain to Overflow Water Depth Drain to Overflow 406 mm Drain Opening (dia.) 51 mm Overflow Opening 2 1/4"x 1/2" 57 x 13 mm Drain to Floor Clearance

NOTES: Please confirm measurements on actual product to ensure proper identification. Bathtub to be installed on the floor supported by 5 self levelling feet. Adjust if required to level the bathtub for adequate drainage. Refer to installation instructions for additional information.

IMPORTANT: Dimensions of fixtures are nominal and may vary \pm %" (6 mm). Weight may vary \pm 5 lb (2.3 kg). Drawing is not to scale. These measurements are subject to change at manufacturer's discretion.

Compliance Certifications -

Meets or Exceeds the following Specifications:

CAN/CSA - B45 Series





60 Shorncliffe Rd., Toronto, Ontario M8Z 5K1 Telephone: 416.231.9030 Fax: 416.231.0929 Fax: 416.231.0929 www.mirolin.com

Customer Service: 416.231.5790 Canada, U.S.A.: 800.**MIROLIN**(647-6546) Fax, Canada: 800.463.2236

R0084162 25 Sep. 2018

Model: 20-2447 END B BARRINGTON

27 of 45

American Standard

Style That Works Better

FloWise™ DUAL FLUSH **ELONGATED TOILET**

VITREOUS CHINA


FloWise™ DUAL FLUSH ELONGATED TOILET

2476 216

- Vitreous china
- · Low-consumption Dual Flush Full flush 6.0 Lpf/1.3 gpf, Partial flush 3.0 Lpf/0.66 gpf.
- · Elongated wash down bowl
- · Internal trapway fully-glazed, 2-1/4" (57mm) ballpass
- · Concealed trapway bowl
- · Chrome-plated top mounted push button actuator
- Easy to clean sanitary dam on bowl
- Includes Elongated Slow Close Seat
- 100% factory flush tested
- · 2 bolt caps

Separate Component Parts:

- ☐ 3067 316 Elongated Bowl with Slow Close Seat
- **4035 216** Unlined Tank



- **☐** 3067 316 Elongated Bowl
- **4035 516** Lined Tank

Nominal Dimensions: 794 x 432 x 765mm (31-1/4" x 17" x 30-1/8")


Compliance Certifications -Meets or Exceeds the Following Specifications:


- ASME A112.19.2M (and 19.6M)
- · CAN/CSA B45 series

To Be Specified

TOI-284

- Colour: 020 White
- Supply with stop:





08/08

NOTES:
THIS TOILET IS DESIGNED TO ROUGH-IN AT A MINIMUM DIMENSION OF 305MM (12")
FROM FINISHED WALL TO C/L OF OUTLET.
SUPPLY NOT INCLUDED WITH FIXTURE AND MUST BE ORDERED SEPARATELY.
* DIMENSION SHOWN FOR LOCATION OF SUPPLY IS SUGGESTED.
FOR ADDITIONAL INFORMATION REFER TO INSTALLATION INSTRUCTIONS SUPPLIED.
IMPORTANT. Dimensions of fixture are peripaid and may use within the prepare of the present

IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerance established by ANSI Standard A112.19.2

established by Anki Graindau A 112.19.2. These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

UPGRADED VALUE ADDED FEATURES AT NO EXTRA CHARGE

© 2008 American Standard

Model: 20-2447 END B BARRINGTON

28 of 45

MOEN[®]

DESCRIPTION

- Metal construction with various finishes identified by suffix
- 16" long 3/8" tubing connections Includes metal or 50/50 pop-up type waste assembly where noted

OPERATION

- Pivot action lever style handle Temperature controlled through 180° degree arc of handle travel **FLOW**

Flow is limited to 1.5 gpm max (5.7L/min) at 60 psi

CARTRIDGE

- 1225 cartridge design
- Nonmetallic/nonferrous and stainless steel material
- Can accommodate reversed piping and back to back installations

- Third party certified to WaterSense®, CSA B-125.1, ASME A112.18.1 and all applicable requirements referenced therein including NSF61/9
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act

 ADA for lever handle

WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original consumer purchaser
- 5 year warranty if used in commercial installations

Specifications



CHATEAU® Single-Handle Lavatory Faucet

with Metal Waste Assembly


Model: L4625 series L4631BC **Bulk Packed (12 per carton):** L64624 series

with 50/50 Waste Assembly **Bulk Packed (12 per carton):** L64625 series

Less Waste **Bulk Packed (12 per carton):** L64600 series

NOTE: THIS FAUCET IS DESIGNED TO BE INSTALLED THRU 3-1" DIA. HOLES, 2" ON CENTER





FOR MORE INFORMATION CALL: 1-800-BUY-MOEN

www.moen.com

Rev 8/15

Model: 20-2447 END B BARRINGTON

29 of 45



Buy it for looks. Buy it for life.®

There is more than 1 version of this model. Page down to identify the version you have.

- Metal construction with various finishes identified by suffix
- Includes non-metalic showerhead, arm, flange and non-metalic diverter tub spout

OPERATION

- Handle operates counterclockwise through a 270° arc with off at 6 o'clock and maximum hot at the 9 o'clock position. Shut off in clockwise direction
- Adjustable temperature limit stop to control maximum hot water temperature
- Pressure balancing mechanism maintains selected discharge temperature to $\pm\,3^\circ$

- Showerhead is limited to 2.5 gpm (9.5 L/min) at 80 psi EP suffix models are limited to 1.75 gpm (6.6 L/min) at 80 psi
- NH suffix models contain no showerhead

CARTRIDGE

- 1222 cartridge design Accommodates back to back installations
- Nonmetallic/nonferrous and stainless steel material

STANDARDS

- Third party certified to meet ASME A112.18.1/CSA B125.1 and all applicable requirements referenced therein
- EP suffix models are third party certified to WaterSense®

ADA (for lever handle

6.5" (165mm) ESC. DIAM.

WARRANTY

Lifetime limited warranty against leaks, drips and finish defects

2"CC (51mm) 1 7/8" IPS (48mm) MAX WALL

FINISHED WALL LINE

4-1/2" (114mm)

WALL OPENING

(133mm

7-1/2" (190mm)

to the original consumer purchaser 5 year warranty if used in commercial installations

Specifications





CHATEAU° POSI-TEMP° Single-Handle Tub/Shower Trim Kit


Models: TL181 series - valve trim only (Bulk Packed 12 per carton) TL182 series - shower trim only (Bulk Packed 12 per carton) TL183 series - tub/shower trim

(Bulk Packed 12 per carton)

Valves: 62300 series

2500 series





THIN WALL APPLICATION

CRITICAL DIMENSIONS

THICK WALL APPLICATION

FLOOR LINE

— 1/2" MIN. CC (13mm) 5/8" MIN. IPS (16mm)

2 1/2" MAX. (63mm)

SHOWER

48" (1219mm) 32" (813mm)

AND TUB ONLY

6'-6" (1981mm) NOMINAL

(DO NOT SCALE)

TL183sp: Rev. 5/13

FOR MORE INFORMATION CALL: 1-800-BUY-MOEN

www.moen.com

Model: 20-2447 END B BARRINGTON

30 of 45

MOEN[®]

DESCRIPTION

 Metal construction with various finishes identified by suffix OPERATION

- · Lever style handles with hot and cold color indicator
- Rotate hot side handle counterclockwise to open (clockwise to close) and the cold side handle (clockwise to open) and (counterclockwise to close)


STANDARDS

- Third party certified to: ASME A112.18.1/CSA B-125.1, and all applicable requirements referenced therein
- ADA 🕒 for lever handles

WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original homeowner
- 10 year limited warranty when used in a multi-family installation
- 5 year limited warranty when used in a commercial installation Visit www.moen.com/support for complete details and limitations


Specifications




CHATEAU® Two-Handle Garden Tub Trim

Models: T994 series

Valves: 4792, 4793, 4794, 4796, 4797, 4798





CRITICAL DIMENSIONS

FOR MORE INFORMATION CALL: 1-800-BUY-MOEN

www.moen.com

02/28/2019 SPC12695 5000011207: Released 00

Rev. 3/19

Model: 20-2447 END B BARRINGTON

31 of 45

SC(B)519 | ALITO Collection





Wall Mount

Strong and sturdy with attractive lines and an imposing frame, the SC(B)519 is fitted with a time-delay OFF feature up to nine minutes, a 550 CFM fan, two bright front mounted LED lights and a digital three-speed push button control panel.

Green Features



3 Speed Push Button Control Panel



Time-Delay OFF Feature



Long-Lasting LED Lights



Grease Cup



Model Colour Ducting Filters Size CF	M
--------------------------------------	---

SCB51930	Stainless Steel	6"	Baffle	30"	550
SCB51936	Stainless Steel	6"	Baffle	36"	550

Cyclone Range Hoods Inc.

Model: 20-2447 END B BARRINGTON


32 of 45


SC(B)519 | ALITO Collection



Features

- · Wall mount range hood
- 6" round duct adapter
- Non-stick aluminum fan blades
- 3 speed push button control
- 2 LED lights (2 x 1.4W, 4000K)
- · Quick release aluminum mesh filters
- · Standard chimney fits up to 9 ft. ceiling
- · Up to 9 minutes time-delay OFF feature
- · Plug-in connection





Options

• Filters:

SCB519 - Quick Release Stainless Steel Baffle Filters

Chimney Flues:

A1.CH10 - short (7'-8' ceilings)

A1.CH18 - standard (8'-9' ceilings)

A1.CH30 - extended (9'-11' ceilings)

• Widths: 24", 30", 36"

Specifications

Air Flow Volume: 550 CFM

Electrical Connection: 120 V/60 Hz

Power Consumption: 300 Watts

Current: 2.5 Amps

- Fan Speed: 1599 RPM

Fan Type: Centrifugal Blower

· Finishes: Stainless Steel

Ducting: 6" Round

Noise Level: Min. 2 Sones
 Max. 6 Sones



Model: 20-2447 END B BARRINGTON

33 of 45



Whirtpool® 21 cu. ft. Top-Freezer Refrigerator WRT541SZD



Fingerprint-Resistant Stainless WRT541SZDZ

Also available in:

White	WRT541SZDW
Black	WRT541SZDB
Monochromatic Stainless Steel	WRT541SZDM

Capacity		
Total Capacity	21 cu. ft.	
Refrigerator Capacity	15 cu. ft.	
Freezer Capacity	6 cu. ft.	
General Features & Properti	es	
EZ Connect Icemaker Kit		
LED Interior Lighting		
ENERGY STAR® Certified		
Electronic Temperature Controls		
Freezer Temperature Controls		
Clear Door Bins		
Adjustable Door Bins		
Quiet Cooling		
Fingerprint Resistant		
Electrical Details		
Amps	6.5	
Volts	115	
Certifications		
ADA Compliant	Yes	
ENERGY STAR® Certified	Yes	

Technical Details	
Refrigerator Type	Top-Freezer
Number of Doors	2
Number of Interior Refrigerator Shelves	3
Number of Refrigerator Door Bins	1 Fixed, 4 Adjustable
Number of Interior Freezer Shelves	1
Number of Freezer Door Bins	2 Fixed
Lighting Type	LED
Ice Maker	Optional
Ice Maker Location	Freezer
Dispenser Type	N/A
Dimensions	
Product Dimensions (H x W x D)	66-1/4" x 32-3/4" x 34"
Depth with Door Open 90°	62-1/4"
Cutout Dimensions	Allow extra 1/2" on sides and top Allow extra 1" on rear
Reference Material	

Key Features & Benefits

Frameless Glass Shelves


Store more items on wall-to-wall shelves for greater storage flexibility.

Flexi-Slide™ Bin

Make space for tall items with the bin that quickly and easily moves side to side.

Humidity-Controlled Crispers

Store fruits and vegetables in their ideal environment.



Dimension Guide Use & Care Guide

Energy Guide

Warranty

NOTE: Dimensions are for planning purposes only. For complete details, see Installation Instructions packed with product. Specifications subject to change without notice.

®/™ © 2020. All rights reserved. Printed in the U.S.A. D200052XXC. WRT541SZDSPECSHEETV01.

Model: 20-2447 END B BARRINGTON

34 of 45



Top Mount Refrigerator

PRODUCT MODEL NUMBERS

WRT311FZD WRT511SZD WRT541SZD

Electrical: A 115-volt, 60-Hz, AC-only, 15-or 20-amp fused, grounded electrical supply is required. It is recommended that a separate circuit serving only your refrigerator be provided. Use an outlet that cannot be turned off by a switch. Do not use an extension cord.


NOTE: Before performing any type of installation, cleaning, or removing a light bulb, turn the control (Thermostat, Refrigerator or Freezer Control depending on the model) to OFF and then disconnect the refrigerator from the electrical source. When you are finished, reconnect the refrigerator to the electrical source and reset the control (Thermostat, Refrigerator or Freezer Control depending on the model) to the desired setting. See "Using the Controls."

Water: A cold water supply with water pressure between 30 and 120 psi (207 and 827 kPa) is required to operate ice maker and water dispenser. If you have questions about your water pressure, call a licensed, qualified plumber.

IMPORTANT: The pressure of the water coming out of a reverse osmosis system going to the water inlet valve of the refrigerator needs to be between 30 and 120 psi (207 and 827 kPa).


Reverse Osmosis Water Supply: If a reverse osmosis water filtration system is connected to your cold water supply, the water pressure to the reverse osmosis system needs to be a minimum of 40 to 60 psi (276 to 414 kPa).

PRODUCT DIMENSIONS



Model Number	Model Size	Reversible Door	Height - Overall "A"	Height - Top of Cabinet "B"	Depth - Door Open 90° "C"	Depth - With Handles "D"	Depth - Without Handles "E"	Depth - Cabinet Only "F"	Width - Cabinet "G"
WRT311FZD	20.5 cu. ft.	Yes	661/4" (168.3 cm)	65½" (166.4 cm)	621/4" (158.1 cm)	32 ⁷ / ₈ " (83.5 cm)	30 ⁵ / ₈ " (77.8 cm)	28½" (72.4 cm)	32¾" (83.2 cm)
WRT511SZD WRT541SZD	21.3 cu. ft.	Yes	66½" (168.3 cm)	65½" (166.4 cm)	62½" (158.1 cm)	34" (86.4 cm)	32½" (82.3 cm)	28½" (72.4 cm)	32¾" (83.2 cm)

LOCATION REQUIREMENTS



To ensure proper ventilation for your refrigerator, allow for a $\frac{1}{2}$ " (1.25 cm) space on each and between overhead cabinets and refrigerator top. Allow at least 1" (2.5 cm) between back of cabinet and the wall. If your refrigerator has an ice maker, make sure you leave some extra space at the back for the water line connections.

If you are installing your refrigerator next to a fixed wall, leave 2" (5 cm) minimum on the hinge side (depending on your model) to allow for the door to swing open.

NOTE: This refrigerator is intended for use in a location where the temperature ranges from a minimum of 55°F (13°C) to a maximum of 110°F (43°C). The preferred room temperature range for optimum performance, which reduces electricity usage and provides superior cooling, is between 60°F (15°C) and 90°F (32°C). It is recommended that you do not install the refrigerator near a heat source, such as an oven or radiator.

Model: 20-2447 END B BARRINGTON





Available Finishes/Colours



YWFE515S0JB Black




YWFF515S0JS Stainless Steel



YWFE515S0JW White

Manuals & Literature:





Use and Care

<u> Warranty</u>

5.3 cu. ft. Whirlpool® electric range with Frozen Bake™ technology

YWFE515S0JS

This Whirlpool® electric range with a dual element stove top helps you get dinner to the table. Skip preheating for favorites like pizza with Frozen Bake™ technology. This self cleaning oven also prevents cooked food from getting cold with the Keep Warm setting. Closed door broiling helps keep the kitchen comfortable.

Top Features

FlexHeat™ Dual Radiant Element

Get two elements in one with a 6" inner ring that's great for smaller pots and pans and a 9" expandable outer ring that makes room for larger cookware.

Frozen Bake™ technology
Skip preheating and cook frozen favorites like pizza in fewer steps with preprogrammed settings that automatically adjust cooking times for you.

Keep Warm setting

Keep dishes from getting cold with this setting that delivers low heat to the oven.

Closed Door Broiling
Maintain the optimal cooking temperature for food while still keeping the kitchen comfortable and cool using this broiling temperature management system that helps prevent overheating.

Dimensions	
Depth	27 3/4
Height	36
Width	29 7/8

Configuration and Overview		
Range Type	Freestanding	
Fuel Type	Electric	
Size (IN,inches)	30	
Enterior		

Exterior	
Door Removable	Yes
Drawer Type	Storage Drawer
Oven Door	Glass Window
Oven Window Size	Extra Large
Handle Color	Stainless Steel
Handle Material	Metal

Exterior	
Handle Type	Reach-Through Handle
Features	
Hot Surface Indicator Light	Yes
Heating Element On	Yes


reatures	
Hot Surface Indicator Light	Yes
Heating Element On Indicator Light	Yes
Power On Indicator Light	No
Griddle	NA
Automatic Convection Conversion Temperature Adjust	No
Power Outage Compatible	No

Model: 20-2447 END B BARRINGTON

36 of 45

WHIRLPOOL 30" (76.0 CM) FREESTANDING ELECTRIC RANGES Model YWFE515S0JS

Product Dimensions



- A. 273/4" (70.5 cm) max. depth with handle
- B. 46⁷/₈" (119.1 cm) overall height (max.) with leveling legs screwed all the way in*
- C. 36" (91.4 cm) cooktop height (max.) with leveling legs screwed all the way in*
- D. 29⁷/₈" (75.9 cm) width
- E. 255/16" (64.3 cm) depth back of range to front of cooktop**
- F. Model/serial/rating plate (located on the frame behind a top corner of the door or either side of the drawer)

IMPORTANT: Range must be level after installation. Follow the instructions in the "Level Range" section. Using the cooktop as a reference for leveling the range is not recommended.

*Range can be raised approximately 1" (2.5 cm) by adjusting the leveling legs.


**Front of door and drawer may extend further forward depending on styling.

Cabinet Dimensions

Cabinet opening dimensions shown are for 25" (64.0 cm) countertop depth, 24" (61.0 cm) base cabinet depth and 36" (91.4 cm) countertop height.

IMPORTANT: If installing a range hood or microwave hood combination above the cooking surface, follow the range hood or microwave hood combination installation instructions for dimensional clearances above the cooktop surface.

A freestanding range may be installed next to combustible walls with zero clearance.



- A. 13" (33.0 cm) max. upper cabinet depth
- B. 30" (76.2 cm) min. opening width
- C. For minimum clearance to top of cooktop, see NOTE*
- D. 30" (76.2 cm) min. opening width
- E. Outlet 8" (20.3 cm) to 22" (55.9 cm) from either cabinet, 7" (17.8 cm) max. from floor.
- F. Cabinet door or hinges should not extend into the cutout.

*NOTE: 24" (61.0 cm) minimum when bottom of wood or metal cabinet is covered by not less than 1/4" (6.4 mm) flame retardant millboard covered with not less than No. 28 MSG sheet steel, 0.015" (0.4 mm) stainless steel, 0.024" (0.6 mm) aluminum or 0.020" (0.5 mm) copper.

30" (76.2 cm) minimum clearance between the top of the cooking platform and the bottom of an uncovered wood or metal cabinet.

Model: 20-2447 END B BARRINGTON

37 of 45

WHIRLPOOL 30" (76.0 CM) FREESTANDING ELECTRIC RANGES Model YWFE515S0JS

Electrical Requirements - Canada Only

AWARNING



Electrical Shock Hazard

Electrically ground range.

Failure to do so can result in death, fire, or electrical shock.

If codes permit and a separate ground wire is used, it is recommended that a qualified electrical installer determine that the ground path is adequate and wire gauge are in accordance with local codes.

Be sure that the electrical connection and wire size are adequate and in conformance with CSA Standard C22.1, Canadian Electrical Code, Part 1 - latest edition, and all local codes and ordinances.

A copy of the above code standards can be obtained from:

Canadian Standards Association 178 Rexdale Blvd. Toronto, ON M9W 1R3 CANADA

 Check with a qualified electrical installer if you are not sure the range is properly grounded.

Range Rating*		Specified Rating of Power Supply Cord Kit and Circuit Protection
120/240 V	120/208 V	Amps
8.8 - 16.5 KW 16.6 - 22.5 KW	7.8 - 12.5 KW 12.6 - 18.5 KW	40 or 50** 50

^{*}The NEC calculated load is less than the total connected load listed on the model/serial/rating plate.

- A time-delay fuse or circuit breaker is recommended.
- This range is equipped with a CSA International Certified Power Cord intended to be plugged into a standard 14-50R wall receptacle. Be sure the wall receptacle is within reach of range's final location.



Do not use an extension cord.

INSTALLATION INSTRUCTIONS


Unpack Range

AWARNING

Excessive Weight Hazard

Use two or more people to move and install range. Failure to do so can result in back or other injury.


- 1. Remove shipping materials, tape and film from range.
- 2. Remove oven racks and parts package from inside oven.
- 3. Do not remove the shipping base at this time.



A. Shipping base

4. On Ranges Equipped with a Storage Drawer:


Remove the storage drawer. See the "Storage Drawer" section. Use a 1/4" (6.4 mm) drive ratchet to lower the rear leveling legs one-half turn. Use a wrench or pliers to lower front leveling legs one-half turn.



- A. 1/4" (6.4 mm) drive ratchet
- B. Rear leveling leg
- C. Wrench or pliers
- D. Front leveling leg

On Ranges Equipped with a Warming Drawer or Premium Storage Drawer:

On ranges equipped with a warming drawer or premium storage drawer, the rear legs cannot be accessed by removing the warming drawer or premium storage drawer. It will be necessary to adjust the rear legs from outside the range. Use wrench or pliers to lower the front and rear leveling legs one half turn.



- A. Rear leveling leg
- B. Wrench or pliers
- C. Front leveling leg

^{**}If connecting to a 50 A circuit, use a 50 A rated cord with kit. For 50 A rated cord kits, use kits that specify use with a nominal 13/8" (3.5 cm) diameter connection opening.

Model: 20-2447 END B BARRINGTON

38 of 45

WHIRLPOOL 30" (76.0 CM) FREESTANDING ELECTRIC RANGES Model YWFE515S0JS

Install Anti-Tip Bracket

AWARNING

Tip Over Hazard

A child or adult can tip the range and be killed.

Install anti-tip bracket to floor or wall per installation instructions.


Slide range back so rear range foot is engaged in the slot of the anti-tip bracket.

Re-engage anti-tip bracket if range is moved.

Do not operate range without anti-tip bracket installed and engaged.

Failure to follow these instructions can result in death or serious burns to children and adults.


- Remove the anti-tip bracket from where it is taped inside the storage drawer or warming drawer.
- 2. Determine which mounting method to use: floor or wall. If you have a stone or masonry floor, you can use the wall mounting method. If you are installing the range in a mobile home, you must secure the range to the floor.
- 3. Determine and mark centerline of the cutout space. The mounting can be installed on either the left-side or right-side of the cutout. Position mounting bracket against the wall in the cutout so that the V-notch of the bracket is 129/16" (31.9 cm) from centerline as shown.



A. 129/16" (31.9 cm) B. Bracket V-notch

 Drill two 1/8" (3 mm) holes that correspond to the bracket holes of the determined mounting method. See the following illustrations.

Floor Mounting



Wall Mounting



- 5. Using the Phillips screwdriver, mount anti-tip bracket to the wall or floor with the two $\#12 \times 1^5/8$ " (4.1 cm) screws provided.
- **6.** Move range close enough to opening to allow for final electrical connections. Remove shipping base, cardboard or hardboard from under range.
- Move range into its final location, making sure rear leveling leg slides into anti-tip bracket.



8. Move range forward onto shipping base, cardboard or hardboard to continue installing the range using the following installation instructions.

Model: 20-2447 END B BARRINGTON

39 of 45





Stainless Steel

Also available in:

White	WDF330PAHW
Black	WDF330PAHB

Capacity			
Total Place Settings	13		
General Features & Propertion	es		
Heavy Cycle			
High Temperature Wash Op	tion		
Heated Dry Option			
ENERGY STAR® Certified	ENERGY STAR® Certified		
Industry's Best Selling Dishwasher Brand [†]			
Designed, Engineered and Assembled in the U.S.A. with American Pride			
Electrical Details			
Amps	10		
Volts	120		
Hz	60		
Certifications			
ENERGY STAR® Certified	Yes		

Technical Details	
Dishwasher Type	Built-in
Control Location	Front
Control Type	Push Button
Number of Wash Cycles	3
Number of Options	4
dBA	55
Number of Racks	2
Tub Material	Plastic
Wash System	Filter
Wash System Type	Removable Filter
Number of Wash Arms	2
Dimensions	
Product Dimensions (H x W x D)	34-1/2" x 23-7/8" x 24-1/2"
Depth with Door Open 90°	49-1/2"

Reference Material

Dimension Guide

Install Guide

Use & Care Guide

Energy Guide

Warranty

Key Features & Benefits

1-Hour Wash Cycle


Clean dishes in half the time so your plates, pans and glasses are thoroughly cleaned up and taken care of in just an hour.*

Soil Sensor

Determines how dirty dishes are and adjusts the Normal cycle as needed to make sure dishes come out clean.

Normal Cycle

Use for normal amounts of food soil to clean up leftover messes from your day-to-day meals.



^{*}Per IEC standards. **Compared to Normal cycle with lightly soiled loads. †Based on 12-month average of sales. TraQline 2018. NOTE: Dimensions are for planning purposes only. For complete details, see Installation Instructions packed with product. Specifications subject to change without notice.

®/™ © 2020. All rights reserved. Printed in the U.S.A. D200052XXA. WDF330PAHSPECSHEETV01.

Model: 20-2447 END B BARRINGTON

40 of 45




Undercounter Dishwasher

PRODUCT MODEL NUMBERS

WDF110PAB	WDF320PAD	WDT710PAH
WDF111PAB	WDF330PAH	WDT720PAD
WDF120PAF	WDF331PAH	WDT730PAH
WDF121PAF	WDF520PAD	WDT735PAG
WDF130PAH	WDF540PAD	WDT735PAH
WDF131PAH	WDF545PAF	

DRAIN REQUIREMENTS

- A new drain hose is supplied with your dishwasher. If drain hose is not long enough, use a new drain hose with a maximum length of 12 ft (3.7 m) that meets all current AHAM/IAPMO test standards, is resistant to heat and detergent, and fits the 1" (25 mm) drain connector of the dishwasher. See the "Tools and Parts" section at the front of the guide for part details and orders.
- Make sure to connect drain hose to waste tee or disposer inlet above drain trap in house plumbing and 20" (508 mm) minimum above the floor. It is recommended that the drain hose either be looped up and securely fastened to the underside of the counter or be connected to an air gap.
- Make sure to use an air gap if the drain hose is connected to house plumbing lower than 20" (508 mm) above subfloor or floor.



- If required, the air gap should be installed in accordance with the air gap installation instructions. When you are connecting the air gap, a rubber hose (not provided) will be needed to connect to the waste tee or disposer inlet.
- Use 1/2" minimum I.D. drain line fittings.

WATER SUPPLY REQUIREMENTS

- This dishwasher has a water heating feature and also requires a connection to a hot water supply line.
- A hot water line with 20 to 120 psi (138 to 862 kPa) water pressure can be verified by a licensed plumber.
- 120°F (49°C) water at dishwasher
- ³/8" O.D. copper tubing with compression fitting or flexible braided water supply line. See the "Tools and Parts" section at the front of the guide for part details and orders.

NOTE: 1/2" minimum plastic tubing is not recommended.

- A 90° elbow with ³/₄" hose connection with rubber washer. See the "Tools and Parts" section at the front of the guide for part details and orders.
- Do not solder within 6" (152 mm) of the water inlet valve.
- If installed in new construction, make sure the house water supply lines have been flushed prior to connecting the dishwasher to remove any debris that may exist in the supply line.

NOTE: If replacing an existing dishwasher, it is recommended to install a new water line (see the "Tools and Parts" section at the front of the guide for part details) and drain hose (supplied) with the new dishwasher.

ELECTRICAL REQUIREMENTS

You Must Have:


- 120-volt, 60 Hz, AC-only, 15- or 20-amp, fused electrical supply
- Copper wire only
- A maximum of 2 field wiring supply conductors (12 AWG largest size) plus 1 grounding conductor are permitted in the terminal box.

We Recommend:

- A time-delay fuse or circuit breaker
- A separate circuit

If Connecting Dishwasher with a Power Cord:

- Use a UL Listed power cord kit marked for use with dishwasher. See the "Tools and Parts" section at the front of the guide for part details and orders.
- Plug into a grounded 3 prong outlet. Outlet must meet all local codes and ordinances.



If Connecting Dishwasher with Direct Wiring:

- Use flexible, armored, or nonmetallic sheathed copper wire with grounding wire that meets the wiring requirements for your home and local codes and ordinances.
- Use a UL Listed/CSA Approved metallic strain relief.

Model: 20-2447 END B BARRINGTON


PRODUCT AND CABINET OPENING DIMENSIONS — 23⁷/8" -(606 mm) — 25¹/₄" -(641 mm) — ³/₄" (19 mm) 30" (762 mm) 331/2" 301 (851 mm) min. with (762 mm) leveling legs removed **4**−3³/₄" (94 mm) 31/2" - 41/2" (88 mm - 106 mm) (533 mm) For 4" (100 mm) toe kick, height of cabinet opening is 341/2" (863 mm). A. Insulation may be compressed (not used on all models). B. Door handles may protrude forward of the face of the dishwasher, (varies by model). Check that all surfaces have no protrusions that would prohibit dishwasher installation. 101/2" NOTE: Shaded areas (864 mm) of cabinet walls show where utility -6³/₄" (102 mm) (172 mm) connections may be installed. (76 mm (159 mm) 2¹/₄" (64 mm) 24" / (620 mm) (44 mm) 2" (51 mm) 24' (620 mm) D C. Measured from the lowest point on the underside of the countertop. May be reduced to 33¹/₂" (851 mm) by removing the wheels and perforated area of insulation (blanket) on dishwasher. D. Minimum, measured from narrowest point of opening.

Model: 20-2447 END B BARRINGTON

42 of 45

5.0 cu.ft I.E.C. Closet-Depth Front Load Washer with Intuitive Controls

Model: WFW560CHW



Specifications

Width: 6858.00, 27.0" Centimeters, Inches

Depth: 8016.88, 31-9/16" Centimeters, Inches


Dimensions	
Capacity	4-3/10
Depth	8016.88 cm, 31-9/16 in
Gross Weight	97068688.00 kg, 214 lbs
Net Weight	92532768.00 kg, 204 lbs
width Appearance	6858.00 cm, 27.0 ir
LCD Touch Screen	No
Window	Yes
Details	
Advanced Vibration Control™	No
Dispense System	Detergent, Fabric Softener & Bleach
Eco Monitor/Efficiency Monitor	No
Hoses Included	4ft 4in Drain Hose Included
Internal Heater	No
Maximum Spin Speed	1160
Out Of Balance Sensing	Yes
Water Factor	3-1/5
Cycles and Options	
Number Of Wash Cycles	35
Electrical	
Power Cord Included	Yes
Controls	
Automatic Temperature Controls	Yes
Control Location	Front
LCD Touch Screen	No

Compatibility Works With No **Options** Number Of Washer Options **Features** Stackable Yes Water Faucet No Cycles Number Of Wash Cycles 35 Exterior Lid/Door Lock Yes Lid/Door Swing Left Modifiers Delay Start No Number Of Rinse Options Number Of Soil Levels 3 Number Of Spin Speeds Number Of Wash/Rinse Temperatures 4 Pre Soak Yes Temperature Selections Hot, Cold, Cool, Warm


Model: 20-2447 END B BARRINGTON

43 of 45


Recessed area or closet installation (stacked washer and dryer)




Custom under counter installation



Recessed area or closet installation (washer only)



Custom cabinet installation




Drain System

It is the responsibility of the installer to install and secure the drain hose in to the provided plumbing/drain in a manner that will avoid the drain hose coming out of o leaking from the plumbing/drain.

Drain system can be installed using a floor drain, wall standpipe, floor standpipe, or laundry tub. Select the method you need.

IMPORTANT: To avoid siphoning, only 4.5" (114 mm) of drain hose should be inside standpipe. Always secure drain hose with cable tie.

Floor standpipe drain system




Minimum diameter for a standpipe drain: 2" (51 mm). Minimum carry-away capacity: 17 gallons (64 L) per minute. A 1/4" (6 mm) diameter to 1" (25 mm) diameter Standpipe Adapter Kit is available; refer to the Quick Start Guide for online ordering information. Top of standpipe must be at least 39" (762 mm) high; install no higher than 96" (2.4 m) from bottom of washer. If you have an overhead sewer and need to pump higher than 96" (2.4 m), a sump pump and associated hardware are needed. See "Alternate Parts"

Model: 20-2447 END B BARRINGTON


44 of 45

Wall standpipe drain system




See requirements in "Floor standpipe drain system."


Laundry tub drain system



Minimum capacity: 20 gallons (76 L). Top of laundry tub must be at least 39" (991 mm) from the floor; install no higher than 96" (2.4 m) from bottom of washer.



Floor drain system



Floor drain system requires a Siphon Break Kit, 2 Connector Kits, and an Extension Drain Hose that may be purchased separately; refer to the Quick Start Guide for online ordering information. Minimum siphon break height: 28" (710 mm) from bottom of washer. (Additional hoses may be needed.)

Electrical Requirements

AWARNING



Electrical Shock Hazard

Plug into a grounded 3 prong outlet.

Do not remove ground prong.

Do not use an adapter.

Do not use an extension cord.

Failure to follow these instructions can result in death, fire. or electrical shock.

- A 120 V, 60 Hz, AC only, 15 or 20 A, fused electrical supply is required. A time-delay fuse or circuit breaker is recommended. It is recommended that a separate circuit breaker serving only this appliance be provided.
- This washer is equipped with a power supply cord having a 3-prong grounding plug.
- To minimize possible shock hazard, the cord must be plugged into a mating, 3-prong, grounding-type outlet, grounded in accordance with local codes and ordinances. If a mating outlet is not available, it is the personal responsibility and obligation of the customer to have the properly grounded outlet installed by a qualified electrician.
- If codes permit and a separate ground wire is used, it is recommended that a qualified electrician determine that the ground path is adequate.
- Do not ground to a gas pipe.
- Check with a qualified electrician if you are not sure the washer is properly grounded.
- Do not have a fuse in the neutral or ground circuit.

GROUNDING INSTRUCTIONS

For a grounded, cord-connected appliance:

This appliance must be grounded. In the event of a malfunction or breakdown, grounding will reduce the risk of electric shock by providing a path of least resistance for electric current. This appliance is equipped with a cord having an equipment-grounding conductor and a grounding plug. The plug must be plugged into an appropriate outlet that is properly installed and grounded in accordance with all local codes and ordinances.

WARNING: Improper connection of the equipment-grounding conductor can result in a risk of electric shock. Check with a qualified electrician or serviceman if you are in doubt as to whether the appliance is properly grounded. Do not modify the plug provided with the appliance: If it will not fit the outlet, have a proper outlet installed by a qualified electrician.

For a permanently connected appliance:

This appliance must be connected to a grounded metal, permanent wiring system, or an equipment-grounding conductor must be run with the circuit conductors and connected to the equipment-grounding terminal or lead on the appliance.

SAVE THESE INSTRUCTIONS

Model: 20-2447 END B BARRINGTON

45 of 45

WHIRLPOOL DRYER Model #: YWED5620HW

Whirlpool Brand Canada English | Washer and Dryers | Dryers | Electric Dryers | YWED5620HW



Define Your Style

7.4 cu. ft. Front Load Electric Dryer with Intuitive Touch Controls



7.4 cu. ft. Front Load Electric Dryer with Intuitive Touch Controls

Model #: YWED5620HW

Dimensions

Depth	78.74 cm, 31.0 in
Depth With Door Open 90 Degree	138.43 cm, 54-1/2 in
Height	98.42 cm, 38-3/4 in
Width	68.58 cm, 27.0 in
Configuration and Overview	
Fuel Type	Electric
Fuel Type Cycles and Options	Electric
	Electric Yes
Cycles and Options	
Cycles and Options Cycle Time Remaining	Yes

Ventilation System

Long Vent	No
Maximum Vent Length	64
Venting Direction	Left, Right, Bottom, Rear

Electrical

Hz	60

Power Cord Included Yes