

#### DO30CM/B



#### **FEATURES**

Black glass, handle-less design for Wolf performance at its sleekest

10 cooking modes for predictably delicious results (Convection, Roast, Bake, Broil, Convection Roast, Stone, Gourmet, Warm, Proof and Dehydrate)

Advanced Dual VertiCross convection system for faster preheats and consistent cooking across all racks

Gourmet feature has menu of presets that automatically controls cooking of popular meals

5.1 cubic feet capacity to handle multiple dishes at once

Interactive color touchscreen for advanced cooking control
Quiet-close doors with spring-and-damper door hinge system

Enhanced interior views with triple-pane glass and three halogen lights

Can be installed flush with surrounding cabinetry for integrated look

Rigorously tested in our U.S. manufacturing facilities for decades of use

Exceptional 24/7 support from our Customer Care team in Madison

#### ACCESSORIES

Bake stone kit (stone, rack and peel)

Dehydration kit (racks and door stop)

Full-extension easy glide oven rack

Temperature probe and broiler pan

Set of three standard oven racks

Accessories available through an authorized Sub-Zero dealer. For local dealer information, visit <u>subzero-wolf.com/locator</u>.




Cartes South.




# PRODUCT SPECIFICATIONS

5-feet	Conduit Length
50 amp dedicated circuit	Electrical Service
240/208 VAC, 60 Hz	Electrical Supply
466 lb	Weight
21 3/8"	Door Clearance
3.3 cu ft	Usable Capacity
5.1 cu ft	Overall Capacity
25 1/4"W x 17 1/2"H x 19 7/8"D	Oven 2 Interior Dimensions
25 1/4"W x 17 1/2"H x 19 7/8"D	Oven 1 Interior Dimensions
29 7/8"W x 50 7/8"H x 23"D	Dimensions
DO30CM/B	Model


#### ELECTRICAL



#### DIMENSIONS



# STANDARD INSTALLATION





#### SU901

Dual Motor (1100 CFM) - EBM Pressure: 800 Pa Noise level: 66 dBA/5.1 sones




Lighting: 2x20W Dichroic lamps





- Ō
- Control panel: 4 speed push-button + timer delay off timer + light switch
- grease filter: commercial style baffle filters










#### Dishwashers

SHV68T53UC 800 Series 24" Panel Ready Dishwasher






















- 44 dBA: Quietest dishwasher brand.
- New 3rd rack adds versatility and offers 30% more loading
- capacity.

  Touch Control Technology allows for quick cycle programming.
  InfoLight® shines on the floor so you know the dishwasher's
- RackMatic® offers 3 height levels, for 9 possible rack positions.

#### Technical Data

1000000	
Adjustable upper rack :	Rackmatic 3-stage
Upper rack cup shelf	2
3rd Rack :	3rd Rack 1.0
Silverware Basket :	Standard
Accessories Parts : 3 small iten	3 small item clips, bottle holder metal
Optional accessories: SGZ1010UC,	SGZ1010UC, SHZ1008UC, SMZ1007UC,
SMZ4000UC, SMZ5000, SMZ5	SMZ5002UC, SMZPC002UC
UPC code:	825225904236
Variant color :	Stainless steel
Panel ready :	Yes
Silence level (dBA):	44
Watts (W):	1300
Current (A):	12.
Volts (V):	120
Frequency (Hz) :	60
Energy Consumption (kWh/yr) :	259
Energy Star® qualified :	Yes
Plug type :	fixed connection
Required cutout size (HxWxD) (in):	33 7/8 " x 23 5/8 " x 24 "

15				ngs:	lace sett	Number of place settings :	Nun
No					nt :	ADA Compliant :	ΑDΑ
TallTub						Tub type:	Tub
Stainless steel	St				••	Tub material:	Tub
35 3/4" x 26" x 29 5/16"	x 26	35 3/4"					
		D) (in) :	Product packaging dimensions (HxWxD) (in):	nensio	aging di	duct pack	Pro
135				<u>ت</u>	hose (cn	Length inlet hose (cm):	Len
53"					hose (in)	Length inlet hose (in):	Len
175.0				Э ::	t hose (c	Length outlet hose (cm):	Len
67 "				⊒.	t hose (i	Length outlet hose (in) :	Len
110				<u></u>	ength (c	Power cord length (cm):	Pov
43 1/2"				<u>ت</u>	ength (ir	Power cord length (in):	Pov
1/16 "	23	×	9/16	× 23		7/8 "	33
		(in):	Overall appliance dimensions (HxWxD) (in):	ension	ance dim	rall appli	Ove
860-890 x 600 x 610	0-890	86	Required cutout size (HxWxD) (mm):	JXMXH)	out size	uired cut	Req
	X Z	00//0	C) (III) .		000		- 100


#### Optional accessories

SGZ1010UC Drain hose extension kit, SHZ1008UC s/s door with handle for dishwasher, SMZ4000UC silverware basket US Duo, SMZ5000 Dishwashing aid set, SMZ5002UC Silverware box, SMZPC002UC Powercord with cold plug




#### Dishwashers

800 Series SHV68T53UC 24" Panel Ready Dishwasher



- measured from the bottom edge of the countertop panel thickness recommended <sup>3</sup>4\* (20 mm), panel weight 7-22 lbs (3-10 kg)
   24\* (510 mm) wide panel may be used depending on cabinet design

measurements in inches (nm)



All connections are at the real of the appliance.
Extension for drain hose available as accessory.

Power cord for connection to electrical outlet (3-prong plug) available as accessory.



#### TAKE YOUR MICROWAVE $\triangleright$ BE TER PLAC

It's your kitchen, your design and your lifestyle. Sharp's Microwave Drawer Oven allows you to focus on the design elements you prefer by removing the microwave from sightlines and enabling more design versatility. The Microwave Drawer offers flexible placement options below an island, peninsula, or standard cabinetry, and can also be installed adjacent to your wall oven. The Microwave Drawer allows you to showcase your design savvy and create a kitchen that flows with your lifestyle.

a sleeker design to match more built-in appliances. Sharp introduces the next generation of this successful appliance—model SMD2477ASC - a 24" microwave drawer with a simpler and

#### Design Flexibility

Sharp's Microwave Drawer product expands the option for microwave placement in almost any kitchen plan—it's a perfect choice for open-plan kitchens, islands, peninsulas, and a great addition to wet bars, family rooms and home theatres.

# **Location and Counter Space Saving**

You may place the drawer under a counter, cooktop or wall oven or above a warming drawer without a built-in kit, additional trim or venting. Sharp microwave drawer provides the best solution for a cleaner, uncluttered counter space.

# SHARP's Exclusive AutoTouch™ System


Sharp's exclusive AutoTouch $^{TM}$  system allows you to open and close the drawer automatically at one-finger operation by pressing a button on the control panel.

# New Hidden Control Panel


The new SMD2477ASC model features a hidden control panel which gives a more integrated look and feel within the kitchen. The new tall control panel, angled at 45° degrees, is easy to see, easy to access and easy to use.

## **Specifications**

TECHNICAL SPECIFICATIONS	
Size	24" wide
Microwave Capacity	1.2 cu.ff
Microwave Power	950 watts
Control Panel	Digital LCD Display
Control Type	Hidden Control Panel
Drawer Opening	AutoTouch™ System
Power Level	11
Sensor Cook, Reheat, Popcorn Settings	13
Reheat Auto Settings	2
Defrost Auto Settings	6
Keep Warm Setting	Yes, up to 30 min.
Melt / Soften / Settings	Yes
Beverage Setting	Yes
Programmable Stages	Yes, 4
Digital Clock	Yes
Kitchen Timer	Yes
Child Lock	Yes
+30 sec	Yes
Interior Oven Light	Yes







Courtes

© 2016 Sharp Electronics Corporation, All rights reserved.

Product specification and design are subject to change without notice.

SHARP ELECTRONICS OF CANADA LID. 335 Britannia Road East, MISSISSAUGA, ONTARIO, L4Z 1W9 www.sharp.ca

#### CE365T/S



#### FEATURES

Five elements, nine zones accommodate different pan sizes

High-frequency pulsation technology for superior performance and control

True simmer setting for soups, sauces and more

Super-low Melt setting for fine chocolate and other delicate foods

Rigorously tested in our U.S. manufacturing facilities for decades of use

Exceptional 24/7 support from our Customer Care team in Madison

Illuminated touch controls

Hot surface indicator lights when temperature exceeds 150° F

Temperature limiter ensures that safe operating temps are never exceeded

Universal "off" turns all elements off

Control panel lock for safety

Automatic timer up to 99 minutes

Bridge zone creates larger 7"x16" cooking area

Ceran ceramic glass resists scratching, staining, impact and heat



# TOP CONFIGURATION



# COOKTOP SPECIFICATIONS

- 1 10 1/2" Triple Element (1050/1950/2700W)
- 1 8" Dual Element (700/2200W)
- 1 5 1/2" Single Element (1200W)
- 2 7" Single Elements With Bridge (4400W)



# PRODUCT SPECIFICATIONS

Dimensions

Model

CE365T/S

Electrical Supply

Electrical Service

50 amp dedicated circuit

4 feet


Conduit Length

ELECTRICAL


#### 3-wire, 240 VAC, 60 Hz 36"W x 3 1/2"H x 21"D



#### DIMENSIONS



# STANDARD INSTALLATION



(390)

NOTE: Shaded area above countertop indicates minimum clearance to combustible surfaces, combustible materials cannot be located within this area.

Electrical supply location only applies to installations with built-in oven.

FRONT VIEW

SIDE VIEW

# DV56H9100EG

Samsung Front-Load Electric Dryer

# 9.5 cu. ft. Capacity IEC

#### Features

- Eco Dry
- Steam Drying Technology:
- Steam Refresh
- Steam Wrinkle Away
- Vent Sensor™
- and Adjusts Drying Time Sensor Dry – Detects Moisture
- Smart Care™
- Stainless Steel Drum
- 15 Preset Drying Cycles
- 11 Options
- 5 Temperature Settings
- 4-Way Venting
- Dual Heaters
- Drying Rack
- Dryer Drum LightReversible See-Through Door

#### Convenience

- Child Lock
- My Cycle Option
- Lint Filter Indicator






# **ENERGY STAR 2013**


**Emerging Technology Award** 

Awarded the U.S. Environmental Protection Agency's 2013 ENERGY STAR® Emerging Technology Award.





9.5 cu. ft. Capacity



Eco Dry

#### Available Colour:



Onyx (shown)

# Signature Features

### 9.5 CU. FT. CAPACITY

Our biggest capacity lets you dry 4 laundry baskets in a single load.\* \*Based on an 8 lbs. load of laundry per basket.

#### ECO DRY

- 25% more energy savings.\*

- With Eco Dry, save up to \$300 over lifetime of the dryer.\*\*
   "Saves 25% of energy based on U.S. Department of Energy standard test. Visit www.energystar.gov for more information." Current Samsung dryers without too Dry use approximately 965 NW while Eco Dry uses approximately 710 kMh. This provides a savings of \$25 annually, which, over the 12 year lifespan of the dryer, offers a saving of approximately \$300.

#### VENT SENSOR™

- Duct blockage sensing.
- Detects problems and reminds you when to clean your vent to avoid lint blockages.
- Cleaning vents regularly improves dryer performance.

# )V56H9100EG

Samsung Front-Load Electric Dryer

# **Installing Options**







# 4-Way Venting

### 15 Preset Dry Cycles:

9.5 cu. ft. Capacity IEC

Normal, Heavy Duty, Towels, Permanent Press, Steam Refresh, Steam Wrinkle Away, Eco Normal, Time Dry, Air Fluff, Quick Dry Active Wear, Bedding, Delicates, Wool, Sanitize,

#### 11 Options:

Stacked Depth

My Cycle, Rack Dry, Adjust Time, Eco Dry, Sound Child Lock, Smart Care, Drum Light Mixed Load Bell, Wrinkle Prevent, Anti-Static,

# 5 Temperature Settings:

High, Medium, Medium Low, Low, Extra Low

#### 5 Dry Levels:

17"

Very Dry, More Dry, Normal Dry, Less Dry, Damp Dry

# 2 Signal Level Settings: On/Off

#### Warranty

One (1) Year Parts and Labour Two (2) Years Control Board Three (3) Years Stainless Steel Drum

-

32

# Product Dimensions & Weight (WxHxD)

Ten (10) Years Direct Drive Motor

Dimensions: 30" x 42 5/8" x 32"

Weight: 159 lbs

### Shipping Dimensions & Weight (WxHxD) Dimensions: $31\frac{7}{8}$ " x $46\frac{1}{4}$ " x $33\frac{5}{8}$ " Weight: 170 lbs

Electric DV56H9100EG Model #

Onyx

887276857893 **UPC** Code

Matching Washer

## WF56H9100AG


887276963105



Stacked







#### **Dimensions**

If the washer and dryer are installed together, the closet front must have at least a 72" unobstructed air opening. Your washer alone does not require a specific air opening.

Rear – 5<sup>7</sup>/<sub>8</sub>" Top – 17"

and alcove installations: Minimum clearances for closet

A. Recessed area


B. Side view - closet or confined area


 Alcove or closet installation **Installing Your Dryer** 

Closet Front - 2"

# With optional pedestal base or stacking kit

Required Dimensions for Installation with Pedestal







24"\*

Closet or Door

# WF56H9100AG

Samsung Front-Load Washer

# 6.5 cu. ft. Capacity IEC

#### **Features**

- PowerFoam™
- Steam Washing
- SuperSpeed
- Smart Care™ Self Clean+
- VRT Plus<sup>®</sup>
- Eco Cold Wash
- Swirl Drum Design
- 9 Direct Drive Motor
- 0 1300 rpm Maximum Spin Speed
- Internal Water Heater
- 15 Preset Wash Cycles
- 13 Options
- Garment+

#### Convenience

- Child Lock
- Door Lock
- Drum Light
- Dispenser Trays: Prewash, Main Wash, Softener, Bleach



ENERGY STAR® rated: CEE Tier 3




MEF=3.55 WCF=2.5 100 kWh/yr




Ranked "Highest in Customer Satisfaction with Clothes Washers" in 2013 & 2014 by J.D. Power and Associates.



Achieved the U.S. Environmental Protection Agency's 2014 ENERGY STAR®
"Most Efficient" designation.





6.5 cu, ft. Capacity



PowerFoam

#### Available Colour:



Onyx (shown)

# Signature Features

# 3x THE LAUNDRY, 1/3 OF THE TIME\*

\*Based on a 3 standard loads of laundry (based on baskets) at 60 minutes 180 minutes which is equivalent to 1 load in the 9100.

\*\*Based on an 8-lb. Icad of laundry. Our biggest capacity lets you wash 4 laundry baskets in a single load.\*\* ance.

#### SUPERSPEED

- 50% faster wash cycle.\*
- Wash a full load in only 30 minutes.\*
- Save over 3 hours of laundry time every week.\*\*
- Laundry gets done quicker without loss of performance.

\*Normal one-hour wash can now be completed in astitle as up to 30 minutes as compared to Samsung WES11 washe without SuperSpozed. Based on DOI is trandard's average of 7.5 loads per week. 
\*10DE constitute reverage of JS5 / 10 lbs. loads per year with average normal-wash cycle of 53 minutes equials a time savings of over 3 hours por week.

#### POWERFOAM

- Powerful washing performance.
- Creates a powerful yet gentle foam that easily penetrates through fabrics.
- Confidently wash even your largest loads.

# WF56H9100AG

Samsung Front-Load Washer

# **Installing Options**









#### 6.5 cu. ft. Capacity IEC 15 Preset Wash Cycles:

Whites, Active Wear, Delicates, Wool, Quick Wash Sanitize, Allergen, Towels, Bedding, Deep Steam, Eco Cold Wash, Normal, Heavy Duty, Permanent Press, Rinse and Spin

#### 13 Options:

Stacked Depth

Child Lock, Smart Care, Drum Light Prewash, Extra Rinse, Extra Spin, Spin Only, Sound, SuperSpeed, Steam, Self Clean+, Delay End, My Cycle,

# 5 Temperature Settings:

1. Alcove or closet installation Installing Your Washer

alcove installations:

A. Recessed area

Minimum clearances for closet and

Extra Hot, Hot, Warm, Eco Warm, Cold

#### 5 Spin Settings:

Side view - closet or confined area

17:

Extra High, High, Medium, Low, No Spin

#### 5 Soil Settings:

Heavy, Heavy Medium, Normal, Low Medium, Light

#### Dispenser Trays:

If the washer and dryer are installed together, the closet front must have at least a 72" unobstructed air opening.
Your washer alone does not require a specific air opening.

Closet Front – 2' Rear - 57/6"

0

Prewash, Main Wash, Softener, Bleach

#### Warranty

ν,

321/2

<u>\</u> -57/6

One (1) Year Parts and Labour

Two (2) Years Control Board

Ten (10) Years Direct Drive Motor Three (3) Years Stainless Steel Drum

Required Dimensions for Installation with Pedestal

581/4" to clear oper

2. With optional pedestal base or stacking kit

Dimensions

 $\rightarrow$ 

# Product Dimensions & Weight (WxHxD) Dimensions: $30"x 42^{5}/_{8}"x 32^{1}/_{2}"$

Required Dimensions for Installation with Stacking Kit

Weight: 267 lbs

# Shipping Dimensions & Weight (WxHxD) Dimensions: $31\frac{7}{8}$ x $46\frac{1}{4}$ x $33\frac{5}{8}$

#### Colour Weight: 278 lbs Model# UPC Code

# Matching Dryer (Electric)

WF56H9100AG 887276963105

DV56H9100EG

887276857893

# Onyx

#### SAMSUNG

24\*\*

Closet or Door

cų

- 57/e\*\*

\*Required spacing.

\*\*External exhaust elbow requires additional space

0

48. \*

ω

ω

321/2

-57/8

ಚಿ

845/8

Onyx

0

5311/16

# 24" Marvel Beverage Center with Two 60/40 Split Convertible Shelves™

Model # ML24BCG1\*\*



Certified to meet ENERGY STAR® requirements

- Dynamic Cooling Technology" delivers rapid cooldown and the industry's best temperature stability
- 60/40 Split Convertible Shelf<sup>m</sup>— cantilevered glass shelving, wine rack with a Vibration Neutralization System<sup>m</sup> or both configurations all in one
- Rollout wine storage
- Solid, black-stained maple shelf fronts (natural maple shelf accessories available)
- MARVEL Intuit" Integrated Controls ensure precise temperature management from 34°F to 42°F
- Thermal-efficient cabinet ensures optimum food preservation and energy efficiency while maximizing capacity
- Tinted, UV-resistant dual pane glass door protects wine from damaging ultra-violet light
- Two-stage, soft white theatre-style LED lighting and midnight black interior
- Cantilevered, fully adjustable shelving system
- Close Door Assist System" gently and automatically closes door
- Audible and visual alarms signal when door is left ajar to protect food integrity and energy use
- Vacation/Sabbath mode conserves energy during times when the unit is not in use and complies with Star-K requirements
- Height adjustment up to 1" with leveling legs
- 4" black adjustable toe kick
- 1-year warranty





### Storage Capacity

Up to (162) 12-oz cans or (18) wine bottles

# **Storage Configuration**

- (2) cantilevered, full-width 60/40 Split Convertible Shelf" black steel-framed glass shelf
- (1) roller-glide 4-bottle wine rack

ML24BCG1RS

# **Product Dimensions**

23%" W x 33%" minimum H x 25%" D (including handle)

# Finish/Door Options

ML24BCF2RP

ML24BCG1LS



ML24BCP2RP

ML24BCF2LP





ML24BCP2LP

Integrated Left Hinge

Panel Overlay Frame Glass Door

Integrated Right Hinge

Panel Overlay Frame Glass Door

Integrated Left Hinge

Panel Overlay Frame Glass Door

Integrated Right Hinge

Panel Overlay Frame Glass Door


Stainless Frame Glass Door,


Right Hinge

Ordering Details
Stainless Frame Glass Door,

Left Hinge








	25 21/32" (65.2 cm)	,S,	23 7/8" (60.7 cm)	"D"
	46 13/32" (117.9 cm)	Ť,	33 3,4" to 34 3,4" (85.7 to 88.3 cm)	Cabinet Dimensions
	25 11/16" "J" (65.2 cm)		23 23/32" (60.2 cm)	"F"
Figure 8				
"H" "G"				

21 ½" D		5A			i cm)
	Energy Star Certified	Agency Approvals	Vacation / Sabbath Mode	Finishes	delivers rapid cool down and the industry's best temperature stability  The distinctive Marvel design features a thermal-efficient cabinet and door com with Dynamic Cooling Technology** for superior temperature stability, faster cootimes and speedy temperature recovery with high frequency.
	EMPTER STAR	CSA	Yes	SS, O	try's best try's best tability I design features a net and door com Jechnology'm for stability, faster co- rperature recovery

Temperature Range Lock Electrical Requirements Length of Power Cord	Intuit**  34° - 42° F  NA  120V / 60Hz / 15A  5'
Length of Power Cord	5,
Product Dimensions	23 %" W x 33 ¾" H x 21 ½" D
Depth to Front of Door	23 23/32"
Depth to Handle	25 21/32"
Depth with door at 90°	46 13/32"
Shipping Weight	160 lbs



#### ishes Key

Stainless Steel Overlay

Toe Grill Finish Hinge

Interior Lighting Other Storage

2 White LED Pods

Classic Hinge

Shelf Fronts

Black painted maple

Cantilever

Shelving System


Capacity Interior Finish

Up to 18 wine bottles or up to 162 12-oz cans

Black 23 %"

Width

Depending on your model cut the overlay door panel to the dimensions shown in Figures 13 to 20. Also see Table "Dy for the height dimension and door styles. The window are out is for glass door models only. If your appliance has a lock also drill the lock hole in the panel, see Figure 22.



(2.9 cm) Clearance for screw head, 4 places, 1"//<sub>4</sub>" (4.3 cm) 434" (12.4 cm) 〜1" (2.5 cm) diameter × ¼" (6 mm) deep 4 places '//'' (6 mm) Clearance for hinge at top and bottom This side facing interi Hinge side of door (7.9 cm) \$ 31%.\* 19.4 cm (4 am)

The preferred method of attaching the panel to the door is to clamp the panel to the door so it cannot move while drilling the screw pilot holes. Use bar clamps or "C" clamps with pads on the clamping surfaces that will not mar the panel or the door. The custom overlay panel should be flush with the top of the door and centered along the width of the door. See Figure 12a. Drill holes through the gasket extrusion using the 10 holes as pilot holes. Use the drill size from the chart in Table "C", being careful not to drill through the front surface of the panel; affill no deeper than ½" (12.7 mm) deep. If the overlay panel is thinnen than %" (16 mm) thick shorter screws will have to be obtained. Fasten the panel to the door with the 10 screws provided in the literature pack. (See Figure 22a). Remove the clamps and replace the gasket in the gasket extrusion channels of the door. Some force may be required to seat the gasket into the channels. Be sure the gasket corners are seated monet.


TO TO 1 12	Softwood %, (2.8 mm) Diameter Piloi Hole	Hardwood %" (3.2 mm) Diameter. Pilot Hole	Material Type #10 Wood Screw
------------	--	---	------------------------------

Holes in gasket

Overlay panel to be centered on width of door.

Figure 12a

Table C



Solid, Left Hand Solid, Left Hand

DIM "A"


olid, Right Hand

3011/52" (77.1 cm)

ML24RAP\*LP
ML24BRF\*RP

ML24BRF\*LP

Solid, Left Hand Glass, Right Hand Glass, Left Hand



MA24RAP\*LP MA24RAP\*RP MA24BRF\*LP MA24BRF\*RP

olid, Left Hand with Lock

Table D

Solid, Right Hand with Lock


Glass, Left Hand with Lock

2723/2" (70.4 cm)

Glass, Right Hand with Lock

Solid, Right Hand Solid, Left Hand






flush with top of door.

For comprehensive installation instructions, please visit www.marvelrefrigeration.com

# T30IF800SP 30-INCH FLUSH FREEZER COLUMN WITH INTERNAL ICE WAKER



FREEDOM® COLLECTION, PANEL-READY, REVERSIBLE DOOR SWING



### FEATURES & BENEFITS

- Freedom® Hinge enables true flush design
- Full-height door-true cabinet integration without exposed venting grille
- All-LED sidewall and theater lighting
- Brightspace interior design
- Accepts custom or stainless steel panels

TEMPERATURE RANGES	
Freezer	-9°F (-23°C) to 7°F
	(140)
SuperFreeze®	-9°F (-23°C) for
	approximately 52 hours
Energy Saving (Economy) Mode	3°F (-16°C)

Energy Saving (Economy) Mode	3°F (-16°C)
ACCESSORIES (OPTIONAL)	
Stainless Steel Panel Options:	
TFL30IR800 - Flat Stainless Steel Panel TCH30IR800 - Chiseled Stainless Steel Panel	anel
Handle Options:	
PR36HNDL10 - 36-Inch Professional	
MS36HNDL10 - 36-Inch Masterpiece®	
FRAMEKIT10 - Freedom® Frame Kit	
HEATRKIT10 - Freedom® Heater Kit	
Filters:	
REPLFLTR10 - Freedom® Water Filter	

	Limited, Entire Appliance, Parts and Labor on Any Part of the Refrigerator that Fails Because of a Manufacturing Defect	WARRANTY	Annual Energy Consumption	ENERGY STAR® Qualified	EFFICIENCY	Net weight (los)	Net Weight (lbs)	Required Cutout Size (H x W x D) (in.)	Appliance Dimensions (H $\times$ W $\times$ D) (in.)	DIMENSIONS & WEIGHT	Plug Type	Power Cord Length (in.)	Volts (V), Frequency (Hz)	Current (A)	Watts (W)	TECHNICAL DETAILS	Defrost Process	SuperFreeze®	Dedicated Evaporator & Compressor System	PERFORMANCE	Freezer Gross Capacity (cu. ft.)	Total Unit Gross Capacity (cu. ft.) - AHAM	CAPACITY	Special Modes	Door Open Alarm	Ice Maker	Door Bins	Full Extension Drawers at 90° Door Opening Angle	Shelf Material	Adjustable Shelves	Full Width Shelves	Lighting	Reversible Door Swing	Panel Ready	GENERAL PROPERTIES
3rd to 6th Year	2 Year		564 kWh	Yes		Sal Des	350 lhs	84" × 30" × 24 <sup>3</sup> / <sub>4</sub> "	84" x 29 3/4" x 24"		120V-3 Prong	78 3/4"	120 V, 60 Hz	15 A	504 W	Mary and Mary	Frost-Free	Yes	Yes		15.8 cu. ft.	15.8 cu. ft.		Sabbath, Economy, Vacation	Yes	Yes	Л	Yes	Metal	3	ω	All-LED Sidewall and Theater Lighting	Yes	Yes	

<sup>\*</sup>System\*; Parts Only

\* Sealed refrigeration system includes compressor, evaporator, condenser, dryer / strainer and connection tubing




SCRNFLTR10 - Filter By-Pass

# 30-INCH FLUSH FREEZER COLUMN WITH INTERNAL T301F800SP

FREEDOM® COLLECTION, PANEL-READY, REVERSIBLE DOOR SWING




### **CUTOUT DIMENSIONS**




### **TOP VIEW CLEARANCE**

-30" (762 mm)→



Door handle must be added to this dimension




La South

# T30IF800SP 30-INCH FLUSH FREEZER COLUMN WITH INTERNAL ICE MAKER



FREEDOM® COLLECTION, PANEL-READY, REVERSIBLE DOOR SWING

### **PANEL DIMENSIONS**



\*Excludes thickness of door panel. If standard panel with 3/4" thickness is mounted, total depth is 24 3/4".

La South


These warranties give you specific legal rights and you may have other rights that vary from state to state. Full warranty and limited warranty from date of installation. For complete warranty details, refer to your Use & Care manual, or ask your dealer.

Specifications are for planning purposes only. Refer to installation instructions and consult your countertop supplier prior to making counter opening. Consult with a heating and ventilation engineer for your specific ventilation requirements. For the most detailed information, refer to installation instructions accompanying product or write to Thermador indicating the model number. Specifications are correct at time of printing. Thermador reserves the right to change product specifications or design without notice. Some models are certified for use in Canada.

Thermador is not responsible for products that are transported from the U.S. for use in Canada.

# T18IW800SP 18-INCH FLUSH CUSTOM WINE PRESERVATION COLUMN







### FEATURES & BENEFITS

- Freedom® Hinge enables true flush design
- Full-height door-true cabinet integration without exposed venting grille
- All-LED theater lighting
- Accepts custom or stainless steel panels
- Reversible door swing

TEMPERATURE RANGES	
Upper Zone	41°F (5°C) to 64°F (18°C)
Lower Zone	41°F (5°C) to 64°F (18°C)

### ACCESSORIES (OPTIONAL)

Stainless Steel Panel Options: TFL18IW800 - 18-Inch Flat Stainless Steel Panel TCH18IW800 - 18-Inch Chiseled Stainless Steel Panel

Handle Options: PR36HNDL10 - 36-Inch Professional Handle MS36HNDL10 - 36-Inch Masterpiece® Handle

FRAMEKIT10 - Freedom® Frame Kit

HEATRKIT10 - Freedom® Heater Kit



Thermadar. \*\*
REAL INNOVATIONS FOR REAL COOKS\*

Number of Shelves         11           Shelf Material         Dark Exotic Hardwood           Full Extension Shelves at 90° Door Opening Angle         Yes           Presenter Shelf         Yes           Bottles Per Shelf         5           Portable Aluminum Wine Presenter         Yes           Iype Of Glass Door         Tempered and UV-protective           Number Of Temperature Zones         2           Door Open Alarm         Yes           Special Modes         Sabbath, Economy, Vacation           CAPACITY         Sabbath, Economy, Vacation           CAPACITY         Sabbath, Economy, Vacation           Current (A)         92 W           Current (A)         92 W           Volts (V)         15 A           Volts (V)         78 3/4"           Power Cord Length (in.)         78 3/4" × 24"           Power Cord Length (in.)         84" x 17 3/4" x 24"           Required Cutout Size (H x W x D) (in.)         84" x 18" x 24 3/4"           Annual Energy Consumption         398 kWh	GENERALI PROPERTIES       Panel Ready     Yes       Reversible Door Swing     Yes       Carbon Air Filter     Yes       Lighting     All-LED Theater       Lighting     Lighting	
---	--	--

<sup>\*</sup> Sealed refrigeration system includes compressor, evaporator, condenser, dryer  $\prime$  strainer and connection tubing




# T18IW800SP 18-INCH FLUSH CUSTOM WINE PRESERVATION COLUMN



### **CUTOUT DIMENSIONS**

FREEDOM® COLLECTION

# 18" (457 mm) 7 Furniture return



(2134 mm)


➤

الم min. 4 (102 mm)

D

51/8" (130 mm) 4" (102 mm)


### TOP VIEW CLEARANCE



\*\* Door handle must be added to this dimension

\* Depends on the thickness of the furniture door.


3/4" (19 mm) is relevant for the stainless steel door. (special Accessory).



# T18IW800SP 18-INCH FLUSH CUSTOM WINE PRESERVATION COLUMN FREEDOM® COLLECTION



### PANEL DIMENSIONS



†Excludes thickness of door panel. If standard panel with 3/4" thickness is mounted, total depth is 24 3/4",



These warranties give you specific legal rights and you may have other rights that vary from state to state. Full warranty and limited warranty from date of installation. For complete warranty details, refer to your Use & Care manual, or ask your dealer.

Specifications are for planning purposes only. Refer to installation instructions and consult your countertop supplier prior to making counter opening. Consult with a heating and ventilation engineer for your specific ventilation requirements. For the most detailed information, refer to installation instructions accompanying product or write to Thermador indicating the model number. Specifications are correct at time of printing. Thermador reserves the right to change product specifications or design without notice. Some models are certified for use in Canada.

Thermador is not responsible for products that are transported from the U.S. for use in Canada.

# T30IR800SP 30-INCH FLUSH CUSTOM FRESH FOOD COLUMN

FREEDOM® COLLECTION, PANEL-READY







### FEATURES & BENEFITS

- Freedom® Hinge enables true flush design
- Full-height door-true cabinet integration without exposed venting grille
- Brightspace interior design with All-LED sidewall and theater
- FLEXTEMP $oldsymbol{ ilde{e}}$  drawer providing the ultimate in preservation
- Accepts custom or stainless steel panels

TEMPERATURE RANGES	
Refrigerator	35°F (2°C) to 46°F (8°C)
Temperature Controlled Drawer	Fish 32°F (0°C) Meat 35°F (1.5°C) Produce 37°F (3°C)
Deli Drawer	Just above 32°F (0°C)
SuperCool	35.5°F (2°C) for approximately 9 hours
Energy Saving (Economy) Mode	45°F (7°C)

# ACCESSORIES (OPTIONAL)

Stainless Steel Panel Options: TFL30IR800 - Flat Stainless Steel

TCH30IR800 - Chiseled Stainless Steel

Handle Options:
PR36HNDL10 - 36-Inch Professional
MS36HNDL10 - 36-Inch Masterpiece®

FRAMEKIT10 - Freedom® Frame Kit

HEATRKIT10 - Freedom® Heater Kit

Limited Warranty for Sealed Refrigeration System*; Parts Only	Limited Warranty for Sealed Refrigeration System*; Parts and Labor	Limited, Entire Appliance, Parts and Labor on Any Part of the Refrigerator that Fails Because of a Manufacturing Defect	WARRANTY	Annual Energy Consumption	ENERGY STAR® Qualified	EFFICIENCY	Net Weight (lbs)	Required Cutout Size (H $\times$ W $\times$ D) (in.)	Appliance Dimensions ( $H \times W \times D$ ) (in.)	DIMENSIONS & WEIGHT	Plug Type	Power Cord Length (in.)	Frequency (Hz)	Volts (V)	Current (A)	Watts (W)	TECHNICAL DETAILS	SuperCool	Freeflow® Cold Air System	Dedicated Evaporator & Compressor System	PERFORMANCE	Refrigerator Gross Capacity (cu. ft.)	Total Unit Gross Capacity (cu. ft.) - AHAM	CAPACITY	Special Modes	Door Open Alarm	Gallon Door Bins	Door Bins	Humidity Control Drawer	Temperature Controlled Drawer	Full Extension Drawers at 90° Door Opening Angle	Shelf Material	Adjustable Shelves	Full Width Shelves	Lighting	Carbon Air Filter	Reversible Door Swing	Panel Ready	GENERAL PROPERTIES
7th to 12th Year	3rd to 6th Year	2 Year		310 kWh	Yes		332 lbs	84" × 30" × 24 3/4"	84" x 29 3/4" x 24"		120V 3-Wire	78 3/4"	60 Hz	120 V	15 A	180 W		Yes	Yes	Yes		17.2 cu. ft.	17.2 cu. ft.		Sabbath, Economy, Vacation	Yes	Yes	4	Yes	Yes	Yes	Glass w/Metal Trim	ω	4	All-LED Sidewall and Theater Lighting	Yes	Yes	Yes	


<sup>\*</sup> Sealed refrigeration system includes compressor, evaporator, condenser, dryer / strainer and connection tubing

ge 1 of 3

# FREEDOM® COLLECTION, PANEL-READY 30-INCH FLUSH CUSTOM FRESH FOOD COLUMN




### **CUTOUT DIMENSIONS**




- left door swing and handle(s). ready-to-install Stainless Steel door(s) with a right or dimensions may vary depending on kitchen reveals and toe kick. Stainless Steel models contain a panel-ready base unit, **A**: Area for installation of power connection. **B**: Niche depth depends on kitchen design. For a flush installation, the depth needs to be at least 24 inches plus the thickness of the door panel. Panel dimensions based on a standard <sup>1</sup>/8" inch reveal and 4 inch toe kick. Custom panel

### 4" (102 mm) 51/8" (130 mm)

### **TOP VIEW CLEARANCE**




\*\* Door handle must be added to this dimension







### PANEL DIMENSIONS



\*Excludes thickness of door panel. If standard panel with 3/4" thickness is mounted, total depth is 24 3/4".



These warranties give you specific legal rights and you may have other rights that vary from state to state. Full warranty and limited warranty from date of installation. For complete warranty details, refer to your Use & Care manual, or ask your dealer.

Specifications are for planning purposes only. Refer to installation instructions and consult your countertop supplier prior to making counter opening. Consult with a heating and ventilation engineer for your specific ventilation requirements. For the most detailed information, refer to installation instructions accompanying product or write to Thermador indicating the model number. Specifications are correct at time of printing. Thermador reserves the right to change product specifications or design without notice. Some models are certified for use in Canada.

Thermador is not responsible for products that are transported from the U.S. for use in Canada.