

STANDARD APPLIANCE OPENINGS

The purchaser acknowledges the following standard spaces for kitchen appliances:

Range Conventional – 30" Width

Hood Fan $-30^{\prime\prime}$ Width (must be the same or larger as range opening as per Ontario Building & Fire Code)

Refrigerator -36" W x 72" H (Approximate - height may change due to bulkheads)

Dishwasher – 24" Width

OTHER 6" Exhaust Vent above stove

UPGRADED APPLIANCE OPENINGS

*Check all that apply - NON-STANDARD APPLIANCE OPTIONS

NOTE: When upgrading appliances, there may be an additional charge to modify cabinetry and/or electrical and plumbing to accommodate the appropriate size from the manufacturer specifications of each appliance

MANUFACTURERS SPECIFICATIONS MUST BE ATTACHED

Slide-in Stove	GESTOVE	same as per Ontario Building Code)	36" / 42" Stove (Hood fan width will be the
OTR - Over 1	Warming Dra	Built-In Micro	Built-In Micro

Required) *(Gas/Electric — Cut-out Charge & Plug

Cooktop

will apply -6" is standard) Hood Ean (may require larger vent, charges Built-In Wall Oven

8" Vent / 10" Vent

appliance will not butt up against cabinetry) STOVE (clearance space will be left with this Chimney-boods ** CENTRE VENT ABOVE

owave with Trim Kit

owave Drawer with Trim Kit

The Range Microwave *Plug required

side by side or French Door, the wall beside the Built-in Refrigerator/Sub Zero — If purchasing a door may be an issue if it is deeper than 24"

to space accomodations *Applicable charges may apply if required to due

*Note: Refrigerator Door Swing

Wine / Bar Fridge (electrical required)

Steam Oven / Built-In Coffee makers

Cargo Waste Bin systems

installing counter above) Front Load Washer & Dryer *(Specs required if

Stackable Washer & Dryer

NOTE: It is the Purchaser's responsibility to coordinate delivery, installation and hook up of appliances and to ensure they are installed as per Manufacturers specifications after closing.

deliver forthwith to the Builder the manufacturer's appliance specifications where the size exceeds the standard

If specs not received, the <u>standard openings</u> as determined by Zancor Homes will be provided. If rework/repair is required due to late specs received, additional costs will be applied.

Appliance Specifications are to be sent to the Zancor Décor Centre no later than
ater thar
<u> </u>

Applian	Appliance Specifications received	- 1
Purchaser Signature 739	Date 00 22/16	
Purchaser Signature 100 100 100 100 100 100 100 100 100 10	Date 00028/16	
PROJECT as the South.	LOT 195	

48" BUILT-IN SIDE-BY-SIDE REFRIGERATOR/FREEZER

SUB*ZERO

BI-48S/S

91/8egro

FEATURES

Dual refrigeration keeps food fresher longer
Air purification system fights spoilage, odors

Crispers and deli drawers in low-temp, high-humidity zones for optimum freshness

Microprocessor control assures peak performance

Water-filtration system reduces contaminants, chlorine taste and odor

Freshness cards for maximum food preservation

Rigorously tested in our U.S. manufacturing facilities to ensure at least 20 years of heavy use

Exceptional 24/7 support from our Customer Care team based in Madison, Wisconsin and just footsteps from our factory

"Soft bright" interior lighting

Magnetic door seal system locks in cold air

Automatic ice maker with "max ice" feature

Adjustable shelves for maximum convenience

ACCESSORIES

Stainless steel kickplate

Grilles for 83" or 88" finished height (84" is standard)

Side panel mounting kit

Accessories are available through an authorized Sub-Zero dealer. For local dealer information, visit subzero-wolf.com/locator.





PRODUCT DETAILS

REFRIGERATOR

- 4 Adjustable glass shelves
- 1 Stationary glass shelf
- 1 High-humidity drawer with divider
- 2 Storage drawers with divider
- 3 Adjustable door shelves
- 2 Stationary door shelves
- Adjustable dairy compartment

FREEZER

- 3 Adjustable wire shelves
- 1 Stationary solid shelf
- 3 Storage drawers
- 5 Adjustable door shelves
- Automatic ice maker

W 748

5-61107

30" E SERIES TRANSITIONAL DROP-DOWN DOOR MICROWAVE OVEN

MOLF

PRODUCT SPECIFICATIONS

MDD30TE/S/TH

Dimensions

29 7/8"W x 17 7/8"H x 20"D

Door Clearance

Weight

14 3/16"

Electrical Service

80 lb

Overall Capacity

Power Cord Length

ELECTRICAL

5 amp dedicated circuit

120 VAC, 60 Hz


1.6 cu ft


4 feet

Electrical Supply


DIMENSIONS







STANDARD INSTALLATION





E SERIES TRANSITIONAL DROP-DOWN DOOR MICROWAVE OVEN

MDD30TE/S/TH

FEATURES

Integrates into any kitchen

Odd 23

Matches E series ovens, coffee systems, convection steam ov

900 watts of power

Generous 1.6. cu. ft. capacity

Quick-start controls for popular items

Gourmet mode cooks automatically from preset recipes

"Keep Warm" mode

Rigorously tested in our U.S. manufacturing facilities for decades of use

Exceptional 24/7 support from our Customer Care team in Madison



5 62 gor

MOLF

30" E SERIES TRANSITIONAL BUILT-IN SINGLE OVEN

PRODUCT SPECIFICATIONS

Dimensions 29 7/8"W x 27 7/8"H x 23 3/4"D 25"W x 16 1/2"H x 19"D SO30TE/S/TH

Oven 1 Interior Dimensions Usable Capacity Overall Capacity

Door Clearance

2.8 cu ft 4.5 cu ft

Electrical Service Electrical Supply


30 amp dedicated chouit

240/208 VAC, 60 Hz


273 lb 22"

Conduit Length


ELECTRICAL



DIMENSIONS



STANDARD INSTALLATION



30" E SERIES TRANSITIONAL BUILT-IN SINGLE OVEN



SO30TE/S/TH LOY 19-5 KK

FEATURES

10 cooking modes make meals easy

Three adjustable oven racks

Cobalt blue porcelain interior

Self clean, delayed start, timed cook, Sabbath mode and more

Installs flush with surrounding cabinetry

Dual convection oven for faster, more consistent cooking

Temperature probe lets you know when it's done

Rigorously tested in our U.S. manufacturing facilities for decades of use

Exceptional 24/7 support from our Customer Care team in Madison

Hidden bake element and recessed broil element

ACCESSORIES

30" baking sheet

Bake stone kit (stone, rack and peel)

Dehydration kit (racks and door stop)

Full-extension easy glide oven rack

Temperature probe and broiler pan

Set of three standard oven racks

Accessories available through an authorized Sub-Zero dealer. For local dealer information, visit subzero-wolf.com/locator.



XI M

36" SEALED BURNER RANGETOP - 6 BURNERS

MOLE

PRODUCT SPECIFICATIONS

SRT366


Weight Dimensions 35 7/8"W x 8 1/2"H x 28 1/2"D 220 **l**b

Electrical Supply 110/120 VAC, 60 Hz


Gas Supply Electrical Service 15 amp dedicated circuit 3/4" rigid pipe

Gas Inlet 1/2" NPT female


ELECTRICAL AND GAS



DIMENSIONS 81/2" (216) 71/2" (191) - 241/8" (613) 8¹/2" (216)



STANDARD INSTALLATION



"Without ventilation hood, 36" (914) minimum clearance countertop to combustible materials, 44" (18) for charboller, NOTE: Shaded area above countertop indicates minimum clearance to combustible surfaces, combustible materials cannot be located within this area. Electrical and gas supply located through bottom of platform. For Island installation, 12" (305) minimum clearance back of range to combustible rear wall above countertop.

5-6110

34" PRO HOOD LINER - 19" DEPTH

PRODUCT SPECIFICATIONS

Model PL341912

Dimensions 34 3/8"W x 12"H x 19 1/4"D
Weight 45 lb

 Weight
 45 lb

 Electrical Supply
 110/120 VAC, 60 Hz

15 amp dedicated circuit

Vertical

10" Round


Bottom of Hood to Countertop


Electrical Service
Discharge Location
Discharge Dimensions

DIMENSIONS

EPO 0

MOLF





ELECTRICAL

DECORATIVE



A MA

34" PRO HOOD LINER - 19" DEPTH

PL341912

FEATURES

Heavy-duty stainless steel construction

Infinite speed blower control

Recessed controls for sleeker look

Heat sentry for safety

Bright halogen lighting

Blower required (internal, in-line or remote blowers available)

Transition with backdraft minimizes backward flow of cold air

Rigorously tested in our U.S. manufacturing facilities for decades of use

Exceptional 24/7 support from our Customer Care team in Madison

ACCESSORIES

Make-up air damper

Accessories available through an authorized Sub-Zero dealer For local dealer information, visit subzero-wolf.com/locator.



BLOWER OPTIONS

- 300 CFM Internal
- 450 CFM Internal
- 900 CFM Internal
- · 1100 CFM Inline
- · 1200 CFM Remote · 900 CFM Remote
- 1500 CFM Remote
- → 600 CFM Internal

36" SEALED BURNER RANGETOP - 6 BURNERS

SRT366

FEATURES

6 dual-stacked, seamless burners

Dual-stacked burners go from 20,000 Btu down to a mere breath of flame

Continuous cast-iron grates for easy movement of pots and pans

Heavy-gauge stainless steel

Rigorously tested in our U.S. manufacturing facilities for decades of use

Exceptional 24/7 support from our Customer Care team in Madison

Signature red infinite control knobs

Individual spark ignition system

ACCESSORIES

Stainless steel, brass or chrome bezels


High altitude conversion kit

Cast iron S-grates and wok grate

Signature red, black or stainless steel control knobs

5" and 10" stainless steel risers, and 20" riser with shelf

Accessories available through an authorized Sub-Zero dealer. For local dealer information, visit subzero-wolf.com/locator.










TOP CONFIGURATION



RANGETOP SPECIFICATIONS

- 1 9,200 Btu Burner
- 2 15,000 Btu Burners
- 2 18,000 Btu Burners
- 1 20,000 Btu Burner




9//8CB0




Dishwashers

24" Recessed Handle Dishwasher 800 Plus Series- Stainless steel SHE7PT55UC



measurements in inches (mm)



All connections are at the rear of the appliance. Extension for drain hose available as accessory. Power cord for connection to electrical outlet (3-prong ptug) available as accessory.

3/3

M88900 5-61,107



Dishwashers

SHE7PT55UC 800 Plus Series- Stainless Dishwasher 24" Recessed Handle














Plug type:

fixed connection 33 7/8 " x 23 5/8 " x 24 "

860-890 x 600 x 610





- 42 dBA: Quietest Dishwasher Brand in the North America.
- A flexible 3rd rack with folding tines adds 30% more loading
- Water softener ensures optimally spot-free and shiny dishes.
- Touch Control Technology allows for quick cycle programming.
 RackMatic® offers 3 height levels, for 9 possible rack positions.
- 42 dBA: Quietest Dishwasher Brand in the North America.

item clips, baking-sheet spray head grey, bottle holder metal	Accessories Parts : 3 small	Silverware Basket :	3rd Rack :	Upper rack cup shelf :	Adjustable upper rack :	
rey, bottle holder metal		Standard	3rd Rack 2.0	2	Rackmatic 3-stage	

saz9091UC, Optional accessories: SMZ5000, SGZ1010UC, SMZ5002UC, SMZPC002UC

Energy Star® qualified : Energy Consumption (kWh/yr) : Frequency (Hz): Volts (V): Current (A) : Watts (W) Silence level (dBA): Panel ready :
Alternative colors available : Variant color : SHE7PT52UC, SHE7PT56UC Stainless steel 1300 259 120 Yes

Required cutout size (HxWxD) (in): 33 7/8
Required cutout size (HxWxD) (mm): 8
Required cutout size (HxWxD) (in): 9
Overall appliance dimensions (HxWxD) (in): 9
9/16 " Length inlet hose (in) : Length inlet hose (cm) : Length outlet hose (in) : Length outlet hose (cm) : Power cord length (cm): Power cord length (in): Product packaging dimensions (HxWxD) (in) : 7/8 23 9/16 35 3/4" x 26" x 29 5/16" × 23 43 1/2" 110 67 " 175.0 135 53"

Number of place settings : Tub material: ADA Compliant Stainless steel TallTub


Optional accessories

SMZ5002UC : Silverware box SMZPC002UC : Powercord with cold plug SMZ5000 : Dishwashing aid set SGZ1010UC: Drain hose extension kit SGZ9091UC: finish salt for dishwashers

V42H5200EP


Samsung Front-Load Electric Dryer

Installing Options









11 Preset Dry Cycles: Steam Refresh, Steam Wrinkle Away, Normal, Heavy

4-Way Venting

7.5 cu. ft. Capacity DOE

Duty, Permanent Press, Bedding, Delicates, Sanitize, Time Dry, Air Fluff, Quick Dry

Stacked Depth

10 Options:
Mixed Load Bell, Wrinkle Prevent, Anti Static,
Small Load Care, My Cycle, Adjust Time, Sound,
Child Lock, Smart Care, Drum Light


Installing Your Dryer


1. Alcove or closet installation

MINIMUM CLEARANCES FOR CLOSET AND ALCOVE INSTALLATIONS:

Top – 1 /" Closet Front – 2"


If the washer and dryer are installed together, the closet front must have at least a 72" unobstructed air opening. Your washer alone does not require a specific air opening.





Dimensions

2. With optional pedestal base or stacking kit



2 Signal Level Settings: On/Off

Very Dry, More Dry, Normal Dry, Damp Dry

4 Dry Levels:

High, Medium, Low, Extra Low

4 Temperature Settings:

Warranty
One (1) Year Parts and Labor
One (1) Year Control Board Three (3) Years Stainless Steel Drum Ten (10) Years Direct Drive Motor

Product Dimensions & Weight (WxHxD) Dimensions: 27" x 3811/16" x 323/8"

Weight: 126 lbs

Shipping Dimensions & Weight (WxHxD) Dimensions: 291/4" x 421/4" x 331/2"

Weight: 134 lbs

Electric	Model #	UPC Code
Platinum	DV42H5200EP	887276963204
White	DV42H5200EW	887276963211

		1 1 1
Platinum	DV42H5200EP	887276963204
White	DV42H5200EW	887276963211
Gas	Model#	UPC Code
Platinum	DV42H5200GP	887276963235
White	DV42H5200GW	887276963242

Platin Matching Washer

Marching Madrice	Š	
Platinum	WF42H5200AP	887276963082
White	WF42H5200AW	887276962993

DV42H5200EP

Samsung Front-Load Electric Dryer

7.5 cu. ft. Capacity DOE

Features

- Steam Drying Technology:
 Steam Refresh
 Steam Wrinkle Away

- Smart Care
 11 Preset Drying Cycles
 10 Options
- 4 Temperature Settings
 4-Way Venting
- Sensor Dry Detects Moisture and Adjusts Drying Time
 Dryer Drum Light
- Reversible See-Through Door

Convenience

- Child Lock
- My Cycle OptionLint Filter Indicator





Steam Dry



Smart Care

Available Colors:



Platinum (shown)



Signature Features

STEAM DRY

- Steam away wrinkles.
 Helps remove odors and freshen clothes.
 Spend less time ironing.
 Fewer trips to the dry cleaner.

SMART CARE

- Troubleshoot with your smartphone.

 Perform a quick diagnosis of your washer and dryer right from your smartphone.*

 The add the ACC TENNISHED SECTION 1881 2.

SENSOR DRY

Automatically adjusts drying time by sensing moisture so your clothes don't over or under dry.



WF42H5200AP

5-6120

Samsung Front-Load Washer

4.8 cu. ft. Capacity IEC

Features

- Steam Washing
 Smart Care[™]
- Self Clean+
- VRT® Vibration Reduction Technology
- Diamond Drum® Design
 Direct Drive Motor
- 1200 rpm Maximum Spin Speed
- Internal Water Heater
 9 Preset Wash Cycles
- 10 Options
- Garment-

Convenience

- Child LockDoor Lock
- Dispenser Trays: Main Wash, Softener, Bleach











Smart Care



Self Clean+

Available Colour:



(shown) Platinum

Signature Features

STEAM WASHING

- Powerful steam removes stains.
- No pre-treatment needed.

SMART CARE

- Troubleshoot with your smartphone.
 Perform a quick diagnosis of your washer right from your smartphone.*
 *Modifiable on Google Physicathic Appliance.

SELF CLEAN+

Ranked "Highest in Customer Satisfaction with Clothes Washers" in 2013 & 2014 by J.D. Power and Associates.

- New self-cleaning technology.
 Keeps your front load washer fresh without the use of harsh chemicals.
 Reminds you to run Self Clean+ every 40 cycles.
 Additional cleaning of the gasket.

Achieved the U.S. Environmental Protection Agency's 2014 ENERGY STAR®
"Most Efficient" designation.

Most Efficient 2014







WF42H5200AP


Samsung Front-Load Washer

4.8

Cu. Ħ.


Capacity IEC

Installing Options









Rinse and Spin

10 Options:

Normal, Heavy Duty, Permanent Press, Sanitize, Allergen, Bedding, Delicates, Quick Wash,


9 Preset Wash Cycles:


Stacked Depth


Steam, Self Clean+, Delay End, My Cycle, Extra Rinse, Extra Spin, Sound, Spin Only, Child Lock, Smart Care

Installing Your Washer

If the washer and dryer are installed together, the closet front must have at least a 72" unobstructed air opening. Your washer alone does not require a specific air opening.








Alcove or closet installation

Minimum clearances for closet and alcove installations:

Sides – 1"
Rear – 5⁷/₈"
Top – 17"
Closet Front – 2"

Dimensions

2. With optional pedestal base or stacking kit Required Dimensions for Installation with Pedestal



Warranty

Main Wash, Softener, Bleach

Dispenser Trays:

3 Soil Settings: Heavy, Normal, Light

High, Medium, Low, No Spin

4 Spin Settings:

Hot, Warm, Eco Warm, Cold

4 Temperature Settings:

Ten (10) Years Direct Drive Motor

One (1) Year Parts and I abour Two (2) Years Control Board Three (3) Years Stainless Steel Drum

Product Dimensions & Weight (WxHxD)
Dimensions: 27" x 38" /16" x 33"
Weight: 194 lbs

Shipping Dimensions & Weight (WxHxD) Dimensions: 291/4" x 4111/16" x 345/8"

Colour Weight: 203 lbs

Model #

Platinum WF42H5200AP **UPC Code** 887276963082

Platinum Matching Dryer (Electric/Gas) DV42H5200FP 887276957135

Platinum DV42H5200GP 887276963235


48" BUILT-IN SIDE-BY-SIDE REFRIGERATOR/FREEZER

SUB-ZERO


PRODUCT SPECIFICATIONS

35–120 psi	Plumbing Pressure
1/4" OD copper, braided stainless steel or PEX tubing	Plumbing Supply
15 amp dedicated circuit	Electrical Service
115 VAC, 60 Hz	Electrical Supply
9.8 cu ft	Freezer Capacity
19.1 cu ft	Refrigerator Capacity
630 lb	Weight
30"	Door Clearance
48"W x 84"H x 24"D	Dimensions
BI-48S/S	Model

ELECTRICAL




INTERIOR VIEW



This illustration is intended for interior reference only and may not represent the exterior of the model being specified.

2 //X

DIMENSIONS 28/16



STANDARD INSTALLATION

