

**PALERMO**  
INSERT

ASPIRE SERIES



Palermo provides professional grade performance, while its 28<sup>1/4"</sup> width and 10<sup>3/4"</sup> depth enables it to be discreetly installed within standard 12" deep cabinetry, making it ideal for smaller kitchens or where the range hood needs to be out of sight. Palermo has a powerful 600 CFM blower to support most cooking needs. Stylish stainless steel push button controls operate a 3-speed blower and halogen lighting.

Easy maintenance, higher efficiency and a cleaner kitchen are ensured by Elica's patented Baffle Slot Filters, which capture a higher percentage of grease and hold larger volumes of grease than traditional baffle filters. Palermo is designed for standard ducted or recirculating installation.

#### MODELS

EPR628SS Palermo 28" Stainless

#### DIMENSIONS

(28 <sup>1/4"</sup>W x 10 <sup>3/4"</sup>D x 9 <sup>1/2"</sup>H)



Halogen Lamps



Stainless Steel  
Push Button Controls



Stainless Steel  
Baffle Slot Filters

Lot B Apr 26/17

## FEATURES

Size (in) & Type Finish	28" Wide Insert Stainless Steel
Controls	Stainless Steel Push Button
Illumination	2, 40 Watt Halogen Lamps, 1 Light Intensity (bulbs included)
Installation Type	Ducted or Recirculating Installation Recirculating Kit Sold Separately
Blower Type	600 CFM, 3-Speed Internal
Blower Performance	Speed 1, 190 CFM, 2.1 Sones Speed 2, 350 CFM, 4.7 Sones Speed 3, 600 CFM, 8.1 Sones
Filter Type	2, Dishwasher-Safe, Stainless Steel Baffle Slot
Duct Transition	6" Round with Back Draft Damper (top)
Electrical	120V-60Hz 260 Watts at 4.6 Amps
Warranty	2 Year Parts & Labor, In-Home Service

## ACCESSORIES



Optional Recirculating Kit with 2 Carbon Filters

CODE: KIT02770  
MODEL: KIT02770



Optional 30" Hood Liner  
29"W x 17 1/2" - 20 1/2"D


CODE: KIT02773  
MODEL: EXXHDL30



Optional 36" Hood Liner  
25"W x 17 1/2" - 20 1/2"D

CODE: KIT02774  
MODEL: EXXHDL36

## LINE DRAWING



## CONSUMABLE PARTS

Replacement Grease Filter (1)  
CODE: GRI0018064

Replacement Carbon Filter (1)  
CODE: FB016A

Replacement Light Bulb (1)  
CODE: 2006EA


Consumable parts are sold in units of one (1). Order accordingly.

LOT 13 APR 26/17

## INSTRUCTION SHEET

### TRIMKITSS2 (Part# 297333610) Trim Kit Dimensions

10613  
3/30/17



**Safety:** Always wear safety glasses when using power tools.

#### Tools Needed:

- Phillips™ Screwdriver
- Flathead Screwdriver
- Safety Glasses
- Adjustable Wrench to fit 1-1/4"
- 3/8" Socket Wrench
- 7/16" Socket Wrench
- Step Ladder
- Tape Measure (min. 7" length)
- Drill & 1/8" Bit

#### Before You Begin

- Be careful when unpacking components. Do not use sharp objects when removing packaging material. This may scratch the surface of trim components.
- Use extreme care when handling the metal trim pieces. Corners are very sharp and easily damaged if dropped.


**FRIGIDAIRE**  
PROFESSIONAL.

60613

3/30/17  
18.6 Cu. Ft.

# All Freezer

## FPU19F8RF



Shown with companion, All-Refrigerator model FPRU19F8RF and optional coordinated Dual 75" Louvered Trim Kit (TRIMKITEZ2).

### Product Dimensions

Height (Cabinet Incl. Hinge)	70-5/8"
Width	32"
Depth (Including Door)	26-1/2"

### More Easy-To-Use Features

#### Soft Freeze™ Zone

Keep frozen foods soft and easy to eat with the Soft Freeze™ Zone. Great for foods like ice cream, sticks of margarine and bread.

#### PowerBright™ LED Lighting

Find frozen foods quickly with PowerBright™ LED Lighting.

#### SpacePro™ Shelving

Optimize your freezer space with adjustable shelving.

#### SpacePro™ Door Bins

Adjustable door bins for quick access to frozen foods.

#### SpacePro™ Storage Baskets

Two full-width adjustable storage baskets keep things organized, and accessible.

#### PowerPlus® Ice Maker

Unlimited access to ice.

#### PrecisionPro Controls™

Adjust settings at the touch of a button.

Sabbath Mode (Star-K® Certified)

Available in:



Stainless  
(F)

### Optional Trim Kits

#### Single 79" Louvered or 75" Collar Trim Kit (TRIMKITEZ1)


Optional trim kit that is designed to provide a built-in look for the All Refrigerator and All Freezer when the units are installed next to each other. Install with louver for 79" fit or easy-to-remove louver for a 75" fitted collar look.

#### Dual 79" Louvered or 75" Collar Trim Kit (TRIMKITEZ2)

Optional trim kit that is designed to provide a built-in look for the All Refrigerator and All Freezer when the units are installed next to each other. Install with louver for 79" fit or easy-to-remove louver for a 75" fitted collar look.

\*Based on a six-hour closed door test of certain common odours in the fresh food compartment of a 21 Cu. Ft. refrigerator.

### Signature Features



#### PureAir Ultra® Filtration System

Fresh air offers great taste. PureAir Ultra® Filtration removes up to 7 times more odour than baking soda to keep ingredients tasting fresh by removing odour particles with fast-acting, highly absorbent carbon technology.\*



#### Smudge-Proof™

Resists fingerprints and cleans easily.



#### SpacePro™ Shelving System

Always have ingredients on-hand and accessible with organizational solutions designed for space optimization like SpacePro™ Door Bins, SpacePro™ Shelving and SpacePro™ Storage Baskets.



#### Automatic Alerts

Alerts you if the door is left open, if the temperature rises or if the power goes out so your food stays at its optimal temperature.

10613

3/30/17

### Features

Door Design	Flat
Door Finish	Smudge-Proof™ Stainless Steel
Door Handle Design	Stainless Steel
Cabinet Finish	Grey
Door Hinge Covers	Hidden
Automatic Door Closer	Yes
Leveling System/Leveling Legs	Yes / 4

### Controls

Controls	PrecisionPro™
Location of Controls	Inside Cabinet, on Top
Temperature Display C°/F°	Yes
Control Lock/Light	No / Yes
Temp Failure Alerts (Audible & Duration)	Yes
Door Ajar Alert (Audible)	Yes
Power Failure Alert (Duration)	Yes
Air Filter / Air Filter Change Indicator Light	PureAir Ultra™ / Yes

### Freezer Features

Freezer Shelves	2 SpacePro™ Adjustable Glass
PowerPlus™ Ice Maker	Yes
Ice Bin	Yes
Full-Width Mid-Level Basket	1 Plastic SpacePro™
Full-Width Bottom Basket	1 Plastic SpacePro™
Full-Width Gallon Door Bin	1 Clear SpacePro™
Half-Width Litre Bin	5 Clear SpacePro™
Soft Freeze™ Zone	Yes
Lighting	8-Point PowerBright™ LED

### Optional Accessories

Single Louvered Trim Kit	PN# TRIMKITEZ1
Dual Louvered Trim Kit	PN# TRIMKITEZ2

### Certifications

Sabbath Mode (Star-K® Certified)	Yes
----------------------------------	-----

### Specifications

Total Capacity (Cu. Ft.)	18.6
Shelf Area (Sq. Ft.)	20.9
Annual Energy (kWh)	593
Annual Energy Cost (12/kWh)	\$71
Power Supply Connection Location	Right Bottom Rear
Water Inlet Location	Left Bottom Rear
Voltage Rating	115V / 60Hz / 20A
Connected Load (kW rating) @ 115 Volts¹	0.55
Amps @ 115 Volts	15
Minimum Circuit Required (Amps)	20
Shipping Weight (Approx.)	245 Lbs.

<sup>1</sup>An electrical supply with grounded three-prong receptacle is required. The power supply circuit must be installed in accordance with current local and national codes & ordinances.


### Optional Trim Kits

Kits include top and side trim pieces, louvered grille, reversible kickplate and leveling system to fit 75" or 79" opening height.

#### Single 79" Louvered or 75" Collar Trim Kit PN# TRIMKITEZ1

#### Dual 79" Louvered or 75" Collar Trim Kit PN# TRIMKITEZ2 (Includes hardware to secure side-by-side units together.)

Note: Both kits attach directly to cabinetry through top trim piece or louvered grille to stabilize unit(s).



NOTE: For planning purposes only. Always consult local and national electric and plumbing codes. Refer to Product Installation Guide for detailed installation instructions on the web at [frigidaire.ca](http://frigidaire.ca).



### Overall Exterior Dimensions

A - Height (Incl. Door)/(Cabinet Incl. Hinge)	71-3/8" / 70-5/8"
B - Width	32"
C - Depth (Incl. Door)	26-1/2"
Depth with Door Open 90°	57-3/8"

### Built-In Cutout Dimensions

#### Single Unit without Trim Kit -

A - Height	72"
B - Width	33"
C - Depth	25-1/4" min. <sup>1</sup>

#### Single Unit with Trim Kit & Leveling System -

A - Height	75" or 79"
B - Width	33"
C - Depth	25-1/4" min. <sup>1</sup>

### Built-In Cutout Dimensions

#### Dual Unit² without Trim Kit -

A - Height	72"
B - Width	66"
C - Depth	25-1/4" min. <sup>1</sup>

#### Dual Unit² with Trim Kit & Leveling System -

A - Height	75" or 79"
B - Width	66"
C - Depth	25-1/4" min. <sup>1</sup>

<sup>1</sup>Minimum depth from face of cabinet side panels and requires recessed electrical outlet.


<sup>2</sup>Side-by-Side

Accessories information available on the web at [frigidaire.ca](http://frigidaire.ca)



L0613

3/30/17



### All-Freezer Cutout Dimensions

#### Built-In Installation (without Trim Kit)

##### Single Unit

(A) 72" (B) 33" (C) 25 1/4" min.†

##### Double Unit (Side-by-Side)

(A) 72" (B) 66" (C) 25 1/4" min.†

#### Built-In Installation (with Trim Kit & Leveling System)

##### Single Unit

(A) 75" or 79" (B) 33" (C) 25 1/4" min.†

##### Double Unit (Side-by-Side)

(A) 75" or 79" (B) 66" (C) 25 1/4" min.†

#### Leveling System

(2) per unit raises height 2-9/16" min.  
Only available with trim kits.



† Minimum depth from face of cabinet side panels and requires recessed electrical outlet.

### Built-In All-Freezer Specifications

- Product Shipping Weight - 245 Lbs.
- An electrical supply with grounded three-prong receptacle is required. The power supply circuit must be installed in accordance with current edition of National Electrical Code (NECA 70) and local codes & ordinances.
- Voltage Rating - 115V/60 Hz/20 Amps
- Connected Load (kW Rating) @ 115 Volts = 0.55 kW
- Amps @ 115 Volts = 15 Amps
- Always consult local and national electric & plumbing codes.
- Water line for ice maker can enter opening through floor or rear wall. Copper tubing recommended between cold water line and water connection location. Water line tubing recommended is 48" minimum length by 1/4" diameter. Installation of easily accessible shutoff valve in water line required.
- Minimum 25-1/4" depth requires recessed electrical outlet and copper water line.
- To allow for ease of installation, tape excess power cord to back of unit.
- To allow for ease of moving out side-by-side units after installation, 84" minimum length of coiled copper tubing recommended.
- When installing freezer adjacent to wall, cabinet or other appliance that extends beyond front edge of unit, 20" minimum clearance recommended to allow for optimum 140° door swing, providing complete drawer / crisper access and removal. (Absolute 4" minimum clearance will ONLY allow for 90° door swing which will provide limited drawer / crisper access with restricted removal.)
- Minimum 3, 3/8" clearance required for sides and top of refrigerator or freezer with 1" clearance at rear to allow for ease of installation, proper air circulation, and plumbing/electrical connections.

- To ensure optimum performance, (do not install in areas where temperature drops below 55°F or rises above 110°F) and avoid installing in direct sunlight or close proximity to range, dishwasher or other heat source.
- Freezer must be placed on level surface of hard material, same height as flooring. Surface must support approximately 800 lbs. when fully loaded. Unit equipped with 4-point leveling.

### "Built-In Look" Specifications

- Minimum opening of 72" H x 33" W x 25-1/4" D required for single-unit "Built-In Look" installation; 66" W required for double-unit installation. (72" H to be measured from finished floor to underside of soffit or overhead cabinet.)
- Remove all wall / floor moulding prior to built-in installation.

### Optional Trim Kit Specifications

- If optional Single or Double Louvered Trim Kit is to be used, different cutout dimensions are required. Kit can be adapted to fit either 75" or 79" opening height. (Refer to cutout dimensions on this page and detailed Louvered Trim Kit installation instructions included with kit or on web.)
- Remove all wall / floor moulding prior to built-in installation.

**Note:** For planning purposes only. Refer to Product Installation Guide on the web at [frigidaire.ca](http://frigidaire.ca) for detailed instructions.


### Optional Accessories

- Single Louvered Trim Kit - (PN # TRIMKITEZ1).
- Double Louvered Trim Kit - (PN # TRIMKITEZ2).
- PureAdvantage™ Air Filter Replacement Cartridge - (PN # 241754001).



Specifications  
subject to change.  
Printed in Canada

60613  
3/30/17



Microwave Ovens    Countertop  
**Countertop NN-SD965S**

<b>MODEL &amp; SIZE</b>	<b>Model Number</b>	NN-SD965S
	<b>Type</b>	Full-size
	<b>Installation</b>	Countertop or built-in
	<b>Oven Capacity</b>	2.2 cu. ft.
	<b>Cooking Power</b>	1200W
	<b>Turntable Diameter</b>	420mm
<b>PANASONIC TECHNOLOGY</b>	<b>Panasonic Inverter</b>	Cyclonic Inverter
	<b>Genius Sensor</b>	Genius®
<b>DESIGN</b>	<b>Color</b>	Stainless Steel
	<b>Control Panel</b>	Dial + Button
	<b>Display Panel</b>	New 6 Digit LCD / Green
<b>STYLE</b>	<b>Door Window</b>	Smoked Glass
	<b>Door Release</b>	Push Open
	<b>Oven Interior</b>	Paint White
<b>PERFORMANCE</b>	<b>Multi-stage Cooking</b>	3 stage
<b>PROGRAMMABLE FEATURES</b>	<b>Sensor Cook</b>	Yes
	<b>Sensor Reheat</b>	Yes
	<b>Auto Cook/Reheat</b>	Yes
	<b>More / Less Control</b>	Yes
	<b>Inverter Turbo Defrost</b>	Yes
	<b>Keep Warm Button</b>	Yes
	<b>Popcorn Button</b>	Yes

60613

		Quick Minute	Yes
SPECIFICATIONS	Cavity Dimensions (W x D x H)		Approx. 469 x 470 x 278 mm 17.6 x 18.5 x 10.7 inch
	Unit Dimensions (W x D x H)		606 x 506 x 356 mm 23.9 x 19.9 x 14 inch
	Carton Dimensions (W x D x H)		675 x 540 x 420 mm
ACCESSORIES	TRIM KITS	27" Model Number	NN-TK922S
		30" Model Number	NN-TK932S
	Accessory		Glass Tray

Copyright ©Panasonic Canada Inc.




10613  
3/30/17

# Built-In Cooktop

FPGC3677RS

36" Gas



## Product Dimensions

Width	36"
Depth	21-3/4"
Height	4-1/4"

## Available in:



Stainless  
(S)

Burners	BTU
Right Front	14,000
Right Rear	750 - 5,000
Left Front	9,500
Left Rear	9,500
Centre	18,200

## Signature Features




### PowerPlus® Burner

Boil, sear, and sauté with power. The PowerPlus® Burner delivers strong performance, every time with 18,200 BTU.



### Durable, Continuous Grates

Cook a variety of dishes at the same time with ease. Our durable, continuous cast-iron grates allow you to slide a variety of heavy pots and pans across burners. Plus, they're dishwasher-safe so you can clean with ease.



### PrecisionPro Controls™

Prepare a range of dishes with precision, whether you're simmering, sautéing, searing or boiling.



### Stainless Steel Cooktop

The entire cooktop surface is stainless steel to blend with the other appliances in your kitchen.

#### Features

Controls	PrecisionPro™
Surface Type	Stainless Steel Recessed
Sealed Gas Burners	Yes
Grates	Continuous Cast Iron w/Black Matte Finish
Right Front Burner (BTU)	14,000
Right Rear Burner (BTU)	750 to 5,000
Left Front Burner (BTU)	9,500
Left Rear Burner (BTU)	9,500
Centre Burner (BTU)	18,200
Control Location	Centre Front
Knob Colour	Stainless
Knob Type	Cast Metal

#### Optional Accessories


Griddle	Included
---------	----------

#### Specifications

Power Supply Connection Location	Right Rear
Gas Supply Connection Location	Right Rear
LP Gas Conversion Kit	Included
Voltage Rating	120V / 60 Hz / 15A
Amps @ 120 Volts¹	1.0
Minimum Circuit Required (Amps)	15
Approved for Electric Single Wall Oven Combination Installation²	Yes
Shipping Weight (Approx.)	60 Lbs

¹For use on adequately wired 120V, dedicated circuit having 2-wire service with a separate ground wire. Appliance must be grounded for safe operation.

²Cooktops are approved for installation above any of our Electric Single Wall Ovens.



**NOTE:** For planning purposes only. Always consult local and national electric and gas codes. Refer to Product Installation Guide for detailed installation instructions on the web at [frigidaire.ca](http://frigidaire.ca).



#### Product Dimensions

A - Width	36"
B - Depth	21-3/4"
C - Height	4-1/4"


#### Cutout Dimensions

Width (Min.) / (Max.)	33-7/8" / 34-1/4"
Depth (Min.) / (Max.)	19-3/8" / 19-3/4"
Height	8"

Granite Countertop Installation Kit available.

Accessories information available on the web at [frigidaire.ca](http://frigidaire.ca)

**Panasonic®**



10613  
3/30/17

## **Installation Instructions**

## **Notice d'installation**

## **Instrucciones para la instalación**

<b>Cabinet</b> <b>Armoire</b> <b>Gabinete</b>	<b>Trim kit</b> <b>Nécessaire d'encastrement</b> <b>Juego de acabados</b>
30" (762 mm) 30 po (762 mm) 30" (762 mm)	NN-TK932S NN-TK732S
<del>27" (686 mm)</del> <del>27 po (686 mm)</del> <del>27" (686 mm)</del>	<del>NN-TK922S</del> <del>NN-TK722S</del>

Read carefully and keep these installation instructions.  
Lisez attentivement et conservez cette notice d'installation.  
Lea cuidadosamente y guarde este instructivo de  
instalación para su referencia.

© Panasonic Appliances Microwave Oven (Shanghai) Co., Ltd. 2012

60113

## Contents

Caution .....	1-3
Step 1. Unpacking List.....	4
Step 2. Feature Diagram .....	5
Step 3. Cabinet Preparation .....	6-9
Step 4. Microwave Oven Installation .....	10-11
Step 5. Cabinet Installation.....	12-14
Step 6. Finishing Installation.....	15-17

## Caution

1. Read and follow all instructions completely.
2. This trim kit can be installed into a cabinet. The cabinet opening must have the following internal dimensions as shown in **fig 1, P6 - P9**.

**MINIMUM INSTALLATION HEIGHT 36¼" (920 mm).**

3. This Trim Kit is designed for use only with the Panasonic Microwave Oven Models listed.
4. For safe use of your oven, DO NOT alter or modify any part of this kit or oven.
5. Oven must be used with a properly grounded receptacle. Refer to operating instructions to determine the correct electrical requirements.
6. Observe all applicable building and electrical codes.
7. The oven must be unplugged before attempting the installation of this kit.
8. The supporting shelf must be capable of supporting 100 lbs (45 kg).
9. Save these instructions for local inspection and relocation of oven.

**TAKE CARE NOT TO KINK OR TRAP THE MICROWAVE ELECTRICAL CABLE.**

The diagram may vary from the actual unit and is only for your reference.

Trim kit	Oven
NN-TK932S NN-TK922S	NN-SE9**S
	NN-SD9**S
	NN-SN9**S
	NN-ST9**S
<del>NN-TK732S</del> <del>NN-TK722S</del>	<del>NN-SE7**S</del>
	<del>NN-SD7**S</del>
	<del>NN-SN7**S</del>

## Step 2. Feature Diagram



Installed Image

## Étape 2. Schéma d'ensemble

Ensemble Installé

## Paso 2. Esquema de funciones

Imagen de la Instalación



Trim Kit Dimensions				
	TK932S	<del>TK922S</del>	<del>TK732S</del>	<del>TK722S</del>
Width	30" (760 mm)	<del>27" (684 mm)</del>	<del>20" (760 mm)</del>	<del>27" (684 mm)</del>
Height	18 5/8" (472 mm)	<del>18 1/2" (472 mm)</del>	<del>16 1/2" (419 mm)</del>	<del>16 1/2" (419 mm)</del>
Depth (Thickness)	3/4" (20 mm)	<del>3/4" (20 mm)</del>	<del>3/4" (20 mm)</del>	<del>3/4" (20 mm)</del>


Dimensions du nécessaire d'encastrement				
	TK932S	TK922S	TK732S	TK722S
Largeur	760 mm (30 po)	684 mm (27 po)	760 mm (30 po)	684 mm (27 po)
Hauteur	472 mm (18 5/8 po)	472 mm (18 1/2 po)	419 mm (16 1/2 po)	419 mm (16 1/2 po)
Profondeur (épaisseur)	20 mm (3/4 po)	20 mm (3/4 po)	20 mm (3/4 po)	20 mm (3/4 po)

Dimensiones del juego de acabados				
	TK932S	TK922S	TK732S	TK722S
Ancho	30" (760 mm)	27" (684 mm)	30" (760 mm)	27" (684 mm)
Altura	18 5/8" (472 mm)	18 1/2" (472 mm)	16 1/2" (419 mm)	16 1/2" (419 mm)
Profundidad (grosor)	3/4" (20 mm)	3/4" (20 mm)	3/4" (20 mm)	3/4" (20 mm)

6061311  
3/30/17

**Step 3-1. Cabinet Preparation (For TK932S)**  
**Étape 3-1. Préparatifs de l'armoire (Pour TK932S)**  
**Paso 3-1. Preparación del gabinete (For TK932S)**

fig 1.





**FRIGIDAIRE**  
PROFESSIONAL.

Lot B  
WAS A7A

# Dishwasher

FPID2497RF

24" Built-In

MAR 30/17

## Product Dimensions

Height (Adjustable)	33-3/4" - 35-3/4"
Width	24"
Depth (Including Door)	24-1/4"



## More Easy-To-Use Features

### PowerPlus™ Dry

Flawlessly finishes dishes so they are cabinet-ready.

### PowerSense Technology™

Automatically adjusts the cycle time based on how much cleaning your dishes need.

### PowerPlus™ Filtration System

For a consistent, reliable clean, our Frigidaire Professional dishwasher has a removable stainless steel filter that prevents re-depositing of food particles.

### Delicate-Care™ Soft Grips

Holds delicate dishes like glasses in place so they don't move around during the cleaning process.

### Multiple Cycle Options

Features a variety of cleaning solutions for a range of cleaning needs like Sanitize to help kill germs, Rinse Only to keep food from sticking to plates, and PowerPlus™ Wash to clean crusty dishes with dried-on food.

### PowerBright™ Floor Light

Alerts you to when dishes are complete with an LED light that beams on the floor.


### Holds up to 14 Place Settings

Wash even more at once with large capacity racks that fit up to 14 place settings in a single load.

### Stemware Holders and Fold-Down Tines


Easily switches from stemware holders to fold-down tines, fold-down tines for when you need to fit larger items on the top rack like pots and pans and stemware holders for when you need to secure glasses.

## Signature Features




### PowerPlus™ 30-Minute Wash

Powerful clean, fast. Washes dishes in a quarter of the time.<sup>1</sup>




### PrecisionPro Wash Zones™

Target clean dishes with hard-to-reach areas of bottles and delicate stemware.



### OrbitPower™ Wash Technology

Powerful clean, with 4 times better wash coverage.<sup>2</sup>



### Smudge-Proof™ Stainless Steel

Resists fingerprints and cleans easily.

ENERGY STAR®  
NSF® International  
Certification



Available in:



Stainless  
(F)

<sup>1</sup>Compared to the normal cycle on 2014 Frigidaire® dishwasher models.

<sup>2</sup>Than a traditional lower spray arm.

frigidaire.ca

10613

3/30/17

### Features

Control Design	Fully-Integrated Pro-Select <sup>1</sup>
Digital Display	Yes
Door Latch/Stay-Put Door Hinge Design	Yes/Yes
Low Rinse-Aid Indicator Light	Yes
Interior Design/Interior Colour	Tall Tub/Stainless Steel
Wash System	Direct Feed
Wash Arm	OrbitPower™
Wash Levels/Wash Speeds	5/Variable
PowerSense Technology™	Yes
AquaSurge™ Technology	Yes
Sound Package	SilentDesign™
Filter/Filter Trap	5 Steel/Removable
Soft Food Disposer	
dB Level	47
Drying System	PowerPlus™ Dry

### Cycles

Number of Cycles	7
PowerPlus™ (Heavy)	Yes
Normal	Yes
Light	
Quick Wash (30-Min)	Yes
Favourite	Yes
China Crystal	Yes
Rinse Only	Yes
Energy Saver Plus	Yes
Upper Rack Wash Only	
Cycle Indicator Light/Control Lock	Yes/Yes
Cycle Complete Floor Beam Indicator	LED

### Options

Heat/No Heat Dry	Yes
Hi-Temp Wash	Yes
NSF® Certified Sanitize Rinse	Yes
Delay Start	1-24 Hour

### Rack System

Rack Design	Deluxe
Rack Coating	Nylon TufRacks™
SpaceWise® Upper Rack -	
Rack Handles	Yes
Delicate-Care™ Soft Grips	Yes
Fold-Down Tines	Yes
Cup Shelves/Stemware Grips	2/6
Versa-Tray™	
Adjustable Rack Height	Yes
Lower Rack -	
SpaceWise® Silverware Basket	3-Piece Split
Fold-Down Tines	2 Full Rows
Small Items Cover	3


### Certifications

ENERGY STAR®	Yes
NSF® International Certification	Yes

### Specifications

Water Inlet Location	Bottom Left
Water Usage (Gallons)	4.0 - 8.0
Water Pressure (PSI)	20 - 120
Integral Air Gap on Supply	Yes
Leveling Legs	3
Power Supply Connection Location	Right Bottom Front
Voltage Rating	120V/60 Hz/15A
Connected Load (kW Rating) @ 120 Volts <sup>1</sup>	1.44
Amps @ 120 Volts	15
Shipping Weight (Approx.)	75 Lbs

<sup>1</sup>For use on adequately wired 120V, dedicated circuit having 2-wire service with a separate ground wire. Appliance must be grounded for safe operation.



NOTE: For planning purposes only. Always consult local and national electric and plumbing codes. Refer to Product Installation Guide for detailed installation instructions on the web at [frigidaire.ca](http://frigidaire.ca).



### Product Dimensions

A - Height (Adjustable)	33-3/4" - 35-3/4"
B - Width	24"
C - Depth (Including Door)	24-1/4"
D - Depth (To Tub Flange)	22-1/2"
Depth with Door Open 90°	50-1/4"

### Cutout Dimensions

Height (Min.)	34"
Height (Max.)	35-3/4"
Width (Min.)	24"
Depth (Min.)	24"

Accessories information available on the web at [frigidaire.ca](http://frigidaire.ca)