CONSTRUCTION SUMMARY OF EXTRAS

Printed 2020-10-20 / 8:36 AM / Page 1 of 2

Site:
Lot:
Model:
Purchaser:
Phone:
Phone/Email: VILLAGE OF KING
4-19
KENNEDY TH-07 (A1 END)
MATTHEW & CHANTELLE VANELLI
647-505-8172
colomboc11@gmail.com



JANUANI 21 2020		
JANUARY 21 2020		
IANIUARY 21 2020		#35
JANUARY 21 2020	SINK - LAUNDRY - UPGRADE TO UNDERMOUNT SINK, BLANCO STELLAR 441398 & MOEN RILEY FAUCET	#34
JANUARY 21 2020	COUNTERTOP - LAUNDRY - UPGRADE TO COMPAC QUARTZ, UPGRADE 3 **INCLUDING TO GO ACROSS/ABOVE WASHER AND DRYER	#33
JANUARY 21 2020	LAUNDRY	
JANUARY 21 2020	-	#32
JANUARY 21 2020		
JANUARY 21 2020	-	#31
JANUARY 21 2020	COUNTERTOP - MASTER ENSUITE - UPGRADE TO COMPAC QUARTZ, UPGRADE 3 *INCLUDE (2) OVAL UNDERMOUNT SINKS	#30
JANUARY 21 2020	#29 CABINETS - MASTER ENSUITE VANITY, CATEGORY 4G W/PAINTED BACK	#29
JANUARY 21 2020	CARRINGTE MARCTER FRONTE VANIES CATEGORY OF CONTROL OF	%2# 82#
JANUARY 21 2020	THES MASSES ENSUITE SHOWER WALL, UPGRADE 4	#2/
JANUARY 21 2020	THES - MASTER ENGINE FLOOR, OF GRADE 4	#37
JANUARY 21 2020		‡ 2
JANUARY 21 2020	MASTER FROILITE	1
JANUARY 21 2020		#25#
JUNOVIKI ST SOSO		5
JANUARY 21 2020	_	#23
JANUARY 21 2020		#22
JANUARY 21 2020		#21
JANUARY 21 2020		#20
JANUARY 21 2020	#19 ELECTRICAL - ADD PLUG IN CELING OF PORTICO	#19
JANUARY 21 2020	ELECTRICAL - ADD PLUG IN CELING OF FRONT AREA OF GARAGE	#18
JANUARY 21 2020		#17
JANUARY 21 2020		#16
JANUARY 21 2020		#15
JANUARY 21 2020	ELECTRICAL - MASTER BED (x1) - 4 INCH POTLIGHTS, w/LED BULB, DELETE STD LIGHT	#14
JANUARY 21 2020		#13
JANUARY 21 2020		#12
JANUARY 21 2020	1 ELECTRICAL - BEDROOM 3 (x1) - 4 INCH POTLIGHTS, w/LED BULB,	#11
JANUARY 21 2020	0 ELECTRICAL - BEDROOM 2 (x1) - 4 INCH POTLIGHTS, w/LED BULB,	#10
JANUARY 21 2020	ELECTRICAL - KITCHEN/BREAKFAST (x12) - 4 INCH POTLIGHTS, W/LED BULB, DELETE STD LIGHT	#9
JANUARY 21 2020		#
JANUARY 21 2020	ELECTRICAL - FAMILY (x6) - 4 INCH POTLIGHTS, w/LED BULB, DELETE STD LIGHT **N/C FOR 1 INCLUDED	#7
JANUARY 21 2020		#6
JANUARY 21 2020	ELECTRICAL - MAIN HALL (x5) - 4 INCH POTLIGHTS, w/LED BULB, DELETE STD LIGHT **N/C, INCLUDED	#
JANUARY 21 2020		#
JANUARY 21 2020	DELETE CLOSET IN FOYER	##
JANUARY 21 2020	_	#2
JANUARY 21 2020		#
INCLUDED IN APS	BONUS PACKAGE: 3 pce Kitchen Aid Stainless Steel kitchen appliances w/white Whirlpool front load washer & dryer - Appliance Canada, Steve Miller (905) 660-2424, 8701 Jane Street #1, Concord	
INCLUDED IN APS	BONUS PACKAGE: 10 Interior potlights (4") with LED Bulb, white trim	
INCLUDED IN APS	BONUS PACKAGE: Stained Oak Stairs	
INCLUDED IN APS	BONUS PACKAGE: Stained 3-1/4" Prefinished Engineered Hardwood on main floor & upper hall (non-tiled areas, excluding bedrooms)	
DATE SELECTED	DESCRIPTION	

CONSTRUCTION SUMMARY OF EXTRAS

Printed 2020-10-20 / 8:36 AM / Page 2 of 2

Site: Lot:

VILLAGE OF KING
4-19
KENNEDY TH-07 (A1 END)
MATTHEW & CHANTELLE VANELLI
647-505-8172

Model:
Purchaser:
Phone:
Phone/Email:

colomboc11@gmail.com



OCT 20 2020		-
	BUILT-IN FRIDGE REQUIRED AS PER FINAL APPLIANCES	# #
	ADDITIONAL FOR KITCHEN	L ₂ =11
	ELECTRICAL - (2) PLUGS REQUIRED AS PER ARTISTIC SMART HOMES	#
	ADDITIONAL	
JULY 6 2020	ELECTRICAL - POTLIGHTS (5) IN ENSUITE BATHROOM, DELETE STD LIGHT	## ##
JULY 6 2020	ELECTRICAL - POTLIGHTS (4) IN LAUNDRY ROOM, DELETE STD LIGHT	#
JULY 6 2020	ELECTRICAL - POTLIGHTS (5) IN BEDROOM 2, DELETE STD LIGHT	#######################################
JULY 6 2020	ELECTRICAL - POTLIGHTS (5) IN BEDROOM 3, DELETE STD LIGHT	#2
JULY 6 2020	COFFERED CEILING IN DINING ROOM	-
	ADDITIONAL / LATE CHANGE	
JUNE 15 2020	INSTALL A PLUG ABOVE SLIDING DOOR FOR FUTURE SECURITY SYSTEM (BECIPICAL)	# #
JUNE 15 2020	CHANGED ITEM - MASTER ENSUITE WINDOW IS TO BE THE STANDARD CLEAR GLASS (NOT OBSCURE)	-
	CHANGE	
MARCH 23 2020	CANCELLED - ELECTRICAL - ADD PLUG IN CELING OF PORTICO	#
-MARCH-23-2020	***LAUNDRY MATE REQUIRED **ORIGINALLY PURCHASED DURING APPOINTMENT IN JANUARY	# #
MARCH 23 2020	CREATE LARGER WALK-IN CLOSET FROM BEDROOM 2 **NO CHARGE AS PER FC	#
MARCH 23 2020	HARDWOOD VENTS - TO MATCH VINTAGE FLOORS ON MAIN FLOOR AND SECOND FLOOR	
JANUARY 21 2020	DELETE SHELVING THROUGHOUT ALL CLOSETS	#59 [
JANUARY 21 2020	RAILINGS - SQUARE OAK POST UPGRADE	#58 F
JANUARY 21 2020	TRIM - UPGRADE 1	#57 1
JANUARY 21 2020	TRIM / RAILINGS	
JANUARY 21 2020	TILES - POWDER ROOM - UPGRADE 6	#56
JANUARY 21 2020	TILES - MUDROOM - UPGRADE 6	#55
JANUARY 21 2020	TILES - FOYER - UPGRADE 6	#54
JANUARY 21 2020	FOYER / MUDROOM / POWDER ROOM	
JANUARY 21 2020	HARDWOOD - IN ALL BEDROOMS IN LIEU OF CARPET	#53 l
JANUARY 21 2020	HARDWOOD - KITCHEN & BREAKFAST IN LIEU TILE, UPGRADE 4	#52
JANUARY 21 2020	HARDWOOD - MAIN FLOOR - FAMILY, DINING, MAIN HALL, UPPER HALL - UPGRADE 4	#51
JANUARY 21 2020	HARDWOOD	
JANUARY 21 2020	N/A	#50
JANUARY 21 2020	KITCHEN - CATEGORY 3 HANDLES	#49
JANUARY 21 2020	KITCHEN - DUMMY DOORS ON END OF STOVE WALL BASE & UPPER	#48
JANUARY 21 2020	KITCHEN - ADD PANTRY BESIDE THE FRIDGE w/4 INTERIOR PULL OUT DRAWERS WITH PREMIUM MOTION	#47
JANUARY 21 2020	KITCHEN - CONVERT BANK OF DRAWERS TO POT DRAWERS	#46
JANUARY 21 2020	KITCHEN SINK - BLANCO 401518 SUPER SINGLE	#45
JANUARY 21 2020	HVAC - GAS LINE **INCLUDES 15 AMP PLUG	#44
JANUARY 21 2020	KITCHEN - BUILT-IN VALANCE BOX FOR PUCK LIGHTS	#43
JANUARY 21 2020	KITCHEN - DELETE UPPERS ABOVE STOVE FOR FUTURE CHIMNEY *CENTRE VENT	#42
JANUARY 21 2020	KITCHEN - UPGRADE STONE INCLUDED COUNTETOP EXTENSION ON ISLAND	#41 1
JANUARY 21 2020	KITCHEN - THICK 1-1/2" GABLE, OVERHANG BOX & DUMMY DOOR ON ENDS INCLUDING GABLE	#40
JANUARY 21 2020	KITCHEN - TWO TONE, ISLAND TO BE DIFFERENT COLOUR	#39
JANUARY 21 2020	KITCHEN - CATEGORY 3	#38
JANUARY 21 2020	KITCHEN - 44" HIGH UPPER CABINETS WITH TRIPLE STEP CROWN MOULDING E62 MLD100, 108" OVERALL HEIGHT	#37
JANUARY 21 2020	KITCHEN	
DATE SELECTED		



FOR THE WAY IT'S MADE!

PRODUCT MODEL NUMBERS


KRFC302E

Electrical: A 115 volt, 60 Hz, AC only 15- or 20-amp fused, grounded electrical supply is required. It is recommended that a separate circuit serving only your refrigerator and approved accessories be provided. Use an outlet that cannot be turned off by a switch. Do not use an

Water: A cold water supply with water pressure of between 35 and 120 psi (241 and 827 kPa) is required to operate the water dispenser and ice maker. If you have questions about your water qualified plumber. pressure, call a licensed,

Reverse Osmosis Water Supply:
IMPORTANT: The pressure of the
water supply coming out of a reverse
osmosis system going to the water inlet
valve of the refrigerator needs to be
between 35 and 120 psi (241 and 827 kPa).


PRODUCT DIMENSIONS **Bottom Mount Refrigerator**



	21.9	Model Size
-	(182.9	Height - Overall
	7136 [181.3 cm]	lop of Cabinet
	441°	Depth - Ocean Open
	451/2* (114.9 cm)	Depth - Drawer Open
	301/2" (76.8 cm)	Handes
	(70.5 cm)	Depth - Without Handles
free man	245g* (62.5 cm)	Depth - Cabinet Only
from month	35%*	Width -

4-9 XIZG G VILLAGE

LOCATION REQUIREMENTS




IMPORTANT: This refrigerator is designed for indo household use only.


To ensure proper ventilation for your refrigerator, allow to \$\frac{1}{2}^2\$ (1.25 cm) of space on each side and at the top. Allow for 1" (2.54 cm) of space behind the "drigerator. If your refrigerator has an ice maker, allow extra space at the back for the water line connections. When installing your refrigerator next to a fixed wall. leave 21/2" (6.3 cm) minimum on the hinge side (some models require more) to allow for the door to swing open.


NOTE: This refrigerator is intended for use in a location where the emperature ranges from a minimum of 55°F (13°C) to a maximum of 110°F (43°C). The preferred room temperature range for optimum performance, which reduces electricity usage and provides superior cooling, is between 60°F (15°C) and 90°F (32°C). It is recommended that you do not install the refrigerator near a heat source, such as an oven or radiator.

ZICS360NNLH BOTTOM-FREEZER REFRIGERATOR MONOGRAM 36" BUILT-IN













STATEMENT HANDLE

Model is shown with the Statement handle, which needs to be ordered separately. To order this handle use model number ZKSB2H2PNSS.



Model is shown with the Minimalist handle, which needs to be ordered separately. To order this handle use model number ZKSB2H2CNSS.





UPFRONT ELECTRONIC CONTROLS WITH DIGITAL READOUT

maximum ease of use Allows precise temperature settings and are positioned for

STATEMENT AND MINIMALIST COLLECTION REFRIGERATOR HANDLES (SOLD SEPARATELY)

Designed to enhance choice and customization, Statement and Minimalist Collection refrigerators do not come with handles. Handles must be chosen separately and ordered through a Monogram representative

HUMIDITY CONTROLLED VEGETABLE COMPARTMENTS AND SEALED SNACK PANS Help maintain freshness and help preserve foods longer

ADJUSTABLE, SPILL PROOF GLASS SHELVES Make it easy to customize storage to handle foods and containers of various sizes

Offer added storage flexibility SIX ADJUSTABLE DOOR BINS 2 SEALED DELI PANS WITH FULL EXTENSION SLIDES

GE WATER" FILTRATION SYSTEM


Delivers clean, great tasting ice

For questions about your appliance, please call 1-800-626-2000

PAGE 1 OF 5

Product Specification Revised 6/20





SPECIFICATIONS


Overall Width	36" (91.4 cm)
(vei dii i leigiii	04 (213.4 cm)
Overall Depth	25 15/16" (65.9 cm)
Door Clearance	36 1/2" (92.7 cm)
Cutout Width	35 1/2" (90.2 cm)
Cutout Height	83 1/2" - 84 1/2" (212.1 - 214.6 cm)
Cutout Depth	24" (61 cm)
Plumbing Requirements	1/4" OD copper tubing or GE SmartConnect kit
Shipping Weight	640 lb (290.3 kg)

ATTENTION ELECTRICIAN:


A 115 volt 60Hz, 15 or 20 amp power supply is required. An individual properly grounded branch circuit or circuit breaker is recommended. Install a properly grounded 3-prong electrical receptacle recessed into the back wall.

For questions about your appliance, please call 1-800-626-2000

OVERALL DIMENSIONS



* Shipping height. Use leveling legs and wheels for maximum 1" height adjustment from shipping height.



These refrigerators are equipped with a 3 position door stop. The factory set 115° door swing can be adjusted to 90° if clearances to adjacent cabinets or walls is restricted. Allow full 130° door swings for pan removal. If the 90° door stop position is used, pan access is maintained, but pan removal is restricted.


Dimensions in parentheses are in centimeters unless otherwise noted. Actual product dimensions may vary due to manufacturing tolerances.


PAGE 2 OF 5

Product Specification Revised 6/20





STANDARD INSTALLATION





ANTI-TIP BRACKET





For questions about your appliance, please call 1-800-626-2000.

PAGE 3 OF 5

Product Specification Revised 6/20

HELPFUL TIPS

- A Mounting the junction box in this location will also allow for front accessibility through access panel.
- B Water supply area.

WARNING:

The refrigerator is top heavy and must be secured to prevent the possibility of tipping forward. Failure to do so may result in death or serious injury. The information below is for cabinet design only. When installing the anti-tip system you must use the product installation instructions.


The information below applies to all installation constructions:


- A wall bracket, bolts and toggles will be supplied with the unit.
- The bolts will be used to attach bracket to wall in 4 locations. Two of the locations must penetrate the center of the wall studs.
- The toggles are used for stability in drywall and when metal studs are encountered. Lag bolts are used in wood studs.
- horizontal line. In installation opening, measure 81-1/2" from floor and draw a
- Locate and mark the wall studs on horizontal line. Verify at least two studs have their centerlines within the center 32–1/2" of installation opening to ensure 2 wall studs are penetrated.
- The bracket will be centered left to right in opening with bottom of bracket on the horizontal line.
- When unit is placed in opening, the bracket tabs will align with openings in back of the unit. The unit will be secured to the bracket using supplied "L" bolts.

See Installation Instructions for detailed instructions.



CUSTOM SIDE PANELS





-2 9/16" (6.5)

HELPFUL TIPS

E Side panels must be used whenever the sides of the refrigerator will be exposed. The 1/4" side panels will slip into the side case trim. Secure the panels to the refrigerator with stick-on hook and loop fastener strips.

Order the side panels from the cabinet manufacturer.

For questions about your appliance, please call 1-800-626-2000.


PAGE 4 OF 5

Product Specification Revised 6/20

00 DD DD




DUAL INSTALLATIONS





SIDE VIEW

DUAL PRODUCT CLEARANCES



For questions about your appliance, please call 1-800-626-2000.

PAGE 5 OF 5

HELPFUL TIPS

- ≥ A separate 115V, 60Hz, 15-or 20-amp power supply is recommended for each product. Additional cutout width may be required when side panels are used.
- ₿ In a side-by-side installation of a left-and-right-hand door swing product, 1" clearance between the units is required. Order ZKBSN720NSS unification kit for an integrated appearance on 2 stainless steel models installed side-by-side.

Product Specification Revised 6/20

RANGE WITH 4 BURNERS MONOGRAM 30" DUAL-FUEL PROFESSIONAL

ZDP304NPSS (NATURAL GAS)

(IN INCHES) DIMENSIONS AND INSTALLATION INFORMATION

natural gas All Dual-Fuel Professional Ranges are factory set for

A propane conversion kit is included with the range. High Altitude kit. WB28K10553 for operation above 6,000 feet is also available. The kits must be installed by a qualified service technician at additional cost.

INSTALLATION INFORMATION

Before installing, consult installation instructions packed with product or online at Monogram.com for current

dimensional data
A 30" or 36" wide professional vent hood with a min mum
300 CFM is recommended for installation over this range
Install the hood 30" to 36" above the cooking surface.

ADVANCE PLANNING

Refer to dimensional drawings for appropriate placement and necessary clearances when planning the installation.

• Working areas adjacent to the range should have


- cabinet bottom 18' minimum clearance between countertop and
- Clearance between range and side wall or combustible
- material must be at least 12" on each side.


 Installation must conform with local codes. In the absence of local codes, the range must comply with the National Fuel Gas Code ANSI Z223.1-990.

MARNING.

instructions for specific hood clearances. to combustibles. A custam hood installation with exposed horizontal combustible surfaces must have an Auto-On feature. Refer to hood installation Installations without a hood require 48' minimum

brick, marble or other stone. and below the hood must be covered with a non-combustible material such as metal, ceramic tile. The surface of the entire back wall above the range





4-19 KING VIL

ELEVATE EVERYTHING

MONOGRAM

Working areas adjacent to the rangetop should have 18" minimum clearance between countertop and the bottom of the wall cabinet.



RANGE WITH 4 BURNERS MONOGRAM 30" DUAL-FUEL PROFESSIONAL

ZDP304NPSS (NATURAL GAS)


(N NCHES) DIMENSIONS AND INSTALLATION INFORMATION

connected to an individual, properly grounded branch circuit protected by a circuit breaker or time-detay fuse. Install a 30-amp circuit for 30" ranges. Ranges must be supplied with 208/240V, 60Hz, and ELECTRICAL REQUIREMENTS


The receptable must be a NEMA 14-50R device to accept the four-prong plug on the range.

The range requires a 12" minimum clearance to a vertical combustible surface at the rear. A backsplash is required for installations with less than 12" clearance. A custom, non-combustible backsplash can be used. OPTIONAL BACKSPLASH ACCESSORIE

SIDE VIEW WITH A BACKSPLASH



UTILITY LOCATIONS




Locate gas and electric as shown

GAS SUPPLY

- The natural gas models are designed to operate at 5" water column pressure. For proper operation, the pressure of the natural gas supplied to the regulator must be between 7" and 13" water column.
- the LP gas supplied to the regulator must be between 11" and 13" water column. The LP models are designed to operate at 10" water column pressure. For proper operation, the pressure of

12" min. to combustibles or 0" to a non-combustible material above the cooking surface



19 KING VILLAGE

ELEVATE EVERYTHING

MONOGRAM




KitchenAid®

24" Dishwasher DETAILED PLANNING DIMENSIONS GUIDE

OPENING/CLEARANCE DIMENSIONS

IMPORTANT: Check that all surfaces have no protrusions that would prohibit dishwasher installation



- A. Measured from the lowest point on the underside of the countertop. May be reduced to 331/2" (85.1 cm) by removing the wheels and perforated area of insulation (blanket) on dishwasher.
- B. Minimum, measured from narrowest point of opening.

NOTE: Comer locations require a 2" (5.1 cm) minimum clearance between the side of the dishwasher door and the wall or cabinet.


4-19 KING VILLAGE

Because Whirlpool Corporation policy includes a continuous commitment to improve our products, we reserve the right to change materials and specifications without notice.

Dimensions are for planning purposes only. For complete details, see installation instructions packed with product. Specifications subject to change without notice.



AVH-308CS 30" Wall mounted hood - MSRP: \$839.00




1-voor Morranto	The second second	Optional duct covers		Electrical requirements	The state of the s	Chimney (ducted out)	Ducling	Duct transition		Filler type		Blower performance	Blower type	Lighting	Control		Stainless steel grade		Dimensions		Model number	
Dordo and labour in bases anniha	Warranty	AD-884S (884mm, AVN-AVH compatible)	Accessories (optionnal)	120V / 60Hz / 2.7 Amps	Electrical Requirements	For ceiling heights up to 9'0"	Ducted	6" Round (Top)	2 Stainless steel baffle filters (included)	2 aluminium micro hole filters (included)	Speed 6, 6.2 sones	Speed 1, 2.4 sones	860 CFM, 6-Speed	2 bulbs, 3W LED (bulbs included)	Soft touch with LED display	Features	201	Exterior Appearence	29 1/2" (W) x 19 3/4" (D) x 3 1/4" (H)	Dimensions	AVH-308CS	Selected Model


4-19 KING VILLAGE

The information contained therein is based on sources that we may be incomplete or may change without notice

Dimensions



Installation



m	٥	C	-	A
Chimney height	Hood height	Recommended height between cooking surface and bottom of the hood	Floor to counter top height (standard)	Floor to ceiling height
Max 44.63"	2.36"	28" to 30"	36"	variable

Duct transition





4-19 KING VILLAGE

The information contained herein is based on sources that we believe to be reliable, but is not guaranteed by us, may be incomplete and/or may change without notice.

4 19 X N G AGE

LOCATION REQUIREMENTS


Proper installation is your responsibility.


You will need:

- A water heater set to 120°F (49°C).
- A grounded electrical outlet located within 6 ft (1.8 m) of power cord on back of washer.
- Hot and cold water faucets located within 4 ft (1.2 m) of hot and cold water fill valves on washer, and water pressure of 20–100 psi (137.9–589.6 kPa).
- A level floor with maximum slope of 1" (25 mm) under entire washer. Installing on carpet or surfaces with foam backing is not recommended.
- Floor must support washer's total weight (with water and load) of 315 lbs (143 kgs).

IMPORTANT: Do not install, store, or operate washer where it will be exposed to weather or in temperatures below 32°F (0°C). Water remaining in washer after use may cause damage in low temperatures. See "Washer Care" in your Use and Care Guide for winterizing information.


Whirlpool Models*





*For additional details (or information) specific to your model refer to the 'Dimensions listed for your model at www.whirlpool.com.


Maytag Models



All dimensions show minimum spacing allowed. For each arrangement, consider allowing more space for ease of installation and servicing, and spacing for companion appliances and clearances for walls, doors, and floor moldings.

Space must be large enough to allow door to fully open. Add spacing of 1" (25 mm) on all sides of washer to reduce noise transfer. If a closet door or lowered door is installed. For and bottom air openings in door are required.

Recessed area or closet installation (stacked washer and dryer):



4 9 X Z G LAGE

Additional parts may be required, depending on your installation. Check local codes. Check existing electrical supply and venting. Read "Electrical Requirements" and "Venting Requirements" before purchasing parts.

If using a power supply cord; Use a UL Listed power supply cord kit marked for use with clothes dryers. The kit should contain:

- A UL Listed 30 A power supply cord, rated 120/240 V minimum. The cord should be type SRD or SRDT and be at least 4 ft. (1.22 m) long. The wires that connect to the dryer must end in ring terminals or spade terminals with upturned
- A UL Listed strain relief.

Optional Equipment (not supplied with dryer): Refer to your Use and Care Guide for information about accessories available for your dryer.

OCATION REQUIREMENTS

Check code requirements. Some codes limit, or do not permit installing dryer in garages, closets, mobile homes, or sleeping quarters. Contact your local building inspector.

AWARNING



Explosion Hazard

Keep flammable materials and vapors, such as gasoline, away from dryer.

Place dryer at least 18 inches (460 mm) above the Iloor for a garage installation.


Failure to do so can result in death, explosion, or fire.

You will need:

- A location allowing for proper exhaust installation See "Venting Requirements."
- A separate 15 or 20 A circuit for a gas dryer or 30 A circuit for an electric dryer.
- If using power supply cord, a grounded electrical outlet located within 2 ft. (610 mm) of either side of dryer. See "Electrical Requirements."
- Floor must support dryer weight of 200 lbs. (90.7 kg), Also consider weight of companion appliance.
- m Cold water faucets located within 4 ft. (1.2 m) of the water fill valves, and water pressure of 20-120 psi (138-827 kPa). You may use your washer's water supply by purchasing the necessary parts noted in "Parts needed."
- Level floor with maximum slope of 1° (25 mm) under entire dryer. If slope is greater than 1° (25 mm), install Extended Dryer Feet Kit, Part Number 279810. If not level, clothes may not tumble properly and automatic sensor cycles may not operate correctly.
- For garage installation, place dryer at least 18° (460 mm) above floor. If using a pedestal, you will need 18° (460 mm) to bottom of dryer.
- The dryer must not be installed or stored in an area where it will be exposed to water and/or weather.


IMPORTANT: Do not operate, install, or store dryer where it will be exposed to water, weather, or at temperatures below 40°F (4°C). Lower temperatures may cause dryer not to shut off at end of automatic sensor cycles, resulting in longer drying times.

DRYER DIMENSIONS Front view:




Side view:

Whirlpool* Models



Maytag* Models



Approx. measurement

NCOR HOMES COLOUR CH CABINETRY / COUNTERTOPS

Purchaser Initial Vendor			** PAGE 1 OF 2 **	
M Q	tty of all Trades PRIOR to	the responsibil or colour charts	e accompanied with a I epancies on sketches, P installation.	Any upgrades in the colour cha to inform the builder of a
VILLAGE OF KING 4-19			***FOR TRADE USE***	
SITE & LOT		Int .	Purchaser has reviewed the colour chart	Pu
N/A		Location	DELETE	Bathroom Accessories
N/A	- 1	Opt. Crown Moulding	DELETE	Mirrors
PLASTER MOULDING			MIRRORS & ACCESSORIES	MIRRO
	ELECTRIC - BLF34	ELECT		LOCATION
		FIREPLACES	FIR	
- SAHARA (4) in lieu of carpet	R UVF MAPLE 5"	SS CHARACTE	HARDWOOD - VINTAGE NSS CHARACTER UVF MAPLE 5" - SAHARA (4)	Bedroom 4
HARDWOOD - VINTAGE NSS CHARACTER UVF MAPLE 5" - SAHARA (4) in lieu of carpet	R UVF MAPLE 5"	SS CHARACTE	HARDWOOD - VINTAGE N	Bedroom 3
HARDWOOD - VINTAGE NSS CHARACTER UVF MAPLE 5" - SAHARA (4) in lieu of carpet	R UVF MAPLE 5"	SS CHARACTE	HARDWOOD - VINTAGE N	Bedroom 2
HARDWOOD - VINTAGE NSS CHARACTER UVF MAPLE 5" - SAHARA (4) in lieu of carpet	R UVF MAPLE 5"	SS CHARACTE	HARDWOOD - VINTAGE N	Master Bedroom
HARDWOOD - VINTAGE NSS CHARACTER UVF MAPLE 5" - SAHARA (4)	ARACTER UVF M	TAGE NSS CH	HARDWOOD - VIN	Upper Hall
HARDWOOD - VINTAGE NSS CHARACTER UVF MAPLE 5" - SAHARA (4)	ARACTER UVF M	TAGE NSS CH	HARDWOOD - VIN	Main hall
HARDWOOD - VINTAGE NSS CHARACTER UVF MAPLE 5" - SAHARA (4)	ARACTER UVF M	TAGE NSS CH	HARDWOOD - VIN	Dining Room
HARDWOOD - VINTAGE NSS CHARACTER UVF MAPLE 5" - SAHARA (4)	ARACTER UVF M.	TAGE NSS CH	HARDWOOD - VIN	Great Room
HARDWOOD - VINTAGE NSS CHARACTER UVF MAPLE 5" - SAHARA (4) in lieu of tile	ER UVF MAPLE 5	NSS CHARACT	HARDWOOD - VINTAGE	Kitchen/ Breakfast
		HARDWOOD / CARPET	HARDWO	
1	ALLURE GREY MATTE 12 X 24	ALLURE GRI		Main Bath Wall
×	ALLURE GREY MATTE 12 X 24	ALLURE GRI		Main Bath Floor
		- 1	- 1	Master Shower JAMB
HONEYCOME WARBLE	WHITE 2X2 H	BORDER -WH	DRIBUTHL WHITE + GREY BOX	Master Shower Floor
24 (4)	TIMELESS WHITE POLISHED 12 X 24 (4)	WELESS WHITI	П	Mstr Ensuite Shower WALL
24 (4)	TIMELESS WHITE POLISHED 12 X 24 (4)	WELESS WHITI	П	Mstr Ensuite Floor
4	ALLURE GREY MATTE 12 X 24	ALLURE GRI		Laundry
	N/A			Kitchen Bk.Splash
	HARDWOOD	НА		Breakfast
	HARDWOOD	НА		Kitchen
	HARDWOOD	НА		Main Hall
	GRAFFITI BLANCO 24 X 24 (6)	GRAFFITI BI		Mud Room
	GRAFFITI BLANCO 24 X 24 (6)	GRAFFITI BI		Powder Room
	N/A			Basement Foyer
)	GRAFFITI BLANCO 24 X 24 (6)	GRAFFITI BI		Main Foyer
		TILES		
CMP LACTEA	DH00010	XTENDED TO	1203 FIBREBOARD - WHITE (CAT 1) *EXTENDED TO CEILING	Laundry BASE & UPPERS
	DH09150	AT 1)	1203 FIBREBOARD - WHITE (CAT 1)	Main Bath
CMP LACTEA	DH09150	CLINEN GLAZE	4401 FIBREBOARD - ASHPHALT W/BLACK LINEN GLAZE (CAT 4G) *PAINTED BACK	Master Ensuite
			N/A	Powder Room
CAESARSTONE OCEAN FOAM	DH07870	N (CAT 3)	3801 FIBREBOARD - WROUGHT IRON (CAT 3)	Island
CEAN FOAI	DH07870	E (CAT 3)	3801 FIBREBOARD - OXFORD WHITE (CAT 3)	Kitchen
COUNTERTOP EDGE	HARDWARE		DOOR STYLE	
	OPS	CABINETRY / COUNTERTOPS	CABINETRY	

INCOR HOMES COLOUR CH

	4					
	Vendor Signature	/		OF 2 ***	PAGE 2	**
28-2626	2			ANCOR	PANCO	
ature Date	Décor Consultant Signature		ES. It is the	***FOR TRADE USE*** in the colour chart must be accompanied with a F all trades to inform the builder of any discrepanci PES and/or colour charts PRIOR to installation.	***FOR TRADE USE*** IT chart must be accomp Inform the builder of a colour charts PRIOR to	***FOR TRADE USE*** Any upgrades in the colour chart must be accompanied with a PES. It is the responsibility of all trades to inform the builder of any discrepancies on sketches, PES and/or colour charts PRIOR to installation.
JAN 21 2020 The Date	Purchaser Signature					DÉCOR NOTES
	3 =		COM	COLOMBOC11@GMAIL.COM	COL	EMAIL:
re Date	Purchaser Signature			647-505-8172		HOME #/CELL #
JAN 21 2020		de	VANELLI	CHANTELLE & MATTHEW VANELLI	CHANT	PURCHASER(S):
		9	LOT: 4-19	VILLAGE OF KING LO	VILLAGI	SITE:
MM CN			άa	ır and selections before signin	d accuracy of colou	Purchaser has checked and acknowledged accuracy of colour and selections before signing
M N			plus costs	a \$5000 administration fee	ning are subject to	Any changes to the colour chart after signing are subject to a $\$5000$ administration fee plus costs
MC CS	the Vendors's selection	e lot variances in istalled. In this event	pre-selected or in	ss some items may have been	onstruction progres	manufacturing/manufacturers. Due to construction progress some items may have been pre-selected or installed. In this event the Vendors's selection must be accepted by the purchaser
INITIALS				DISCLAIMER	Scible to Building	irs of all materials are as close as no
				NO		ELECTRICAL for Bar Fridge
				NO	ktop	ELECTRICAL for Gas Stove / Cooktop
				NO	OTR	ELECTRICAL for Built-in Micro / OTR
			1	NO		ELECTRICAL for Built-in Oven
				6 INCH		Hood Fan Venting SIZE
				YES - STANDARD		WATERLINE to Fridge
			+	YES		GAS LINE TO STOVE
		DECLINED	VES / NO Packa	UPG (SEF)	- III ochequie E	Sphilaine Larvage Teceiven III
	ETAILED ON PES	WADES TO BE D	EN13-OFGK	FIGURE VEGO		
T & UNDERMOUNT SINK	SINGLE HOLE FAUCET &	SING	UPGKADE	OP ABBLIANCE BEOLIBEN	ZANCOR AL	Harry
- 1	OVAL UNDE		SIANDARD	OF GRADE SINK	UPGN	
OVAL UNDERMOUNT	OVAL UNI		STANDARD	UPGRADE SINK	UPGR	Main Bath
OVAL UNDERMOUNT	OVAL UNI		STANDARD	UPGRADE SINK	UPGR	Master Ensuite
			STANDARD	STANDARD	STA	Powder room
SUPER SINGLE	SUPER		STANDARD	UPGRADE SINK	UPGR,	Kitchen
NOTES			FAUCETS	FIXTURES	FIX	
		WAKINI GKEY	DES TO BE	PILIMRING- LIPGRADES TO BE DETAILED ON BES		Caginoan
		WAR CORN	PAINT	STATE OF THE PARTY		Throughout
	SET	STANDARD GRIPSET	10			exterior Door Hardware
	EL LEVER	STANDARD SATIN NICKEL LEVER	STANDA			Interior Door Hardware
	МООТН	STANDARD 2 PANEL SMOOTH	STAND			Interior Doors
	/4' STEP	UPGRADE 1 - 3" X 5-1/4' STEP	UPGRA			Casing/Baseboards
			TRIM			
AND CASE OUR INTRODUCE	A	N/A			ils:	Main to Basement Railing Details:
	METAL - SINGLE COLLAR WITH ALT PLAIN IPPG TO SOLIARE OAK BOST WITH REVEL COBNEEDS STANDARD.	L - SINGLE COLL	METAL	LIPG TO SOLIARE		Main to 2nd PICKETS: Main to 2nd POSTS & HANDRAIL:
: AS POSSIBLE	STAIN STAIRS TO MATCH HARDWOOD AS CLOSE AS	MATCH HARD	N STAIRS TO	STAI		Stain / Paint:
	TAIRS	OAK STAIRS				Stair:
	Z	& STAIR STA	& PICKETS	STAIRS, RAILING & PICKETS & STAIR STAIN		
		750011 41	10.00			

MC

0

PARTIAL PLAN W/LINEN DELETE SHEWES PLIABLE SHOWING 3 Alone POLLMISNI SECOND FLOOR ELEV. 'A-1' END CONDITION **TH-7** (LINEN NEW STATE gound warman Sound INSULATION STUDY NOOK MASTER BEDROOM 14'0" X 18'10" A STANDANTON SHARINGS OPT TRAY CEILING BEDRAMA' 2 0 WHIS SHA 0 1 NSWATTON WINDOW. SHELLING WHE MILE SHEWS dow location tlarger closest


BASEMENT FLOOR ELEV. 'A-1' END CONDITION LOCATION OF FURNACE AND HOT WATER HEATER MAY VARY UNEXCAVATED UNFINISHED BASEMENT

TWH

TH-7

KING VILLAGE (BLOCK 81) $\mathcal{L} - |Q|$

& FLAT CAP (in lieu of standard turned 2-3/4" oak post) 3-1/4" LARGER SQUARE OAK POST w/BEVEL CORNERS





your kitchen. your taste.


CLIEN !:

80 Sante Drive, Vaughan, ON L4K 3C4 T 416.746.1811 F 905.761.5901 www.qtk.ca info@qtk.ca

DATE: APR 30, 2020

LOT #: 19

TOP: HINGE TYPE: CT P.O.# ROOM: KITCHEN DOOR STYLE DOOR PANEL GLASS P.O.# DONE BY: CABINET LIGHTING TYPE: SPECIES JOB NAME BLK 4 - LOT 19 DOOR HANDLE: DIRECTION: MODEL: TH-07
FINISH MOUNTING HEIGHT: 95 1/2" DRW HANDLE: DIAMETER: LOCATION:



DATE: APR 30, 2020

MODEL: TH-07 LOT #: 19

JOB NAME BLK 4 - LOT 19


ROOM: KITCHEN

HINGE TYPE: **CT P.O.#** DOOR STYLE DOOR PANEL LAYOUT : **GLASS** P.O.# CABINET LIGHTING TYPE: SPECIES DOOR HANDLE: DIRECTION: FINISH MOUNTING HEIGHT: 95 1/2" DRW HANDLE: DIAMETER: LOCATION:

KITCHEN

TOP:

86% STOVE PIPE CENTER 8 3PD 1 CUTLERY INSERT STOVE 3PD FRGB 2 BIN RECYCLE SINK DISHWASHER PANTRY W/ 8 8 8 8 TOP **EXTENDED COUNTER** 30"







DATE: APR 30, 2020


LOT #: 19

SITE: VILLAGE AT KINGS RIDGE JOB NAME BLK 4 - LOT 19

TOP: HINGE TYPE: ROOM: KITCHEN DOOR STYLE FRIDGE WALL P.O.# DOOR PANEL GLASS DONE BY: ס 0.# CABINET LIGHTING TYPE: SPECIES DOOR HANDLE: DIRECTION: 200 **₩** MODEL: TH-07 FINISH MOUNTING HEIGHT: 95 1/2" DRW HANDLE: DIAMETER: LOCATION: မ္တ O







DATE: APR 30, 2020

LOT #: 19


ROOM: KITCHEN DOOR STYLE DOOR PANEL LAYOUT : SPECIES DOOR HANDLE: MODEL: TH-07 FINISH DRW HANDLE:

-다


HINGE TYPE: CT P.O.# GLASS P.O.# CABINET LIGHTING TYPE: DIRECTION: LOCATION: DIAMETER:

MOUNTING HEIGHT: 95 1/2"


ISLAND FRONT




ISLAND REAR



ISLAND SIDE



ISLAND SIDE





CLIENT: ZANCOR HOMES


JOB NAME

SITE: VILLAGE AT KINGS RIDGE

DATE: JAN 10, 2020

LOT#:

MODEL: TAKE OFF





CLIENT: ZANCOR HOMES

ROOM: LAUNDRY SITE: VILLAGE AT KINGS RIDGE

JOB NAME TH-07

DATE: JAN 10, 2020


LOT#:

MODEL: TAKE OFF

TOP: HINGE TYPE: CT P.O.# DOOR STYLE DOOR PANEL GLASS P.O.# LAYOUT DONE BY: CABINET LIGHTING TYPE: SPECIES DOOR HANDLE: DIRECTION: FINISH MOUNTING HEIGHT: 87" DRW HANDLE: DIAMETER: LOCATION:

LAUNDRY PLAN -A ଷ୍ଟ ਰੂ - 24" --

LAUNDRY ELEV.



G ZANCOR D

Stone Countertop Edge Profiles **Where applicable as per site specifications**

Standard Countertop Edge in Kitchen

"DPR"


Standard Countertop Edge in Vanity



Option 1 — Countertop Edges

Optional Edge in Kitchen - \$250


Optional Edge in Vanity - \$125

















Option 2 — Countertop Edges


Option 2 Edge in Kitchen – Custom \$\$


"N"

















DATE

SITE

Homeowner(s) Initials

MANCOR



APPLIANCE ACKNOWLEDGEMENT



CONTACT: Steve Miller @ Appliance Canada (905) 660-2424 / 8401 Jane Street, Unit #1, Vaughan

- ₩ NOTE: Any upgraded appliances are to be paid by the Purchaser, directly to the appliances company.
- homeowner. Additional charges to the Purchaser may apply for cabinetry, electrical and plumbing in order to accommodate the specs given by the
- It is the Purchaser's responsibility to provide Zancor Homes with the correct specification for each appliance where it exceeds the standard openings. Zancor Homes will not be responsible for applinaces not fitting due to late changes.
- It is the Purchasers responsibility to coordinate delivery, installation and hook up of appliances and to ensure they are installed as per Manufacturers specifications after closing. Standard appliance openings are approximate and the minimum required. Sizes may vary due to onsite condition and/or
- been made to the cabinetry. when modifications have

S
\exists
Z
\triangleright
ARD
0
OPE
m
Z
9
יע
NGS ACCE
\mathbf{Q}
R
Ð
Ť
U
Œ
~
7
Z
Ω
王
P
SE
T
~

Dishwasher Opening Stove Opening Fridge Opening \blacksquare 24" 30" 36" (+/-) x 74" (+/-) **Hood Fan Vent Hood Fan Opening** V **Space above the fridge is required due to proper air flow 30" وآ HOMEOWNER INITIALS

Appliance Specs are DUE 2 WEEKS FROM SIGNED DATE (if not received during appointment)

Specs that require changes/modifications after this date will not be accepted

UPGRADE APPLIANCE OPENING REQUIREMENTS:

Built-In

Flush Inset

HOMEOWNER INITIA

JAN 2 1 2020	WALL OVEN & MICRO	HOOD FAN & VENT	RANGE	FRIDGE
Cens	Single Oven Double Oven Steam Oven	Under Cabinet (Standard) Chimney (centre vent) Insert / Liner	48" AGas Induction	Paneled / Integrated
4-19	Warming Drawer Over the Range Microwave Built-in Microwave (*trim kit required)	8 Inch 10 Inch	Cooktop (Apron front) Cooktop (Dropin) **Countertop Cut-out charge required for cooktop	LWater Line Required SAD

SITE

[O

DATE

stst Any upgrades checked in this appliance form must be accompanied with specs provided by the Puchaser.

^{**}It is the responsibility of the trade to inform the Builder of any discrepancies with specs, sketches, extras and/or colour chart PRIOR to production/installation.



INTERIOR FINISHES ACKNOWLEDGEMENT / WAIVER

Purchaser accepts and acknowledges that the Builder reserves the right to substitute materials with those of equal or better quality where the manufacture, scheduling or delivery of materials may directly impact the Builder's ability to meet its' contractual obligations under the Agreement of Purchase and Sale.

UPGRADES/EXTRAS: All upgrades and additional selections indicated on the colour chart must be accompanied by an upgrades/extras sheet (PES) and full payment otherwise the selection will be invalid. All colour charts and upgrades/extras will not proceed until verified and signed by an authorized signing officer at the Vendor's head office. CHANGES WILL NOT BE NOT B PERMITTED UPON COMPLETION AND SUBMISSION OF THE COLOUR CHART.

including various lighting may affect the overall finished look. Stone tops are sealed at time of installation and should never be cleaned with lemon oil or vinegar. Stones are porous materials, therefore any spilled substance require immediate attention. Stone countertops require regular seal re-application as part of home maintenance. Purchaser acknowledges colour and product variations as well as natural imperfections may exist with the selection of natural stone materials and shall not hold the $\mathcal M$ PORCELAIN & NATURAL STONES: Due to the properties of natural stones including but not limited to marble, granite, quartz, two pieces are exactly the same. Variations in colour, tone, granularity (pitting, fissures) and pattern are

STONE COUNTERTOP JOINTS: Purchaser is aware that one joint will be at each corner and on either side of slide-in-range (if applicable). It will also be where the length of the counter top exceeds the length of a stone slab. Slabs are usually approximately 5'x 8'

CERAMIC TILES: Due to manufacturing, shade (dye lots), product variations may exist that can affect the overall look of the finished product. Although every effort will be made to ensure the colours and materials selected are as close as possible to the samples, the purchaser acknowledges that the sample tiles supplied in the Design Centre may not be identical to the materials installed in the home.

including but not limited to wood type, knotting, graining, density, age, humidity, and air temperature can result in substantial variations in stain intensity. The purchaser accepts that although the Vendor will do their best to match stain the unfinished differences between the two products. stairs as close as possible to the pre-finished floors, it is not possible to have an identical match and that there MAY be shade STAIR STAINS: Due to the natural properties of wood, many variables can affect the overall look of the finished product

site conditions, certain cabinetry upgrades may not be possible. The purchaser acknowledges that the Builder cannot guarantee the cabinetry finish or provision of certain upgrades and shall not hold the Builder liable for provision of same. of lighting in the areas of designated cabinetry placement may also highlight characteristics of cabinetry finish. All cabinets shall be finished with a white melamine interior box unless a finished interior is upgraded. Due to building specifications and/or onmay affect the overall look of the finished product. Such factors make exact colour matching impossible. but not limited to wood species, CABINETRY: Due to the natural properties of wood, slight variations apparent with cabinetry are to be expected. This includes wood grain, colour, finish, product variations, and natural imperfections are all factors that The type and intensity

UPGRADES/EXTRAS: All upgrades and additional selections indicated on the colour chart must be accompanied by an upgrades/extras sheet (PES) and full payment otherwise the selection will be invalid. All colour charts and upgrades/extras will not proceed until verified and signed by an authorized signing officer at the Vendor's head office. **CHANGES WILL NOT BE PERMITTED UPON COMPLETION AND SUBMISSION OF THE COLOUR CHART.**

efforts to install the hardwood flooring materials in keeping with good workmanship, the Builder shall not be responsible nor held liable for minor variances of fluctuation in hardwood flooring materials. pre-finished product in a controlled environment. Expansion, compression and cupping are characteristics of hardwood flooring once installed in the home. The purchaser acknowledges these may become apparent over time and despite the Builders' of the finished product. Variations include but not limited to wood type or laminate finish, colour/stain and wood grain are significant factors that make exact colour matching impossible. The purchaser acknowledges that the hardwood flooring is a HARDWOOD / LAMINATE FLOORING: Due to the properties of wood and laminate, many variables can affect the overall look

HARDWOOD / LAMINATE WAIVER:

areas. I/We understand there is a concern due to possible water and other substances being frequently splashed or spilled onto I/We understand hardwood flooring is classified as a porous material and as such not recommended by the Builder in certain the floor and in contravention of Ontario Building Code Section 9.30.1.2(1)

flooring, felted-synthetic-fibre floor coverings, concrete, terrazzo, ceramic tile, mastic or other types of flooring providing Finished flooring bathrooms, kitchens, public entrance halls, laundry & general storage areas shall consist of resilient" similar degrees of water resistance

SEE COLOUR CHART FOR LOCATIONS	uilder in relation to the matter.
osorbency in the mentioned areas, and agree to waive any claims against the Township of residence. TABION 224/22 the	sorpency in the mentioned are
the hardwood floor or subfloor due to moisture	and the charter to assume full

DATE

NANCOR

221 North Rivermede Road, Concord, Ontario L4K 3N7 * T: (905) 738.7010 F: (905) 738.5948